

Remote Vapor Tension Panel Thermometers Specifications

	MODELS							
	6142-06	6142-13	6142-20	6142-58	6642-06	6642-12	6742-19	6812-01
Temperature Range	40° to 240°F 10° to 115°C	-40 to 120°F -40 to 50°C	-40° to 60°F -40° to 15°C	-40° to 60°F -40° to 15°C	-40° to 60°F -40° to 15°C	40° to 240°F 10° to 115°C	-40° to 60°F -40° to 15°C	-40° to 60°F -40° to 15°C
Accuracy	±5°F @ 110°F ±3°F @ 200°F	±2°F @ 40°F ±4°F @ 10°F ±5°F @ 110°F	±2°F from 10° to 40°F ±3°F below 10°F and above 40°F	±2°F from 10° to 40°F ±3°F below 10°F and above 40°F	±2°F from 10° to 40°F ±3°F below 10°F and above 40°F	±5°F @ 110°F ±3°F @ 200°F	±2°F from 10° to 40°F ±3°F below 10°F and above 40°F	±2°F from 10° to 40°F ±3°F below 10°F and above 40°F
Dial	2" dia.	2" dia.	2" dia.	2" dia.	2" dia.	2" dia.	2" dia.	2" dia.
Capillary Length	48"	48"	48"	240"	48"	48"	48"	48"
Flange	Front	Front	Front	Front	Strap hanger no flange	Strap hanger no flange	U bracket no flange	Back
Connection	Back	Back	Back	Back	Bottom	Bottom	Back	Back
Mounting	Flush	Flush	Flush	Flush	N/A	N/A	N/A	Surface
Weight	5.2 oz	5.2 oz	4.7 oz	6.8 oz	4.6 oz	5.1 oz	5.6 oz	5.7 oz
Regulatory Listings	NSF	NSF	NSF	N/A	N/A	N/A	NSF	NSF
Warranty	1 Year	1 Year	1 Year	1 Year	1 Year	1 Year	1 Year	1 Year

	MODELS						
	6812-02	7112-01	7112-02	7112-05	7612-06	8122-01	8822-01
Temperature Range	-40° to 120°F -40° to 50°C	-40° to 60°F -40° to 15°C	-40° to 120°F -40° to 50°C	40° to 240°F 10° to 115°C	-40° to 60°F -40° to 15°C	-40° to 60°F -40° to 15°C	-40° to 60°F -40° to 15°C
Accuracy	±2°F @ 40°F ±4°F @ 10°F ±5°F @ 110°F	±2°F from 10° to 40°F ±3°F below 10°F and above 40°F	±2°F @ 40°F ±4°F @ 10°F ±5°F @ 110°F	±5°F @ 110°F ±3°F @ 200°F	±2°F from 10° to 40°F ±3°F below 10°F and above 40°F	±2°F from 10° to 40°F ±3°F below 10°F and above 40°F	±2°F from 10° to 40°F ±3°F below 10°F and above 40°F
Dial	2" dia.	2.5" dia.	2.5" dia.	2.5" dia.	2.5" dia.	3.5" dia.	3.5" dia.
Capillary Length	48"	48"	48"	48"	48"	48"	48"
Flange	Back	Front	Front	Front	Strap Hanger	Front No Flange	Back
Connection	Back	Back	Back	Back	Bottom	Back	Back
Mounting	Surface	Flush	Flush	Flush	N/A	Flush	Surface
Weight	6.2 oz	5.3 oz	5.8 oz	5.8 oz	5.6 oz	9.0 oz	9.0 oz
Regulatory Listings	N/A	NSF	N/A	N/A	N/A	N/A	N/A
Warranty	1 Year	1 Year	1 Year	1 Year	1 Year	1 Year	1 Year