



RESIDENTIAL/COMMERCIAL Second Stage Regulators Type 988LP



**988LP-03
988LP-35**



**Back Mount
988LP-34**

Product description

The second stage regulator reduces the pressure (10-5 psi) coming from a first stage regulator directly to the inlet pressure (11" w.c.) of the user appliance. Therefore Type 988 LP regulators are designed for Type A installations, see page 6 of the present catalogue. They have to be used outdoors in correct mounting position with venthole turned downwards. In the standard version these regulators are delivered with vent-hole in line with the inlet fitting.

Technical Specifications

Body And Cover: Aluminium
Diaphragm: Reinforced
Supplying Pressure: 5-15 PSIG
Cover Screws: Stainless Steel
Inlet Fitting Screws: Stainless Steel
Gas Type: Propane
Setting Point: inlet Pressure 10 PSIG, 140,000 BTU, Outlet Pressure 11" w.c.
Provided Flows: Flow Based On 10 PSIG Inlet Pressure and 20% Drop (In accordance with UL 144)
Type 988LP - L 6.027 x W 4.33 x H 4.94" Weight: 40.75 oz

| Type (Part No.) | Capacities in BTU/hr propane | Inlet connection, inches | Outlet connection, inches | Outlet pressure range, inches w.c. | Outlet pressure setting, inches w.c. |
|---|------------------------------|--------------------------|---------------------------|------------------------------------|--------------------------------------|
| 988LP - 03 (98.1.890.0003) | 800,000 | 1/2" NPT | 1/2" NPT | 9 to 13 | 11 |
| 988LP - 34 (98.1.890.0005) | 650,000 | | 3/4" NPT 90° | | |
| 988LP - 35 (98.1.890.0035) | 500,000 | | 1/2" NPT | | |

INSTALLATION
INSTRUCTIONS

RV AND OUTDOOR
COOKING REGULATORS

AUTOGAS
EQUIPMENT

FILLING
HEADS

BULK STORAGE AND
TRUCK EQUIPMENT

DOT/ASME
CONTAINER VALVES

REGULATORS