



RESIDENTIAL/COMMERCIAL 2-PSIG Regulators

Type 988TP



988TP-22

Type 998TP



998TP-08

Product description

Type 988 TP regulators are designed for C Type of installations.

They are to be used outdoors in correct mounting position with vent-hole turned downwards.

In the standard version Type 988 TP regulators are delivered with the vent-hole turned in line with the outlet fitting. There is a special configuration of inlet and outlet fittings for the Type 998 TP model:

- Back Mount 998 LP-07 (fig. A).

Technical Specifications

Body And Cover: Aluminium

Diaphragm: Reinforced

Supplying Pressure: 5-15 PSIG

Cover Screws: Stainless Steel

Inlet Fitting Screws: Stainless Steel

Gas Type: Propane

Setting Point: inlet Pressure 10 PSIG, 140,000 BTU, Outlet Pressure 2 PSIG

Provided Flows: Flow Based On 10 PSIG Inlet Pressure with a 20% Drop (In accordance with UL 144)

Type 988TP - L 6.692 x W 4.33 x H 4.94" Weight: 41.625 oz

Type 998TP - L 7.055 x W 5.657 x H 4.964" Weight: 57.5 oz



998TP-07

Fig.A

Back Mount

Weight: 57.875 oz

Type (Part No.)	Capacities in BTU/hr propane	Inlet connection, inches	Outlet connection, inches	Outlet adjustment range, PSIG	Outlet pressure setting, PSIG
988TP - 22 (98.1.890.0022)	700,000	1/2" NPT	1/2" NPT	1 to 2.2	2
998TP - 06 (99.1.890.0006)	1,680,000	3/4" NPT	3/4" NPT		
998TP - 07 (99.1.890.0007)	1,500,000		3/4" NPT 90°		
998TP - 08 (99.1.890.0008)	1,460,000	1/2" NPT	1/2" NPT		

INSTALLATION
INSTRUCTIONS

RV AND OUTDOOR
COOKING REGULATORS

AUTOGAS
EQUIPMENT

FILLING
HEADS

BULK STORAGE AND
TRUCK EQUIPMENT

DOT/ASME
CONTAINER VALVES

REGULATORS