

AQUASTATS


Honeywell

L8148 Multi-Function Aquastat Relays

Immersion type controllers that combine high limit protection with switching relay control of burner and circulator motors.

INCLUDES:

- High limit opens burner circuit only.
- Includes transformer and accessory terminals for adding a remote low limit controller.
- Case available for horizontal or vertical mounting.
- Requires a 24 VAC thermostat with heat anticipator set at 0.2 amps.



Honeywell

SPECIFICATIONS		ELECTRICAL RATINGS	
Application:	High limit	Burner:	@ 24 VAC 0.8 max. FLA
Connections:	Quick connect/screw		@ 120 VAC 7.4 FLA, 44.4 LRA
Frequency:	60 Hz		@ 240 VAC 3.7 FLA, 22.7 LRA
Mounting:	Vertical	Circulator:	@ 120 VAC 7.4 FLA, 4.4 LRA
Switch Action:	SPST high limit		@ 240 VAC 3.7 FLA, 22.2 LRA
Insulation:	-1/2" to 3" deep less well and Circulator		
Capillary:	-1/2"		
Dimensions:	6-1/8" H x 4-5/16" W x 3-1/8" D		

High limit range	Diff.	Includes	Mfr#	Item#	Reman#
140° - 240°F	8°F fixed	---	L8148A1017	C312-8	C312-8R
180° - 240°F	15°F fixed	---	L8148E1265	L8148E1265	
140° - 240°F	8°F fixed	Heat conductive compound and range stops	L8148J1009	C312-9	C312-9R

NOTE: Remanufactured products available only on exchange for similar defective units.

Honeywell

Remanufactured Combination Aquastat Controllers

High limit for oil-fired water heaters.

FEATURES:

- Single bulb controller
- Integral scale marked HOT-NORMAL-WARM.
- Stop set at 150°F.



Temperature Range	Thread Size	Insulation	Insertion Well Length	Mfr#	Reman#
100 - 200°F	3/4" npt	4"	5" with plastic sleeve	L4103A1001	C270R

NOTE: Remanufactured products available only on exchange for similar defective units.