

AQUASTATS

Honeywell

Aquastats

Multiple function immersion type controllers used to regulate water temperature in gas and oil fired boilers.



Honeywell

4

SPECIFICATIONS

High Limit:	130 - 240°F
High Limit Diff.:	10°F fixed
Circulator Low Limit:	110 - 220°F
Circulator Low Limit Diff.:	10 - 250°F adj.
Full Load Amps:	8A @ 120 VAC, 5.1A @ 240 VAC

Switching Function	Adjustable Differential	Mfr#	Item#	Reman#
SPST, high limit, SPST, low limit	Yes	L4081A1023*	C320-15	
SPST, high limit, SPST, circulator	No	L4081B1013	C322-5	
SPST, high limit, SPST, circulator	Yes	L4081B1047*	C322-4	C322-4R
SPST, high limit, SPST, circulator	No	L4081B1096	C322-4A	C322-4R
SPST, high limit, SPST, low limit circulator	Yes on low limit side	L6081A1010**	C332-6	

*Includes: Well, well adapter and tube of heat conductive compound.


**Includes: Well adapter, dial stop, 3" insulation, tube of heat-conductive compound and adjustable wrench.

NOTE: Remanufactured products available only on exchange for similar defective units.

White-Rodgers

Surface (Strap-On) Aquastats

Provides easy mounting to pipes to sense water temperature in a variety of applications. For high limit, reverse acting or SPDT switching action control.



WHITE-RODGERS

Range °F	Differential ° F	Switch Position	Replaces	Mfr#	Item#
100 - 240	10 fixed	SPDT	Honeywell L6006C-1018	1127-2	C340