

FFAP-A15Z-TFD-072

HCFC, R-22, 60Hz, 3-Phase, 460V

Availability: Custom US OEM Or Wholesaler

Mechanical		Electrical	
Unit Height (in):	16.6	Max Fuse Size:	15
Unit Length (in):	24.1	Min Circuit Ampacity:	6.3
Unit Width (in):	18.4	Compressor:	ZS09KAE-TFD-118
Ship Weight (lbs):	110.0	Compressor LRA - Low:	
Condenser Type:	Air	Compressor LRA - High:	28.0
CopeVap Water Storage:	NA	Compressor LRA - Half winding:	
Liquid Connection Size (in)/Type:	0.375 SWEAT	Compressor RLA	3.2
Suction Connection Size (in)/Type:	0.875 SWEAT	UL:	Listed
Discharge Line Size(in):	0.5	UL File #:	SA633
Water Inlet (in):		UL Guide Card:	LZFE
Water Outlet (in):			
Oil Type:	3MA	Amps Per Motor:	
Oil Recharge Amount (oz):	25	Fan Motor Quantity:	1

Performance

Release Date:	21-Jun-2022	Return Gas Temp. (°F):	40
Compressor:	ZS09KAE-TFD-118 x 1	Subcooling (°F):	5
Performance No:	41491	Air Flow Rate (CFM):	1070

90 °F Ambient Air Temperature

Evap Temp(°F)	Unit Capacity (BTU/hr)	Cond. Temp.(°F)	Temp. Diff.(°F)	EER(BTU/wh)
0	6,700	102.5	12.5	5.4
5	7,440	103.7	13.7	5.9
10	8,250	104.9	14.9	6.4

15	9,130	106.3	16.3	6.9
20	10,100	107.7	17.7	7.5
25	11,100	109.3	19.3	8.1