

**FPAK-013Z-TFD-072**

HFC, R-134a, 60Hz, 3-Phase, 460V

Availability: Standard US Wholesaler

Mechanical		Electrical	
Unit Height (in):	16.6	Max Fuse Size:	15
Unit Length (in):	24.1	Min Circuit Ampacity:	8.3
Unit Width (in):	18.3	Compressor:	ZS15KAE-TFD-118
Ship Weight (lbs):	100.0	Compressor LRA - Low:	
Condenser Type:	Air	Compressor LRA - High:	29
CopeVap Water Storage:	NA	Compressor LRA - Half winding:	
Liquid Connection Size (in)/Type:	0.375 SWEAT	Compressor RLA	5.4
Suction Connection Size (in)/Type:	0.875 SWEAT	UL:	Listed
Discharge Line Size(in):	0.375	UL File #:	SA633
Water Inlet (in):		UL Guide Card:	LZFE
Water Outlet (in):		Amps Per Motor:	
Oil Type:	POE	Fan Motor Quantity:	1
Oil Recharge Amount (oz):	25		

**Performance**

Release Date:	13-Feb-2023	Return Gas Temp. (°F):	40
Compressor:	ZS15KAE-TFD-118 x 1	Subcooling (°F):	5
Performance No:	44136	Air Flow Rate (CFM):	1070

**90 °F Ambient Air Temperature**

Evap Temp(°F)	Unit Capacity (BTU/hr)	Cond. Temp.(°F)	Temp. Diff.(°F)	EER(BTU/wh)
-5	5,960	101.0	11.0	4.9
0	6,740	102.4	12.4	5.4
5	7,590	103.8	13.8	5.9

10	8,500	105.3	15.3	6.4
15	9,490	106.9	16.9	7.0
20	10,600	108.7	18.7	7.6
25	11,700	110.6	20.6	8.2