

PROTECTORELAYS

Honeywell

Protectorelay® Oil Burner Controls **New and Remanufactured**

Provides automatic, non-recycling control of an intermittent (formerly called constant) ignition oil burner system. Controls oil burner, oil valve (if desired) and ignition transformer in response to a call for heat.



Honeywell

FEATURES:

- Solid state flame sensing circuit.

Safety Switch Timing	Thermostat Anticipator Setting	Includes	Elec'l Rating		Mfr#	Item#	Reman#
			FLA 120 Vac	FLA 240 Vac			
15 sec.	0.2A	Manual trip lever safety switch to assure burner shutdown during servicing	10.0A	5.0A	R8184G4066	R75-37	R75-41R
30 sec.	0.2A	Manual trip lever safety switch to assure burner shutdown during servicing	10.0A	5.0A	R8184G4074	R75-42	R75-42R
45 sec.	0.2A	Consumer warning label	7.4A	3.7A	R8184G4009	R75-40	R75-40R
45 sec.	0.2A	Manual trip lever safety switch to assure burner shutdown during servicing also includes remote alarm switch which makes a circuit to turn an alarm when the safety switch locks out*	7.4A	3.7A	R8184G4082	R75-44	
45 sec.	0.2A	- - -	7.4A	3.7A	R8184M1051	R75-58	R75-58R

*Use with Q539 subbases for remote lockout indication.

Ignition Rating: R8184G (45 sec. models), R8184L: 360 VA; R8184G (15,30 sec. models): 500VA, R8184M (40VA)

NOTE: Remanufactured products available only on exchange for similar defective units.