

KNIPEX Cobra®

Hightech Water Pump Pliers

- > Push the button for adjustment on the workpiece
- > Fine adjustment for optimum adaptation to different sizes of workpieces and a comfortable handle width
- > Self-locking on pipes and nuts: no slipping on the workpiece and low handforce required
- > Gripping surfaces with special hardened teeth, teeth hardness approx. 61 HRC: high wear resistance and stable gripping
- > Box-joint design for high stability due to double guide
- > Reliable catching of the hinge bolt: no unintentional shifting
- > Pinch guard prevents operators' fingers being pinched
- > Chrome vanadium electric steel, forged, multi stage oil-hardened
- > DIN ISO 8976

87 02 250 / 87 02 250 T / 87 05 250

- > With slim multi-component grips without collar for better handling and easier transport

87 02 180 T / 87 02 250 T / 87 02 300 T*

- > Pliers with tether attachment point for mounting a fall protection

KNIPEX Cobra® – the Hightech Water Pump Pliers.

No more time-consuming presetting of the required opening size. Just position the upper jaw to the workpiece, push button and move close the lower jaw, ingeniously simple.



Fine adjustment by pushing a button: fast and comfortable



Fast and firm adjustment directly on the workpiece



87 01 125



87 01 250



87 02 180




87 02 180 T



87 03 250




87 05 250



87 05 250



Teeth set against the direction of rotation have a self-locking effect and prevent slipping on the workpiece.



| Article No. | EAN 4003773- | ↔ mm | | Pliers | Head | Handles | ∅ Inch | ∅ mm | mm | Adjustment positions | g |
|-------------|--------------|--|--|-------------------|-----------|---|--------|------|----|----------------------|-----|
| 87 01 125 | 069935 | 125 | | grey atramentized | polished | with non-slip plastic coating | 1 | 27 | 27 | 13 | 85 |
| 87 01 150 | 060116 | 150 | | grey atramentized | polished | with non-slip plastic coating | 1 1/4 | 32 | 30 | 11 | 145 |
| 87 01 180 | 022015 | 180 | | grey atramentized | polished | with non-slip plastic coating | 1 1/2 | 42 | 36 | 18 | 170 |
| 87 01 250 | 022022 | 250 | | grey atramentized | polished | with non-slip plastic coating | 2 | 50 | 46 | 25 | 335 |
| 87 01 300 | 034087 | 300 | | grey atramentized | polished | with non-slip plastic coating | 2 3/4 | 70 | 60 | 30 | 530 |
| 87 02 180 | 042396 | 180 | | grey atramentized | polished | with multi-component grips | 1 1/2 | 42 | 36 | 18 | 196 |
| 87 02 180 T | 080145 | 180 | | grey atramentized | polished | with multi-component grips, with integrated tether attachment point for a tool tether | 1 1/2 | 42 | 36 | 18 | 200 |
| 87 02 250 | 040316 | 250 | | grey atramentized | polished | with slim multi-component grips | 2 | 50 | 46 | 25 | 366 |
| 87 02 250 T | 080152 | 250 | | grey atramentized | polished | with multi-component grips, with integrated tether attachment point for a tool tether | 2 | 50 | 46 | 25 | 370 |
| 87 02 300 | 029144 | 300 | | grey atramentized | polished | with multi-component grips | 2 3/4 | 70 | 60 | 30 | 580 |
| 87 02 300 T | 080169 | 300 | | grey atramentized | polished | with multi-component grips, with integrated tether attachment point for a tool tether | 2 3/4 | 70 | 60 | 30 | 600 |
| 87 03 125 | 073949 | 125 | | verchromt | verchromt | with non-slip plastic coating | 1 | 25 | 27 | 13 | 85 |
| 87 03 180 | 005667 | 180 | | verchromt | verchromt | with non-slip plastic coating | 1 1/2 | 42 | 36 | 18 | 175 |
| 87 03 250 | 043805 | 250 | | verchromt | verchromt | with non-slip plastic coating | 2 | 50 | 46 | 25 | 335 |
| 87 03 300 | 041382 | 300 | | verchromt | verchromt | with non-slip plastic coating | 2 3/4 | 70 | 60 | 30 | 530 |
| 87 05 250 | 005681 | 250 | | verchromt | verchromt | with slim multi-component grips | 2 | 50 | 46 | 25 | 366 |
| 87 05 300 | 014126 | 300 | | grey atramentized | polished | with multi-component grips | 2 3/4 | 70 | 60 | 30 | 580 |
| 87 09 125 | 074151 | Assortment of spare parts for adjustment for 86 / 87-125 | | | | | | | | | |
| 87 09 150 | 074168 | Assortment of spare parts for adjustment for 87 150 | | | | | | | | | |
| 87 09 180 | 034360 | Range of spare parts adjustment for 87 180 | | | | | | | | | |

KNIPEX Cobra® XL / XXL

Water Pump Pliers

- > Greater gripping capacity but much lower weight than comparable pipe wrenches
- > Fast push-button adjustment directly on the workpiece, no unintentional slipping of the joint
- > Fine adjustment for optimum adaptation to different sizes of workpieces and a comfortable handle width
- > Self-locking on pipes and nuts: no slipping on the workpiece and low handforce required
- > Gripping surfaces with special hardened teeth, teeth hardness approx. 61 HRC: high wear resistance and stable gripping
- > Box-joint design for high stability due to double guide
- > Pinch guard prevents operators' fingers being pinched
- > Chrome vanadium electric steel, forged, multi stage oil-hardened
- > DIN ISO 8976



87 01 400

87 01 560

KNIPEX Cobra® XL
length 400 mm – weight 1195 g

gripping a union nut of a 2" pipe fitting
large gripping capacity of 95 mm,
would require a 3-inch pipe wrench



smaller dimensions and less weight than 1 1/2" pipe wrenches

2" pipe wrench
length 560 mm – weight 2670 g



gripping the 2" union nut exceeds the capacity of a 2" pipe wrench; no confident working conditions

| Article No. | EAN 4003773- | ↔ mm | | Pliers | Head | Handles | ∅ Inch | ∅ mm | mm | Adjustment positions | ⚖ g |
|-------------|-----------------|--|--|-------------------|----------|----------------|--------|------|-----|----------------------|--------|
| 87 01 400 | 005636 | 400 | | grey atramentized | polished | plastic coated | 3 1/2 | 90 | 95 | 27 | 1195 |
| 87 01 560 | 044321 | 560 | | grey atramentized | polished | plastic coated | 4 1/2 | 115 | 120 | 20 | 2780 |
| 87 09 400 | 034391 | Range of spare parts adjustment for 87 400 | | | | | | | | | |
| 87 09 560 | 049845 | Range of spare parts adjustment for 87 560 | | | | | | | | | |

KNIPEX Cobra® Set

5-piece

- > High-quality roll-up bag made from durable polyester fabric
- > With hook-and-loop fastener
- > Equipped with KNIPEX Cobra® high-tech water pump pliers in five different lengths from 125 to 300 mm
- > Dimensions, open (L x H): 430 x 325 mm



00 19 55 55

| Article No. | EAN | | | Quantity | g |
|----------------|----------------|--|---|----------|---|
| 00 19 55 55 | 4003773-082613 | | Cobra® Set, 5-piece | | 1575 |
| | | | 87 01 125 | 1 | KNIPEX Cobra®, Hightech Water Pump Pliers |
| | | | 87 01 150 | 1 | |
| | | | 87 01 180 | 1 | |
| | | | 87 01 250 | 1 | |
| | | | 87 01 300 | 1 | |
| 00 19 55 55 LE | 082620 | | Roll-up case for pliers wrenches, empty | | 260 |


KNIPEX Cobra®...matic

Water Pump Pliers

- > All features of the KNIPEX Cobra® 87 01 250
- > Automatic adjustment at the touch of a button directly on the workpiece
- > The sheltered positioned spring ensures that the pliers close automatically once the push-button is activated (one-hand operation!)
- > Chrome vanadium electric steel, forged, multi stage oil-hardened
- > DIN ISO 8976



87 11 250



| Article No. | EAN | ↔ mm | | Pliers | Head | Handles | ∅ Inch | ∅ mm | ∅ mm | Adjustment positions | g |
|-------------|--------|------|--|----------------------------|----------|-------------------------------|--------|------|------|----------------------|-----|
| 87 11 250 | 035473 | 250 | | grey atramentized | polished | with non-slip plastic coating | 2 | 50 | 46 | 25 | 335 |
| 87 19 250 | 022640 | | | Spare spring for 87 11 250 | | | | | | | |

KNIPEX Cobra® QuickSet

Hightech Water Pump Pliers

- ▶ Fully open, push, grab!
- ▶ Additional fast adjustment on the workpiece by sliding the pliers handle
- > Combines the proven, reliable locking of the hinge bolt with an additional push function which makes it easier to work in very confined and inaccessible areas
- > The adjustment directly on the workpiece is possible by simply sliding the pliers handle
- > Reliable locking of the hinge bolt with the first workload. The gripping width of the pliers is then fixed and can only be adjusted by pressing the button
- > To re-activate the sliding function, the hinge bolt must be released by pressing the push button and the pliers must be completely opened again
- > Chrome vanadium electric steel, forged, multi stage oil-hardened
- > DIN ISO 8976



87 21 250



87 22 250

The KNIPEX Cobra® QuickSet combines all proven properties of the KNIPEX Cobra® with an additional push on function which makes it easier to work in very confined and inaccessible areas.

Adjustment directly on the workpiece is possible by simply sliding the pliers handle. The hinge bolt locks itself with the first workload. The gripping width of the pliers is then fixed and can only be adjusted by pressing the button. The hinge bolt must be released by pressing the button and the pliers must be completely opened once to activate the QuickSet function again.



Press the button – open pliers completely



Position jaw – simply slide and close pliers



Hinge bolt locks itself with the first workload



| Article No. | EAN 4003773- | ↔ mm | | Pliers | Head | Handles | ⊘ Inch | ⊘ mm | ⬡ mm | Adjustment positions | ⚖ g |
|-------------|--------------|------------------------------------|---|-------------------|----------|---------------------------------|--------|------|------|----------------------|-----|
| 87 21 250 | 072775 | 250 | | grey atramentized | polished | with non-slip plastic coating | 2 | 50 | 46 | 25 | 335 |
| 87 21 300 | 078524 | 300 | ▨ | grey atramentized | polished | with non-slip plastic coating | 2 3/4 | 70 | 60 | 25 | 530 |
| 87 22 250 | 077794 | 250 | ▨ | grey atramentized | polished | with slim multi-component grips | 2 | 50 | 46 | 25 | 366 |
| 87 29 01 | 079002 | range of spare parts for 87 2x-250 | | | | | | | | | |
| 87 29 300 | 084570 | range of spare parts for 87 21 300 | | | | | | | | | |