


MARS NO.	MFG. NO.	HP	VOLTS	RPM/ SPEEDS	ROT ⁽¹⁾	AMPS	DIMENSIONS		
							A	B	D

miller furnace (cont'd)



10815	10815	1/5	115	1050/1	CCW	4.0	3.5	4.4	–
5 inch diam., 3 mounting arms with grommet and bushings									
REPLACES: Trane/GE applications WW94X036, WW94X236, WW94X237, WW94X381; small condenser fan motor replaces WWG4M168; A.O Smith 326P155, OML6433									

nordyne



02251	5KCP29FCA322S	1/8	208-230	1075/1	CW	1.1	2.25	3.85	1/2"
5" diam., totally enclosed, 41" leads, Capacitor required 5 @ 370 (MARS No. 120056)									
REPLACES: NORDYNE									

prestcold




05811	5KSM81HFL3004T	16W	115	1550/1	CW	1.1	.5	3.5	–
3 1/2 inch diam., enclosed, 3 tapped holes or side pad mount, shaded pole, 1/4 inch threaded shaft									
REPLACES: Prestcold No. 401-0032-01									



05821	5KSM81HFL3006T	16W	230	1550/1	CW	.55	.5	3.5	–
3 1/2 inch diam., enclosed 3 tapped holes or side pad, shaded pole, 1/4 inch threaded shaft									
REPLACES: Prestcold No, 401-0033-01									



02141 Dual	5KSP29F7574T	1/10	115/230	1550/1	CCW	4.6/2.1	1.5	5.6	–
5 inch diam., open, resilient base, strap or end mount, shaded pole, 3/8 inch shaft									
REPLACES: Prestcold No. 401-0052-01, 401-0036-01									



03251	5KCP39DG3304T	1/6	115	1075/1	CCW	2.3	4.0	4.3	–
5 1/2 inch diam., open 2 1/4 inch resilient rings, 5 @ 370V capacitor required (MARS No. 12005)									
REPLACES: Prestcold No. 401-0037-01									