

Expanding Foam

- Seals and fills small cracks, gaps and voids
- Creates a rigid, closed cell barrier against draft, noise, moisture and air infiltration
- Tack free within 10 minutes



ITEM NO.	DESCRIPTION	STD QTY	U M
20417	12 oz HVAC Expanding Foam	12	EA

DAP® Fire Break Flame Resistant Foam Sealant

- Meets UL 1715, UL 94 V-O, modified ASTM E814
- Approved fire block penetration sealant (orange)
- Fills & seals service penetrations
- UL tested
- Class A fire resistant



ITEM NO.	DESCRIPTION	STD QTY	U M
19016	12 oz DAP Fire Break Foam Sealant	12	EA

BOSS® 812 Fire Block Foam

- Will adhere to almost any substrate
- Seals around copper & PVC pipes, conduits, ducting, etc.
- Prevents the spread of smoke & toxic gasses
- Installed in seconds, reducing labor cost by up to 90%
- Specialized 360° Dispensing Can
- CFC Free



ITEM NO.	DESCRIPTION	STD QTY	U M
20421	[812] 12 oz Fire Block Foam	12	EA

Thum-Gum™ Sealing Compound

- Non-hardening putty for larger sealing jobs
- For plugging openings through foundations
- For plugging refrigeration tube entry



ITEM NO.	DESCRIPTION	STD QTY	PLT QTY	U M
1003	1 lb Bag Sealing Compound	24	1080	EA
1004	2 lb Box Sealing Compound	20	900	EA

Thum-Gum™ Caulking Cords

- A non-hardening putty
- Seals storm windows
- Great as weather strip
- Seals sink & drain boards
- Application temperature range: 60°F to 100°F



ITEM NO.	DESCRIPTION	STD QTY	PLT QTY	U M
1005	3/16" x 100' Caulking Cord	12	300	EA
16923	3/8" x 25' Caulking Cord	12	300	EA

Design Polymerics Duct Sealant

- UL Listed
- Gray in color
- Fiber reinforced
- Crack & peel resistant
- Non-flammable & mildew resistant
- Excellent dry adhesion
- Meets requirements of NFPA 90A & 90B
- Indoor & outdoor usage
- Water based



ITEM NO.	DESCRIPTION	STD QTY	PLT QTY	U M
14047	[DP1010] 1 Gal Duct Sealant	4	180	EA
14048	[DP1020] 1/12 Gal Duct Sealant	25		EA
14049	[DP1020] 1 Gal Duct Sealant	4	180	EA
14058	[DP1030] 1 Gal Duct Sealant	4	180	EA

Design Polymerics 1090 Duct Sealant

- LEED Qualified, Low VOC
- UL Classified
- California Compliant
- Indoor and Outdoor Usage
- 5 cycles of freeze/thaw with no deterioration
- 0°F to 110°F application temperature
- Meets Requirements of NFPA 90A & 90B, ASTM E-84, and UL-723



ITEM NO.	DESCRIPTION	STD QTY	PLT QTY	U M
14063	[DP1090] 1 Gal Duct Sealant	4	180	EA