



**Series 7700MF**  
**Brass Ball Valve**

Full Port | Brass  
PEX F1960 Connection  
MIP x Barbed

Item No.	Desc.	Connection	Inner	MC
107-321NL	1/4"	MIP x FIP	20	200

**Features:**

- 500 PSI WOG
- -20°F to 350°F temperature range
- Suitable for vacuum use up to 7 PSI



**Series 7700CMP**  
**Brass Ball Valve**

Brass  
Compression Connection

Item No.	Size	Connection	Inner	MC
107-023NL	1/2"	OD x OD	-	12
107-023NLA	1/2"	OD x OD	6	36
107-024NL	3/4"	OD x OD	-	12
107-024NLA	3/4"	OD x OD	6	36
107-025	1"	OD x OD	6	24

**Features:**

- 200 PSI WOG
- -20°F to 350°F temperature range
- Suitable for vacuum use up to 7 PSI
- Compression ends for solderless connection to copper tubing



**Series 7700TD**  
**Stop & Waste**  
**Brass Ball Valve**

Forged Brass | Full Port

Item No.	Size	Connection	Inner	MC
107-753NL	1/2"	FIP x FIP	-	10
107-754NL	3/4"	FIP x FIP	-	10
107-755NL	1"	FIP x FIP	-	15

**Features:**

- 600 PSI WOG/150 WSP (1/2" - 2")
- -20°F to 300°F temperature range
- Full port for maximum flow rate
- Packing Gland - blowout-proof stem design
- PTFE seat and packing
- Chrome-plated brass ball & stem
- Rust-resistant heavy-duty handle with vinyl grip
- Suitable for vacuum use up to 7 PSIA
- Port allows non-pressure side to drain when closed



**Series 7700TD**  
**Stop & Waste**  
**Brass Ball Valve**

Forged Brass | Full Port

Item No.	Size	Connection	Inner	MC
107-553NL	1/2"	SWT x SWT	-	10
107-554NL	3/4"	SWT x SWT	-	10
107-555NL	1"	SWT x SWT	-	10

**Features:**

- 600 PSI WOG/150 WSP (1/2" - 2")
- -20°F to 300°F temperature range
- Full port for maximum flow rate
- Packing Gland - blowout-proof stem design
- PTFE seat and packing
- Chrome-plated brass ball & stem
- Rust-resistant heavy-duty handle with vinyl grip
- Suitable for vacuum use up to 7 PSIA
- Port allows non-pressure side to drain when closed

