

Scotch® Super 33+ Electrical Tape

- UL Listed; UL 510 Standard
- CSA Certification; Standard C22.2 No.197-M1983
- Pressure-sensitive rubber based adhesive
- Compatible with rubber & synthetic splicing compounds, as well as epoxy & polyurethane resins
- For indoor or outdoor applications



ITEM NO.	DESCRIPTION	STD QTY	U M
13945	Super 33+, 3/4" x 66', 7 Mil Black Tape	10	RL

Scotch® 35 Vinyl Electrical Color Coding Tape

- UL Listed - UL 510 Standard
- CSA Certification; Standard C22.2 No. 197-M1983
- RoHS Compliant 2002/95/EC
- Color coding for phase identification, job identification & safety insulating electrical wiring
- Protecting electrical conductors, motor leads & piping from moisture, alkalis, acids, corrosion, abrasion & weather



ITEM NO.	DESCRIPTION	STD QTY	U M
14117	3/4" x 66' Red Electrical tape	10	RL
14118	3/4" x 66' White Electrical tape	10	RL
14119	3/4" x 66' Blue Electrical tape	10	RL
14120	3/4" x 66' Green Electrical tape	10	RL
14121	3/4" x 66' Yellow Electrical tape	10	RL
14122	3/4" x 66' Orange Electrical tape	10	RL

Scotch® Super 88 Electrical Tape

- UL Listed; UL 510 Standard
- CSA Certification; Standard C22.2 No. 197-M1983
- RoHS Compliant 2002/95/EC
- Pressure-sensitive rubber-based adhesive
- Compatible with rubber & synthetic splicing compounds, as well as epoxy & polyurethane resins
- For indoor or outdoor applications



ITEM NO.	DESCRIPTION	STD QTY	U M
14086	Super 88, 3/4" x 66', 8.5 Mil Black Tape	10	RL

3M™ Temflex™ Vinyl Electrical Tape

- UL Listed; UL 510 Standard
- CSA Certification; Standard C22.2 No. 197-M1983
- RoHS Compliant 2002/95/EC
- Rated up to 600 volts
- For indoor or outdoor applications



ITEM NO.	DESCRIPTION	STD QTY	U M
15060	[69764] Temflex 3/4" x 60' Black Tape	100	EA

P.V.C. Electrical Tape

- UL Listed
- High quality all-purpose black vinyl 7 mil
- Maximum voltage: 600 volts
- Maximum temperature: 176° F / 80° C



ITEM NO.	DESCRIPTION	STD QTY	CTN QTY	U M
13229	3/4" x 60' Black Electrical Tape	10	200	RL

Scotch® 130C Linerless Electrical Tape

- Linerless, self-bonding, insulating tape
- Rated through 69 kV
- High thermal conductivity
- Ethylene propylene base
- Insulate splices & terminate cables whose overload temperatures can reach 130 °C
- Stable over wide application temperature range
- Weather resistant



ITEM NO.	DESCRIPTION	STD QTY	U M
16089	130C Splicing Tape 3/4" x 30', 30 Mil	1	RL

STANDARDS & BASES
EQUIPMENT
CONDENSATE
DRAINING PLUMBING & CHEMICALS
SEALANTS LUBES
VENTING
ELECTRONICS &
ELECTRICAL
TOOLS
MISCELLANEOUS
INDEX