WASHDOWN


Permanent Split Capacitor Direct Drive Fan Single Shaft 5.0" Diameter, Open Air Over

APPLICATIONS:

Designed to meet manufacturer's requirements for direct drive fan and blowers.

FEATURES:

- · Reversible Unless Noted
- Sleeve Bearings have All Angle Thrust System
- Suitable for Use With 370V Capacitors
- · Continuous Duty, Air Over
- 24" Line Leads Unless Otherwise Noted
- · Automatic Reset Thermal Overload Protector
- Connection & Capacitor Information Furnished in Nameplate Data
- 208v will not be marked on DOE regulated spread-voltage motors. Refer to online data
- Discount Symbol: DS-3HAC



Permanent Split Capacitor, 5.0" Diameter, Stud or Hub Ring Mount (2.5")

НР	RPM/ Spds.	Voltage	Catalog Number	List	Bearings	Cap. MFD	Amps	Shaft N	Base XD	Shell XI	Total C	Stud YM	Ship Wt.	Notes
1/5	1075/3	203-230	8952	+	SAB	5 .0	1.6	4 .0	5.3	4 .9	9.9	N/A	11	
	1075/4	115	1268	+	SAB	4 .0	3 .4	3 .5	4 .6	4 .1	8 .7	1	10	98
1/4	1050/3	115	1390	+	SAB	7 .5	2.8	4 .0	4 .9	4 .3	8 .9	1	12	H24
	1050/3	208-230	1391	+	SAB	7 .5	1.5	4 .0	4 .9	4 .3	8 .9	1	12	H24
1/3	1075/3	115	8955	+	SAB	15 .0	3 .8	4 .0	5 .1	-	10 .2	.75	8	

◆ Refer to Motorboss for Pricing



Note H24: Hub Rings not included

Note 98:

50/60 Hz