

# DUAL READOUT THERMOMETER

Average customer product rating:



Measuring system temperature requires multiple tools, and sometimes multiple trips to the truck. The hilmor Dual Readout Thermometer was designed to change that. It's the industry's only manifold-compatible compact thermometer with two readings to make calculations simple. You can use it on any manifold. You can use it independently. But most important, you can use it to maximize efficiency. Sold with two K-style thermocouple clamps.

[Download Instruction Sheet](#)



## How To Videos



To purchase this

To purchase this  
product online:

[+ BUY ONLINE](#)

More Views



## Features & Benefits

### Makes Calculations Easier

The industry's only manifold-compatible compact thermometer with two readings to help simplify the calculation of superheat and subcool.

### Superior Versatility

Use it on any gauge set, or remove it and use it independently.

### Reads Temperatures Quickly

Two easy-to-use, K-style tube clamp thermocouples get you to the temperature reading quickly.

[Product Specifications](#)

[Warranty](#)

[Related Tools](#)

[Retool with hilmor](#)

## Product Specifications

<b>Reference Model Number</b>	1839106
<b>Product Description</b>	With two clamps
<b>2 Thermocouple Clamps Included</b>	1839108 TCC Thermocouple Clamp
<b>Product Dimensions</b>	Length: 1 <sup>3</sup> / <sub>4</sub> ", Width: 1 <sup>5</sup> / <sub>8</sub> ", Height: 3 <sup>7</sup> / <sub>8</sub> ", Weight: 0.7 lbs.
<b>Replacement Parts</b>	1839108 TCC Thermocouple Clamp
<b>Batteries</b>	AA x 1 (included)
<b>Battery Life</b>	151 hours typical alkaline
<b>Connection Type</b>	K
<b>Temperature Measurement</b>	Range: -76° F to 999.9° F, Resolution: 0.1° F/C, Accuracy: ± 2.0° C/± 3.6°
<b>Operating Temperature Range</b>	0° C to +50° C

