



2021 CORDLESS CATALOG



Nothing but **HEAVY DUTY.**





THE WORLD LEADER IN CORDLESS INNOVATION



DEDICATION TO THE TRADES

Since the company began in 1924, Milwaukee Tool has led the industry in both durability and performance. With an unwavering commitment to the trades, MILWAUKEE® continues to lead with a focus on providing innovative, cordless, trade-specific solutions. MILWAUKEE® is dedicated to delivering a steady stream of advanced solutions for the trades that offer increased productivity and unmatched durability.

GAME-CHANGING SOLUTIONS

At MILWAUKEE®, the phrase “good enough” doesn’t exist in our vocabulary. Our goal is to solve problems in ways that have never been done before. The result: tools and equipment that offer unmatched levels of performance, productivity and durability.



BUILT ON THE BEST FOUNDATION



REDLITHIUM™ BATTERIES

They last longer, think faster and work harder than all other professional LITHIUM-ION batteries. Built to withstand even the harshest environments, REDLITHIUM™ Batteries deliver more work over the life of the battery, no matter what the job.



MILWAUKEE® HIGH PERFORMANCE MOTORS

Highly advanced motor technology boosts efficiency, generating more power from a compact power source. That means the ultimate performance, durability and run-time comes in a smaller, lighter package.



REDLINK™ INTELLIGENCE

An advanced combination of hardware and software, REDLINK™ Intelligence enables full-circle communication between our batteries and tools, allowing for unmatched levels of performance, protection and productivity.

USER-DRIVEN INNOVATIONS

Instead of making assumptions about what users need, we set out to deliver disruptive innovation by getting out on the jobsite, alongside trade professionals, to understand their challenges – the frustrations, needs, and previous limitations. We set out to completely rethink a solution with new-to-world technology and unparalleled levels of design and engineering. Whether it's bringing cordless power to traditionally corded or gas products and manual activities, or advances to fundamental tools and equipment, we are dedicated to improving workplace productivity and safety.



M18™ FORCE LOGIC™ Press Tool w/ ONE-KEY™
THE SMALLEST, MOST INTELLIGENT PRESS TOOL

The M18™ FORCE LOGIC™ Press Tool w/ ONE-KEY™ is the industry's smallest, most intelligent press tool. With an in-line design and brushless motor, it achieves more run-time per charge and faster cycle times while being significantly smaller and nearly 20% lighter than the leading competitor. The M18™ FORCE LOGIC™ Press Tool w/ ONE-KEY™ and compatible jaws are designed to work with over 20 unique fitting systems offering 1/2" to 4" capacity. With the addition of ONE-KEY™ compatibility, the press tool automatically logs and wirelessly uploads connection data from every press made with the tool which can be passed onto key stakeholders through customizable reports.



M12 FUEL™ 3/8" Digital Torque Wrench w/ ONE-KEY™
UP TO 50% FASTER INSTALLATION **DELIVERS TORQUE ACCURACY UP TO +/- 2%** **FASTER, MORE PRODUCTIVE TORQUE REPORTING**

The M12 FUEL™ Digital Torque Wrench w/ ONE-KEY™ is the industry's first torque wrench with a motor, delivering increased productivity, precise torque accuracy, and user demanded reporting functionality. The torque wrench delivers up to 50% faster installation time, replacing the hand tool or two tool installation process and providing accuracy within 2% for torque critical fasteners. This battery powered torque wrench is equipped with MILWAUKEE® ONE-KEY™, giving you the power to record all the fasteners and produce a downloadable report via ONE-KEY™.



M18 FUEL™ 8-1/4" Table Saw w/ ONE-KEY™
GENERATES 15A CORDED POWER **24 1/2" RIP CAPACITY** **RIP UP TO 600 LFT PER CHARGE**

The world's first 18V table saw, the M18 FUEL™ 8-1/4" Table Saw w/ ONE-KEY™ generates the power of a 15 amp corded saw. With a rip capacity up to 24-1/2" and a vertical capacity up to 2-1/2" to tackle 2x dimensional lumber, this saw boasts the impressive capacity that users have come to expect on a traditional corded table saw. Equipped with ONE-KEY™, users can also easily track, manage, and secure the table saw through the ONE-KEY™ app on their phone.



M18™ FORCE LOGIC™ 10 Ton Knockout Tool
THE EASIEST WAY TO PUNCH

The MILWAUKEE® Knockout System makes every step in the hole making process both faster and easier. The EXACT™ Punches and Dies are set up separate from the tool for extreme ease of use, utilizing a quick-connect alignment system that allows users to snap the tool onto the punches and dies without fighting against its weight and pull the trigger to punch the hole with ease.

M18 FUEL™ 1" D-Handle Extended Anvil High Torque Impact Wrench w/ ONE-KEY™

UP TO 2,000 FT-LBS NUT-BUSTING TORQUE **UP TO 200 BOLTS PER CHARGE** **ELIMINATES COMPRESSORS & HOSES**

Our M18 FUEL™ 1" D-Handle Extended Anvil High Torque Impact Wrench w/ ONE-KEY™ is engineered for the performance, run-time, and unmatched portability heavy duty technicians demand. The POWERSTATE™ Brushless Motor delivers up to 2,000 ft-lbs of nut-busting torque and 1,900 ft-lbs of fastening torque, enabling you to complete the most demanding applications. With the run-time for up to 120 lug nut removals and installations on a single HIGH OUTPUT™ HD12.0 Battery, this portable impact wrench provides unmatched performance. Lug Nut Mode, which can be enabled through the ONE-KEY™ app, prevents the over-torque of lug nuts by automatically shutting off the tool, providing more control. The REDLINK PLUS™ Intelligence ensures you achieve maximum performance and protects the High Torque Impact Wrench against overloads, over-heating, and over-discharge.



M18 FUEL™ Pipe Threader w/ ONE-KEY™
AUTOSTOP™ KICKBACK CONTROL **SIDE-GRIP THREAD STARTS** **THREADS FASTER THAN CORDED**

The M18 FUEL™ Pipe Threader w/ ONE-KEY™ revolutionizes pipe threading. Featuring AUTOSTOP™ kickback control, the tool protects against severe kickback. This, combined with the integrated side-grip for easier thread starts, delivers unrivaled tool control. The world's first cordless pipe threader threads faster than corded alternatives and delivers unmatched productivity.

MX FUEL™ 14" Cut-Off Saw
INSTANT START, ZERO EMISSIONS

NO GAS HEADACHES **FASTEST CUTS FROM START TO FINISH** **6 FT IN CONCRETE, 72 CUTS IN #5 REBAR PER CHARGE**

The MX FUEL™ 14" Cut-Off Saw delivers instant starts and zero emissions while providing you with no gas headaches, fastest cuts from start to finish, and can cut 6 ft of concrete or 72 cuts in #5 rebar per charge. By providing a 5" cut depth and eliminating the hassle of pull starts, the MX FUEL™ 14" Cut-Off Saw helps you maximize your productivity in every application. The MX FUEL™ REDLITHIUM™ Battery Pack provides instant power with less noise and vibration, and zero emissions for a safer workspace indoors or outdoors.



M18™ FORCE LOGIC™ 10,000 PSI Hydraulic Pump
THE EASIEST WAY TO POWER HYDRAULICS

The M18™ FORCE LOGIC™ 10,000 PSI Hydraulic Pump is designed to be fully compatible with all existing 10,000 PSI rated hydraulic hoses and heads. Delivering the easiest set-up, at up to 80% smaller and up to 75 lbs lighter than gas units, the pump can easily be carried by a single person. Delivering 3X the flow rate of competitive cordless pumps; 24-second cycle times and up to 60 presses on a single battery on 1590 ACSR connectors, the pump provides gas-like performance.

THE WORLD LEADER IN CORDLESS INNOVATION

Milwaukee Tool is committed to driving unrivaled performance and productivity for the professional trades through our groundbreaking developments in cordless technology.

Our leadership in cordless innovation has helped to shape the industry. We were the first to introduce LITHIUM-ION technology to power tools, and have achieved significant leaps forward in advanced motors, the most intelligent electronics, and connected tools. This leadership allows us to continue providing a steady stream of solutions that exceed the demands of the trades.

REDLITHIUM™ BATTERIES

CELL TECHNOLOGY

Not all batteries are created equal. In our world-class battery lab, battery cells are engineered to deliver the highest performing packs on the jobsite.

PACK CONSTRUCTION

Unique patented designs protect every REDLITHIUM™ Battery, safeguarding your investment through drops, weather exposure, and harsh environments.

ROBUST ELECTRONICS

Innovative communication systems monitor cells, providing temperature and overload protection, while optimizing performance for every tool and battery combination.

MORE POWER | **MORE RUN-TIME** | **LONGER BATTERY LIFE**



POWERSTATE™ BRUSHLESS MOTORS


HIGH PERFORMANCE

MILWAUKEE's high performance POWERSTATE™ Brushless Motors contain top-grade rare earth magnets and greater copper content, delivering more power and torque for superior application performance.

PURPOSE BUILT

Each motor is uniquely engineered for the demands of the tool.

Motor-optimization ensures the perfect combination of performance, portability and productivity.



POWERSTATE™ BRUSHLESS MOTORS



LONGER MOTOR LIFE | **MORE POWER** | **MORE RUN-TIME**

REDLINK™ INTELLIGENCE

DURABILITY

Best-in-class thermal and overload monitoring protects tools in extreme jobsite conditions.

PRODUCTIVITY

Advanced communication features, such as DRIVE CONTROL™, allow users to quickly move from light to heavy applications with the touch of a button.

ONE-KEY™


Get more out of your tools and equipment than ever before with integrated tool tracking, security and customization. ONE-KEY™ combines smarter tools with the industry's only free-to-use inventory management program.



FULL SYSTEM COMPATIBILITY

With industry-leading intelligence connecting every battery, tool and charger. MILWAUKEE's M18™ System has upheld full forward and backward compatibility for over a decade.

2007
2 TOOLS



2021
200+ TOOLS

UNMATCHED PROTECTION | **OPTIMIZED PERFORMANCE** | **MORE PRODUCTIVITY**

THE WORLD LEADER IN CORDLESS INNOVATION

M12

PORTABLE PRODUCTIVITY.
TRADE FOCUSED. SYSTEM WIDE.

Pages 9 – 36



M18

PERFORMANCE DRIVEN.
TRADE FOCUSED. SYSTEM WIDE.

Pages 37 – 82

**MIX
FUEL**

EQUIPMENT REDEFINED.
TRADE FOCUSED. SYSTEM WIDE.

Pages 83 – 94

ONE KEY

UNLOCKING THE DIGITAL JOBSITE.™



SMART TOOLS
& EQUIPMENT



SYNC
WIRELESSLY



ONLINE + MOBILE
RECORD KEEPING

DIGITAL PLATFORM FOR
TOOLS & EQUIPMENT

CUSTOMIZE. TRACK. MANAGE.

Customize
by dialing in
performance



Track your tools
and equipment
location from
anywhere



Lock and
disable
remotely

Manage
your assets
your way



See pages 18, 22, 41, 43, 45-49, 53, 55, 61 – 64, 67 – 69, 71, 75, 77, 89 – 94
for ONE-KEY™ Compatible Tools and Equipment



Apple, the Apple logo are trademarks of Apple Inc., registered in the U.S. and other countries.
App Store is a service mark of Apple Inc. Google Play and the Google Play logo are trademarks of Google Inc.

VISIT ONEKEY.MILWAUKEETOOL.COM
FOR MORE INFORMATION

DOWNLOAD THE
FREE APP NOW!



**LEARN
MORE**



<https://qr.mke.tl/2anjm>



M12

**PORTABLE PRODUCTIVITY
TRADE FOCUSED
SYSTEM WIDE**

**ALL M12™ TOOLS FIT
M12™ BATTERIES**
125+ TOOLS




DRIVEN TO OUTPERFORM.™

M12 FUEL™ is engineered for the most demanding tradesmen in the world. M12 FUEL™ delivers unrivaled performance in a compact structure and features three MILWAUKEE® exclusive innovations – the POWERSTATE™ Brushless Motor, REDLITHIUM™ Battery Pack and REDLINK PLUS™ Intelligence Hardware and Software – that deliver unmatched power, run-time and durability.

Simply put, M12 FUEL™ is best-in-class, full-circle technology that drives, protects and powers your cordless tools beyond the rest.


M12 FUEL

LONGER MOTOR LIFE | **MORE** POWER | **MORE** RUN-TIME



1 POWERSTATE™ BRUSHLESS MOTOR

- MILWAUKEE® Designed and Built Brushless Motor
- Outperforms All Leading Competitors
- Up to 10X Longer Motor Life



2 REDLINK PLUS™ INTELLIGENCE

- Most Advanced Electronic System on the Market for Maximum Performance
- Total System Communication with Overload Protection Increases Tool Life
- Built-In Fuel Gauge Displays Remaining Charge



3 REDLITHIUM™ CP2.0 & XC4.0 BATTERY PACKS

- Up to 2X More Run-Time
- Up to 20% More Power
- Over 2X More Recharges than Leading Competitors
- Operates Below -18°C / 0°F



**PORTABLE PRODUCTIVITY
TRADE FOCUSED
SYSTEM WIDE**

M12 FUEL
1/2" Hammer Drill/Driver Kit

2504-22 (2504-20 Tool-Only)

Specifications:

Peak Torque	350 in-lbs
RPM	0 – 1,700
BPM	0 – 25,500
Chuck Type	1/2" Metal Single Sleeve – Ratcheting Chuck
Length / Weight	6.6" / 2.3 lbs

Includes: (1) M12™ REDLITHIUM™ XC4.0 Battery Pack, (1) M12™ REDLITHIUM™ CP2.0 Battery Pack, Belt Clip, Charger, Carrying Case



M12™ 3/8" Right Angle Drill/Driver Kit

2415-21 (2415-20 Tool-Only)

Specifications:

Peak Torque	100 in-lbs
RPM	0 – 800
Clutch Settings	11 Settings plus Drill Mode
Chuck Type	3/8" Single Sleeve
Head Profile	3.8"
Weight	2.4 lbs

Includes: (1) M12™ REDLITHIUM™ CP1.5 Battery Pack, Charger, Soft Carrying Case



M12™ 3/8" Hammer Drill/Driver Kit

2408-22 (2408-20 Tool-Only)

Specifications:

Peak Torque	275 in-lbs
RPM	0 – 400 / 0 – 1,500
BPM	0 – 22,500
Chuck Type	3/8" Metal Single Sleeve
Length / Weight	7.5" / 2.7 lbs

Includes: (2) M12™ REDLITHIUM™ CP1.5 Battery Packs, Belt Clip, Charger, Carrying Case



M12 FUEL
1/4" Hex 2-Speed Screwdriver Kit

2402-22 (2402-20 Tool-Only)

Specifications:

Peak Torque	325 in-lbs
RPM	0 – 450 / 0 – 1,700
Chuck Type	1/4" Hex Quick Change
Length / Weight	6.6" / 2.0 lbs

Includes: (2) M12™ REDLITHIUM™ CP2.0 Battery Packs, Belt Clip, Charger, Carrying Case



M12 FUEL
1/2" Drill/Driver Kit

2503-22 (2503-20 Tool-Only)

Specifications:

Peak Torque	350 in-lbs
RPM	0 – 1,700
Chuck Type	1/2" Metal Single Sleeve – Ratcheting Chuck
Length / Weight	6.6" / 2.3 lbs

Includes: (1) M12™ REDLITHIUM™ XC4.0 Battery Pack, (1) M12™ REDLITHIUM™ CP2.0 Battery Pack, Belt Clip, Charger, Carrying Case



M12™ 1/4" Hex 2-Speed Screwdriver Kit

2406-22 (2406-20 Tool-Only)

Specifications:

Peak Torque	275 in-lbs
RPM	0 – 400 / 0 – 1,500
Chuck Type	1/4" Hex Quick Change
Length / Weight	6.8" / 1.8 lbs

Includes: (2) M12™ REDLITHIUM™ CP1.5 Battery Packs, Belt Clip, Charger, Carrying Case



M12 FUEL
Installation Drill/Driver Kit

2505-22 (2505-20 Tool-Only)

Specifications:

Max Torque	300 in-lbs
RPM (2-Mode)	0 – 400 / 0 – 1,600
Attachments	3/8" Metal Chuck, 1/4" Hex, Offset and Right Angle
Length / Weight	5.1" / 2.0 lbs

Includes: (2) M12™ REDLITHIUM™ CP2.0 Battery Packs, (4) Attachments (3/8" Metal Chuck, 1/4" Hex, Offset and Right Angle), Belt Clip, Charger, Compartmentalized Contractor Bag



M12™ 1/4" Hex Screwdriver Kit

2401-22 (2401-20 Tool-Only)

Specifications:

Peak Torque	175 in-lbs
RPM	0 – 500
Chuck Type	1/4" Hex Quick Change
Length / Weight	6.5" / 2.0 lbs

Includes: (2) M12™ REDLITHIUM™ CP1.5 Battery Packs, Belt Clip, Charger, Soft Carrying Case



M12™ 3/8" Drill/Driver Kit

2407-22 (2407-20 Tool-Only)

Specifications:

Peak Torque	275 in-lbs
RPM	0 – 400 / 0 – 1,500
Chuck Type	3/8" Metal Single Sleeve
Length / Weight	7.4" / 2.5 lbs

Includes: (2) M12™ REDLITHIUM™ CP1.5 Battery Packs, Belt Clip, Charger, Carrying Case



M12 FUEL
1/4" Hex Impact Driver Kit

2553-22 (2553-20 Tool-Only)

Specifications:

Fastening Torque	1,300 in-lbs
IPM	0 – 4,000
RPM	0 – 3,300
Chuck Type	1/4" Hex Quick Change
Length / Weight	5.1" / 1.8 lbs

Includes: (2) M12™ REDLITHIUM™ CP2.0 Battery Packs, Belt Clip, Charger, Carrying Case



M12 FUEL
SURGE™ 1/4" Hex Hydraulic Driver Kit

2551-22 (2551-20 Tool-Only)

Specifications:

Sustained Fastening Torque	450 ft-lbs
IPM	0 – 3,400
RPM	0 – 3,200
Chuck Type	1/4" Hex Quick Change
Length / Weight	5.2" / 2.4 lbs

Includes: (2) M12™ REDLITHIUM™ CP2.0 Battery Packs, Belt Clip, Charger, Contractor Bag



M12™ 1/4" Hex Impact Driver Kit

2462-22 (2462-20 Tool-Only)

Specifications:

Fastening Torque	1,000 in-lbs
IPM	0 – 3,300
RPM	0 – 2,500
Chuck Type	1/4" Hex
Length / Weight	6.5" / 2.3 lbs

Includes: (2) M12™ REDLITHIUM™ CP1.5 Battery Packs, Belt Clip, Charger, Carrying Case



M12™ 1/4" Hex Right Angle Impact Driver Kit

2467-21 (2467-20 Tool-Only)

Specifications:

Fastening Torque	600 in-lbs
IPM	0 – 3,300
RPM	0 – 2,450
Chuck Type	1/4" Hex
Head Profile	1.4"
Weight	2.6 lbs

Includes: (1) M12™ REDLITHIUM™ CP1.5 Battery Pack, Charger, Soft Carrying Case



M12 FUEL
1/2" Stubby Impact Wrench Kit

2555-22, 2555P-22 (2555-20 Tool-Only)

Specifications:

Peak Torque	250 ft-lbs
IPM	0 – 3,200
RPM	0 – 2,700
Anvil Type	1/2" Friction Ring
Length / Weight	4.9" / 2.1 lbs

Includes: 2555-22 1/2" Stubby Impact Wrench; 2555P-22 1/2" Stubby Impact Wrench w/ Pin Detent; **All Kits Include:** (1) M12™ REDLITHIUM™ XC4.0 Battery Pack, (1) M12™ REDLITHIUM™ CP2.0 Battery Pack, Belt Clip, Charger, Soft Carrying Case



M12 FUEL
3/8" Stubby Impact Wrench Kit

2554-22 (2554-20 Tool-Only)

Specifications:

Peak Torque	250 ft-lbs
IPM	0 – 3,200
RPM	0 – 2,700
Anvil Type	3/8" Friction Ring
Length / Weight	4.8" / 2.1 lbs

Includes: (1) M12™ REDLITHIUM™ XC4.0 Battery Pack, (1) M12™ REDLITHIUM™ CP2.0 Battery Pack, Belt Clip, Charger, Soft Carrying Case



M12 FUEL
1/4" Stubby Impact Wrench Kit

2552-22 (2552-20 Tool-Only)

Specifications:

Peak Torque	100 ft-lbs
IPM	0 – 4,300
RPM	0 – 3,200
Anvil Type	1/4" Friction Ring
Length / Weight	5.1" / 1.8 lbs

Includes: (1) M12™ REDLITHIUM™ XC4.0 Battery Pack, (1) M12™ REDLITHIUM™ CP2.0 Battery Pack, Belt Clip, Charger, Soft Carrying Case



M12 FUEL
3/8" Impact Wrench Kit

2454-22 (2454-20 Tool-Only)

Specifications:

Peak Torque	117 ft-lbs
IPM	0 – 3,500
RPM (2-Mode)	0 – 1,200 / 0 – 2,650
Anvil Type	3/8" Friction Ring
Length / Weight	6.5" / 2.4 lbs

Includes: (2) M12™ REDLITHIUM™ CP2.0 Battery Packs, Belt Clip, Charger, Carrying Case



M12™ 3/8" Impact Wrench Kit

2463-22 (2463-20 Tool-Only)

Specifications:

Peak Torque	100 ft-lbs
IPM	0 – 3,300
RPM	0 – 2,500
Anvil Type	3/8" Friction Ring
Length / Weight	6.5" / 2.3 lbs

Includes: (2) M12™ REDLITHIUM™ CP2.0 Battery Packs, Belt Clip, Charger, Carrying Case



M12™ 1/4" Impact Wrench Kit

2461-22 (2461-20 Tool-Only)

Specifications:

Peak Torque	38 ft-lbs
IPM	0 – 3,800
RPM	0 – 2,500
Anvil Type	1/4" Friction Ring
Length / Weight	6.0" / 2.1 lbs

Includes: (2) M12™ REDLITHIUM™ CP1.5 Battery Packs, Belt Clip, Charger, Carrying Case



M12 FUEL
1/2" Right Angle Impact Wrench w/ Friction Ring Kit

2565-22 (2565-20 Tool-Only)

Specifications:

Peak Torque	220 ft-lbs
IPM / RPM	0 – 3,600 / 0 – 3,000
Head Profile	2.2"
Length / Weight	14.2" / 3.3 lbs

Includes: (2) M12™ REDLITHIUM™ CP2.0 Battery Packs, Charger, Carrying Case
Related Accessory:
49-16-2564 M12 FUEL™ Right Angle Impact Wrench Rubber Boot



M12 FUEL
1/2" Right Angle Impact Wrench w/ Pin Detent Kit

2565P-22 (2565P-20 Tool-Only)

Specifications:

Peak Torque	220 ft-lbs
IPM / RPM	0 – 3,600 / 0 – 3,000
Head Profile	2.2"
Length / Weight	14.2" / 3.3 lbs

Includes: (2) M12™ REDLITHIUM™ CP2.0 Battery Packs, Charger, Carrying Case
Related Accessory:
49-16-2564 M12 FUEL™ Right Angle Impact Wrench Rubber Boot



M12 FUEL
3/8" Right Angle Impact Wrench w/ Friction Ring Kit

2564-22 (2564-20 Tool-Only)

Specifications:

Peak Torque	220 ft-lbs
IPM / RPM	0 – 3,600 / 0 – 3,000
Head Profile	2.2"
Length / Weight	14.2" / 3.2 lbs

Includes: (2) M12™ REDLITHIUM™ CP2.0 Battery Packs, Charger, Carrying Case
Related Accessory:
49-16-2564 M12 FUEL™ Right Angle Impact Wrench Rubber Boot



M12 FUEL
1/2" Ratchet Kit

2558-22 (2558-20 Tool-Only)

Specifications:

Fastening Torque	60 ft-lbs
RPM	0 – 175
Anvil Type	1/2" Ball Detent
Head Profile	1.1"
Length / Weight	12.5" / 3.1 lbs

Includes: (2) M12™ REDLITHIUM™ CP2.0 Battery Packs, Charger, Carrying Case
Related Accessory:
49-16-2558 M12 FUEL™ 1/2" Ratchet Rubber Boot



M12 FUEL
3/8" Ratchet Kit

2557-22 (2557-20 Tool-Only)

Specifications:

Fastening Torque	55 ft-lbs
RPM	0 – 200
Anvil Type	3/8" Ball Detent
Head Profile	1.1"
Length / Weight	11.8" / 2.8 lbs

Includes: (2) M12™ REDLITHIUM™ CP2.0 Battery Packs, Charger, Carrying Case
Related Accessory:
49-16-2557 M12 FUEL™ 3/8" Ratchet Rubber Boot



M12 FUEL
3/8" Extended Reach Ratchet Kit

2560-21 (2560-20 Tool-Only)

Specifications:

Fastening Torque	55 ft-lbs
RPM	0 – 200
Anvil Type	3/8" Ball Detent
Head Profile	1.1"
Length / Weight	15.1" / 3.1 lbs

Includes: (1) M12™ REDLITHIUM™ CP2.0 Battery Pack, Charger, Contractor Bag
Related Accessory:
49-16-2560 M12 FUEL™ 3/8" Extended Reach Ratchet Rubber Boot



M12 FUEL
1/4" Extended Reach Ratchet Kit

2559-21 (2559-20 Tool-Only)

Specifications:

Fastening Torque	40 ft-lbs
RPM	0 – 250
Anvil Type	1/4" Ball Detent
Head Profile	0.76"
Length / Weight	14.4" / 2.3 lbs

Includes: (1) M12™ REDLITHIUM™ CP2.0 Battery Pack, Charger, Contractor Bag
Related Accessory:
49-16-2559 M12 FUEL™ 1/4" Extended Reach Ratchet Rubber Boot



M12 FUEL
3/8" High Speed Ratchet Kit

2567-22 (2567-20 Tool-Only)

Specifications:

Fastening Torque	35 ft-lbs
RPM	0 – 450
Anvil Type	3/8" Ball Detent
Head Profile	0.75"
Length / Weight	11.1" / 2.1 lbs

Includes: (2) M12™ REDLITHIUM™ CP2.0 Battery Packs, Charger, Carrying Case
Related Accessories:
49-16-2567 M12 FUEL™ High Speed Ratchet Rubber Boot
49-09-2567 3/8" High Speed Ratchet Tall Shift Knob Assembly



M12 FUEL
1/4" High Speed Ratchet Kit

2566-22 (2566-20 Tool-Only)

Specifications:

Fastening Torque	35 ft-lbs
RPM	0 – 450
Anvil Type	1/4" Ball Detent
Head Profile	0.75"
Length / Weight	11.1" / 2.1 lbs

Includes: (2) M12™ REDLITHIUM™ CP2.0 Battery Packs, Charger, Carrying Case
Related Accessories:
49-16-2567 M12 FUEL™ High Speed Ratchet Rubber Boot
49-09-2566 1/4" High Speed Ratchet Tall Shift Knob Assembly



M12™ 3/8" Ratchet Kit

2457-21 (2457-20 Tool-Only)

Specifications:

Fastening Torque	35 ft-lbs
RPM	0 – 250
Anvil Type	3/8" Ball Detent
Head Profile	0.8"
Length / Weight	10.8" / 1.9 lbs

Includes: (1) M12™ REDLITHIUM™ CP1.5 Battery Pack, 3/8" – 1/4" Adapter, Charger, Soft Carrying Case



M12™ 1/4" Ratchet Kit

2456-21 (2456-20 Tool-Only)

Specifications:

Fastening Torque	30 ft-lbs
RPM	0 – 250
Anvil Type	1/4" Ball Detent
Head Profile	0.8"
Length / Weight	10.8" / 1.9 lbs

Includes: (1) M12™ REDLITHIUM™ CP1.5 Battery Pack, Charger, Soft Carrying Case



M12™ Rivet Tool Kit

2550-22 (2550-20 Tool-Only)

Specifications:

Pull Force	2,000 lbs
Stroke Length	0.8"
Rivet Sizes	3/32" – 3/16"
Rivet Material	Aluminum, Steel and Stainless Steel
Length / Weight	6.5" (without mandrel collector) / 4.5 lbs

Includes: (2) M12™ REDLITHIUM™ CP1.5 Battery Packs, (4) Nose Pieces (3/32", 1/8", 5/32", 3/16"), Belt Hook, Charger, Contractor Bag



M12 FUEL
5/8" SDS Plus Rotary Hammer Kit

2416-21XC

Specifications:

RPM	0 – 900
BPM	0 – 6,200
2-Mode Operation	Rotary Hammer and Rotation Only
Length / Weight	10.0" / 3.9 lbs

Includes: (1) M12™ REDLITHIUM™ XC4.0 Battery Pack, Charger, Carrying Case
Related Accessory:
2509-22 M12™ HAMMERVAC™ Universal Dust Extractor Kit



M12™ 1/2" SDS Plus Rotary Hammer Kit

2412-22XC (2412-20 Tool-Only)

Specifications:

RPM	0 – 800
BPM	0 – 5,350
2-Mode Operation	Rotary Hammer and Rotation Only
Length / Weight	9.0" / 3.9 lbs

Includes: (2) M12™ REDLITHIUM™ XC3.0 Battery Packs, Charger, Carrying Case
Related Accessory:
2509-22 M12™ HAMMERVAC™ Universal Dust Extractor Kit



M12™ HAMMERVAC™ Universal Dust Extractor

2509-22 (2509-20 Tool-Only)

Specifications:

Universal Handle System	Compatible with Major Brands of SDS Plus Rotary Hammers and AC and DC Hammer Drills
Replaceable Certified HEPA Filter	Filters 99.97% of Debris 0.3 Microns and Above
AUTOPULSE™	Filter Cleaning Mechanism achieves Table 1 OSHA Compliance
Self-Powered by M12™ REDLITHIUM™ Battery Pack	No Cords or Hoses for Maximum Portability
3-Mode Switch	Yes (Auto-On and Auto-Off w/ Delay)
Max Diameter	1-1/4"
Max Depth	8"

Includes: Small Diameter Nozzle, Large Diameter Nozzle;
2509-22 (2) M12™ REDLITHIUM™ CP2.0 Batteries, Charger, Contractor Bag
Related Accessories:
49-90-2302 M12™ HAMMERVAC™ Universal Dust Extractor Nozzle
49-90-2343 M12™ HAMMERVAC™ Universal Dust Extractor Dust Box, Filter
49-90-2016 3 pk Fleece Dust Bags





M12™ Palm Nailer Kit

2458-21 (2458-20 Tool-Only)

Specifications:

Impact Energy	2.2 ft-lbs (3.0 J)
BPM	0 – 2,700
Collet Capacity	6D – 16D
Head Profile	3/4"
Magnetic Tip	Yes
Weight	3.4 lbs

Includes: (1) M12™ REDLITHIUM™ CP1.5 Battery Pack, Hand Strap, Charger, Soft Carrying Case



M12™ 23 Gauge Pin Nailer Kit

2540-21 (2540-20 Tool-Only)

Specifications:

Nail Diameter	23 Gauge
Nail Size	1/2" – 1-3/8"
Magazine Capacity	120 Nails
Magazine Loading	Side Load
Firing Modes	Sequential
Length / Weight	8.7" / 3.8 lbs

Includes: (1) M12™ REDLITHIUM™ CP1.5 Battery Pack, Reversible Belt Clip, Jam Clearing Guide, Hex Wrench, Secondary Tip, Charger, Contractor Bag



M12™ 3/8" Crown Stapler Kit

2447-21 (2447-20 Tool-Only)

Specifications:

Staple Crown Size	3/8" Flat Crown
Staple Length	1/4" – 9/16"
Staple Type	T-50
Length / Weight	7.3" / 3.0 lbs

Includes: (1) M12™ REDLITHIUM™ CP1.5 Battery Pack, Charger, Contractor Bag



M12 FUEL 1/4" Right Angle Die Grinder Kit

2485-22 (2485-20 Tool-Only)

Specifications:

Power Output	0.3 HP
RPM	0 – 24,500
Collet Size	1/4"
Accessory Size	2"
Height / Length	8.7" / 4.5"
Weight	1.7 lbs

Includes: (2) M12™ REDLITHIUM™ CP2.0 Battery Packs, (2) Wrenches, Charger, Carrying Case

Related Accessories:

- 49-16-2485 M12 FUEL™ 1/4" Right Angle Die Grinder Rubber Boot
- 48-07-2486 1/4" Cut-Off Wheel Arbor
- 48-66-2486 1/8" Collet & Nut Kit
- 49-94-2000 2" Metal Cut-Off Wheel



M12 FUEL 1/4" Straight Die Grinder Kit

2486-22 (2486-20 Tool-Only)

Specifications:

Power Output	0.3 HP
RPM	0 – 21,000
Collet Size	1/4"
Accessory Size	2"
Height / Length	2" / 11"
Weight	1.6 lbs

Includes: (2) M12™ REDLITHIUM™ CP2.0 Battery Packs, (2) Wrenches, Charger, Carrying Case

Related Accessories:

- 48-07-2486 1/4" Cut-Off Wheel Arbor
- 48-66-2486 1/8" Collet & Nut Kit
- 49-94-2000 2" Metal Cut-Off Wheel



M12 FUEL 1/2" Digital Torque Wrench w/ ONE-KEY™ Kit

2466-22 (2466-20 Tool-Only)

Specifications:

Torque Range	12.5 – 150 ft-lbs
RPM	0 – 100
Tool Accuracy	CW: +/-2% of Full Scale / CCW: +/-3% of Full Scale (Range: 20% – 100% of Full Scale)
Ratcheting Angle	4.5°
Anvil Size	1/2" Ball Detent
Measuring Units	ft-lbs, in-lbs, Nm, kg-cm
Length / Weight	23.5" / 5.7 lbs

Includes: (2) M12™ REDLITHIUM™ CP2.0 Battery Packs, Certificate of Calibration, Charger, Carrying Case



M12 FUEL 3/8" Digital Torque Wrench w/ ONE-KEY™ Kit

2465-22 (2465-20 Tool-Only)

Specifications:

Torque Range	10 – 100 ft-lbs
RPM	0 – 100
Tool Accuracy	CW: +/-2% of Full Scale / CCW: +/-3% of Full Scale (Range: 20% – 100% of Full Scale)
Ratcheting Angle	4.5°
Anvil Size	3/8" Ball Detent
Measuring Units	ft-lbs, in-lbs, Nm, kg-cm
Length / Weight	23.3" / 5.5 lbs

Includes: (2) M12™ REDLITHIUM™ CP2.0 Battery Packs, Certificate of Calibration, Charger, Carrying Case



M12™ Spot Polisher Kit

2438-22X, 2438-22 (2438-20 Tool-Only)

Specifications:

Polishing RPM	0 – 2,800
Sanding RPM	0 – 8,300
Length / Weight	5.1" / 2.4 lbs

Includes: 2438-22X (1) M12™ REDLITHIUM™ XC3.0 Battery Pack, (1) M12™ REDLITHIUM™ CP1.5 Battery Pack; 2438-22 (2) M12™ REDLITHIUM™ CP1.5 Battery Packs; **All Kits Include:** 5 Pc Accessory Pack, Side Handle, Charger, Soft Carrying Case



M12 FUEL Low Speed Tire Buffer Kit

2409-22 (2409-20 Tool-Only)

Specifications:

DRIVE CONTROL™	2-Mode
Collet	7/16" Quick Change
RPM (Buffing)	0 – 2,500
RPM (Drilling)	0 – 1,200
Length / Weight	10.1" / 1.8 lbs

Includes: (1) M12™ REDLITHIUM™ XC4.0 Battery Pack, (1) M12™ REDLITHIUM™ CP2.0 Battery, Quick Change Adapter, Charger, Carrying Case
Related Accessories:
49-93-2410 2" Flared Contour Buffing Wheel
49-93-2409 2-1/2" Flared Contour Buffing Wheel



M12 FUEL 5-3/8" Circular Saw Kit

2530-21XC (2530-20 Tool-Only)

Specifications:

RPM	3,600
Bevel Capacity	50°
Cut Capacity	1-5/8" at 90°; 1-1/8" at 45°
Arbor	10 mm
Blade Guards	Aluminum
Weight	6.2 lbs

Includes: (1) M12™ REDLITHIUM™ XC4.0 Battery Pack, Circular Saw Blade, Wrench, Charger, Contractor Bag



M12 FUEL HACKZALL® One-Handed Reciprocating Saw Kit

2520-21XC (2520-20 Tool-Only)

Specifications:

SPM	0 – 3,000
Stroke Length	5/8"
Keyless Blade Clamp	QUIK-LOK™ (Accepts all SAWZALL® Blades)
Length / Weight	13.3" / 4.1 lbs

Includes: (1) M12™ REDLITHIUM™ XC4.0 Battery Pack, Charger, Contractor Bag



M12™ HACKZALL® One-Handed Reciprocating Saw Kit

2420-22, 2420-21 (2420-20 Tool-Only)

Specifications:

SPM	0 – 3,000
Stroke Length	1/2"
Keyless Blade Clamp	QUIK-LOK™ (Accepts all SAWZALL® Blades)
Length / Weight	11.0" / 2.6 lbs

Includes: 2420-22 (2) M12™ REDLITHIUM™ CP1.5 Battery Packs; 2420-21 (1) M12™ REDLITHIUM™ CP1.5 Battery Pack; **All Kits Include:** Charger, Contractor Bag



M12™ High Performance Jig Saw Kit

2445-21 (2445-20 Tool-Only)

Specifications:

SPM	0 – 2,800
Stroke Length	3/4"
Bevel Capacity	45° (Positive Locks at 90° and 45°)
Blade Clamp	QUIK-LOK™ T-Shank
Length / Weight	8.8" / 4.2 lbs

Includes: (1) M12™ REDLITHIUM™ CP1.5 Battery Pack, Anti-Splintering Insert, Non-Marring Shoe, Charger, Contractor Bag



M12 FUEL Oscillating Multi-Tool Kit

2526-21XC (2526-20 Tool-Only)

Specifications:

Speed Settings	12
OPM	10,000 – 20,000
Oscillation Angle	3.9°
Tool-Free Accessory Change	Yes
LED Light	Yes
Length / Weight	13" / 3.2 lbs

Includes: (1) M12™ REDLITHIUM™ XC4.0 Battery Pack, (5) Sanding Sheets, (1) Sanding Pad, (1) Wood Cutting Blade, Charger, Contractor Bag



M12™ Oscillating Multi-Tool Kit

2426-22, 2426-21 (2426-20 Tool-Only)

Specifications:

Speed Settings	12
OPM	5,000 – 20,000
Length / Weight	10.9" / 2.1 lbs

Includes: 2426-22 (2) M12™ REDLITHIUM™ CP1.5 Battery Packs; 2426-21 (1) M12™ REDLITHIUM™ CP1.5 Battery Pack; **All Kits Include:** Wood Cutting Blade, Sanding Pad, (5) Assorted Sanding Sheets, Charger, Contractor Bag



M12 FUEL HATCHET™ 6" Pruning Saw Kit

2527-21 (2527-20 Tool-Only)

Specifications:

Bar Length	6"
Chain Gauge	.043"
Chain Pitch	3/8" Low Profile
Chain Speed	5 m/s
Oiler	Automatic
Trigger	Variable Speed
Length / Weight	18.3" / 4.8 lbs

Includes: (1) M12™ REDLITHIUM™ XC4.0 Battery Pack, 6" Oregon® Bar & Chain, Scrench, Scabbard, Charger

Related Accessories: 49-16-2732 6" Saw Chain; 49-16-2733 6" Guide Bar



M12 FUEL Compact Band Saw Kit

2529-21XC (2529-20 Tool-Only)

Specifications:

SPM	0 – 570
Blade Size	30-9/16"
Cut Capacity	2-1/2" x 2-1/2"
LED Light	Yes
Hang Hook	Yes
Reamer Attachment	Yes
Compatibility	

Includes: (1) M12™ REDLITHIUM™ XC4.0 Battery Pack, 12/14 TPI Compact Extreme Thin Metal Band Saw Blade, Charger, Contractor Bag

Related Accessories: 49-90-2029 Compact Band Saw Reamer Attachment; 48-39-0630 30-9/16" 8/10 TPI Compact Extreme Thick Metal Band Saw Blade 3 pk; 48-39-0631 30-9/16" 12/14 TPI Compact Extreme Thick Metal Band Saw Blade 3 pk; 48-39-0635 30-9/16" 8/10 TPI Compact Extreme Thick Metal Band Saw Blade 25 pk; 48-39-0636 30-9/16" 12/14 TPI Compact Extreme Thick Metal Band Saw Blade 25 pk; 48-39-0637 30-9/16" 8/10 TPI Compact Extreme Thick Metal Band Saw Blade 100 bulk; 48-39-0639 30-9/16" 12/14 TPI Compact Extreme Thick Metal Band Saw Blade 100 bulk



M12™ Sub-Compact Band Saw Kit

2429-21XC (2429-20 Tool-Only)

Specifications:

SFPM	280
Blade Size	27"
Cut Capacity	1-5/8" x 1-5/8"
Length / Weight	11.0" / 6.7 lbs



Meets OSHA Guarding Requirements. Suitable for One-Handed Use.

Includes: (1) M12™ REDLITHIUM™ XC3.0 Battery Pack, 18 TPI Sub-Compact Portable Band Saw Blade, Charger, Carrying Case
Related Accessories: 48-39-0572 18 TPI Sub-Compact Portable Band Saw Blades (3 pk); 48-39-0711 12/14 TPI Extreme Metal Sub-Compact Portable Band Saw Blades (3 pk)



M12 FUEL 3" Compact Cut-Off Tool Kit

2522-21XC (2522-20 Tool-Only)

Specifications:

Blade Size	3"
RPM	20,000
Arbor Size	3/8"
Cut Depth	0.64"
Blade Rotation	Reversible
Length / Weight	8.9" / 2.4 lbs

Includes: (1) M12™ REDLITHIUM™ XC4.0 Battery Pack, Dust Accessory Shoe, (3) Accessory Blades (Metal Cut-Off, Carbide Abrasive, Diamond Tile), Blade Wrench, Charger, Contractor Bag



M12™ Rotary Tool Kit

2460-21 (2460-20 Tool-Only)

Specifications:

Speed Settings	6
RPM	5,000 – 32,000
Collet	1/8", Universal
Length / Weight	9.5" / 1.3 lbs

Includes: (1) M12™ REDLITHIUM™ CP1.5 Battery Pack, (5) Cutting Wheels, Mandrel, Wrench, Charger, Soft Carrying Case
Related Accessory: 49-94-1500 5 Pc Reinforced Cut-Off Wheels



M12™ 10 oz Caulk & Adhesive Gun Kit

2441-21 (2441-20 Tool-Only)

Specifications:

Force	400 lbs
Inches Per Minute	0 – 29
Speed Settings	6
Auto-Reverse Anti-Drip	Yes
Weight	4.1 lbs

Includes: (1) M12™ REDLITHIUM™ CP1.5 Battery Pack, 10 oz Carriage, M12™ 10 oz Plunger Rod and Piston Assembly, Charger



M12™ 20 oz Aluminum Barrel Sausage Style Caulk & Adhesive Gun Kit

2442-21

Specifications:

Force	400 lbs
Inches Per Minute	0 – 29
Speed Settings	6
Auto-Reverse Anti-Drip	Yes
Weight	4.9 lbs

Includes: (1) M12™ REDLITHIUM™ CP1.5 Battery Pack, 20 oz Aluminum Sausage Style Barrel, M12™ 20 oz Plunger Rod and Piston Assembly, Nozzle, Charger



M12™ Quart Caulk & Adhesive Gun Kit

2444-21

Specifications:

Force	400 lbs
Inches Per Minute	0 – 29
Speed Settings	6
Auto-Reverse Anti-Drip	Yes
Weight	5.5 lbs

Includes: (1) M12™ REDLITHIUM™ CP1.5 Battery Pack, Quart Carriage, M12™ Quart Plunger Rod and Piston Assembly, Charger



Caulk Gun Accessories

Compatible with 2441-21, 2442-21, 2444-21

31-12-0700 Caulk Gun Nozzle – Black
48-08-0900 M12™ 10 oz Caulk and Adhesive Gun Conversion Kit
48-08-0905 M12™ 20 oz Aluminum Barrel Sausage Style Caulk and Adhesive Gun Conversion Kit
48-08-0910 M12™ Quart Caulk and Adhesive Gun Conversion Kit
48-08-1091 20 oz Aluminum Barrel Kit
48-08-1096 20 oz Clear Barrel Kit

M12™ Grease Gun Kit

2446-21XC (2446-20 Tool-Only)

Specifications:

Output Pressure	Over 8,000 PSI
Run-Time	Up to 7 Grease Cartridges Per Charge
Grease Capacity	14 oz Cartridge, 16 oz Bulk, 16 oz Suction
Air Bleeder Valve	Yes
Weight	7.2 lbs

Includes: (1) M12™ REDLITHIUM™ XC3.0 Battery Pack, 36" Flex Hose with Spring Guard, Grease Coupler, Charger, Carrying Case



M12™ Soldering Iron Kit

2488-21 (2488-20 Tool-Only)

Specifications:

Max Temperature	750°F
Heat Output	90 Watts
Heat-Up Time	18 Seconds
Heat Indicator	Yes
Interchangeable Tips	Chisel and Point
Length / Weight	11.6" / 0.9 lbs

Includes: (1) M12™ REDLITHIUM™ CP1.5 Battery Pack, Chisel Tip, Pointed Tip, Charger, Carrying Case



M12™ Cable Stapler Kit

2448-21 (2448-20 Tool-Only)

Specifications:

Firing Mode	Sequential
Magazine Capacity	45
Magazine Loading	Front Load
Run-Time	1,200 Staplers per Charge on M12™ CP2.0 Battery
Length / Weight	6.5" / 5.0 lbs

Includes: (1) M12™ REDLITHIUM™ CP2.0 Battery Pack, Charger, Carrying Case
Related Accessory: MNM1-600 1" Insulated Cable Staples



M12™ Cable Stripper Kit

2435CU-21S, 2435AL-21, 2435X-21 (2435-20 Tool-Only)

Specifications:

Variable Speed Trigger	Yes
Tool Free Depth Gauge	Yes
Compatible Bushing Types	Industry Standard Quick-Change
Dimensions (L x W x H)	8.6" x 2.8" x 11.5"
Weight	3.6 lbs



Includes: 2435CU-21S 1/0 AWG – 750 MCM Cu THHN / XHHW Bushings; 2435AL-21 1/0 AWG – 750 MCM Al THHN / XHHW Bushings; 2435X-21 1/0 AWG – 500 MCM Cu RHW / RHH / USE Bushings;
All Kits Include: (1) M12™ REDLITHIUM™ CP2.0 Battery Pack, Multi-Voltage Charger, Carrying Case

Reference Available Bushings on Pg. 66



M12™ 600 MCM Cable Cutter Kit

2472-21XC (2472-20 Tool-Only)

Specifications:

Cut Capacity	600 MCM Copper, 750 MCM Aluminum, 1-3/16" Communication Cable
Jaw Opening	1-7/16"
Two-Speed	Yes
Length / Weight	10.5" / 6.7 lbs



Includes: (1) M12™ REDLITHIUM™ XC3.0 Battery Pack, Charger, Carrying Case
Related Accessory: 48-44-0410 M12™ 600 MCM Cable Cutter Blade

M12™ Plastic Pipe Shear Kit

2470-21 (2470-20 Tool-Only)

Specifications:

Cut Capacity	Up to 2" Schedule 80 PVC
Torque	1,900 in-lbs
Blade	3 mm Reinforced Stainless Steel
Length / Weight	14.4" / 4.4 lbs



Includes: (1) M12™ REDLITHIUM™ CP1.5 Battery Pack, Charger, Carrying Case
Related Accessory: 48-44-0405 M12™ Plastic Pipe Shear Blade

M12™ Copper Tubing Cutter Kit

2471-22, 2471-21 (2471-20 Tool-Only)

Specifications:

Cut Capacity	3/8" – 1" (1/2" – 1-1/8" O.D.)
Tubing Type	M, L and K Copper
RPM	500
Length / Weight	14.0" / 3.2 lbs



Includes: 2471-22 (2) M12™ REDLITHIUM™ CP1.5 Battery Packs; 2471-21 (1) M12™ REDLITHIUM™ CP1.5 Battery Pack;
All Kits Include: Charger, Carrying Case
Related Accessory: 48-38-0010 Copper Cutter Wheel (2 pk)



M12 FUEL ProPEX® Expander Kit w/ 1/2" – 1" RAPID SEAL™ ProPEX® Expander Heads

2532-22 (2532-20 Tool-Only)

Specifications:

Capacity	3/8" – 1"
Auto Rotate	Built-In
Trigger	Dual Actuating
Dimensions (L x W x H)	7.1" x 3.7" x 12.8"
Weight	4.5 lbs



Includes: (3) ProPEX® Expander Heads w/ RAPID SEAL™ (1/2", 3/4", 1"), ProPEX® Expander Cone Grease, Carrying Case; 2532-22 (2) M12™ REDLITHIUM™ CP2.0 Battery Packs, Charger
Related Accessories: 49-16-2414 1/2" ProPEX® Expander Head w/ RAPID SEAL™ 49-16-2415 5/8" ProPEX® Expander Head w/ RAPID SEAL™ 49-16-2416 3/4" ProPEX® Expander Head w/ RAPID SEAL™ 49-16-2418 1" ProPEX® Expander Head w/ RAPID SEAL™

M12™ ProPEX® Expansion Tool Kit

2432-22 (2432-20 Tool-Only)

Specifications:

Capacity	3/8" – 1"
Auto-Rotate	Built-In
Head Compatibility	3/8" – 1" M12™ / Uponor
Dimensions (L x W x H)	7.1" x 3.7" x 12.8"
Weight	5.0 lbs



Includes: (3) ProPEX® Expansion Heads (1/2", 3/4", 1"), ProPEX® Tool Cone Grease, Carrying Case; 2432-22 (2) M12™ REDLITHIUM™ CP1.5 Battery Packs, Charger
Related Accessories: 49-08-2400 ProPEX® Expander Cone Grease 49-16-2403 3/8" ProPEX® Expansion Head 49-16-2404 1/2" ProPEX® Expansion Head 49-16-2405 5/8" ProPEX® Expansion Head 49-16-2406 3/4" ProPEX® Expansion Head 49-16-2408 1" ProPEX® Expansion Head

M12™ PEX Expansion Tool Kit

2474-22

Specifications:

Capacity	3/8" – 1"
Auto-Rotate	Built-In
Head Compatibility	3/8" – 1" M12™
Dimensions (L x W x H)	7.1" x 3.7" x 12.8"
Weight	5.0 lbs



Includes: (2) M12™ REDLITHIUM™ CP1.5 Battery Packs, (3) PEX Expansion Heads (1/2", 3/4", 1"), PEX Tool Cone Grease, Charger, Carrying Case
Related Accessories: 49-16-2424 1/2" PEX Expander Head 49-16-2426 3/4" PEX Expander Head 49-16-2428 1" PEX Expander Head 49-08-2402 PEX Tool Grease



M12™ TRAPSSNAKE™ 6' Toilet Auger Kit

2576-21 (2576-20 Tool-Only)

Specifications:

RPM	0 – 500
Cable Lock	Yes
Cable Size	6' x 1/2"
Cable Head	Retriever Bulb
Replacement Cables	Available
Weight	9.0 lbs



Includes: (1) M12™ REDLITHIUM™ CP1.5 Battery Pack, Cable, Charger
Related Accessories: 48-53-2576 TRAPSSNAKE™ 6' Toilet Auger Replacement Cable 48-22-2576 TRAPSSNAKE™ Toilet Auger Case

M12™ TRAPSSNAKE™ 4' Urinal Auger Kit

2574-21 (2574-20 Tool-Only)

Specifications:

RPM	0 – 500
Cable Lock	Yes
Cable Size	4' x 3/8"
Cable Head	Bulb
Replacement Cables	Available
Weight	6.4 lbs



Includes: (1) M12™ REDLITHIUM™ CP1.5 Battery Pack, Cable, Charger
Related Accessories: 48-53-2577 TRAPSSNAKE™ 4' Urinal Auger Replacement Cable 48-22-2577 TRAPSSNAKE™ Urinal Auger Case

M12™ TRAPSSNAKE™ Driver Upgrade Kit

2575-21

Specifications:

RPM	500
Height	11"
Weight	4.5 lbs



Includes: (1) M12™ REDLITHIUM™ CP1.5 Battery Pack, Charger
Related Accessories: 49-16-2576 TRAPSSNAKE™ 6' Toilet Auger 49-16-2574 TRAPSSNAKE™ 4' Urinal Auger 49-16-2573 TRAPSSNAKE™ 25' Auger w/ CABLE DRIVE™

M12™ Pipeline Locator Kit

2580-21

Specifications:

Sonde Frequencies	512Hz, 640Hz, 8,192kHz, 33kHz, 83kHz
Line Trace	33kHz, 83kHz
Power Frequency	50Hz, 60Hz
Radio Frequency	10kHz – 22.7kHz Bandwidth
Display Type	4.3" Color LCD Display
Water & Dust Rating	IP65



Includes: (1) M12™ REDLITHIUM™ CP1.5 Battery Pack, Charger, Carrying Case



M12™ Drain Snake Kit

2571-21 (2571-20 Tool-Only)

Specifications:

Max Drain Line Capacity	1-1/4" – 2-1/2", Up to 25'
Drum Capacity	1/4" x 25', Best for 1-1/4" – 2" drain lines; 5/16" x 25', Best for 1-1/4" – 2-1/2" drain lines
Variable Speed Spin	0 – 500 RPM
LED Light	Yes
Weight (without cable)	6.5 lbs



Includes: (1) M12™ REDLITHIUM™ CP1.5 Battery Pack, 5/16" x 25' Inner Core Bulb Head Cable with Inner Drum, Charger, 5 Gallon Storage Bucket
Related Accessories: 48-53-2561 5/16" x 25' Inner Core Bulb Head Cable w/ RUST GUARD™ Plating 48-53-2562 5/16" x 25' Inner Core Drop Head Cable w/ RUST GUARD™ Plating 48-53-2563 1/4" x 25' Inner Core Bulb Head Cable w/ RUST GUARD™ Plating 48-53-2564 1/4" x 25' Inner Core Drop Head Cable w/ RUST GUARD™ Plating

M12™ AIRSNAKE™ Drain Cleaning Air Gun Kit

2572B-21, (2572B-20 Tool-Only)

Specifications:

Max Drain Line Capacity	1" – 4", Up to 35'
Automatic Pressure Loading	Yes
Variable Pressure	0 – 50 PSI
Variable Pressure Dial	Yes
LED Light	Yes
Length / Weight	20.8" / 7.1 lbs



Includes: 2572B-21 (1) M12™ REDLITHIUM™ CP2.0 Battery Pack, Charger;
All Kits Include: 2572B-20: 1" – 2" Drain Plug, 2" – 3" Drain Plug, 3" – 4" Drain Plug, Drain Shroud Attachment, Toilet Seal Attachment, 10" Extension, (3) Straight Connectors, 15" Offset Connector, Carrying Case



M12™ FORCE LOGIC™ Press Tool Kit

2473-22 (2473-20 No Jaw Kit)

Specifications:

Capacity	1/2" – 1-1/2" Varies by Material
Calibration Interval	32,000 Cycles (LED Indicator)
Approximate Cycle Time	5 Seconds
Press Force	5,400 lbs
Length / Weight	12.8" / 3.8 lbs

Includes: 2473-22 (3) Jaws (1/2", 3/4", 1"); 2473-20 (No Jaws Included); **All Kits Include:** (2) M12™ REDLITHIUM™ CP1.5 Battery Packs, Charger, Carrying Case

Related Accessories:

- 49-16-2450 1/2" CTS-V Press Jaw
- 49-16-2451 3/4" CTS-V Press Jaw
- 49-16-2452 1" CTS-V Press Jaw
- 49-16-2453 1-1/4" CTS-V Press Jaw
- 49-16-2450B 1/2" IPS-P Press Jaw
- 49-16-2451B 3/4" IPS-P Press Jaw
- 49-16-2452B 1" IPS-P Press Jaw
- 49-16-2451C 1/2" PEX-Crimp Press Jaw
- 49-16-2453C 3/4" PEX-Crimp Press Jaw
- 49-16-2454C 1" PEX-Crimp Press Jaw
- 49-16-2455C 1-1/4" PEX-Crimp Press Jaw
- 49-16-2456C 1-1/2" PEX-Crimp Press Jaw
- 49-16-2496B 1/2"-1" IPS-P Press Jaw Kit



M12™ M-SPECTOR FLEX™ 9 ft Inspection Camera Cable Kit

2316-21

Specifications:

Screen Size	3.5" High-Resolution LCD
Camera Resolution	640 x 480
Camera Head Diameter	12.5 mm (0.49")
Cable Length	9 ft
Wireless Distance	Up to 15 ft

Includes: (1) M12™ REDLITHIUM™ CP1.5 Battery Pack, SD Card, USB Cable, Charger, Carrying Case



M12™ M-SPECTOR FLEX™ 3 ft Inspection Camera Cable Kit

2315-21

Specifications:

Screen Size	3.5" High-Resolution LCD
Camera Resolution	640 x 480
Camera Head Diameter	12.5 mm (0.49")
Cable Length	3 ft
Wireless Distance	Up to 15 ft

Includes: (1) M12™ REDLITHIUM™ CP1.5 Battery Pack, SD Card, USB Cable, Charger, Carrying Case



M-SPECTOR FLEX™ Inspection Camera Accessories

Compatible with 2317-21, 2316-21, 2315-21

- 48-53-0155 M-SPECTOR FLEX™ 3 ft Inspection Camera Cable w/ PIVOTVIEW™
- 48-53-0151 M-SPECTOR FLEX™ 9 ft Inspection Camera Cable
- 48-53-0150 M-SPECTOR FLEX™ 3 ft Inspection Camera Cable



M12™ M-SPECTOR 360™ Rotating Inspection Scope Kit

2313-21 (2313-20 Tool-Only)

Specifications:

Screen Size	2.7" High-Resolution LCD
Display Resolution	320 x 240
Camera Head Diameter	9 mm (0.35")
Cable Length	3 ft
LED Brightness	4 LEDs, 5 Settings

Includes: (1) M12™ REDLITHIUM™ CP1.5 Battery Pack, Hook, Magnet, Mirror Attachments, Charger, Contractor Bag



M12™ M-SPECTOR 360™ 9 ft Rotating Inspection Scope Kit

2314-21

Specifications:

Screen Size	2.7" High-Resolution LCD
Display Resolution	320 x 240
Camera Head Diameter	9 mm (0.35")
Cable Length	9 ft
LED Brightness	4 LEDs, 5 Settings

Includes: (1) M12™ REDLITHIUM™ CP1.5 Battery Pack, Hook, Magnet, Mirror Attachments, Pipe Guide, Charger, Contractor Bag



M-SPECTOR 360™ Rotating Inspection Scope Accessories

Compatible with 2313-21, 2314-21

- 48-53-0112 3 Pc Accessory (Includes Hook, Magnet, Mirror Attachments)
- 48-53-0113 Pipe Guide Accessory



M12™ 12:1 Infrared TEMP-GUN™

2278-20 Tool-Only

Specifications:

Distance-to-Spot Ratio	12:1
Temperature Range	-22°F – 1,022°F (-30°C – 550°C)
Basic Accuracy	+/-1.8%
Max/Min/Avg/Dif	Yes
High/Low Alerts	Yes
Emissivity	Fixed, .95
Drop Test	6 ft

Battery and Charger Sold Separately



M12™ Green Laser Kit - 360° 3-Plane

3632-21

Specifications:

Range with Detector	165 ft
Working Range	125 ft
Accuracy	+/-1/8" @ 33 ft
Self-Leveling	+/-4° Tilt
Water & Dust Rating	IP54
Impact Resistant	1 m

Includes: (1) M12™ REDLITHIUM™ XC4.0 Battery Pack, Target, Charger, Carrying Case



M12™ Green Laser Kit - Cross Line & Plumb Points

3622-21 (3622-20 Tool-Only)

Specifications:

Range with Detector	165 ft
Working Range	125 ft
Accuracy	+/-1/8" @ 33 ft
Self-Leveling	+/-4° Tilt
Water & Dust Rating	IP54
Impact Resistant	1 m

Includes: (1) M12™ REDLITHIUM™ CP3.0 Battery Pack, Target, Charger, Carrying Case



USB Rechargeable Green Laser - Cross Line & Plumb Points

3522-21

Specifications:

Ranger with Detector	165 ft
Working Range	100 ft
Accuracy	+/-1/8" @ 33 ft
Self-Leveling	+/-4° Tilt
Water & Dust Rating	IP54
Impact Resistant	1 m

Includes: (1) REDLITHIUM™ USB 3.0 Battery, Heavy Duty Cord and Wall Plug, Riser, Carrying Case



USB Rechargeable Green Laser - Cross Line

3521-21

Specifications:

Ranger with Detector	165 ft
Working Range	100 ft
Accuracy	+/-1/8" @ 33 ft
Self-Leveling	+/-4° Tilt
Water & Dust Rating	IP54
Impact Resistant	1 m

Includes: (1) REDLITHIUM™ USB 3.0 Battery, Heavy Duty Cord and Wall Plug, Carrying Case



USB Rechargeable Green Laser - 3-Point

3510-21

Specifications:

Working Range	150 ft
Accuracy	+/-1/8" @ 33 ft
Self-Leveling	+/-4° Tilt
Water & Dust Rating	IP54
Impact Resistant	1 m

Includes: (1) REDLITHIUM™ USB 3.0 Battery, Heavy Duty Cord and Wall Plug, Carrying Case



Laser Accessories

Compatible with 3632-21, 3622-21, 3522-21, 3521-21, 3510-21

- 48-35-1211 165' Laser Line Detector
- 48-35-1411 72" Laser Tripod
- 48-35-1311 360° Laser Bracket
- 48-35-1111 Responsive Laser Alignment Target
- 48-35-1313 Laser Track Clip

M12™ ROCKET™ Dual Power Tower Light

2132-20 Tool-Only


Specifications:

Lumens	1,400 / 700
Modes	High, Low
Height	30.5" Collapsed, 5' 8" Fully Extended
Weight	6.7 lbs

Battery and Charger Sold Separately



POWERED BY



M12™ ROVER™ Service & Repair Flood Light w/ USB Charging

2367-20 Tool-Only

Specifications:

Lumens	700 / 250
Modes	High, Low
Run-Time (w/ M12™ XC4.0 Battery)	8 hr / 24 hr
Water & Dust Rating	IP54
USB Charger	2.1A USB Charging Port for External Devices



Battery and Charger Sold Separately

M12™ Metal Flashlight Kit

2355-21 (2355-20 Tool-Only)

Specifications:

Lumens	800 / 325 / 800
Modes	High, Medium, Strobe
Beam Distance	375 yd / 343 m
Beam Focus	Slide, Spot/Flood
Water & Dust Rating	IP54
Structure	6000 Series Aluminum, Type II Anodize Finish
Length / Weight	9.0" / 1.2 lbs



Includes: (1) M12™ REDLITHIUM™ CP1.5 Battery Pack, Lanyard, Charger

M12™ Spot Light

2353-20 Tool-Only

Specifications:

Lumens	750 / 400 / 750
Modes	High, Low, Strobe
Beam Distance	700 yd / 640 m
Water & Dust Rating	IP54
Length / Weight	6.1" / 1.4 lbs



Battery and Charger Sold Separately

Includes: Lanyard

M12™ Trouble Light w/ USB Charging

2362-20 Tool-Only

Specifications:

Lumens	400 / 200 / 40 / 400
Modes	High, Medium, Low, Strobe
Run-Time	Up to 67 Hours
Beam Pattern	Adjustable Task – Area
Water & Dust Rating	IPX4
Hands-Free	2 Hooks for Hanging
USB Charger	2.1A USB Charging Port for External Devices
Length / Weight	10.5" / 1.0 lb



Battery and Charger Sold Separately

M12™ ROVER™ Mounting Flood Light

2364-20 Tool-Only

Specifications:

Lumens	1,000 / 400 / 200
Modes	High, Medium, Low
Hands-Free	Integrated Magnet, Spring Loaded Clamp
Water & Dust Rating	IP54
Length / Weight	7.5" / 2.2 lbs



Battery and Charger Sold Separately

M12™ Underhood Light Kit

2125-21XC (2125-20 Tool-Only)

Specifications:

Lumens	1,350 / 600
Modes	High, Low
Hooks	FINISHGUARD™ to Resist Wear & Provide Lasting Protection
Length / Weight	48" Collapsed, 78" Fully Extended / 2.2 lbs



Includes: (1) M12™ REDLITHIUM™ XC4.0 Battery Pack, Charger



M12™ Underbody Light

2126-21 (2126-20 Tool-Only)

Specifications:

Lumens	1,200 / 800 / 600
Modes	High, Medium, Low
Water & Dust Rating	IP54
Mounting	Magnetic Base



Battery and Charger Sold Separately

Includes: 2126-21 M12™ Underbody Light, (1) M12™ REDLITHIUM™ XC4.0 Battery Pack, Charger; 2126-20 M12™ Underbody Light

M12™ Stick Light

2351-20 Tool-Only

Specifications:

Lumens	220
Hands-Free	Multi-Position Stainless Steel Hook
Water & Dust Rating	IP54
Length / Weight	9.3" / 0.6 lbs



Battery and Charger Sold Separately

Related Accessory:

49-24-2351 M12™ Stick Light Magnet Holds light to metal surfaces for hands-free use

M12™ Work Light

49-24-0146 Tool-Only

Specifications:

Lumens	100
Hands-Free	Integrated Magnet
Head Rotation	90°



Battery and Charger Sold Separately



M12™ Heated TOUGHSHELL™ Jacket Kit

Black 204B-21 (S – 3X)*, 204B-20 Jacket-Only ■ 204B
Gray 204G-21 (S – 3X)*, 204G-20 Jacket-Only ■ 204G
Red 204R-21 (S – 3X)*, 204R-20 Jacket-Only ■ 204R
Blue 204BL-21 (S – 3X)*, 204BL-20 Jacket-Only ■ 204BL



Specifications:

Heat Zones	3 (Chest, Back, Pockets)
Heat Settings	3 (High, Medium, Low)
Run-Time	Up to 12 Hours
Battery Pocket	Battery Pass-Thru, Front or Back Pocket
Outer Material	TOUGHSHELL™ Stretch Polyester
Wind / Water Resistant	Yes
Washer / Dryer Safe	Yes

Includes: (1) M12™ REDLITHIUM™ CP3.0 Battery Pack, Micro-USB 3 ft Cable and Wall Plug, Charger and Power Source

M12™ Women's Heated SOFTSHELL Jacket Kit

Black 232B-21 (S – 2X)*, 232B-20 Jacket-Only ■ 232B



Specifications:

Heat Zones	3 (Back, Collar, Pockets)
Heat Settings	3 (High, Medium, Low)
Run-Time	Up to 8 Hours
Outer Material	Polyester SOFTSHELL
Wind / Water Resistant	Yes
Washer / Dryer Safe	Yes

Includes: (1) M12™ REDLITHIUM™ CP2.0 Battery Pack, Micro-USB 3 ft Cable and Wall Plug, Charger and Power Source

M12™ Heated QUIETSHELL Jacket Kit

Camo 222C-21 (S – 3X)*, 222C-20 Jacket-Only ■ 222C



Specifications:

Heat Zones	3 (Chest, Back, Pockets)
Heat Settings	3 (High, Medium, Low)
Run-Time	Up to 8 Hours
Outer Material	QUIETSHELL Stretch Polyester
Wind / Water Resistant	Yes
Washer / Dryer Safe	Yes

Realtree EDGE © 2021 of Jordan Outdoor Enterprises, Ltd., all rights reserved

Includes: (1) M12™ REDLITHIUM™ CP2.0 Battery Pack, Micro-USB 3 ft Cable and Wall Plug, Charger and Power Source

M12™ Heated AXIS™ Layering System w/ HYDROBREAK™ Rain Shell Kit

Black/Gray 203RN-21 (S – 3X)*

Specifications:

Heat Zones	3 (Chest, Back, Shoulders)
Heat Settings	3 (High, Medium, Low)
Run-Time	Up to 8 Hours
Outer Material	Polyurethane Laminate / Ripstop Polyester
Waterproof	10K mm
Washer / Dryer Safe	Yes



Includes: HYDROBREAK™ Rain Shell, M12™ Heated AXIS™ Jacket, (1) M12™ REDLITHIUM™ CP2.0 Battery Pack, Micro-USB 3 ft Cable and Wall Plug, Charger and Power Source



M12™ Heated AXIS™ Layering System w/ GRIDIRON™ Work Shell Kit

Black 255B-21 (S – 3X)* ■ 255B

Specifications:

Heat Zones	3 (Chest, Back, Shoulders)
Heat Settings	3 (High, Medium, Low)
Run-Time	Up to 8 Hours
Outer Material	GRIDIRON™ Ripstop Polyester
Insulation	60G Body / 40G Sleeve
Washer / Dryer Safe	Yes



Includes: GRIDIRON™ Work Shell, M12™ Heated AXIS™ Jacket, (1) M12™ REDLITHIUM™ CP2.0 Battery Pack, Micro-USB 3 ft Cable and Wall Plug, Charger and Power Source

*MODEL NUMBER EXAMPLE
202B-21XL = M12™ Heated TOUGHSHELL™ Black Jacket Kit in Extra Large

M12™ Heated AXIS™ Jacket Kit

Black 203B-21 (S - 3X)*, 203B-20 Jacket-Only
Olive Green 203OG-21 (S - 3X)*, 203OG-20 Jacket-Only

Specifications:

Heat Zones	3 (Chest, Back, Shoulders)
Heat Settings	3 (High, Medium, Low)
Run-Time	Up to 8 Hours
Outer Material	AXIS™ Ripstop Polyester
Wind / Water Resistant	Yes
Washer / Dryer Safe	Yes



Includes: (1) M12™ REDLITHIUM™ CP2.0 Battery Pack, Micro-USB 3 ft Cable and Wall Plug, Charger and Power Source



M12™ Women's Heated AXIS™ Jacket Kit

Black 233B-21 (S - 2X)*, 233B-20 Jacket-Only

Specifications:

Heat Zones	3 (Chest, Back, Shoulders)
Heat Settings	3 (High, Medium, Low)
Run-Time	Up to 8 Hours
Outer Material	AXIS™ Ripstop Polyester
Wind / Water Resistant	Yes
Washer / Dryer Safe	Yes



Includes: (1) M12™ REDLITHIUM™ CP2.0 Battery Pack, Micro-USB 3 ft Cable and Wall Plug, Charger and Power Source



M12™ Heated AXIS™ Vest Kit

Black 303B-21 (S - 3X)*, 303B-20 Vest-Only

Specifications:

Heat Zones	2 (Chest, Back)
Heat Settings	3 (High, Medium, Low)
Run-Time	Up to 6 Hours
Outer Material	AXIS™ Ripstop Polyester
Wind / Water Resistant	Yes
Washer / Dryer Safe	Yes



Includes: (1) M12™ REDLITHIUM™ CP1.5 Battery Pack, M12™ Battery Holder, Charger

M12™ Women's Heated AXIS™ Vest Kit

Black 333B-21 (S - 2X)*, 333B-20 Vest-Only

Specifications:

Heat Zones	2 (Chest, Back)
Heat Settings	3 (High, Medium, Low)
Run-Time	Up to 6 Hours
Outer Material	AXIS™ Ripstop Polyester
Wind / Water Resistant	Yes
Washer / Dryer Safe	Yes



Includes: (1) M12™ REDLITHIUM™ CP1.5 Battery Pack, M12™ Battery Holder, Charger

M12™ Heated Hoodie Kit

Black 302B-21 (S - 3X)*, 302B-20 Hoodie-Only
Gray 302G-21 (S - 3X)*, 302G-20 Hoodie-Only
Red 302R-21 (S - 3X)*, 302R-20 Hoodie-Only
Navy Blue 302BL-21 (S - 3X)*, 302BL-20 Hoodie-Only

Specifications:

Heat Zones	2 (Chest, Back)
Heat Settings	3 (High, Medium, Low)
Run-Time	Up to 6 Hours
Wind Resistant	Yes
Washer / Dryer Safe	Yes



Includes: (1) M12™ REDLITHIUM™ CP1.5 Battery Pack, M12™ Battery Holder, Charger



USB Rechargeable WORKSKIN™ Heated Base Layer Kit

405B-21 (S - 3X)*

Specifications:

Heat Zones	2 (Chest, Back)
Heat Settings	2 (High, Low)
Run-Time	Up to 3 Hours
Material	WORKSKIN™ Midweight Fabric Construction
Washer / Dryer Safe	Yes



Includes: (2) REDLITHIUM™ USB 3.0 Batteries, USB Charger/Controller, Heavy Duty Cord and Wall Plug

USB Rechargeable Heated Gloves Kit

561-21 (M - XL)*

Specifications:

Heat Zones	2 (Fingers, Back of Hand)
Heat Settings	3 (High, Medium, Low)
Run-Time	Up to 6 Hours
Material	GRIDIRON™ Ripstop Polyester
Wind / Water Resistant	Yes



Includes: (2) REDLITHIUM™ USB Batteries, (2) USB Charger/Controllers, Heavy Duty Cord and Wall Plug

M18™ / M12™ Wireless Jobsite Speaker

2891-20 Tool-Only


Specifications:

Modes	Bluetooth®, AUX (Cable Not Included)
Bluetooth® Range	100 ft
USB Charging Port	2.1A USB Charging Port for External Devices



Battery and Charger Sold Separately

Includes: AC Adapter



M12™ Radio + Charger

2951-20 Tool-Only


Specifications:

Modes	AM, FM, Bluetooth®
Bluetooth® Range	100 ft
USB Charging Port	2.1A USB Charging Port for External Devices



Battery and Charger Sold Separately

Includes: AC Adapter, (2) AAA Batteries



M12™ Wireless Jobsite Speaker


2592-20 Tool-Only

Specifications:

Modes	Bluetooth®, AUX (Cable Not Included)
Bluetooth® Range	30 ft
USB Charging Port	2.1A USB Charging Port for External Devices



Battery and Charger Sold Separately



M12™ Compact Inflator Kit

2475-21XC (2475-20 Tool-Only)

Specifications:

PSI Rating	0 - 120 PSI
Hose Length	26"
Gauge Accuracy	+/- 3%
Duty Cycle	50% at 10 Minutes On and 10 Minutes Off
Height / Weight	7.5" / 2.2 lbs



Includes: (1) M12™ REDLITHIUM™ XC4.0 Battery Pack, (4) Attachments (Ball Inflation Needle, Presta Chuck, Inflator Nozzle, Schrader Chuck), Charger

M12™ Compact Spot Blower

0852-20 Tool-Only

Specifications:

Air Volume	175 CFM
Air Velocity	110 MPH
Length (without 10" extension)	15"
Height	8.5"
Width	4.7"
Weight	3.3 lbs



Battery and Charger Sold Separately

Includes: Extension Nozzle, Rubber Nozzle, Wide Sweeping Nozzle

M12 FUEL 1.6 Gallon Wet/Dry Vacuum Kit

0960-21 (0960-20 Tool-Only)

Specifications:

Air Volume	45 CFM
Suction (H ₂ O)	42"
Run-Time (w/ M12™ XC6.0 Battery)	Up to 26 Min
Inlet Diameter	1-1/4"
Weight	9.7 lbs



Includes: HEPA Filter, Crevice Tool, Utility Nozzle, Wall Mount, 5' Flexible Hose; **0960-21:** (1) M12™ REDLITHIUM™ XC6.0 Battery Pack, Charger
Related Accessories:
49-90-1900 HEPA Filter
49-90-2015 Foam Wet Filter
49-90-2017 1-1/4" Round Brush Tool
49-90-2018 Vacuum Power Tool Adapter



M12™ Compact Vacuum

0850-20 Tool-Only

Specifications:

Air Volume	33 CFM
Suction (H ₂ O)	15"
Run-Time (w/ M12™ XC4.0 Battery)	Up to 29 mins
Inlet Diameter	1-1/4"
Weight	2.3 lbs



Battery and Charger Sold Separately

Includes: Utility Nozzle, Extension Wand, Crevice Tool, Filter Assembly
Related Accessory:
49-90-1950 Filter

M12™ Power Source

49-24-2310

Specifications:

USB Charging Port	2.1A USB Charging Port for External Devices
On-Board Fuel Gauge	Yes
Powered By	All M12™ Batteries



Battery Sold Separately

Powers all MILWAUKEE® M12™ Heated Gear

Related Accessory:

48-59-1201 M12™ Compact Charger and Power Source

M12™ REDLITHIUM™ XC4.0 System Starter Kit

48-59-2440

Includes: (1) M12™ REDLITHIUM™ XC4.0 Battery Pack, Charger



M18™ & M12™ Rapid Charger

48-59-1808

Specifications:

Compatibility	All M18™ and M12™ Batteries
Charge Sequence	Sequential (First In, First Charged)
Charge Speed	Charges Individual Batteries up to 40% Faster
On-Board Indicator Light	Yes
Integrated Hang-Holes	Yes
Cell Voltage Monitoring	Yes



Batteries Sold Separately

M18™ & M12™ Multi-Voltage Charger

48-59-1812

Specifications:

Compatibility	All M18™ and M12™ Batteries
Charge Sequence	Sequential (First In, First Charged)
Integrated Hang-Holes	Yes
On-Board Indicator Light	Yes
Cell Voltage Monitoring	Yes



Batteries Sold Separately

M12™ REDLITHIUM™ CP2.0 System Starter Kit

48-59-2420

Includes: (1) M12™ REDLITHIUM™ CP2.0 Battery Pack, Charger



M18™ & M12™ Vehicle Charger

48-59-1810

Specifications:

Compatibility	All M18™ and M12™ Batteries
Charge Sequence	Sequential (First In, First Charged)
On-Board Indicator Light	Yes
Cell Voltage Monitoring	Yes



Batteries Sold Separately

M12™ Four Bay Sequential Charger

48-59-1204

Specifications:

Compatibility	All M12™ Batteries
Charge Sequence	Sequential (First In, First Charged)
Integrated Hang-Holes	Yes
Skip Button	Manually Designate which Battery Charges First
On-Board Indicator Light	Yes
Cell Voltage Monitoring	Yes



Batteries Sold Separately

M12™ Compact Charger and Power Source

48-59-1201

Specifications:

Compatibility	All M12™ Batteries
USB Charging Port	2.1A USB Charging Port for External Devices
On-Board Indicator Light	Yes
Cell Voltage Monitoring	Yes
Charges By	USB Port or AC Outlet



Battery Sold Separately

Includes: 3 ft Micro-USB Cable and 2.1A Wall Charger

M18™ & M12™ Rapid Charge Station

48-59-1807

Specifications:

Compatibility	All M18™ and M12™ Batteries
Charge Sequence	Charges 3 Batteries Simultaneously
Charge Speed	Charges Individual Batteries up to 40% Faster
Capacity	Holds (3) M18™ and (3) M12™ Batteries
Integrated Hang-Holes	Yes
Cell Voltage Monitoring	Yes
Pass-Through Plug	Yes



M12™ Charger

48-59-2401

Specifications:

Compatibility	All M12™ Batteries
Integrated Hang-Holes	Yes
On-Board Indicator Light	Yes
Cell Voltage Monitoring	Yes



Battery Sold Separately

Batteries Sold Separately

Pass-Through Plug

UPGRADE. OUTWORK. OUTLAST.

UP TO **3X** MORE RUN-TIME
UP TO **20%** MORE POWER
OVER **2X** MORE LIFE

REDLITHIUM™ CP3.0/XC6.0

M12 REDLITHIUM™ BATTERIES GUIDE



CP Less weight and smaller size

XC More power and run-time

48-11-2430
M12™ REDLITHIUM™ CP3.0 Battery Pack

48-11-2460
M12™ REDLITHIUM™ XC6.0 Battery Pack

48-11-2420
M12™ REDLITHIUM™ CP2.0 Battery Pack

48-11-2440
M12™ REDLITHIUM™ XC4.0 Battery Pack

48-11-2401
M12™ REDLITHIUM™ CP1.5 Battery Pack

48-11-2411
2-Pack


48-11-2402
M12™ REDLITHIUM™ XC3.0 Battery Pack

48-11-2412
2-Pack



PERSONAL LIGHTING

MILWAUKEE® delivers the industry's first line of trade focused, high performance personal lights designed to ADAPT, PERFORM AND SURVIVE. Built to withstand the toughest conditions on and off the jobsite, MILWAUKEE® lights combine the best cordless battery and LED technology delivering convenient, portable solutions that increase productivity and safety.



REDLITHIUM™ USB

RECHARGEABLE

ALL DAY RUN-TIME*

MORE RECHARGES

3X FASTER CHARGE TIME**

MILWAUKEE® delivers the industry's first line of trade focused, high performance personal lights designed to get maximum performance and user driven innovation with REDLITHIUM™ USB Personal Lights. REDLITHIUM™ USB lights combine the best in cordless battery and LED technology to deliver High Output with ALL DAY RUN-TIME, More Recharges and 3X Faster Charge Time. Get more from REDLITHIUM™ USB with one battery that powers multiple solutions.

POWERED BY



*Dependent on mode selection and based on 10 hour work day
**Compared to 0.5a charge rate



RECHARGEABLE

ALL NEW SUB-COMPACT RECHARGEABLE LIGHTS

Where work makes size critical, MILWAUKEE® Rechargeable Personal Lights leverage a built-in battery and USB charging to deliver high performance output and rechargeable capabilities in the most compact personal lights.

BUILT-IN BATTERY



REDLITHIUM™ USB Hard Hat Headlamp Kit 2111-21

Lumens	475 / 300 / 300, 150, 25
Modes	Spot/Flood, Spot – High, Flood – High/Medium/Low
Water & Dust Rating	IP54
Powered By	REDLITHIUM™ USB

Includes: (1) REDLITHIUM™ USB Battery, 2 ft Heavy Duty USB Cord, Hard Hat Clips



REDLITHIUM™ USB 1,100L Twist Focus Flashlight 2161-21

Lumens	1,100 / 600 / 100
Modes	High, Medium, Low
Spot Beam Distance	175 m
Beam Focus	Twist Focus, Spot/Flood
Water & Dust Rating	IP54
Powered By	REDLITHIUM™ USB

Includes: (1) REDLITHIUM™ USB 3.0 Battery, 2 ft Heavy Duty USB Cord



REDLITHIUM™ USB Low-Profile Headlamp Kit 2115-21

Lumens	600 / 350 / 125 / 25
Modes	High, Medium, Low, Eco
Battery Position	Rear
Water & Dust Rating	IP54
Powered By	REDLITHIUM™ USB

Includes: (1) REDLITHIUM™ USB Battery, 2 ft Heavy Duty USB Cord, (4) Hard Hat Clips



REDLITHIUM™ USB 800L Compact Flashlight 2160-20

Lumens	800 / 100
Modes	High, Low
Spot Beam Distance	150 m
Beam Focus	Bullseye Beam
Water & Dust Rating	IP54
Powered By	REDLITHIUM™ USB

Includes: (1) REDLITHIUM™ USB Battery Pack, 2 ft Heavy Duty USB Cord



REDLITHIUM™ USB BEACON™ Hard Hat Light Kit 2116-21

Lumens	600 / 400, 200, 25 / 400
Modes	Spot/Flood, Flood – High/Medium/Low, Spot – High
BEACON™ Mode	Steady & Blinking
Spot Beam Distance	125 m
Water & Dust Rating	IP54
Powered By	REDLITHIUM™ USB

Includes: (1) REDLITHIUM™ USB Battery, 2 ft Heavy Duty USB Cord, (2) Hard Hat Clips



REDLITHIUM™ USB ROVER™ Magnetic Flood Light Kit 2112-21

Lumens	445 / 100
Modes	High, Low
Hands-Free	Dual Magnets
Water & Dust Rating	IP54
Height	6.0"
Powered By	REDLITHIUM™ USB

Includes: (1) REDLITHIUM™ USB Battery, 2 ft Heavy Duty USB Cord



REDLITHIUM™ USB Pivoting Flashlight Kit 2113-21

Lumens	500 / 400 / 100
Modes	Spot – High, Flood – High, Flood – Low
Spot Beam Distance	155 m
Pivoting Head	110°
Water & Dust Rating	IP54
Height	6.3"
Powered By	REDLITHIUM™ USB

Includes: (1) REDLITHIUM™ USB Battery, 2 ft Heavy Duty USB Cord



REDLITHIUM™ USB ROVER™ Pivoting Flood Light Kit

2114-21

Lumens	550 / 250 / 100
Modes	High, Medium, Low
Pivoting Head	210°
Water & Dust Rating	IP54
Height	4.4"
Powered By	REDLITHIUM™ USB

Includes: (1) REDLITHIUM™ USB Battery, 2 ft Heavy Duty USB Cord



REDLITHIUM™ USB Portable Power Source and Charger Kit

48-59-2013

Cell Chemistry	LITHIUM-ION
On-Board Indicator Light	Yes
Cell Voltage Monitoring	Yes
USB Charging Port	2.1A USB Charging Port for External Devices
Height	3.9"

Includes: (1) REDLITHIUM™ USB Battery, REDLITHIUM™ USB Portable, 2 ft Heavy Duty USB Cord, Power Source and Charger



Rechargeable 250L Penlight w/ Laser

2010R

Lumens	250 / 50
Modes	High, Low
Water & Dust Rating	IP54
Laser	Integrated Laser Pointer
Powered By	Built-In-Battery

Includes: USB Charging Cable



REDLITHIUM™ USB Utility Hot Stick Light Kit

2119-22

Lumens	350, 100
Modes	Flood – High/Low
kV Rating	100kV
Water & Dust Rating	IP67
Height / Length	0.5" / 7.4"
Powered By	REDLITHIUM™ USB

Includes: (2) REDLITHIUM™ USB Batteries, 2 ft Heavy Duty USB Cord, REDLITHIUM™ USB Charger & Portable Power Source, 12V DC Vehicle Plug, 2.1A Wall Plug



Rechargeable 500L Every Day Carry Flashlight w/ Magnet

2011R

Lumens	500 / 100 / 10
Modes	High, Medium, Low
Water & Dust Rating	IP67
Hands-Free	Magnetic Mounting
Powered By	Built-In-Battery

Includes: USB Charging Cable, (4) Hard Hat Clips



REDLITHIUM™ USB3.0 Battery

48-11-2131

Amp Hours	3
Cell Chemistry	LITHIUM-ION
Voltage	4V



REDLITHIUM™ USB Portable Power Source and Charger

48-59-2012

Cell Chemistry	LITHIUM-ION
On-Board Indicator Light	Yes
Cell Voltage Monitoring	Yes
USB Charging Port	2.1A USB Charging Port for External Devices
Height	3.9"

Includes: REDLITHIUM™ USB Portable, 2 ft Heavy Duty USB Cord, Power Source and Charger



Rechargeable 450L Magnetic Headlamp and Task Light

2012R

Lumens	500 / 100 / 10
Modes	High, Medium, Low
Water & Dust Rating	IP67
Mounting	Detachable Magnetic Light Head
Powered By	Built-In-Battery

Includes: USB Charging Cable



MILWAUKEE® Penlight

2105

Lumens	100
Water & Dust Rating	IP67
Height	5.4"
Powered By	(2) AAA

Includes: (2) AAA Batteries



MILWAUKEE® Headlamp

2103

Lumens	350 / 150 / 25
Modes	High, Medium, Low
Impact Rating	2 m
Water & Dust Rating	IP54
Powered By	(3) AAA

Includes: (4) Hard Hat Clips, (3) AAA Batteries



MILWAUKEE® C I, II, III / D 1 Intrinsically Safe Spot/Flood Headlamp

2004hzi

Lumens	310 / 155 / 235 / 155 / 25
Modes	Spot/Flood Hybrid, Spot High, Flood High, Flood Medium, Flood Low
Intrinsically Safe Rating	Classes I, II, III / Division 1 Groups A – G
Impact Rating	9 ft
Water & Dust Rating	IP64
Powered By	(3) AAA

Includes: Rubber Strap, Nylon Strap, DUAL LOCK™ Adhesive, (4) Hard Hat Clips, Hex Wrench, (3) AAA Batteries



MILWAUKEE® Spot/Flood Headlamp

2104

Lumens	450 / 350, 150, 25 / 350
Modes	Spot/Flood, Flood – High/Medium/Low, Spot
Spot Beam Distance	100 m
Water & Dust Rating	IP54
Powered By	(3) AAA

Includes: (4) Hard Hat Clips, (3) AAA Batteries



MILWAUKEE® 325L Focusing Flashlight

2107

Lumens	325 / 25
Modes	High, Low
Spot Beam Distance	115 m
Beam Focus	Slide, Spot/Flood
Water & Dust Rating	IP67
Height	5.0"
Powered By	(3) AAA

Includes: (3) AAA Batteries



2107S Also Available, Includes Holster



ROVER™ Magnetic Flood Light

2108

Lumens	300 / 100
Modes	High, Low
Water & Dust Rating	IP54
Height	4.8"
Powered By	(2) AA

Includes: (2) AA Batteries



M12™ COMBO KITS

	2 PIECE KITS							4 PIECE KIT
	2459-22	2494-22	2497-22	2577-21	2582-22	2596-22	2598-22	2498-24
Kit Tool Total	2	2	2	2	2	2	2	4
M12 FUEL™ Low Speed Tire Buffer	■							
M12 FUEL™ 1/2" Hammer Drill/Driver					■		■	
M12™ 3/8" Hammer Drill/Driver			■					
M12 FUEL™ 1/2" Drill/Driver	■					■		
M12™ 3/8" Drill/Driver		■						■
M12 FUEL™ 1/4" Hex Impact Driver						■	■	
M12™ 1/4" Hex Impact Driver		■	■					■
M12 FUEL™ SURGE™ 1/4" Hex Hydraulic Driver					■			
M12™ HACKZALL® Reciprocating Saw								■
M12™ TRAPSSNAKE™ 6' Toilet Auger				■				
TRAPSSNAKE™ 4' Urinal Auger Extension				■				
M12™ Work Light								■
Also Includes								
M12™ Charger	■	■	■	■	■	■	■	■
M12™ REDLITHIUM™ CP1.5 Battery Pack		2	2	1				2
M12™ REDLITHIUM™ CP2.0 Battery Pack	1				1	1	1	
M12™ REDLITHIUM™ XC4.0 Battery Pack	1				1	1	1	
Carrying Case	■							
Contractor Bag		■	■		■	■	■	■



**PORTABLE PRODUCTIVITY
TRADE FOCUSED
SYSTEM WIDE**

M18 M12

RAPID CHARGER


- Charges All M18™ and M12™ Batteries
- Charges Batteries Sequentially (First In, First Charged)

CHARGES PACKS UP TO 40% FASTER



M12™ REDLITHIUM™ CP3.0/XC6.0


- Up to 3X More Run-Time
- Up to 20% More Power
- Over 2X More Life



**LEARN
MORE**



or visit <https://qr.mke.tt/298fv>



M18

**PERFORMANCE DRIVEN
TRADE FOCUSED
SYSTEM WIDE**

**ALL M18™ TOOLS FIT
M18™ BATTERIES**

200+ TOOLS




DRIVEN TO OUTPERFORM.™

For the first time in power tool history, M18 FUEL™ products are delivering game-changing corded performance without the cord. The motors on MILWAUKEE® M18 FUEL™ tools are more powerful and energy efficient – outliving any other brand. To add to the revolutionary technology, M18 FUEL™ possesses the smartest electronics found in any power tool. REDLINK PLUS™ electronics manage an array of power requirements across 200+ M18™ tools using one common battery. MILWAUKEE® built, the M18™ Battery delivers cleaner, more consistent power, lasts longer and delivers more run-time in the harshest jobsite conditions.

M18 FUEL

LONGER MOTOR LIFE | **MORE** POWER | **MORE** RUN-TIME



1 POWERSTATE™ BRUSHLESS MOTOR

This best-in-class brushless motor works harder and lives longer than all leading competitors.

- MILWAUKEE® Designed and Built Brushless Motor
- Outperforms All Leading Competitors
- Longer Motor Life



2 REDLINK PLUS™ INTELLIGENCE

The most advanced system of hardware and software in cordless power tool electronics today.

- Most Advanced Electronic System on the Market for Maximum Performance
- Total System Communication with Overload Protection Increases Tool Life



3 REDLITHIUM™ XC5.0 BATTERY PACK

Compatible with the entire M18™ System, it delivers more run-time, power and recharges than the competition.

- Most Durable Pack on the Market
- Over 2X More Recharges than Leading Competitor
- Fuel Gauge Displays Remaining Charge
- Operates Below -18°C / 0°F

NOW AVAILABLE

HIGH OUTPUT™

50% MORE POWER & RUNS COOLER
VS REDLITHIUM™ HD



REDLITHIUM™ HIGH OUTPUT™ HD12.0



**PERFORMANCE DRIVEN
TRADE FOCUSED
SYSTEM WIDE**

M18 FUEL
1/2" Hammer Drill/Driver w/ ONE-KEY™ Kit

2806-22 (2806-20 Tool-Only)

Specifications:

Peak Torque	1,200 in-lbs
RPM	0 – 550 / 0 – 2,000
BPM	0 – 32,000
DRIVE CONTROL™	3-Mode (Customizable)
Chuck Type	1/2" All Metal Ratcheting
Length / Weight	6.9" / 4.8 lbs

Includes: (2) M18™ REDLITHIUM™ XC5.0 Battery Packs, Belt Clip, Bit Holder, Side Handle, Multi-Voltage Charger, Carrying Case



M18™ 1/2" Hammer Drill/Driver Kit

2607-22, 2607-22CT (2607-20 Tool-Only)

Specifications:

Peak Torque	500 in-lbs
RPM	0 – 450 / 0 – 1,800
BPM	0 – 28,800
Chuck Type	1/2" All Metal Ratcheting
Length / Weight	7.8" / 4.5 lbs

Includes: 2607-22 (2) M18™ REDLITHIUM™ XC3.0 Battery Packs; 2607-22CT (2) M18™ REDLITHIUM™ CP1.5 Battery Packs;
All Kits Include: Multi-Voltage Charger, Carrying Case



M18 FUEL
1/2" Hammer Drill/Driver Kit

2804-22 (2804-20 Tool-Only)

Specifications:

Peak Torque	1,200 in-lbs
RPM	0 – 550 / 0 – 2,000
BPM	0 – 32,000
Chuck Type	1/2" All Metal Ratcheting
Length / Weight	6.9" / 4.8 lbs

Includes: (2) M18™ REDLITHIUM™ XC5.0 Battery Packs, Belt Clip, Bit Holder, Side Handle, Multi-Voltage Charger, Carrying Case



M18 FUEL
1/2" Drill/Driver w/ ONE-KEY™ Kit

2805-22 (2805-20 Tool-Only)

Specifications:

Peak Torque	1,200 in-lbs
RPM	0 – 550 / 0 – 2,000
DRIVE CONTROL™	3-Mode (Customizable)
Chuck Type	1/2" All Metal Ratcheting
Length / Weight	6.9" / 4.8 lbs

Includes: (2) M18™ REDLITHIUM™ XC5.0 Battery Packs, Belt Clip, Bit Holder, Side Handle, Multi-Voltage Charger, Carrying Case



M18 FUEL
1/2" Drill/Driver Kit

2803-22 (2803-20 Tool-Only)

Specifications:

Peak Torque	1,200 in-lbs
RPM	0 – 550 / 0 – 2,000
Chuck Type	1/2" All Metal Ratcheting
Length / Weight	6.9" / 4.8 lbs

Includes: (2) M18™ REDLITHIUM™ XC5.0 Battery Packs, Belt Clip, Bit Holder, Side Handle, Multi-Voltage Charger, Carrying Case



M18™ 1/2" Compact Brushless Drill/Driver Kit

2801-22CT (2801-20 Tool-Only)

Specifications:

Peak Torque	500 in-lbs
RPM	0 – 500 / 0 – 1,800
Chuck Type	1/2" All Metal Ratcheting
Length / Weight	6.5" / 3.7 lbs

Includes: (2) M18™ REDLITHIUM™ CP2.0 Battery Packs, Belt Clip, Multi-Voltage Charger, Carrying Case



M18™ 1/2" Compact Drill/Driver Kit

2606-22CT (2606-20 Tool-Only)

Specifications:

Peak Torque	500 in-lbs
RPM	0 – 450 / 0 – 1,800
Chuck Type	1/2" All Metal Ratcheting
Length / Weight	7.3" / 3.8 lbs

Includes: (2) M18™ REDLITHIUM™ CP1.5 Battery Packs, Multi-Voltage Charger, Carrying Case



M18 FUEL
Mud Mixer w/ 180° Handle Kit

2810-22 (2810-20 Tool-Only)

Specifications:

RPM	0 – 550
DRIVE CONTROL™	8-Speed Dial
Handle Type	180° Rotating Handle
Chuck Type	1/2" Keyed
Length / Weight	16.6" / 7.7 lbs

Includes: (2) M18™ REDLITHIUM™ XC5.0 Battery Packs, Chuck Key, Multi-Voltage Charger, Contractor Bag



M18 FUEL
HOLE HAWG® 1/2" Right Angle Drill Kit

2807-22 (2807-20 Tool-Only)

Specifications:

RPM	1 – 1,500
Chuck Type	1/2" All Metal Keyed
Capacity	For Augers up to 1-1/4"; Self-Feed Bits up to 2"
Built-In LED	Yes
Length / Weight	15.6" / 7.7 lbs

Includes: (2) M18™ REDLITHIUM™ HIGH OUTPUT™ XC6.0 Battery Packs, Chuck Key, Key Holder, Top Handle, Rapid Charger, Carrying Case



M18™ Brushless 1/2" Hammer Drill/Driver Kit

2902-22 (2902-20 Tool-Only)

Specifications:

Peak Torque	725 in-lbs
RPM	0 – 550 / 0 – 1,800
Chuck Type	1/2" All Metal Ratcheting
Length / Weight	7.0" / 4.6 lbs

Includes: (2) M18™ REDLITHIUM™ XC4.0 Battery Packs, Belt Clip, Side Handle, Multi-Voltage Charger, Carrying Case



M18™ 3/8" Right Angle Drill/Driver Kit

2615-21, 2615-21CT (2615-20 Tool-Only)

Specifications:

Peak Torque	125 in-lbs
RPM	0 – 1,500
Clutch Settings	11 Settings plus Drill Mode
Chuck Type	3/8" Single Sleeve
Head Profile	3-3/4"
Weight	4.3 lbs

Includes: 2615-21 (1) M18™ REDLITHIUM™ XC3.0 Battery Pack; 2615-21CT (1) M18™ REDLITHIUM™ CP1.5 Battery Pack;
All Kits Include: Multi-Voltage Charger, Carrying Case



M18 FUEL
HOLE HAWG® Right Angle Drill Kit w/ QUIK-LOK™

2808-22 (2808-20 Tool-Only)

Specifications:

RPM	1 – 1,500
Chuck Type	7/16" QUIK-LOK™
Capacity	For Augers up to 1-1/4"; Self-Feed Bits up to 2"
Built-In LED	Yes
Length / Weight	15.6" / 7.1 lbs

Includes: (2) M18™ REDLITHIUM™ HIGH OUTPUT™ XC6.0 Battery Packs, Top Handle, Rapid Charger, Carrying Case



M18 FUEL
SUPER HAWG™ 1/2" Right Angle Drill Kit

2809-22 (2809-20 Tool-Only)

Specifications:

RPM	0 – 1,550
Chuck Type	1/2" All Metal Keyed
Capacity	For Self-Feed Bits up to 4-5/8"; Hole Saws up to 6-1/4"
Length / Weight	20.5" / 14.4 lbs



RED LITHIUM
HIGH OUTPUT XC6.0

Includes: (2) M18™ REDLITHIUM™ HIGH OUTPUT™ XC6.0 Battery Packs, Top Handle, Side Handle, Chuck Key, Rapid Charger, Contractor Bag

M18 FUEL
SUPER HAWG™ Right Angle Drill Kit w/ QUIK-LOK™

2811-22 (2811-20 Tool-Only)

Specifications:

RPM	0 – 1,550
Chuck Type	7/16" Hex QUIK-LOK™
Capacity	For Self-Feed Bits up to 4-5/8"; Hole Saws up to 6-1/4"
Length / Weight	20.5" / 14.9 lbs



RED LITHIUM
HIGH OUTPUT XC6.0

Includes: (2) M18™ REDLITHIUM™ HIGH OUTPUT™ XC6.0 Battery Packs, Top Handle, Side Handle, Rapid Charger, Contractor Bag

M18 FUEL
1-1/2" Magnetic Drill Kit

2787-22HD

Specifications:

Capacity	1-1/2" Annular Cutter; 1/2" Twist Bit
RPM	400 / 690
Magnet	Operates Without Electricity
Dimensions (L x W x H)	13.8" x 7.5" x 15.5"
Weight	30.5 lbs



RED LITHIUM
HIGH OUTPUT XC8.0

Includes: (2) M18™ REDLITHIUM™ HIGH OUTPUT™ XC8.0 Battery Packs, Magnetic Lubrication Tank, 3/4" Weldon to 1/2" Chuck Adapter, Chuck Key, (2) 1" Retracting Pilot Pins, Safety Strap, Rapid Charger, Carrying Case

M18 FUEL
1-1/2" Lineman Magnetic Drill Kit

2788-22HD

Specifications:

Capacity	1-1/2" Annular Cutter; 1/2" Twist Bit
RPM	400 / 690
Magnet	Operates Without Electricity
Dimensions (L x W x H)	13.8" x 7.5" x 15.5"
Weight	30.4 lbs



RED LITHIUM
HIGH OUTPUT XC8.0

Includes: (2) M18™ REDLITHIUM™ HIGH OUTPUT™ XC8.0 Battery Packs, Magnetic Lubrication Tank, 3/4" Weldon to 1/2" Chuck Adapter, Chuck Key, (2) 1" Retracting Pilot Pins, Safety Strap, 12V Inverter, Rapid Charger, Carrying Case

M18 FUEL
1-3/4" SDS Max Rotary Hammer w/ ONE-KEY™ Kit

2718-22HD, 2718-21HD (2718-20 Tool-Only)

Specifications:

Impact Energy	8.1 ft-lbs
RPM	0 – 380
BPM	0 – 2,900
Clutch	AUTOSTOP™ E-Clutch
Vibration	10 m/s²
2-Mode Operation	Rotary Hammer and Hammer Only
Weight	19.7 lbs



RED LITHIUM
HIGH OUTPUT HD12.0

Includes: 2718-22HD (2) M18™ REDLITHIUM™ HIGH OUTPUT™ HD12.0 Battery Packs; 2718-21HD (1) M18™ REDLITHIUM™ HIGH OUTPUT™ HD12.0 Battery Pack;

All Kits Include: Side Handle, Grease Tube, Rapid Charger, Carrying Case



M18 FUEL
1-9/16" SDS Max Rotary Hammer Kit

2717-22HD (2717-20 Tool-Only)

Specifications:

RPM	0 – 450
BPM	0 – 3,000
Impact Energy	5.1 ft-lbs
2-Mode Operation	Rotary Hammer and Hammer Only
Weight	13.8 lbs



RED LITHIUM
HIGH OUTPUT XC8.0

Includes: (2) M18™ REDLITHIUM™ HIGH OUTPUT™ XC8.0 Battery Packs, Side Handle, Depth Rod, Rapid Charger, Carrying Case

M18 FUEL
1-1/8" SDS Plus Rotary Hammer w/ ONE-KEY™ & HAMMERVAC™ Dedicated Dust Extractor Kit

2915-22DE (2915-20 Tool-Only)

Specifications:

RPM	0 – 800
BPM	0 – 4,600
Impact Energy	3.6 ft-lbs
3-Mode Operation	Rotary Hammer, Hammer Only and Rotation Only
Weight	11.2 lbs



RED LITHIUM
HIGH OUTPUT XC6.0

Includes: (2) M18™ REDLITHIUM™ HIGH OUTPUT™ XC6.0 Battery Packs, HAMMERVAC™ Dedicated Dust Extractor, Side Handle w/ Depth Gauge, Large Diameter Dust Nozzle, Small Diameter Dust Nozzle, Rapid Charger, Carrying Case

M18 FUEL
HAMMERVAC™ 1-1/8" Dedicated Dust Extractor

2915-DE

Specifications:

Compatibility	For use with 2915-20
AUTOPULSE™ Filter Cleaning Mechanism	Yes
No Exposure Dust Removal	Yes
Max Depth Capacity	8"
Max Diameter Capacity	1-1/8"
Weight	4.3 lbs



Includes: Replacement Nozzle, HEPA Filter

M18 FUEL
1" SDS Plus Rotary Hammer Kit

2912-22, 2912-22DE (2912-20 Tool-Only)

Specifications:

RPM	0 – 1,330
BPM	0 – 4,800
Impact Energy	2 ft-lbs
3-Mode Operation	Rotary Hammer, Hammer Only and Rotation Only
Weight	9.1 lbs



RED LITHIUM
HIGH OUTPUT XC6.0

Includes: 2912-22 (2) M18™ REDLITHIUM™ HIGH OUTPUT™ XC6.0 Battery Packs; 2912-22DE (2) M18™ REDLITHIUM™ HIGH OUTPUT™ XC6.0 Battery Packs, HAMMERVAC™ Dedicated Dust Extractor, Large Diameter Dust Nozzle, Small Diameter Dust Nozzle;

All Kits Include: Side Handle w/ Depth Rod, Rapid Charger, Carrying Case



M18 FUEL
HAMMERVAC™ 1" Dedicated Dust Extractor

2912-DE

Specifications:

Compatibility	For use with 2912-20
AUTOPULSE™ Filter Cleaning Mechanism	Yes
No Exposure Dust Removal	Yes
Max Depth Capacity	6"
Max Diameter Capacity	1"
Weight	4.2 lbs



Includes: Replacement Nozzle, HEPA Filter

M18 FUEL
1" SDS Plus D-Handle Rotary Hammer Kit

2713-22 (2713-20 Tool-Only)

Specifications:

Capacity	1"
Impact Energy	2.2 ft-lbs
RPM	0 – 1,500
BPM	0 – 4,400
Length / Weight	16.5" / 8.5 lbs



Includes: 2713-22 (2) M18™ REDLITHIUM™ XC5.0 Battery Packs, Multi-Voltage Charger;

All Kits Include: Side Handle, Depth Rod, Carrying Case

Related Accessory: 2509-22 M12™ HAMMERVAC™ Universal Dust Extractor

M18™ 5/8" SDS Plus Rotary Hammer Kit

2612-22, 2612-21 (2612-20 Tool-Only)

Specifications:

RPM	0 – 1,300
BPM	0 – 7,000
Impact Energy	1.0 ft-lbs
2-Mode Operation	Rotary Hammer and Rotation Only
Weight	5.5 lbs



Includes: 2612-22 (2) M18™ REDLITHIUM™ XC3.0 Battery Packs;

2612-21 (1) M18™ REDLITHIUM™ XC3.0 Battery Pack;

All Kits Include: Side Handle, Depth Rod, Multi-Voltage Charger, Carrying Case

Related Accessory: 2509-22 M12™ HAMMERVAC™ Universal Dust Extractor

M18 FUEL
4' Concrete Pencil Vibrator Kit

2910-21 (2910-20 Tool-Only)

Specifications:

VPM	0 – 12,500
Head Diameter	1"
Square Head	Yes
Shaft Length	4 ft
Variable Speed Trigger	Yes
Overload Protection	Yes
Weight	11.1 lbs



RED LITHIUM
HIGH OUTPUT XC6.0

Includes: (1) M18™ REDLITHIUM™ HIGH OUTPUT™ XC6.0 Battery Pack, Rapid Charger

M18 FUEL
8' Concrete Pencil Vibrator Kit

2911-21 (2911-20 Tool-Only)

Specifications:

VPM	0 – 12,500
Head Diameter	1"
Square Head	Yes
Shaft Length	8 ft
Variable Speed Trigger	Yes
Overload Protection	Yes
Weight	14.3 lbs



RED LITHIUM
HIGH OUTPUT XC6.0

Includes: (1) M18™ REDLITHIUM™ HIGH OUTPUT™ XC6.0 Battery Pack, Rapid Charger

M18 FUEL
1/4" Hex Impact Driver w/ ONE-KEY™ Kit

2857-22, 2857-22CT (2857-20 Tool-Only)

Specifications:

Max Torque	2,000 in-lbs
IPM	0 – 4,300
RPM	0 – 3,600
DRIVE CONTROL™	4-Mode (Customizable)
Chuck Type	1/4" Hex
Single Hand Bit Insertion	Yes
Length / Weight	4.6" / 3.8 lbs

Includes: 2857-22 (2) M18™ REDLITHIUM™ XC5.0 Battery Packs;
2857-22CT (2) M18™ REDLITHIUM™ CP2.0 Battery Packs;
All Kits Include: Belt Clip, Bit Holder, Multi-Voltage Charger, Carrying Case



M18™ Compact Brushless 1/4" Hex Impact Driver Kit

2850-22CT (2850-20 Tool-Only)

Specifications:

Max Torque	1,600 in-lbs
IPM	0 – 4,200
RPM	0 – 3,400
Chuck Type	1/4" Hex
Length / Weight	5.1" / 2.9 lbs

Includes: (2) M18™ REDLITHIUM™ CP2.0 Battery Packs, Belt Clip, Multi-Voltage Charger, Carrying Case



M18 FUEL
1/4" Hex Impact Driver Kit

2853-22, 2853-22CT (2853-20 Tool-Only)

Specifications:

Max Torque	2,000 in-lbs
IPM	0 – 4,300
RPM	0 – 3,600
DRIVE CONTROL™	4-Mode
Chuck Type	1/4" Hex
Single-Handed Bit Insertion	Yes
Length / Weight	4.6" / 3.8 lbs

Includes: 2853-22 (2) M18™ REDLITHIUM™ XC5.0 Battery Packs;
2853-22CT (2) M18™ REDLITHIUM™ CP2.0 Battery Packs;
All Kits Include: Belt Clip, Bit Holder, Multi-Voltage Charger, Carrying Case



M18™ 1/4" Hex Compact Impact Driver Kit

2656-22CT (2656-20 Tool-Only)

Specifications:

Max Torque	1,500 in-lbs
IPM	0 – 3,450
RPM	0 – 2,750
Chuck Type	1/4" Hex Quick Change
Length / Weight	5.5" / 3.8 lbs

Includes: (2) M18™ REDLITHIUM™ CP1.5 Battery Packs, Belt Clip, Multi-Voltage Charger, Carrying Case



M18 FUEL
SURGE™ 1/4" Hex Hydraulic Driver Kit

2760-22, 2760-22CT (2760-20 Tool-Only)

Specifications:

Sustained Max Torque	450 in-lbs
IPM	0 – 4,000
RPM	0 – 3,000
DRIVE CONTROL™	4-Mode
Length / Weight	5.0" / 3.9 lbs

Includes: 2760-22 (2) M18™ REDLITHIUM™ XC5.0 Battery Packs;
2760-22CT (2) M18™ REDLITHIUM™ CP2.0 Battery Packs;
All Kits Include: Belt Clip, Bit Holder, Multi-Voltage Charger, Carrying Case



M18™ 1/4" 2-Speed Impact Driver Kit

2657-22, 2657-22CT (2657-20 Tool-Only)

Specifications:

Max Torque	1,500 in-lbs
IPM	0 – 3,450
RPM	0 – 2,750
Chuck Type	1/4" Hex Quick Change
Length / Weight	5.5" / 3.8 lbs

Includes: 2657-22 (2) M18™ REDLITHIUM™ XC3.0 Battery Packs;
2657-22CT (2) M18™ REDLITHIUM™ CP1.5 Battery Packs;
All Kits Include: Belt Clip, Multi-Voltage Charger, Carrying Case



M18™ Brushless 1/4" Hex 3-Speed Impact Driver

2851-20 Tool-Only

Specifications:

Max Torque	1,600 in-lbs
IPM	0 – 4,200
RPM	0 – 3,400
Chuck Type	1/4" Hex
DRIVE CONTROL™	3-Mode
Length / Weight	5.1" / 2.0 lbs

Battery and Charger Sold Separately

Includes: Belt Clip



M18 FUEL
1/4" Blind Rivet Tool w/ ONE-KEY™ Kit

2660-22CT (2660-20 Tool-Only)

Specifications:

Rivet Sizes	3/16" (4.8 mm), 7/32" (6.0 mm), 1/4" (6.4 mm), 9/32" (7.0 mm)
Rivet Material	Aluminum, Steel, Stainless Steel
Pull Force	4,500 lbs
Length / Weight	12.5" / 5.6 lbs

Includes: (2) M18™ REDLITHIUM™ CP2.0 Battery Packs, (4) Retention Nose Pieces, Nose Piece Wrench, Mandrel Collector, Hanging Ring, Belt Clip, Multi-Voltage Charger, Contractor Bag

Related Accessories:

49-16-2660NR Non-Retention Nose Piece 4 pk

49-16-2660EXT 6" Extension

49-16-2660B Protective Boot



M18 FUEL
Drywall Screw Gun Kit

2866-22, 2866-22CT (2866-20 Tool-Only)

Specifications:

RPM	0 – 4,500
Belt Clip	Yes
Auto Start Mode	Yes
Length / Weight	9.0" / 4.1 lbs

Includes: 2866-22 (2) M18™ REDLITHIUM™ XC5.0 Battery Packs;
2866-22CT (2) M18™ REDLITHIUM™ CP2.0 Battery Packs;
All Kits Include: Belt Clip, PR2 Bit, Multi-Voltage Charger, Contractor Bag

Related Accessory:

49-20-0001 MILWAUKEE® Collated Magazine

Screw Capacity: Up to 2"

Compatible with all major screw brands

Related Tool:

2627-22 M18™ Cut Out Tool Kit Pg. 52



M18™ Right Angle Impact Driver Kit

2667-22, 2667-21CT (2667-20 Tool-Only)

Specifications:

Max Torque (2-Mode)	350 / 675 in-lbs
IPM	0 – 2,400 / 0 – 3,400
RPM	0 – 1,500 / 0 – 2,250
Anvil Type	1/4" Hex
Length / Weight	14.1" / 3.9 lbs

Includes: 2667-22 (2) M18™ REDLITHIUM™ XC3.0 Battery Packs;
2667-21CT (1) M18™ REDLITHIUM™ CP1.5 Battery Pack;
All Kits Include: Belt Clip, Multi-Voltage Charger, Carrying Case



M18™ Right Angle Impact Wrench Kit

2668-22, 2668-21CT (2668-20 Tool-Only)

Specifications:

Fastening Torque (2-Mode)	30 / 60 ft-lbs
Nut-Busting Torque	60 ft-lbs
IPM	0 – 2,400 / 0 – 3,400
RPM	0 – 1,500 / 0 – 2,250
Anvil Type	3/8"
Length / Weight	14.3" / 3.9 lbs

Includes: 2668-22 (2) M18™ REDLITHIUM™ XC3.0 Battery Packs;
2668-21CT (1) M18™ REDLITHIUM™ CP1.5 Battery Pack;
All Kits Include: Belt Clip, Multi-Voltage Charger, Carrying Case



M18 FUEL
1/2" Compact Impact Wrench w/ Pin Detent w/ ONE-KEY™ Kit

2759-22, 2759B-22 (2759-20, 2759B-20 Tool-Only)

Specifications:

Fastening Torque	220 ft-lbs
Nut-Busting Torque	220 ft-lbs
IPM	0 – 3,200
RPM	0 – 2,500
DRIVE CONTROL™	4-Mode (Customizable)
Length / Weight	6.1" / 4.2 lbs

Includes: 2759-22 1/2" Compact Impact Wrench w/ Pin Detent w/ ONE-KEY™; 2759B-22 1/2" Compact Impact Wrench w/ Friction Ring w/ ONE-KEY™;
All Kits Include: (2) M18™ REDLITHIUM™ XC5.0 Battery Packs, Belt Clip, Bit Holder, Multi-Voltage Charger, Carrying Case



M18 FUEL
1/2" Compact Impact Wrench w/ Friction Ring Kit

2855-22 (2855-20 Tool-Only)

Specifications:

Fastening Torque	250 ft-lbs
Nut-Busting Torque	250 ft-lbs
IPM	0 – 3,500
RPM	0 – 2,400
DRIVE CONTROL™	4-Mode w/ Auto Shut-Off Mode & Bolt Removal Mode
Length / Weight	4.8" / 3.9 lbs

Includes: (2) M18™ REDLITHIUM™ XC5.0 Battery Packs, Belt Clip, Multi-Voltage Charger, Carrying Case



M18 FUEL
1/2" Compact Impact Wrench w/ Pin Detent Kit

2855P-22 (2855P-20 Tool-Only)

Specifications:

Fastening Torque	250 ft-lbs
Nut-Busting Torque	250 ft-lbs
IPM	0 – 3,500
RPM	0 – 2,400
DRIVE CONTROL™	4-Mode w/ Auto Shut-Off Mode & Bolt Removal Mode
Length / Weight	4.8" / 3.9 lbs

Includes: (2) M18™ REDLITHIUM™ XC5.0 Battery Packs, Belt Clip, Multi-Voltage Charger, Carrying Case



M18™ 1/2" Compact Impact Wrench Kit

2659-22 (2659-20 Tool-Only)

Specifications:

Fastening Torque	183 ft-lbs
Nut-Busting Torque	183 ft-lbs
IPM	0 – 3,350
RPM	0 – 2,450
Anvil Type	1/2" Pin Detent
Length / Weight	6.0" / 4.1 lbs

Includes: (2) M18™ REDLITHIUM™ XC3.0 Battery Packs, Belt Clip, Multi-Voltage Charger, Carrying Case



M18 FUEL

3/8" Impact Wrench w/ Friction Ring w/ ONE-KEY™ Kit

2758-22, 2758-22CT (2758-20 Tool-Only)

Specifications:

Fastening Torque	210 ft-lbs
Nut-Busting Torque	210 ft-lbs
IPM	0 – 3,200
RPM	0 – 2,500
DRIVE CONTROL™	4-Mode (Customizable)
Length / Weight	5.9" / 4.2 lbs

Includes: 2758-22 (2) M18™ REDLITHIUM™ XC5.0 Battery Packs; 2758-22CT (2) M18™ REDLITHIUM™ CP2.0 Battery Packs; **All Kits Include:** Belt Clip, Bit Holder, Multi-Voltage Charger, Carrying Case



M18 FUEL

1/2" Mid-Torque Impact Wrench w/ Friction Ring Kit

2962-22 (2962-20 Tool-Only)

Specifications:

Fastening Torque	650 ft-lbs
Nut-Busting Torque	550 ft-lbs
IPM	0 – 3,100
RPM	0 – 2,575
DRIVE CONTROL™	4-Mode w/ Auto Shut-Off Mode & Bolt Removal Mode
Length / Weight	6.0" / 5.1 lbs

Includes: (2) M18™ REDLITHIUM™ XC5.0 Battery Packs, Belt Clip, Multi-Voltage Charger, Carrying Case



M18 FUEL

1" High Torque Impact Wrench w/ ONE-KEY™ Kit

2867-22 (2867-20 Tool-Only)

Specifications:

Fastening Torque	1,500 ft-lbs
Nut-Busting Torque	1,800 ft-lbs
IPM	0 – 2,450
RPM	0 – 1,650
DRIVE CONTROL™	4-Mode (Customizable)
Length / Weight	10.9" / 13 lbs

Includes: (2) M18™ REDLITHIUM™ HIGH OUTPUT™ XC8.0 Battery Packs, Tool-Free Adjustable Handle, Lanyard Loop, Rapid Charger, Contractor Bag



REDLITHIUM HIGH OUTPUT XC8.0

M18 FUEL

1/2" High Torque Impact Wrench w/ Pin Detent w/ ONE-KEY™ Kit

2862-22 (2862-20 Tool-Only)

Specifications:

Fastening Torque	750 ft-lbs
Nut-Busting Torque	1,100 ft-lbs
IPM	0 – 2,400
RPM	0 – 1,800
DRIVE CONTROL™	4-Mode (Customizable)
Length / Weight	8.1" / 7.2 lbs

Includes: (2) M18™ REDLITHIUM™ XC5.0 Battery Packs, Multi-Voltage Charger, Carrying Case



M18 FUEL

3/8" Compact Impact Wrench w/ Friction Ring Kit

2854-22, 2854-22CT (2854-20 Tool-Only)

Specifications:

Fastening Torque	250 ft-lbs
Nut-Busting Torque	250 ft-lbs
IPM	0 – 3,500
RPM	0 – 2,400
DRIVE CONTROL™	4-Mode w/ Auto Shut-Off Mode & Bolt Removal Mode
Length / Weight	4.8" / 3.9 lbs

Includes: 2854-22 (2) M18™ REDLITHIUM™ XC5.0 Battery Packs; 2854-22CT (2) M18™ REDLITHIUM™ CP2.0 Battery Packs; **All Kits Include:** Belt Clip, Multi-Voltage Charger, Carrying Case



M18 FUEL

3/8" Mid-Torque Impact Wrench w/ Friction Ring Kit

2960-22, 2960-22CT (2960-20 Tool-Only)

Specifications:

Fastening Torque	600 ft-lbs
Nut-Busting Torque	550 ft-lbs
IPM	0 – 3,100
RPM	0 – 2,575
DRIVE CONTROL™	4-Mode w/ Auto Shut-Off Mode & Bolt Removal Mode
Length / Weight	6.0" / 5.0 lbs

Includes: 2960-22 (2) M18™ REDLITHIUM™ XC5.0 Battery Packs; 2960-22CT (2) M18™ REDLITHIUM™ CP2.0 Battery Packs; **All Kits Include:** Belt Clip, Multi-Voltage Charger, Carrying Case



M18 FUEL

3/4" High Torque Impact Wrench w/ Friction Ring w/ ONE-KEY™ Kit

2864-22 (2864-20 Tool-Only)

Specifications:

Fastening Torque	1,200 ft-lbs
Nut-Busting Torque	1,600 ft-lbs
IPM	0 – 1,850
RPM	0 – 1,850
DRIVE CONTROL™	4-Mode (Customizable)
Length / Weight	8.6" / 7.9 lbs

Includes: (2) M18™ REDLITHIUM™ XC5.0 Battery Packs, Belt Clip, Multi-Voltage Charger, Carrying Case



M18 FUEL

1/2" High Torque Impact Wrench w/ Pin Detent Kit

2766-22 (2766-20 Tool-Only)

Specifications:

Fastening Torque	750 ft-lbs
Nut-Busting Torque	1,100 ft-lbs
IPM	0 – 2,400
RPM	0 – 1,850
DRIVE CONTROL™	4-Mode w/ Bolt Removal Mode
Length / Weight	8.1" / 7.1 lbs

Includes: (2) M18™ REDLITHIUM™ XC5.0 Battery Packs, Multi-Voltage Charger, Carrying Case



M18™ 3/8" Compact Impact Wrench Kit

2658-22, 2658-22CT (2658-20 Tool-Only)

Specifications:

Fastening Torque	167 ft-lbs
Nut-Busting Torque	167 ft-lbs
IPM	0 – 3,350
RPM	0 – 2,450
Anvil Type	3/8" Friction Ring
Length / Weight	6.0" / 4.1 lbs

Includes: 2658-22 (2) M18™ REDLITHIUM™ XC3.0 Battery Packs; 2658-22CT (2) M18™ REDLITHIUM™ CP1.5 Battery Packs; **All Kits Include:** Belt Clip, Multi-Voltage Charger, Carrying Case



M18 FUEL

1" D-Handle High Torque Impact Wrench w/ ONE-KEY™ Kit

2868-22HD (2868-20 Tool-Only)

Specifications:

Fastening Torque	1,900 ft-lbs
Nut-Busting Torque	2,000 ft-lbs
IPM	0 – 1,440
RPM	0 – 1,200
DRIVE CONTROL™	4-Mode (Customizable)
Length / Weight	17.94" / 21 lbs

Includes: (2) M18™ REDLITHIUM™ HIGH OUTPUT™ HD12.0 Battery Packs, Tool-Free Adjustable Handle, Lanyard Loop, Rapid Charger, Contractor Bag



REDLITHIUM HIGH OUTPUT HD12.0

M18™ 3/4" High Torque Impact Wrench w/ Friction Ring Kit

2664-22 (2664-20 Tool-Only)

Specifications:

Fastening Torque	525 ft-lbs
Breakaway Torque	700 ft-lbs
IPM	0 – 2,200
RPM	0 – 1,900
Length / Weight	9.0" / 6.8 lbs

Includes: (2) M18™ REDLITHIUM™ XC3.0 Battery Packs, Multi-Voltage Charger, Carrying Case



M18™ 1/2" High Torque Impact Wrench w/ Pin Detent Kit

2662-22 (2662-20 Tool-Only)

Specifications:

Fastening Torque	450 ft-lbs
Breakaway Torque	640 ft-lbs
IPM	0 – 2,200
RPM	0 – 1,900
Length / Weight	8.9" / 6.7 lbs

Includes: (2) M18™ REDLITHIUM™ XC3.0 Battery Packs, Multi-Voltage Charger, Carrying Case



M18 FUEL

1/2" Mid-Torque Impact Wrench w/ Pin Detent Kit

2962P-22 (2962P-20 Tool-Only)

Specifications:

Fastening Torque	650 ft-lbs
Nut-Busting Torque	550 ft-lbs
IPM	0 – 3,500
RPM	0 – 2,400
DRIVE CONTROL™	4-Mode w/ Auto Shut-Off Mode & Bolt Removal Mode
Length / Weight	4.8" / 3.9 lbs

Includes: (2) M18™ REDLITHIUM™ XC5.0 Battery Packs, Belt Clip, Multi-Voltage Charger, Carrying Case



M18 FUEL

1" D-Handle Ext. Anvil High Torque Impact Wrench w/ ONE-KEY™ Kit

2869-22HD (2869-20 Tool-Only)

Specifications:

Fastening Torque	1,900 ft-lbs
Nut-Busting Torque	2,000 ft-lbs
IPM	0 – 1,440
RPM	0 – 1,200
DRIVE CONTROL™	4-Mode (Customizable)
Length / Weight	23.2" / 27.2 lbs

Includes: (2) M18™ REDLITHIUM™ HIGH OUTPUT™ HD12.0 Battery Packs, Tool-Free Adjustable Handle, Lanyard Loop, Rapid Charger, Contractor Bag



REDLITHIUM HIGH OUTPUT HD12.0

M18 FUEL

1/2" Ext. Anvil Controlled Torque Impact Wrench w/ ONE-KEY™ Kit

2769-22 (2769-20 Tool-Only)

Specifications:

Fastening Torque	750 ft-lbs
Nut-Busting Torque	1,100 ft-lbs
IPM	0 – 2,400
RPM	0 – 1,800
DRIVE CONTROL™	4-Mode (Customizable)
Anvil Type	1/2" Friction Ring
Length / Weight	10.1" / 5.8 lbs

Includes: (2) M18™ REDLITHIUM™ XC5.0 Battery Packs, Multi-Voltage Charger, Contractor Bag



M18 FUEL

1/2" High Torque Impact Wrench w/ Friction Ring w/ ONE-KEY™ Kit

2863-22 (2863-20 Tool-Only)

Specifications:

Fastening Torque	1,000 ft-lbs
Nut-Busting Torque	1,400 ft-lbs
IPM	0 – 2,100
RPM	0 – 1,750
DRIVE CONTROL™	4-Mode (Customizable)
Length / Weight	8.4" / 7.6 lbs

Includes: (2) M18™ REDLITHIUM™ XC5.0 Battery Packs, Multi-Voltage Charger, Carrying Case



M18 FUEL
1/2" High Torque Impact Wrench w/ Friction Ring Kit

2767-22 (2767-20 Tool-Only)

Specifications:

Fastening Torque	1,000 ft-lbs
Nut-Busting Torque	1,400 ft-lbs
IPM	0 – 2,100
RPM	0 – 1,750
DRIVE CONTROL™	4-Mode w/ Bolt Removal Mode
Length / Weight	8.4" / 7.5 lbs

Includes: (2) M18™ REDLITHIUM™ XC5.0 Battery Packs, Multi-Voltage Charger, Carrying Case



M18 FUEL
SUPER SAWZALL® Reciprocating Saw Kit

2722-21HD (2722-20 Tool-Only)

Specifications:

SPM	0 – 3,000
Stroke Length	1-1/4"
Blade Clamp	QUIK-LOK™ (Accepts all SAWZALL® Blades)
Speeds	5-Speeds
Orbital Action	Selectable; On/Off
Anti-Vibration	Yes
Weight	12.2 lbs

Includes: (1) M18™ REDLITHIUM™ HIGH OUTPUT™ HD12.0 Battery Pack, Rapid Charger, Contractor Bag



M18™ 1/2" High Torque Impact Wrench w/ Friction Ring Kit

2663-22 (2663-20 Tool-Only)

Specifications:

Fastening Torque	450 ft-lbs
Breakaway Torque	640 ft-lbs
IPM	0 – 2,200
RPM	0 – 1,900
Length / Weight	8.9" / 6.7 lbs

Includes: (2) M18™ REDLITHIUM™ XC3.0 Battery Packs, Multi-Voltage Charger, Carrying Case



M18 FUEL
7/16" Hex Utility High Torque Impact Wrench w/ ONE-KEY™ Kit

2865-22 (2865-20 Tool-Only)

Specifications:

Max Torque	750 ft-lbs
IPM	0 – 2,800
RPM	0 – 2,200
Bit Insertion	QUIK-LOK™ Single-Handed Bit Insertion
DRIVE CONTROL™	4 Modes (Customizable)
High Voltage Rating	69kV
Length / Weight	8.2" / 7.4 lbs

Includes: (2) M18™ REDLITHIUM™ XC5.0 Battery Packs, Lanyard Loop, 12V Inverter, Multi-Voltage Charger, Contractor Bag



M18 FUEL
SAWZALL® Reciprocating Saw Kit

2821-22, 2821-21 (2821-20 Tool-Only)

Specifications:

Stroke Length	1-1/4"
Blade Clamp	QUIK-LOK™ (Accepts all SAWZALL® Blades)
SPM	0 – 3,000
Adjustable Shoe	Yes
Hang Hook	Yes
Length / Weight	17.1" / 6.8 lbs

Includes: 2821-22 (2) M18™ REDLITHIUM™ XC5.0 Battery Packs; 2821-21 (1) M18™ REDLITHIUM™ XC5.0 Battery Pack;
All Kits Include: Multi-Voltage Charger, Carrying Case



M18™ SAWZALL® Reciprocating Saw Kit

2621-22, 2621-21 (2621-20 Tool-Only)

Specifications:

SPM	0 – 3,000
Stroke Length	1-1/8"
Blade Clamp	Lever-Action QUIK-LOK™ (Accepts all SAWZALL® Blades)
Anti-Vibration	Yes
Weight	7.9 lbs

Includes: 2621-22 (2) M18™ REDLITHIUM™ XC3.0 Battery Packs; 2621-21 (1) M18™ REDLITHIUM™ XC3.0 Battery Pack;
All Kits Include: Multi-Voltage Charger, Carrying Case



M18 FUEL
HACKZALL® One-Handed Reciprocating Saw Kit

2719-21 (2719-20 Tool-Only)

Specifications:

SPM	3,000
Stroke Length	7/8"
Blade Clamp	QUIK-LOK™ (Accepts all SAWZALL® Blades)
Weight	5.6 lbs

Includes: (1) M18™ REDLITHIUM™ XC5.0 Battery Pack, Multi-Voltage Charger, Contractor Bag



M18™ HACKZALL® One-Handed Reciprocating Saw Kit

2625-21, 2625-21CT (2625-20 Tool-Only)

Specifications:

SPM	0 – 3,000
Stroke Length	3/4"
Blade Clamp	QUIK-LOK™ (Accepts all SAWZALL® Blades)
Anti-Vibration	Yes
Weight	5.6 lbs

Includes: 2625-21 (1) M18™ REDLITHIUM™ XC3.0 Battery Pack; 2625-21CT (1) M18™ REDLITHIUM™ CP1.5 Battery Pack;
All Kits Include: Multi-Voltage Charger, Contractor Bag



M18 FUEL
7-1/4" Circular Saw Kit

2732-21HD (2732-20 Tool-Only)

Specifications:

RPM	5,800
Bevel Capacity	50°
Cut Capacity	2-1/2" at 90°; 1-7/8" at 45°
Arbor	5/8"
Blade Guards	Magnesium
Weight	12.0 lbs

Includes: (1) M18™ REDLITHIUM™ HIGH OUTPUT™ HD12.0 Battery Pack, Circular Saw Blade, Wrench, Rapid Charger, Contractor Bag



M18 FUEL
7-1/4" Rear Handle Circular Saw Kit

2830-21HD (2830-20 Tool-Only)

Specifications:

RPM	5,800
Bevel Capacity	53°
Cut Capacity	2-1/2" at 90°; 1-7/8" at 45°
Arbor	Diamond
Blade Guards	Magnesium
Weight	10.0 lbs

Includes: (1) M18™ REDLITHIUM™ HIGH OUTPUT™ HD12.0 Battery Pack, Circular Saw Blade, Wrench, Rapid Charger, Contractor Bag



M18™ Brushless 7-1/4" Circular Saw Kit

2631-21 (2631-20 Tool-Only)

Specifications:

RPM	5,000
Bevel Capacity	50°
Cut Capacity	2-1/2" at 90°; 1-7/8" at 45°
Arbor	5/8"
Blade Guards	Magnesium
Weight	8.8 lbs

Includes: (1) M18™ REDLITHIUM™ XC5.0 Battery Pack, Circular Saw Blade, Wrench, Multi-Voltage Charger, Contractor Bag



M18 FUEL
6-1/2" Circular Saw Kit

2730-22, 2730-21 (2730-20 Tool-Only)

Specifications:

RPM	5,000
Bevel Capacity	50°
Cut Capacity	2-3/16" at 90°; 1-5/8" at 45°
Arbor	5/8"
Blade Guards	Magnesium
Weight	8.0 lbs

Includes: 2730-22 (2) M18™ REDLITHIUM™ XC5.0 Battery Packs; 2730-21 (1) M18™ REDLITHIUM™ XC5.0 Battery Pack;
All Kits Include: Circular Saw Blade, Wrench, Multi-Voltage Charger, Contractor Bag



M18™ 6-1/2" Circular Saw Kit

2630-22 (2630-20 Tool-Only)

Specifications:

RPM	3,500
Bevel Capacity	50°
Cut Capacity	2-1/8" at 90°; 1-9/16" at 45°
Arbor	5/8"
Blade Guards	Plastic
Weight	8.5 lbs

Includes: (2) M18™ REDLITHIUM™ XC3.0 Battery Packs, Circular Saw Blade, Rip Fence, Wrench, Multi-Voltage Charger, Contractor Bag



M18 FUEL™ D-Handle Jig Saw Kit

2737-21 (2737-20 Tool-Only)

Specifications:

SPM	3,500
Stroke Length	1"
Bevel Capacity	45°
Blade Clamp	Lever-Action QUIK-LOK™ T-Shank
Orbital Settings	4
Weight	6.4 lbs

Includes: (1) M18™ REDLITHIUM™ XC5.0 Battery Pack, Dust Collection Tube, Shoe Guard, Anti-Splinter Guard, Dust Cover, Wrench, Multi-Voltage Charger, Carrying Case



M18™ Random Orbit Sander Kit

2648-21 (2648-20 Tool-Only)

Specifications:

OPM	12,000
Variable Speed	7,000 – 12,000 OPM
Pad Size	5.0"
Orbit Diameter	3/32"
Weight	2.7 lbs

Includes: (1) M18™ REDLITHIUM™ XC3.0 Battery Pack, (2) Pieces of 80 Grit Sandpaper, Universal Hose Adapter, Universal Hook & Loop Pad, Multi-Voltage Charger, Contractor Bag



M18™ 3-1/4" Planer Kit

2623-21 (2623-20 Tool-Only)

Specifications:

RPM	14,000
Planing Width	3-1/4"
Max Planing Depth	5/64"
Rabbet Depth	27/64"
Length / Weight	12.4" / 7.8 lbs

Includes: (1) M18™ REDLITHIUM™ XC3.0 Battery Pack, Bevel Edge Guide, (2) Double-Edged Carbide Blades, Multi-Voltage Charger, Contractor Bag



M18 FUEL™ Barrel Grip Jig Saw

2737B-20 Tool-Only

Specifications:

SPM	3,500
Stroke Length	1"
Bevel Capacity	45°
Blade Clamp	Lever-Action QUIK-LOK™ T-Shank
Orbital Settings	4
Weight	4.6 lbs

Battery and Charger Sold Separately

Includes: Dust Collection Tube, Shoe Guard, Anti-Splinter Guard, Dust Cover, LED Cover, Wrench



M18 FUEL™ Compact Router

2723-20 Tool-Only

Specifications:

RPM	10,000 – 31,000
Speeds	6
Collet Size	1/4"
Adjustable Range	1.5"
Height / Weight	6.9" / 3.0 lbs

Battery and Charger Sold Separately

Includes: Fixed Base, Straight Edge Guide, 5-3/4" Template Bushing Sub-base plate, Dust Shroud, 11/16" Collet Wrench, 7/16" Spindle Wrench

Related Accessories:

- 48-10-5601 Compact Router Plunge Base
- 48-10-5602 Compact Router Offset Base



M18 FUEL™ Oscillating Multi-Tool Kit

2836-21 (2836-20 Tool-Only)

Specifications:

Speed Settings	12
OPM	10,000 – 20,000
Oscillation Angle	4.2°
Auto-Load Feature	Yes
LED Light	Yes
Length / Weight	14.5" / 4.2 lbs

Includes: (1) M18™ REDLITHIUM™ XC5.0 Battery Pack, (5) Sanding Sheets, Sanding Pad, Wood Cutting Blade, Charger, Contractor Bag



M18™ Multi-Tool Kit

2626-22 (2626-20 Tool-Only)

Specifications:

Speed Settings	12
OPM	11,000 – 18,000
Tool-Free Accessory Change	Yes
Length / Weight	14.0" / 4.2 lbs

Includes: (2) M18™ REDLITHIUM™ XC3.0 Battery Packs, Wood Cutting Blade, Sanding Pad, (5) Assorted Sanding Sheets, Multi-Voltage Charger, Contractor Bag



M18™ Cut Out Tool Kit

2627-22, 2627-22CT (2627-20 Tool-Only)

Specifications:

RPM	28,000
Tool-Free Depth Adjustment	Yes
LED Light	Yes
Belt Clip	Yes
Length / Weight	8.9" / 1.8 lbs

Includes: 2627-22 (2) M18™ REDLITHIUM™ XC3.0 Battery Packs; 2627-22CT (2) M18™ REDLITHIUM™ CP1.5 Battery Packs; **All Kits Include:** Belt Clip, (2) 1/8" Drywall Bits, 1/8" Collet, 1/4" Collet, Wrench, Multi-Voltage Charger, Contractor Bag

Related Tool:

2866-22 M18 FUEL™ Drywall Screw Gun Kit Pg. 46



M18™ 10 oz Caulk and Adhesive Gun Kit

2641-21CT (2641-20 Tool-Only)

Specifications:

Force	950 lbs
Inches Per Minute	0 – 21
Speed Settings	6
Auto-Reverse Anti-Drip	Yes
Weight	5.8 lbs

Includes: (1) M18™ REDLITHIUM™ CP1.5 Battery Pack, 10 oz Carriage, M18™ 10 oz Plunger Rod and Piston Assembly, Multi-Voltage Charger



M18™ 20 oz Aluminum Barrel Sausage Style Caulk & Adhesive Gun Kit

2642-21CT

Specifications:

Force	950 lbs
Inches Per Minute	0 – 21
Speed Settings	6
Auto-Reverse Anti-Drip	Yes
Weight	6.5 lbs

Includes: (1) M18™ REDLITHIUM™ CP1.5 Battery Pack, 20 oz Aluminum Sausage Style Barrel, M18™ 20 oz Plunger Rod and Piston Assembly, Nozzle, Multi-Voltage Charger



M18™ 20 oz Clear Barrel Sausage Style Caulk & Adhesive Gun Kit

2643-21CT

Specifications:

Force	950 lbs
Inches Per Minute	0 – 21
Speed Settings	6
Auto-Reverse Anti-Drip	Yes
Weight	6.6 lbs

Includes: (1) M18™ REDLITHIUM™ CP1.5 Battery Pack, 20 oz Clear Sausage Style Barrel, M18™ 20 oz Plunger Rod and Piston Assembly, Nozzle, Multi-Voltage Charger



Caulk Gun Accessories

Compatible with 2641-21CT, 2642-21CT, and 2643-21CT

- 31-12-0700 Caulk Gun Nozzle – Black
- 48-08-1076 M18™ 10 oz Caulk and Adhesive Gun Conversion Kit
- 48-08-1091 20 oz Aluminum Barrel Kit
- 48-08-1093 M18™ 20 oz Aluminum Barrel Sausage Style Caulk and Adhesive Gun Conversion Kit
- 48-08-1094 M18™ 20 oz Clear Barrel Sausage Style Caulk and Adhesive Gun Conversion Kit
- 48-08-1095 M18™ Quart Caulk and Adhesive Gun Conversion Kit
- 48-08-1096 20 oz Clear Barrel Kit



M18 FUEL
7-1/4" Dual Bevel Sliding Compound Miter Saw Kit
 2733-21 (2733-20 Tool-Only)

Specifications:

Blade Size	7-1/4"
No Load RPM	5,000
Max Bevel Angle	48° / 48°
Max Miter Angle	48° / 48°
Max Vertical Capacity	3-1/2"
Max Horizontal Capacity	2x8
Weight	28.0 lbs

Includes: (1) M18™ REDLITHIUM™ XC5.0 Battery Pack, Blade Wrench, Blade, Clamp, Multi-Voltage Charger



M18 FUEL
8-1/4" Table Saw w/ ONE-KEY™ Kit
 2736-21HD (2736-20 Tool-Only)

Specifications:

RPM	6,300
Blade Size	8-1/4"
Arbor Size	5/8"
Max Bevel	47°
Cut Depth	2-1/2" at 90°; 1-3/4" at 45°
Rip Capacity	24" Left of Blade; 12" Right of Blade
Weight	45.0 lbs

Includes: (1) M18™ REDLITHIUM™ HIGH OUTPUT™ HD12.0 Battery Pack, Blade, Wrench, Anti-Kickback Pawls, Guard, Riving Knife, Fence, Push Stick, Miter Gauge, Rapid Charger



M18 FUEL
12" Dual Bevel Sliding Compound Miter Saw w/ ONE-KEY™ Kit
 2739-21HD (2739-20 Tool-Only)

Specifications:

Blade Size	12"
No Load RPM	3,500
Max Bevel Angle	48° / 48°
Max Miter Angle	50° / 60°
Max Vertical Capacity	6-3/4"
Max Horizontal Capacity	2x14
Weight	47.6 lbs

Includes: (1) M18™ REDLITHIUM™ HIGH OUTPUT™ HD12.0 Battery Pack, Blade, Clamp, Handles, Rapid Charger



M18 FUEL
10" Dual Bevel Sliding Compound Miter Saw Kit
 2734-21 (2734-20 Tool-Only)

Specifications:

Blade Size	10"
No Load RPM	4,000
Max Bevel Angle	48° / 48°
Max Miter Angle	50° / 60°
Max Vertical Capacity	5-3/4"
Max Horizontal Capacity	2x12
Weight	47.0 lbs

Includes: (1) M18™ REDLITHIUM™ HIGH OUTPUT™ XC8.0 Battery Pack, Blade Wrench, Carbide Tipped Blade, Clamp, Dust Bag, Rapid Charger



M18 FUEL
15 Gauge Finish Nailer Kit
 2839-21CT (2839-20 Tool-Only)

Specifications:

Nail Diameter	15 Gauge
Nail Size	1-1/4" – 2-1/2"
Magazine Capacity	110
Magazine Loading	Bottom Load
Max Fire Rate	3 Nails per Second
Nails Per Charge	750
Firing Modes	Sequential & Contact Actuation

Includes: (1) M18™ REDLITHIUM™ CP2.0 Battery Pack, Multi-Voltage Charger, Contractor Bag



M18 FUEL
16 Gauge Angled Finish Nailer Kit
 2841-21CT (2841-20 Tool-Only)

Specifications:

Nail Diameter	16 Gauge
Nail Size	1-1/4" – 2-1/2"
Magazine Capacity	110
Magazine Loading	Bottom Load
Max Fire Rate	3 Nails per Second
Nails per Charge	800
Firing Modes	Sequential & Contact Actuation

Includes: (1) M18™ REDLITHIUM™ CP2.0 Battery Pack, Multi-Voltage Charger, Contractor Bag



M18 FUEL
21° Framing Nailer Kit
 2744-21 (2744-20 Tool-Only)

Specifications:

Collation Angle	21° Round Head Nail
Nail Size	2" – 3-1/2"
Nail Collation	20° – 22°
Magazine Capacity	45 Nails
Max Fire Rate	3 Nails per Second
Firing Modes	Sequential or Contact Actuation

Includes: (1) M18™ REDLITHIUM™ XC5.0 Battery Pack, Rafter Hook, Hex Key, Multi-Voltage Charger, Contractor Bag
Related Accessory:
 48-08-2744 21° Framing Nailer Extended Capacity Magazine



M18 FUEL
30° Framing Nailer Kit
 2745-21 (2745-20 Tool-Only)

Specifications:

Collation Angle	30° Clipped or Full Head Nail
Nail Size	2" – 3-1/2"
Nail Collation	30° – 34°
Magazine Capacity	57 Nails
Max Fire Rate	3 Nails per Second
Firing Modes	Sequential or Contact Actuation

Includes: (1) M18™ REDLITHIUM™ XC5.0 Battery Pack, Rafter Hook, Hex Key, Multi-Voltage Charger, Contractor Bag
Related Accessory:
 48-08-2745 30° Framing Nailer Extended Capacity Magazine



M18 FUEL
18 Gauge Brad Nailer Kit
 2746-21CT (2746-20 Tool-Only)

Specifications:

Nail Diameter	18 Gauge
Nail Size	5/8" – 2-1/8"
Magazine Capacity	110 Nails
Max Fire Rate	3 Nails per Second
Magazine Loading	Side Load
Firing Modes	Sequential or Contact Actuation

Includes: (1) M18™ REDLITHIUM™ CP2.0 Battery Pack, Reversible Belt Hook, Multi-Voltage Charger, Contractor Bag



M18 FUEL
18 Gauge 1/4" Narrow Crown Stapler Kit
 2749-21CT (2749-20 Tool-Only)

Specifications:

Staple Diameter	18 Gauge
Staple Crown Size	1/4"
Staple Length	3/8" – 1-1/2"
Magazine Capacity	108 Staples
Max Fire Rate	4 Staples per Second
Magazine Loading	Front Load

Includes: (1) M18™ REDLITHIUM™ CP2.0 Battery Pack, Reversible Belt Hook, Multi-Voltage Charger, Contractor Bag



M18 FUEL
16 Gauge Straight Finish Nailer Kit
 2741-21CT (2741-20 Tool-Only)

Specifications:

Nail Diameter	16 Gauge
Nail Size	3/4" – 2-1/2"
Nail Collation Angle	0°
Magazine Capacity	110 Nails
Max Fire Rate	3 Nails per Second
Magazine Loading	Bottom Load
Length / Weight	11.9" / 7.2 lbs

Includes: (1) M18™ REDLITHIUM™ CP2.0 Battery Pack, Multi-Voltage Charger, Contractor Bag






M18™ SWITCH TANK™ 4-Gallon Backpack Water Supply Kit
2820-21WS

Specifications:

Tank Capacity	4 Gallon
Pump Type	Dual Diaphragm Pump
PSI Range	20 – 60 PSI (5 Modes)
Flow Rate Range	0.16 – 1.13 Gal/Min
Dry Weight	18.5 lbs

Includes: M18™ SWITCH TANK™ Powered Base, SWITCH TANK™ 4 Gallon Water Supply Tank Assembly, (1) M18™ REDLITHIUM™ XC3.0 Battery Pack, 10' Hose w/ Quick-Connect, Water Spray Nozzle, Multi-Voltage Charger



M18 FUEL™ 2 Gallon Compact Quiet Compressor
2840-20 Tool-Only

Specifications:

SCFM	1.2 @ 90 PSI
Capacity	2 Gallon
Sound Level	68 dB(a)
Dimensions (L x W x H)	16.3" / 18.5" / 10.3"
Weight	31.2 lbs
Regulator	Single Turn
Pump Type	Oil Free



Battery and Charger Sold Separately




M18™ SWITCH TANK™ 4-Gallon Backpack Concrete Sprayer Kit
2820-21CS

Specifications:

Tank Capacity	4 Gallon
Pump Type	Dual Diaphragm Pump
PSI Range	20 – 120 PSI (5 Modes)
Spray Distance	Up to 25'
Flow Rate Range	0.14 – 0.82 Gal/Min
Dry Weight	18.3 lbs

Includes: M18™ SWITCH TANK™ Powered Base, SWITCH TANK™ 4 Gallon Concrete Sprayer Tank Assembly, (1) M18™ REDLITHIUM™ XC3.0 Battery Pack, Adjustable Nozzle, Fan Nozzle, Multi-Voltage Charger



M18 FUEL™ 9" Cut-Off Saw w/ ONE-KEY™ Kit
2786-22HD (2786-20 Tool-Only)

Specifications:

RPM	6,600
Blade Size	9"
Arbor Size	7/8"
Cut Depth	3.4"
Load Indicator Light	Yes
Blade Brake	RAPIDSTOP™
Weight	10.6 lbs





Includes: (2) M18™ REDLITHIUM™ HIGH OUTPUT™ HD12.0 Battery Packs, Abrasive Blade, Diamond Blade, Wrench, Hex Key, Rapid Charger

SWITCH TANK™ Accessories

Compatible with 2820-20

Related Accessories:

- 49-16-28WS SWITCH TANK™ 4 Gallon Water Supply Tank Assembly
- 49-16-28CS SWITCH TANK™ 4 Gallon Concrete Sprayer Tank Assembly
- 49-16-28PS SWITCH TANK™ 4 Gallon Sprayer Tank Assembly



M18 FUEL™ Deep Cut Band Saw Kit
2729-22, 2729-21 (2729-20 Tool-Only)

Specifications:

SFPM	0 – 380
Cut Capacity	5" x 5"
Shoe	Tool-Free
LED Light	Yes
Hang Hook	Yes
Weight	15.9 lbs



Includes: 2729-22 (2) M18™ REDLITHIUM™ XC5.0 Battery Packs; 2729-21 (1) M18™ REDLITHIUM™ XC5.0 Battery Pack; **All Kits Include:** Blade, Multi-Voltage Charger, Carrying Case



M18 FUEL™ Deep Cut Dual-Trigger Band Saw Kit
2729S-22 (2729S-20 Tool-Only)

Specifications:

SFPM	0 – 380
Cut Capacity	5" x 5"
Shoe	Tool-Free Locking
LED Light	Yes
Hang Hook	Yes
Dual-Trigger Design	Yes
Weight	13.8 lbs



Includes: (2) M18™ REDLITHIUM™ XC5.0 Battery Packs, Set of Band Saw Blade Covers, Blade, Multi-Voltage Charger, Contractor Bag

M18 FUEL™ Compact Band Saw Kit
2829-22 (2829-20 Tool-Only)

Specifications:

SFPM	0 – 540
Cut Capacity	3-1/4" x 3-1/4"
Shoe	Tool-Free Locking
LED Light	Yes
Hang Hook	Yes
Dual-Trigger Design	No
Weight	7.7 lbs



Includes: (2) M18™ REDLITHIUM™ HIGH OUTPUT™ CP3.0 Battery Packs, Blade, Rapid Charger, Contractor Bag

M18 FUEL™ Compact Dual-Trigger Band Saw Kit
2829S-22

Specifications:

SFPM	0 – 540
Cut Capacity	3-1/4" x 3-1/4"
Shoe	Tool-Free Locking
LED Light	Yes
Hang Hook	Yes
Dual-Trigger Design	Yes
Weight	7.7 lbs



Includes: (2) M18™ REDLITHIUM™ HIGH OUTPUT™ CP3.0 Battery Packs, Set of Band Saw Blade Covers, Blade, Rapid Charger, Contractor Bag

Band Saw Accessories

Deep Cut Band Saw Accessory:

- Compatible with 2729-20, 2729S-22
- 49-90-2729 Deep Cut Band Saw Blade Covers

Compact Band Saw Accessories:

- Compatible with 2829-20, 2829S-22
- 49-90-2829 Compact Band Saw Blade Covers
- 49-90-2029 Compact Band Saw Reamer Attachment

M18 FUEL™ Metal Cutting Circular Saw Kit
2782-22 (2782-20 Tool-Only)

Specifications:

RPM	3,900
Blade Size	5-3/8" – 5-7/8"
Arbor Size	20 mm
Hang Hook	Yes
Length / Weight	4.7" / 6.5 lbs



Includes: (2) M18™ REDLITHIUM™ XC5.0 Battery Packs, 30T Blade, Multi-Voltage Charger, Contractor Bag

M18 FUEL™ 8" Metal Cutting Circular Saw Kit
2982-21 (2982-20 Tool-Only)

Specifications:

Blade Cut Capacity	2-9/16"
RPM	4,000
Arbor Size	5/8"
Chip Collection	Yes
Overload Indicator Light	Yes
Electric Blade Brake	Yes
Length / Weight	15.5" / 12.1 lbs



Includes: (1) M18™ REDLITHIUM™ HIGH OUTPUT™ XC8.0 Battery Pack, Blade, Allen Key, Rapid Charger, Contractor Bag

M18 FUEL

14" Abrasive Chop Saw Kit

2990-21HD (2990-20 Tool-Only)

Specifications:

RPM	4,000
RAPID STOP™	Yes
Blade Brake	
Tool-Free Blade Adjust	Yes
Tool-Free Fence Adjust	Yes
Cut Capacity	5"
Dimensions (L x W x H)	20.2" / 11.5" / 16.5"
Weight	38.1 lbs



Includes: (1) M18™ REDLITHIUM™ HIGH OUTPUT™ HD12.0 Battery Pack, Rapid Charger

M18 FUEL

7" / 9" Large Angle Grinder Kit

2785-22HD, 2785-21HD (2785-20 Tool-Only)

Specifications:

RPM	6,600
Switch Type	Dual-Action Trigger
Overload Protection	Yes
Electronic Clutch	Yes
Tool-Free Accessory Change and Guard	Yes
Length / Weight	18.5" / 11.9 lbs



Includes: 2785-22HD (2) M18™ REDLITHIUM™ HIGH OUTPUT™ HD12.0 Battery Packs; 2785-21HD (1) M18™ REDLITHIUM™ HIGH OUTPUT™ HD12.0 Battery Pack;

All Kits Include: 9" T27 Guard, Anti-Vibration Side Handle, Back Flange, Dust Vent Clip, FIXTEC™ Nut, Spanner Wrench, Rapid Charger, Carrying Case



M18 FUEL

4-1/2" - 6" Braking Grinder Kit Paddle Switch, No-Lock

2980-22, 2980-21 (2980-20 Tool-Only)

Specifications:

RPM	9,000
Switch Type	Paddle, No-Lock
Brake	Yes
Overload Protection	Yes
Electronic Clutch	Yes
Tool-Free Accessory Change and Guard	Yes
Length / Weight	15.0" / 5.3 lbs



Includes: 2980-22 (2) M18™ REDLITHIUM™ HIGH OUTPUT™ XC6.0 Battery Packs; 2980-21 (1) M18™ REDLITHIUM™ HIGH OUTPUT™ XC6.0 Battery Pack;

All Kits Include: T27 Guard, Side Handle, Back Flange, FIXTEC™ Nut, Wrench; Rapid Charger, Contractor Bag

M18 FUEL

4-1/2" - 6" Braking Grinder Kit Slide Switch, Lock-On

2981-22, 2981-21 (2981-20 Tool-Only)

Specifications:

RPM	9,000
Switch Type	Slide, Lock-On
Brake	Yes
Overload Protection	Yes
Electronic Clutch	Yes
Tool-Free Accessory Change and Guard	Yes
Length / Weight	15.0" / 5.3 lbs



Includes: 2981-22 (2) M18™ REDLITHIUM™ HIGH OUTPUT™ XC6.0 Battery Packs; 2981-21 (1) M18™ REDLITHIUM™ HIGH OUTPUT™ XC6.0 Battery Pack;

All Kits Include: T27 Guard, Side Handle, Back Flange, FIXTEC™ Nut, Wrench, Rapid Charger, Contractor Bag



M18 FUEL

4-1/2" / 5" Grinder Kit Paddle Switch, No-Lock

2780-22, 2780-21 (2780-20 Tool-Only)

Specifications:

RPM	8,500
Switch Type	Paddle, No-Lock
Power to Grind	Yes
Overload Protection	Yes
Electronic Clutch	Yes
Tool-Free Accessory Change and Guard	Yes
Length / Weight	15.0" / 8.2 lbs



Includes: 2780-22 (2) M18™ REDLITHIUM™ XC5.0 Battery Packs; 2780-21 (1) M18™ REDLITHIUM™ XC5.0 Battery Pack;

All Kits Include: Multi-Voltage Charger, Carrying Case



M18 FUEL

4-1/2" / 5" Grinder Kit Slide Switch, Lock-On

2781-22, 2781-21 (2781-20 Tool-Only)

Specifications:

RPM	8,500
Switch Type	Slide, Lock-On
Power to Grind	Yes
Overload Protection	Yes
Electronic Clutch	Yes
Tool-Free Accessory Change and Guard	Yes
Length / Weight	15.0" / 8.2 lbs



Includes: 2781-22 (2) M18™ REDLITHIUM™ XC5.0 Battery Packs; 2781-21 (1) M18™ REDLITHIUM™ XC5.0 Battery Pack;

All Kits Include: Multi-Voltage Charger, Carrying Case

M18 FUEL

4-1/2" / 5" Braking Grinder Kit

2783-22 (2783-20 Tool-Only)

Specifications:

RPM	8,500
Switch Type	Paddle, No-Lock
Brake	Yes
Clutch	Yes
Overload Protection	Yes
Tool-Free Accessory Change and Guard	Yes
Length / Weight	15.3" / 8.2 lbs



Includes: T27 Guard, T1 Guard, Side Handle, Flange Nut, FIXTEC™ Nut; 2783-22 (2) M18™ REDLITHIUM™ XC5.0 Battery Packs, Multi-Voltage Charger, Contractor Bag

M18 FUEL

4-1/2" / 5" Variable Speed Braking Grinder, Paddle Switch No-Lock

2888-20 Tool-Only

Specifications:

Wheel Diameter	4-1/2" / 5"
Switch Type	Paddle, No-Lock
No Load RPM	3,500 - 8,500
Spindle	5/8" - 11
E-Clutch / Kickback Protection	Yes
Overload Protection	Yes
Tool-Free Guard Change	Yes
Tool-Free Accessory Change	Yes
Anti-Vibration Handle	Yes
Length / Weight	13.18" / 3.16 lbs



Battery and Charger Sold Separately

M18 FUEL

1/4" Die Grinder Kit

2784-22 (2784-20 Tool-Only)

Specifications:

Collet Size	1/4"
RPM	20,000
Switch Type	Slide, Lock-On
Length / Weight	18.0" / 4.6 lbs



Includes: (2) M18™ REDLITHIUM™ XC5.0 Battery Packs, 11/16" Wrench, 1/2" Wrench, Multi-Voltage Charger, Carrying Case

M18 FUEL

5" Flathead Braking Grinder, Paddle Switch No-Lock

2886-20 Tool-Only

Specifications:

Wheel Diameter	5"
Switch Type	Paddle, No-Lock
No Load RPM	3,500-8,500
Spindle	5/8" - 11
E-Clutch / Kickback Protection	Yes
Overload Protection	Yes
Tool-Free Guard Change	Yes
Tool-Free Accessory Change	No
Anti-Vibration Handle	Yes
Length / Weight	14.02" / 3.1 lbs



Battery and Charger Sold Separately

M18 FUEL

5" Flathead Braking Grinder, Slide Switch Lock-On

2887-20 Tool-Only

Specifications:

Wheel Diameter	5"
Switch Type	Slide, No-Lock
No Load RPM	8,500
Spindle	5/8" - 11
E-Clutch / Kickback Protection	Yes
Overload Protection	Yes
Tool-Free Guard Change	Yes
Tool-Free Accessory Change	No
Anti-Vibration Handle	Yes
Length / Weight	14.02" / 3.1 lbs



Battery and Charger Sold Separately

M18™ 4-1/2" Cut-Off / Grinder Kit

2680-22 (2680-20 Tool-Only)

Specifications:

RPM	9,000
Switch	Paddle
Guard Adjustment	Tool-Free
Overload Protection	Yes
Weight	5.9 lbs



Includes: (2) M18™ REDLITHIUM™ XC3.0 Battery Packs, Type 1 Guard, Type 27 Guard, Spanner Wrench, Side Handle, Multi-Voltage Charger, Contractor Bag

M18 FUEL

4-1/2" / 5" Variable Speed Braking Grinder, Slide Switch Lock-On

2889-20 Tool-Only

Specifications:

Wheel Diameter	4-1/2" / 5"
Switch Type	Slide, Lock-On
No Load RPM	3,500 - 8,500
Spindle	5/8" - 11
E-Clutch / Kickback Protection	Yes
Overload Protection	Yes
Tool-Free Guard Change	Yes
Anti-Vibration Handle	Yes
Length / Weight	Yes



Battery and Charger Sold Separately

M18™ Compact Heat Gun Kit

2688-21 (2688-20 Tool-Only)

Specifications:

Temperature	750°F
Guarded Nozzle	Yes
Ladder Hook	Yes
Length / Weight	6.4" / 3.3 lbs

Includes: (1) M18™ REDLITHIUM™ XC5.0 Battery Pack, 3/8" Concentrator Nozzle, Hook Nozzle, Multi-Voltage Charger, Carrying Case



M18™ 14 Gauge Double Cut Shear Kit

2636-22 (2636-20 Tool-Only)

Specifications:

Head	14 Gauge Double Cut
360° Tool-Free Rotating Head	Yes
Variable Speed Trigger	Yes
Length / Weight	17.3" / 6.2 lbs

Includes: (2) M18™ REDLITHIUM™ XC3.0 Battery Packs, Hex Key, Belt Clip, Multi-Voltage Charger, Contractor Bag



M18™ 18 Gauge Single Cut Shear Kit

2637-22 (2637-20 Tool-Only)

Specifications:

Head	18 Gauge Single Cut
360° Tool-Free Rotating Head	Yes
Variable Speed Trigger	Yes
Length / Weight	18.0" / 5.8 lbs

Includes: (2) M18™ REDLITHIUM™ XC3.0 Battery Packs, Hex Key, Belt Clip, Multi-Voltage Charger, Contractor Bag



M18™ 18 Gauge Double Cut Shear Kit

2635-22 (2635-20 Tool-Only)

Specifications:

Head	18 Gauge Double Cut
360° Tool-Free Rotating Head	Yes
Variable Speed Trigger	Yes
Length / Weight	17.3" / 5.6 lbs

Includes: (2) M18™ REDLITHIUM™ XC3.0 Battery Packs, Hex Key, Belt Clip, Multi-Voltage Charger, Contractor Bag



M18 FUEL 7" Variable Speed Polisher Kit

2738-22, 2738-21 (2738-20 Tool-Only)

Specifications:

Capacity	7" Maximum
RPM	0 – 2,200
Variable Speed Dial and Trigger	Yes
Lock-On / Lock-Off	Yes
Length / Weight	19.8" / 6.4 lbs

Includes: 2738-22 (2) M18™ REDLITHIUM™ XC5.0 Battery Packs, Backing Pad; 2738-21 (1) M18™ REDLITHIUM™ HIGH OUTPUT™ XC8.0 Battery Pack;

All Kits Include: Screen Cover, Side Handle, Bail Handle with (2) Bolts, Rapid Charger



M18™ Brushless Threaded Rod Cutter Kit

2872-21 (2872-20 Tool-Only)

Specifications:

Cutting Capacity	1/4", 3/8" and 1/2"
Replacement Cutting Dies	Yes
Dimensions (L x W x H)	10.0" x 5.0" x 6.3"
Weight	7.7 lbs

Includes: (1) M18™ REDLITHIUM™ CP2.0 Battery Pack, Cutting Dies, Allen Key, Multi-Voltage Charger, Carrying Case

Related Accessory: 48-44-2872 1/4", 3/8", 1/2" Replacement Cutting Die Set



M18™ 2-Speed Grease Gun Kit

2646-22CT, 2646-21CT (2646-20 Tool-Only)

Specifications:


Output Pressure	Up to 10,000 PSI (690 BAR)
Run-Time	Up to 10 Cartridges Per Charge
Grease Capacity	14 oz Cartridge, 16 oz Bulk, 16 oz Suction
Air Bleeder Valve	Yes
Weight	8.5 lbs

Includes: 2646-22CT (2) M18™ REDLITHIUM™ CP1.5 Battery Packs; 2646-21CT (1) M18™ REDLITHIUM™ CP1.5 Battery Pack;

All Kits Include: 48" Flex Hose with Spring Guard, High Pressure Grease Coupler, Shoulder Strap, Multi-Voltage Charger, Carrying Case

Related Accessories:

- 49-16-2646 M18™ Grease Gun 400g Clear Barrel
- 49-16-2647 M18™ Replacement Grease Gun Hose with High Pressure Coupler
- 49-16-2648 M18™ Right Angle Grease Gun Coupler
- 49-16-2649 M18™ High Pressure Grease Coupler (2 pk)



M18™ FORCE LOGIC™ 6T Utility Crimper Kits



w/ BG-D3 Jaw
2678-22BG
(2678-20 Tool-Only)



w/ O-D3 Jaw
2678-22O
(2678-20 Tool-Only)



w/ Snub Nose Jaw
2678-22
(2678-20 Tool-Only)



w/ Kearney Jaw
2678-22K
(2678-20 Tool-Only)

Specifications:

Output Force	6 Tons
Adaptive Pressure Control System	Yes; PFM™
Reporting and Tool Diagnostics	Built-In; ONE-KEY™ Compatible
Cycle Time	2.9 Seconds
Head Rotation	340°
Height / Length	5.4" / 14.0"

Includes: 2678-22BG 6T Fixed BG Crimping Jaw; 2678-22O 6T Fixed O Crimping Jaw; 2678-22 6T Snub Nose Crimping Jaw; 2678-22K 6T Kearney Crimping Jaw; **All Kits Include:** (2) M18™ REDLITHIUM™ CP2.0 Battery Packs, Multi-Voltage Charger, Utility Bag

M18™ FORCE LOGIC™ 6T Pistol Utility Crimper Kits



w/ BG-D3 Jaw
2977-22BG
(2977-20 Tool-Only)



w/ O-D3 Jaw
2977-22O
(2977-20 Tool-Only)

Specifications:

Output Force	6 Tons
Adaptive Pressure Control System	Yes; PFM™
Reporting and Tool Diagnostics	Built-In; ONE-KEY™ Compatible
Cycle Time	2.9 Seconds
Head Rotation	340°
Height / Length	12.3" / 17.3"

Includes: 2977-22BG 6T Fixed BG Crimping Jaw; 2977-22O 6T Fixed O Crimping Jaw; **All Kits Include:** (2) M18™ REDLITHIUM™ CP2.0 Battery Packs, Multi-Voltage Charger, Utility Bag



M18™ FORCE LOGIC™ 6T Utility Crimper Accessories

Compatible with 2678-20, 2977-20, 2978-20

6T Utility Crimper Jaws

- 49-16-BGD3 6T Fixed BG Crimping Jaw
- 49-16-10D3 6T Fixed O Crimping Jaw
- 49-16-11D3 6T Snub Nose Crimping Jaw
- 49-16-KEAR 6T Kearney Crimping Jaw

Cutter Jaws

Also Compatible with 2672-21, 2672-21S, and 2672-21F

- 49-16-2772 750 MCM Cu/Al Cutting Jaw
- 49-16-2773 477 ACSR Cutting Jaw
- 49-16-2777 1/2" EHS Guy Wire Cutting Jaw
- 49-16-2778 Fine-Stranded Wire Cutting Jaw

Cutter Replacement Blades

- 48-44-0411 Replacement Copper Blades
- 48-44-0412 Replacement Steel Blades
- 48-44-2777 1/2" EHS Guy Wire Replacement Blades
- 48-44-2778 Fine-Stranded Wire Replacement Blades

W Style Dies

- 49-16-WBG0 W Style Die: "W-BG"
- 49-16-WO00 W Style Die: "W-O"
- 49-16-WC00 W Style Die: "W-C"
- 49-16-W161 W Style Die: "W-161"
- 49-16-W162 W Style Die: "W-162"
- 49-16-W163 W Style Die: "W-163"
- 49-16-W164 W Style Die: "W-164"
- 49-16-W165 W Style Die: "W-165"
- 49-16-W166 W Style Die: "W-166"
- 49-16-W237 W Style Die: "W-237"
- 49-16-W239 W Style Die: "W-239"
- 49-16-W243 W Style Die: "W-243"
- 49-16-W247 W Style Die: "W-247"
- 49-16-W249 W Style Die: "W-249"
- 49-16-W840 W Style Die: "W-K840"

M18™ FORCE LOGIC™ 600 MCM Crimper Kit

2679-22, 2679-750C, 2679-750A, 2679-350A, 2679-600C



Specifications:

Output Force	6 Tons
Adaptive Pressure Control System	Yes; PFM™
Reporting and Tool Diagnostics	Built-In; ONE-KEY™ Compatible
Cycle Time	2.9 Seconds
Head Rotation	350°
Height / Length	5.4" / 13.3"

Includes: 2679-750C 750 MCM Cu/Al Crimping Jaw, All Copper U Style Dies (49-16-KITC Die Kit and 49-16-750C Die Kit); 2679-750A 750 MCM Cu/Al Crimping Jaw, All Aluminum U Style Dies (49-16-KITA Die Kit and 49-16-750A Die Kit); 2679-350A 49-16-KITA Die Kit; **All Kits Include:** 2679-22 600 MCM Commercial U Crimping Jaw, (2) M18™ REDLITHIUM™ CP2.0 Battery Packs, Multi-Voltage Charger, Carrying Case

FORCE LOGIC™ 600 MCM Crimper Accessories

Compatible with 2679-22, 2679-750C, 2679-750A, 2679-350A, 2679-600C

Related Accessories:

- 49-16-U000 600 MCM Crimping Jaw
- 49-16-U111 750 MCM Cu/Al Cable Crimping Jaw
- 49-16-2780 750 MCM Cu/Al Cable Cutting Jaw

Cutter Replacement Blades

- 48-44-0411 750 MCM Cu/Al Cable Cutting Blades

Accessory Kits

- 49-16-KITA #8 AWG – 350 MCM Aluminum U Style Die Kit
- 49-16-750A 400 – 750 MCM Aluminum U Style Die & Jaw Kit
- 49-16-KITC #8 AWG – 600 MCM Copper U Style Die Kit
- 49-16-750C 750 MCM Copper U Style Die & Jaw Kit

Copper U Style Dies

- 49-16-U001C #1 Copper U Style Die
- 49-16-U002C #2 Copper U Style Die
- 49-16-U004C #4 Copper U Style Die
- 49-16-U006C #6 Copper U Style Die
- 49-16-U008C #8 Copper U Style Die
- 49-16-U01AC 1/0 Copper U Style Die
- 49-16-U02AC 2/0 Copper U Style Die
- 49-16-U03AC 3/0 Copper U Style Die
- 49-16-U04AC 4/0 Copper U Style Die
- 49-16-U250C 250 MCM Copper U Style Die
- 49-16-U300C 300 MCM Copper U Style Die
- 49-16-U350C 350 MCM Copper U Style Die
- 49-16-U400C 400 MCM Copper U Style Die
- 49-16-U500C 500 MCM Copper U Style Die
- 49-16-U600C 600 MCM Copper U Style Die
- 49-16-U750C 750 MCM Copper U Style Die

Aluminum Dual-Rated U Style Dies

- 49-16-U001 #1 Aluminum U Style Die
- 49-16-U002 #2 Aluminum U Style Die
- 49-16-U004 #4 Aluminum U Style Die
- 49-16-U006 #6 Aluminum U Style Die
- 49-16-U008 #8 Aluminum U Style Die
- 49-16-U01A 1/0 Aluminum U Style Die
- 49-16-U02A 2/0 Aluminum U Style Die
- 49-16-U03A 3/0 Aluminum U Style Die
- 49-16-U04A 4/0 Aluminum U Style Die
- 49-16-U250 250 MCM Aluminum U Style Die
- 49-16-U300 300 MCM Aluminum U Style Die
- 49-16-U350 350 MCM Aluminum U Style Die
- 49-16-U400 400 MCM Aluminum U Style Die
- 49-16-U500 500 MCM Aluminum U Style Die
- 49-16-U600 600 MCM Aluminum U Style Die
- 49-16-U750 750 MCM Aluminum U Style Die

M18™ FORCE LOGIC™ 750 MCM Dieless Crimper Kit




2877-22

Specifications:

Crimping Capacity	#6 – 750 MCM Cu & Al
Adaptive Distance Control	Yes; Auto Distance Control
Reporting and Tool Diagnostics	Built-In; ONE-KEY™ Compatible
Dimensions (L x W x H)	18.9" x 3.3" x 6.5"
Weight	9.0 lbs

Includes: (2) M18™ REDLITHIUM™ CP2.0 Battery Packs, Multi-Voltage Charger, Carrying Case




M18™ FORCE LOGIC™ 12T Utility Crimper Kit

2778-22 (2778-20 Tool-Only)

Specifications:

Output Force	12 Tons
Head Rotation	350°
Reporting and Tool Diagnostics	Built-In; ONE-KEY™ Compatible
Length / Weight	16.0" / 11.9 lbs

Includes: (1) M18™ REDLITHIUM™ XC5.0 Battery Pack, (1) M18™ REDLITHIUM™ CP2.0 Battery Pack, Carabiner, Multi-Voltage Charger and Inverter, Utility Bag





M18™ FORCE LOGIC™ 750 MCM Crimper Kit

2779-22, 2779-750A, 2779-750C

Specifications:

Output Force	12 Tons
Head Rotation	350°
Reporting and Tool Diagnostics	Built-In; ONE-KEY™ Compatible
Length / Weight	16.0" / 11.5 lbs

Includes: 2779-750A 49-12-KITA; 2779-750C 49-12-KITC; **All Kits Include:** 2779-22 (1) M18™ REDLITHIUM™ XC5.0 Battery Pack, (1) M18™ REDLITHIUM™ CP2.0 Battery Pack, Multi-Voltage Charger, Carrying Case

Related Accessories:

- Accessory Kits**
- 49-12-KITC EXACT™ #6 AWG – 750 MCM Cu 12T U Style Die Kit
- 49-12-KITA EXACT™ #6 AWG – 750 MCM Al 12T U Style Die Kit



M18™ FORCE LOGIC™ 15T Crimper Kit

2879-22 (2879-20 Tool-Only)

Specifications:

Crimping Capacity	#8 – 1500 MCM Cu, #8 – 1250 MCM Al
Output Force	15 Tons
Adaptive Pressure Control	Yes; PFM™
Reporting and Tool Diagnostics	Built-In; ONE-KEY™ Compatible
Dimensions (L x W x H)	23.3" x 3.1" x 5.5"
Weight	16.1 lbs

Includes: (1) M18™ REDLITHIUM™ XC5.0 Battery Pack, (1) M18™ REDLITHIUM™ CP2.0 Battery Pack, P-to-U Die Adapter, Carabiner, Multi-Voltage Charger, Contractor Bag

Related Accessories:

- 49-15-PUAD P-to-U Die Adapter
- 49-15-P750 15T 750 MCM Al P-Die
- 49-15-P800 15T 800 MCM Al P-Die
- 49-15-P000 15T 1000 MCM Al P-Die
- 49-15-P750C 15T 750 MCM Cu P-Die
- 49-15-P800C 15T 800 MCM Cu P-Die
- 49-15-P000C 15T 1000 MCM Cu P-Die



M18™ FORCE LOGIC™ 10,000 PSI Hydraulic Pump Kit

2674-21HD (2674-20 Tool-Only)

Specifications:

Operating Pressure	10,000 psi / 700 bar
Usable Oil Capacity	1.4 qts
Flow Rate at Low Pressure	125.0 in³/min
Flow Rate at High Pressure	25.6 in³/min
Ingress Protection	IP54
Dimensions (L x W x H)	15.8" x 11.5" x 13.9"
Weight	29.7 lbs

Includes: (1) M18™ REDLITHIUM™ HIGH OUTPUT™ HD12.0 Battery Pack, Rapid Charger

Related Accessories:

- 49-12-2776 Bucket Hanger
- 49-12-2775 6' Controller Extension



M18™ FORCE LOGIC™ Cable Cutter Kit w/ 750 MCM Cu Jaws

2672-21

Specifications:

Cut Capacity	750 MCM Cu, 1000 MCM Al
Average Cut Speed	3 Seconds
Head Rotation	350°
Auto Reset	Yes
Tool Diagnostics	Built-In; ONE-KEY™ Compatible
Height / Length	5.4" / 14.0"

Includes: (1) M18™ REDLITHIUM™ CP2.0 Battery Pack, 750 MCM Cable Cutter Jaw, Allen Wrench, Multi-Voltage Charger, Carrying Case



M18™ FORCE LOGIC™ Cable Cutter Kit w/ 477 ACSR Jaws

2672-21S

Specifications:

Cut Capacity	477 HEN ACSR
Average Cut Speed	3 Seconds
Head Rotation	350°
Auto Reset	Yes
Tool Diagnostics	Built-In; ONE-KEY™ Compatible
Height / Length	5.4" / 14.0"

Includes: (1) M18™ REDLITHIUM™ CP2.0 Battery Pack, 477 ACSR Cutting Jaw, Carabiner, Allen Wrench, Multi-Voltage Charger and Inverter, Bucket Bag



M18™ FORCE LOGIC™ Cable Cutter Kit w/ Fine-Stranded Wire Jaws

2672-21F

Specifications:

Cut Capacity	777.7 MCM Fine-Stranded Wire
Average Cut Speed	3 Seconds
Head Rotation	350°
Auto Reset	Yes
Tool Diagnostics	Built-In; ONE-KEY™ Compatible
Height / Length	5.4" / 14.0"

Includes: (1) M18™ REDLITHIUM™ CP2.0 Battery Pack, Fine-Stranded Wire Cutting Jaw, Allen Wrench, Multi-Voltage Charger, Carrying Case



M18™ FORCE LOGIC™ Cable Cutter Accessories

Compatible with 2672-21, 2672-21S and 2672-21F

Cutter Jaws

- 49-16-2772 750 MCM Cu/Al Cutting Jaw
- 49-16-2773 477 ACSR Cutting Jaw
- 49-16-2777 1/2" EHS Guy Wire Cutting Jaw
- 49-16-2778 Fine-Stranded Wire Cutting Jaw

Cutter Replacement Blades

- 48-44-0411 Copper Replacement Blades
- 48-44-0412 ACSR Replacement Blades
- 48-44-2777 1/2" EHS Guy Wire Replacement Blades
- 48-44-2778 Fine-Stranded Wire Replacement Blades



M18™ FORCE LOGIC™ 3" Underground Cable Cutter Kit w/ Wireless Remote

2776R-21

Specifications:

Cut Capacity	1500 MCM Cu 15kV
Tool Diagnostics	Built-In; ONE-KEY™ Compatible
Height / Length	12.4" / 20.8"
Weight	15.8 lbs

Includes: (1) M18™ REDLITHIUM™ XC5.0 Battery Pack, Remote, Carabiner, Multi-Voltage Charger and Inverter, Utility Bag

Related Accessory:

- 49-16-2774 3" Underground Replacement Blades



M18™ FORCE LOGIC™ 3" Underground Cable Cutter Kit

2776-21

Specifications:

Cut Capacity	1500 MCM Cu 15kV
Tool Diagnostics	Built-In; ONE-KEY™ Compatible
Height / Length	12.4" / 20.8"
Weight	15.8 lbs

Includes: (1) M18™ REDLITHIUM™ XC5.0 Battery Pack, Carabiner, Multi-Voltage Charger and Inverter, Utility Bag

Related Accessory:

- 49-16-2774 3" Underground Replacement Blades



M18™ FORCE LOGIC™ 1590 ACSR Cutter Kit

2777-21

Specifications:

Cut Capacity	Up to 1590 Falcon ACSR
Tool Diagnostics	Built-In; ONE-KEY™ Compatible
Height / Length	10.6" / 16.8"
Weight	11.8 lbs

Includes: (1) M18™ REDLITHIUM™ XC5.0 Battery Pack, Carabiner, Side Handle, Multi-Voltage Charger and Inverter, Utility Bag

Related Accessory:

- 49-16-2775 1590 ACSR Replacement Blades





M18™ FORCE LOGIC™ 6 Ton Knockout Tool Kit

2677-23, 2677-21 (2677-20 No Punches or Dies)

Specifications:

Mild Steel Capacity	4" in 14 Gauge
Stainless Steel Capacity	2" in 14 Gauge
Output Force	6 Tons
Quick-Connect Draw Stud	Yes
Rapid Reset	Yes
Height / Weight	4.5" / 4.3 lbs



Includes: 2677-23 (1) M18™ REDLITHIUM™ CP2.0 Battery Pack, EXACT™ 1/2" – 4" Conduit Punches and Dies; 2677-21 (1) M18™ REDLITHIUM™ CP2.0 Battery Pack, EXACT™ 1/2" – 2" Conduit Punches and Dies; 2677-20 (1) M18™ REDLITHIUM™ CP2.0 Battery Pack (No Punches or Dies Included); **All Kits Include:** (2) Draw Studs, Quick Connect Alignment System, Multi-Voltage Charger, Carrying Case



M18™ FORCE LOGIC™ 10 Ton Knockout Tool Kit

2676-23, 2676-22 (2676-20 No Punches or Dies)

Specifications:

Mild Steel Capacity	6" in 12 Gauge
Stainless Steel Capacity	6" in 14 Gauge
Output Force	10 Tons
Quick-Connect Draw Stud	Yes
Rapid Reset	Yes
Height / Weight	5.5" / 7.1 lbs



Includes: 2676-23 (2) M18™ REDLITHIUM™ XC3.0 Battery Packs, EXACT™ 1/2" – 4" Conduit Punches and Dies; 2676-22 (2) M18™ REDLITHIUM™ XC3.0 Battery Packs, 1/2" – 2" EXACT™ Conduit Punches and Dies; 2676-20 (2) M18™ REDLITHIUM™ XC3.0 Battery Packs (No Punches or Dies Included); **All Kits Include:** (3) Draw Studs, Quick-Connect Alignment System, Multi-Voltage Charger, Carrying Case

M18™ FORCE LOGIC™ Knockout Accessories

Compatible with 2677-20 and 2676-20

EXACT™ Accessory Kits

- 49-16-2692 1/2" – 1-1/4" Knockout Set
- 49-16-2693 1/2" – 2" Knockout Set
- 49-16-2694 1/2" – 2" Hand Ratchet Knockout Set
- 49-16-2695 2-1/2" – 4" Knockout Set

EXACT™ Punches and Dies

- 49-16-2660* 1/2" Die
- 49-16-2660S 1/2" Die
- 49-16-2661* 1/2" Punch
- 49-16-2661S 1/2" Punch
- 49-16-2662 3/4" Die
- 49-16-2663 3/4" Punch
- 49-16-2664 1" Die
- 49-16-2665 1" Punch
- 49-16-2666 1-1/4" Die
- 49-16-2667 1-1/4" Punch
- 49-16-2668 1-1/2" Die
- 49-16-2669 1-1/2" Punch
- 49-16-2670 2" Die
- 49-16-2671 2" Punch
- 49-16-2672 2-1/2" Die
- 49-16-2673 2-1/2" Punch
- 49-16-2674 3" Die
- 49-16-2675 3" Punch
- 49-16-2676 3-1/2" Die
- 49-16-2677 3-1/2" Punch
- 49-16-2678 4" Die
- 49-16-2679 4" Punch
- 49-16-2686 5" Die
- 49-16-2687 5" Punch
- 49-16-2688 6" Die
- 49-16-2689 6" Punch

*These items are intended only for Mild Steel.

EXACT™ Sink Punches & Dies

- 49-16-2705 7/8" Sink Die
- 49-16-2706 7/8" Sink Punch
- 49-16-2700 1-3/8" Sink Die
- 49-16-2701 1-3/8" Sink Punch

Rapid Reset Draw Studs

- 49-16-2703 Rapid Reset 3/4" Draw Stud
- 49-16-2704 Rapid Reset 1-1/8" Draw Stud
- 49-16-2708 Rapid Reset 1-1/8" Long Draw Stud

Draw Studs

- 49-16-2621 3/8" Ball Bearing Draw Stud
- 49-16-2622 3/4" Ball Bearing Draw Stud
- 49-16-2680 7/16" Draw Stud
- 49-16-2681 3/4" Draw Stud
- 49-16-2682 1-1/8" Draw Stud
- 49-16-2707 1-1/8" Long Draw Stud

Adapters

- 49-16-2684 3/8" Adapter for EXACT™ 2-1/2" – 4" Dies to 3/4" Draw Studs
- 49-16-2685 Adapter for M18™ FORCE LOGIC™ Knockout Tool to other major brands of punches and dies

M18™ Cable Stripper Kit

2935CU-21S, 2935AL-21, 2935X-21 (2935-20 Tool-Only)

Specifications:

Variable Speed Trigger	Yes
Tool Free Depth Gauge	Yes
Compatible Bushing Types	Industry Standard Quick-Change
Dimensions (L x W x H)	8.5" x 2.8" x 11.3"
Weight	3.8 lbs



Includes: 2935CU-21S 1/0 AWG – 750 MCM Cu THHN / XHHW Bushings; 2935AL-21 1/0 AWG – 750 MCM Al THHN / XHHW Bushings; 2935X-21 1/0 AWG – 500 MCM Cu RHW / RHH / USE Bushings; **All Kits Include:** (1) M18™ REDLITHIUM™ CP2.0 Battery Pack, Multi-Voltage Charger, Carrying Case

Cable Stripper Accessories

Compatible with 2935-20, 2435-20

Bushing Kits

- 49-16-BKITC 1/0 AWG – 750 MCM Cu THHN / XHHW Bushing Kit
- 49-16-BKITA 1/0 AWG – 750 MCM Al THHN / XHHW Bushing Kit

Bushings - Cu THHN / XHHW

- 49-16-B01AC 1/0 AWG Cu THHN / XHHW Bushing
- 49-16-B02AC 2/0 AWG Cu THHN / XHHW Bushing
- 49-16-B03AC 3/0 AWG Cu THHN / XHHW Bushing
- 49-16-B04AC 4/0 AWG Cu THHN / XHHW Bushing
- 49-16-B250S 250 MCM Cu THHN / XHHW S Bushing
- 49-16-B250C 250 MCM Cu THHN / XHHW Bushing
- 49-16-B300S 300 MCM Cu THHN / XHHW S Bushing
- 49-16-B300C 300 MCM Cu THHN / XHHW Bushing
- 49-16-B350S 350 MCM Cu THHN / XHHW S Bushing
- 49-16-B350C 350 MCM Cu THHN / XHHW Bushing
- 49-16-B400S 400 MCM Cu THHN / XHHW S Bushing
- 49-16-B400C 400 MCM Cu THHN / XHHW Bushing
- 49-16-B500S 500 MCM Cu THHN / XHHW S Bushing
- 49-16-B500C 500 MCM Cu THHN / XHHW Bushing
- 49-16-B600S 600 MCM Cu THHN / XHHW S Bushing
- 49-16-B600C 600 MCM Cu THHN / XHHW Bushing
- 49-16-B750C 750 MCM Cu THHN / XHHW Bushing

Bushings - Al THHN / XHHW

- 49-16-B01A 1/0 AWG Al THHN / XHHW Bushing
- 49-16-B02A 2/0 AWG Al THHN / XHHW Bushing
- 49-16-B03A 3/0 AWG Al THHN / XHHW Bushing
- 49-16-B04A 4/0 AWG Al THHN / XHHW Bushing
- 49-16-B250 250 MCM Al THHN / XHHW Bushing
- 49-16-B300 300 MCM Al THHN / XHHW Bushing
- 49-16-B350 350 MCM Al THHN / XHHW Bushing
- 49-16-B400 400 MCM Al THHN / XHHW Bushing
- 49-16-B500 500 MCM Al THHN / XHHW Bushing
- 49-16-B600 600 MCM Al THHN / XHHW Bushing
- 49-16-B750 750 MCM Al THHN / XHHW Bushing

Bushings - Cu RHW / RHH / USE

- 49-16-B01AX 1/0 AWG Cu RHW / RHH / USE Bushing
- 49-16-B02AX 2/0 AWG Cu RHW / RHH / USE Bushing
- 49-16-B03AX 3/0 AWG Cu RHW / RHH / USE Bushing
- 49-16-B04AX 4/0 AWG Cu RHW / RHH / USE Bushing
- 49-16-B250X 250 MCM Cu RHW / RHH / USE Bushing
- 49-16-B300X 300 MCM Cu RHW / RHH / USE Bushing
- 49-16-B350X 350 MCM Cu RHW / RHH / USE Bushing
- 49-16-B500X 500 MCM Cu RHW / RHH / USE Bushing

Replacement Blade for Bushings

- 48-44-2935 Replacement Blade for Cable Stripper Bushings

M18 FUEL ANGLER™ Pulling Fish Tape Kit

2873A-22, 2873B-22 (2873-20 Tool-Only)

Specifications:

Pull Force	(4) #10 Wires
Powered Feed & Retract	Yes, AUTO-RUN™ Powered & Retract
Dimensions (L x W x H)	13.2" x 6.0" x 17.7"
Weight	19.1 lbs (2873B), 16.2 lbs (2873A), 8.3 lbs (2873-20)



Includes: 2873A-22: ANGLER™ 120' x 1/8" Steel Pulling Fish Tape; 2873B-22: ANGLER™ 240' x 1/8" Steel Pulling Fish Tape Replacement Cartridge; **All Kits Include:** (2) M18™ REDLITHIUM™ CP2.0 Battery Packs, Multi-Voltage Charger

Related Accessories:

- 48-44-5176 M18 FUEL™ ANGLER™ 120' x 1/8" Steel Pulling Fish Tape Replacement Cartridge
- 48-44-5178 M18 FUEL™ ANGLER™ 240' x 1/8" Steel Pulling Fish Tape Replacement Cartridge
- 48-44-5195 M18 FUEL™ ANGLER™ 100' Non-Conductive Polyester Pulling Fish Tape Replacement Cartridge



M18 FUEL
Pipe Threader w/ ONE-KEY™ Kit

2874-22HD

Specifications:

Capacity	1/8" – 2"
Kickback Control	AUTOSTOP™
Threading Support Arm	Yes
Trigger	Variable Speed
Die Head Retention Lock	Yes
Die Head Compatibility	RIDGID® 12R, Reed R12+



REDLITHIUM
HIGH OUTPUT HD12.0

Includes: (2) M18™ REDLITHIUM™ HIGH OUTPUT™ HD12.0 Battery Packs, Threading Support Arm, Rapid Charger, Carrying Case



M18™ FORCE LOGIC™ Press Tool Kit w/ ONE-KEY™ with 1/2" - 2" CTS Jaws

2922-22 (2922-20 No Jaw Kit)

Specifications:

Capacity	1/2" – 4" (Varies by Material)
Calibration Interval	50,000 Cycles
Approx Cycle Time	4 Seconds
Press Force	7,200 lbs
ONE-KEY™ Compatible	Report. Track. Manage.
Performance Reporting	Wireless, Mobile, Desktop
Length/Weight	14.1" / 6.5 lbs

Includes: (2) M18™ REDLITHIUM™ CP2.0 Battery Packs, (6) CTS Jaws (1/2", 3/4", 1", 1-1/4", 1-1/2", 2"), Multi-Voltage Charger, Carrying Case; **2922-20** No Jaws Included



M18™ FORCE LOGIC™ Long Throw Press Tool Kit

2773-22L (2773-20L No Jaw Kit)

Specifications:

Capacity	1/2" – 4" (Varies by Material)
Calibration Interval	50,000 Cycles (LED Indicator)
Approximate Cycle Time	4 Seconds, 8 Seconds at Extended Stroke
Press Force	7,200 lbs
Length / Weight	20.1" / 10.1 lbs

Includes: 2773-22L (2) M18™ REDLITHIUM™ XC3.0 Battery Packs, (3) Jaws (1/2", 3/4", 1"), Multi-Voltage Charger, Carrying Case; **2773-20L** No Jaws Included



FORCE LOGIC™ Press Tool Accessories

Compatible with 2922-20 and 2773-20L

Accessory Kits

- 49-16-2696 1/2" – 1" IPS-P Press Jaw Kit
- 49-16-2690 2-1/2" – 4" CTS-Vr1 Press Ring Kit
- 49-16-2691* 1-1/4" – 2" IPS-Ar1 Press Ring Kit
- 49-16-2697 1/2" – 2" IPS-P Press Ring Kit
- 49-16-2698* 2-1/2" – 4" IPS-Pr2 Press Ring Kit

CTS Jaws & Rings

- 49-16-2650 1/2" CTS-V Press Jaw
- 49-16-2651 3/4" CTS-V Press Jaw
- 49-16-2652 1" CTS-V Press Jaw
- 49-16-2653 1-1/4" CTS-V Press Jaw
- 49-16-2654 1-1/2" CTS-V Press Jaw
- 49-16-2655 2" CTS-V Press Jaw
- 49-16-2656 2-1/2" CTS-Vr1 Press Ring
- 49-16-2657 3" CTS-Vr1 Press Ring
- 49-16-2658 4" CTS-Vr1 Press Ring

IPS Jaws & Rings

- 49-16-2650B 1/2" IPS-P Press Jaw
- 49-16-2651B 3/4" IPS-P Press Jaw
- 49-16-2652B 1" IPS-P Press Jaw
- 49-16-2653B 1-1/4" IPS-Pr1 Press Ring
- 49-16-2654B 1-1/2" IPS-Pr1 Press Ring
- 49-16-2655B 2" IPS-Pr1 Press Ring
- 49-16-2656B* 2-1/2" IPS-Pr2 Press Ring
- 49-16-2657B* 3" IPS-Pr2 Press Ring
- 49-16-2658B* 4" IPS-Pr2 Press Ring
- 49-16-2650S 1/2" IPS-IA Press Jaw
- 49-16-2651S 3/4" IPS-IA Press Jaw
- 49-16-2652S 1" IPS-IA Press Jaw
- 49-16-2653S 1-1/4" IPS-IAr2 Press Ring
- 49-16-2654S* 2" IPS-IAr2 Press Ring
- 49-16-2655S* 2" IPS-IAr2 Press Ring

PEX Jaws & Rings

- 49-16-2651C 1/2" PEX-CRIMP Jaw
- 49-16-2653C 3/4" PEX-CRIMP Jaw
- 49-16-2654C 1" PEX-CRIMP Jaw
- 49-16-2655C 1-1/4" PEX-CRIMP Jaw
- 49-16-2656C 1-1/2" PEX-CRIMP Jaw
- 49-16-2657C 2" PEX-CRIMP Jaw

*Compatible with 2773-20L only.

ACR Jaws & Rings

- 49-16-2650M 1/4" Streamline™ ACR Press Jaw
- 49-16-2652M 3/8" Streamline™ ACR Press Jaw
- 49-16-2653M 1/2" Streamline™ ACR Press Jaw
- 49-16-2654M 5/8" Streamline™ ACR Press Jaw
- 49-16-2655M 3/4" Streamline™ ACR Press Jaw
- 49-16-2656M 7/8" Streamline™ ACR Press Jaw
- 49-16-2651M 1-1/8" Streamline™ ACR Press Ring
- 49-16-2661M 1/4" – 7/8" Streamline™ ACR Press Jaw Kit
- 49-16-2650R 1/4" RLS® Press Jaw
- 49-16-2652R 3/8" RLS® Press Jaw
- 49-16-2653R 1/2" RLS® Press Jaw
- 49-16-2654R 5/8" RLS® Press Jaw
- 49-16-2655R 3/4" RLS® Press Jaw
- 49-16-2656R 7/8" RLS® Press Jaw
- 49-16-2657R 1-1/8" RLS® Press Jaw
- 49-16-2658R 1-3/8" RLS® Press Jaw
- 49-16-2660R 1/4" – 1-3/8" RLS® Press Jaw Kit

M18™ Short Throw Press Tool w/ PEX Crimp Jaws Kit

2674-22C, 2674-20C

Specifications:

Capacity	Up to 1"
Cycle Time	3 Seconds
Auto Cycle	Yes
Length / Weight	13.5" / 4.8 lbs



Includes: 2674-22C (2) M18™ REDLITHIUM™ CP2.0 Battery Packs, Multi-Voltage Charger; **2674-20C** Battery and Charger Sold Separately; **All Kits Include:** (3) PEX Crimp Jaws (1/2", 3/4", 1"), Carrying Case



M18™ Short Throw Press Tool w/ Viega® PureFlow® Jaws Kit

2674-22P, 2674-20P

Specifications:

Capacity	Up to 1"
Cycle Time	3 Seconds
Auto Cycle	Yes
Length / Weight	13.5" / 4.8 lbs



Includes: 2674-22P (2) M18™ REDLITHIUM™ CP2.0 Battery Packs, Multi-Voltage Charger; **2674-20P** Battery and Charger Sold Separately; **All Kits Include:** (3) Viega® PureFlow® Jaws (1/2", 3/4", 1"), Carrying Case

Short Throw Press Tool Accessories

Compatible with 2674-20C and 2674-20P

- 49-16-2630C 3/8" PEX Crimp Jaw
- 49-16-2631C 1/2" PEX Crimp Jaw
- 49-16-2632C 5/8" PEX Crimp Jaw
- 49-16-2633C 3/4" PEX Crimp Jaw
- 49-16-2634C 1" PEX Crimp Jaw
- 49-16-2630P 3/8" Viega® PureFlow® Jaw
- 49-16-2631P 1/2" Viega® PureFlow® Jaw
- 49-16-2632P 5/8" Viega® PureFlow® Jaw
- 49-16-2633P 3/4" Viega® PureFlow® Jaw
- 49-16-2634P 1" Viega® PureFlow® Jaw

M18™ FORCE LOGIC™ 2" - 3" ProPEX® Expansion Tool Kit

2633-22HD

Specifications:

Capacity	2", 2-1/2" and 3"
Auto-Rotation	Built-In
Auto-Cycle	Built-In
Dimensions (L x W x H)	14.5" x 11.8" x 4.8"
Weight	13.1 lbs



REDLITHIUM
HIGH OUTPUT XC8.0

Includes: (2) M18™ REDLITHIUM™ HIGH OUTPUT™ XC8.0 Battery Packs, (3) ProPEX® Expansion Heads (2", 2-1/2", 3"), Side Handle, Grease, Multi-Voltage Charger, Carrying Case

Related Accessories:

- 49-08-2401 150g ProPEX® Expander Cone Grease
- 49-16-2614 2" ProPEX® Expansion Head
- 49-16-2616 2-1/2" ProPEX® Expansion Head
- 49-16-2618 3" ProPEX® Expansion Head

M18 FUEL 2" ProPEX® Expander Kit w/ ONE-KEY™ with 1-1/4" - 2" ProPEX® Expander Heads

2932-22XC

Specifications:

Capacity	3/8" – 2"
Auto-Rotation	Built-In
Dimensions (L x W x H)	9" x 4.3" x 13.6"
Weight	10.9 lbs



Includes: (2) M18™ REDLITHIUM™ XC5.0 Battery Packs, (3) ProPEX® Expansion Heads (1-1/4", 1-1/2", 2"), 150g Expander Grease, Multi-Voltage Charger, Carrying Case

Related Accessories:

- 49-16-2608 1" ProPEX® Expansion Head
- 49-16-2610 1-1/4" ProPEX® Expansion Head
- 49-16-2612 1-1/2" ProPEX® Expansion Head
- 49-16-2613 2" ProPEX® Expansion Head for M18 FUEL™ Expander
- 49-08-2403 150g ProPEX® Expander Cone Grease w/ 2" Applicator Head



M18™ ProPEX® Expansion Tool Kit

2632-22XC (2632-20 Tool-Only)

Specifications:

Capacity	3/8" – 1-1/2"
Auto-Rotation	Built-In
Dimensions (L x W x H)	8.7" x 4.4" x 10.8"
Weight	9.2 lbs



Includes: (2) M18™ REDLITHIUM™ XC3.0 Battery Packs, (3) ProPEX® Expansion Heads (1", 1-1/4", 1-1/2"), Grease, Multi-Voltage Charger, Carrying Case

Related Accessories:

- 49-08-2400 ProPEX® Expander Cone Grease
- 49-16-2608 1" ProPEX® Expansion Head
- 49-16-2610 1-1/4" ProPEX® Expansion Head
- 49-16-2612 1-1/2" ProPEX® Expansion Head

M18 FUEL
Sewer Sectional Machine Kit w/ CABLE DRIVE™ for 7/8" & 1-1/4" Cable

2871A-22, 2871-22

Specifications:

Maximum Drain Line Capacity	2" – 8" up to 200'
Cable Capacity	7/8" and 1-1/4"
Powered Cable Feed & Retract	Yes, CABLE DRIVE™
Cable Spin Speed	700 RPM
Height / Length	23" / 35"
Weight	74 lbs



REDLITHIUM
HIGH OUTPUT HD120

Includes: 2871A-22 (7) 1-1/4" x 15' All Purpose Open Wind Cables, (2) Cable Containers, Straight Auger, Funnel Auger, Small Opening Tool, Medium Opening Tool, 3" Grease Cutter, 3" Root Cutter, 4" Root Cutter, Pin Key, Head Attachment Case;

All Kits Include: (2) M18™ REDLITHIUM™ HIGH OUTPUT™ HD12.0 Battery Packs, Rear Guide Hose, Rapid Charger



M18 FUEL
Sectional Machine for 5/8" & 7/8" Cable

2818-21, 2818A-21, 2818B-21

Specifications:

Maximum Drain Line Capacity	1-1/4" – 6" out to 150'
Cable Capacity	5/8" and 7/8"
Cable Feed & Retract	Manual
Cable Spin Speed	650 RPM
Height / Length	15.1" / 14.6"
Weight	27.3 lbs



REDLITHIUM
HIGH OUTPUT HD120

Includes: 2818-21: Large Rear Guide Hose; 2818A-21: Large Rear Guide Hose, Medium Cable Container, (5) 7/8" x 15' All Purpose Open Wind Sectional Cables, 2" – 4" Head Attachment Kit;

2818B-21: Small Rear Guide Hose, Small Cable Container, (6) 5/8" x 7-1/2' All Purpose Open Wind Sectional Cables, 1/4" – 2" Head Attachment Kit;

All Kits Include: (1) M18™ REDLITHIUM™ HIGH OUTPUT™ HD12.0 Battery Pack, Carry Strap, Rapid Charger



Sectional Machine Cables and Accessories

Related Accessories:

- 47-53-2871 Cable Container
- 47-53-2872 Rear Guide Hose
- 47-53-2874 Small Rear Guide Hose
- 47-53-2873 Large Rear Guide Hose
- 47-53-2869 Small Cable Container
- 47-53-2870 Medium Cable Container
- 48-08-0555 Carrying Strap

Compatible with 2818-20

5/8"

- 48-53-2680 5/8" x 7.5' All Purpose Sectional Cable
- 48-53-3811 Drop Head Bulb Auger w/ RUST GUARD™ for 5/8" Sectional Cable
- 48-53-3812 Drop Head Straight Auger w/ RUST GUARD™ for 5/8" Sectional Cable
- 48-53-3813 Flexible Funnel Auger w/ RUST GUARD™ for 5/8" Sectional Cable
- 48-53-3814 Flexible Opening Tool w/ RUST GUARD™ for 5/8" Sectional Cable
- 48-53-3815 2" Opening Tool w/ RUST GUARD™ for 5/8" Sectional Cable
- 48-53-3820 1-1/4" – 2" Head Attachment Kit w/ RUST GUARD™ for 5/8" Sectional Cable

Compatible with 2818-20 and 2871-20

7/8"

- 48-53-2852 7/8" x 15' All Purpose Sectional Cable
- 48-53-3829 Flexible Straight Auger w/ RUST GUARD™ for 7/8" Sectional Cable
- 48-53-3830 Straight Auger w/ RUST GUARD™ for 7/8" Sectional Cable
- 48-53-3828 Flexible Funnel Auger w/ RUST GUARD™ for 7/8" Sectional Cable
- 48-53-3831 Funnel Auger w/ RUST GUARD™ for Sectional Cable
- 48-53-3825 2" Root Cutter w/ RUST GUARD™ for 7/8" Sectional Cable
- 48-53-3832 3" Root Cutter w/ RUST GUARD™ for 7/8" Sectional Cable
- 48-53-3833 4" Root Cutter w/ RUST GUARD™ for 7/8" Sectional Cable
- 48-53-3834 6" Root Cutter w/ RUST GUARD™ for 7/8" Sectional Cable
- 48-53-3827 2" Opening Tool w/ RUST GUARD™ for 7/8" Sectional Cable
- 48-53-3835 3" Opening Tool w/ RUST GUARD™ for 7/8" Sectional Cable
- 48-53-3836 4" Opening Tool w/ RUST GUARD™ for 7/8" Sectional Cable
- 48-53-3837 3" Grease Cutter w/ RUST GUARD™ for 7/8" Sectional Cable
- 48-53-3838 4" Grease Cutter w/ RUST GUARD™ for 7/8" Sectional Cable
- 48-53-3839 2" – 4" Head Attachment Kit w/ RUST GUARD™ for 7/8" Sectional Cable
- 48-53-3840 3" – 6" Head Attachment Kit w/ RUST GUARD™ for 7/8" Sectional Cable

Compatible with 2871-20

1-1/4"

- 48-53-2851 1-1/4" x 15' All Purpose Sectional Cable
- 48-53-2854 1-1/4" x 15' Heavy Duty Sectional Cable
- 48-53-4830 Straight Auger w/ RUST GUARD™ for 1-1/4" Sectional Cable
- 48-53-4831 Funnel Auger w/ RUST GUARD™ for 1-1/4" Sectional Cable
- 48-53-4832 3" Root Cutter w/ RUST GUARD™ for 1-1/4" Sectional Cable
- 48-53-4833 4" Root Cutter w/ RUST GUARD™ for 1-1/4" Sectional Cable
- 48-53-4834 6" Root Cutter w/ RUST GUARD™ for 1-1/4" Sectional Cable
- 48-53-4835 3" Opening Tool w/ RUST GUARD™ for 1-1/4" Sectional Cable
- 48-53-4836 4" Opening Tool w/ RUST GUARD™ for 1-1/4" Sectional Cable
- 48-53-4837 3" Grease Cutter w/ RUST GUARD™ for 1-1/4" Sectional Cable
- 48-53-4838 4" Grease Cutter w/ RUST GUARD™ for 1-1/4" Sectional Cable
- 48-53-4840 3" – 8" Head Attachment Kit w/ RUST GUARD™ for 1-1/4" Sectional Cable
- 44-60-0005 Pin Key for Drain Cleaning
- 48-53-2839 Head Attachment Case



M18 FUEL
SWITCH PACK™ Sectional Kit for 5/16" - 5/8" Cable

2775-211, 2775A-211, 2775B-211, 2775C-222, 2775E-211

Specifications:

Maximum Drain Line Capacity	1-1/4" – 4" up to 100' (not for roots)
Drum Capacity	Inner Core Cables: 5/16" x 75', Best for 1-1/4" – 2-1/2" drain lines; 3/8" x 50', Best for 2" – 3" drain lines; 1/2" x 50', Best for 3" – 4" drain lines Open Wind Cables: 5/8" x 50', Best for 1-1/4" – 3" drain lines (soft blockages)
Backpack Straps	Yes
Removable Drum	Yes, Tool-Free
Cable Spin Speed	250 RPM
Electronic Foot Pedal	Yes
Integrated Drum Brake	Yes
Length	15.8"



Includes: 2775A-211: 5/16" x 75' Inner Core Drop Head Cable w/ RUST GUARD™ Plating;

2775B-211: 3/8" x 50' Inner Core Coupling Cable w/ RUST GUARD™ Plating, (4) Cable Head Attachments w/ RUST GUARD™ Plating (1-1/2" Spade Bit, 1-1/2" C-Cutter, Medium Funnel, Medium Drop Head), Pin Key;

2775C-222: Additional M18™ REDLITHIUM™ XC5.0 Battery Pack, Additional SWITCH PACK™ Drum w/ Anchor Cable, (2) 1/2" x 50' Inner Core Coupling Cables w/ RUST GUARD™ Plating, (4) Cable Head Attachments w/ RUST GUARD™ Plating (1-1/2" Spade Bit, 1-1/2" C-Cutter, Medium Funnel, Medium Drop Head), Pin Key;

2775E-211: 5/8" x 50' Open Wind Coupling Cable w/ RUST GUARD™ Plating, (4) Cable Head Attachments w/ RUST GUARD™ Plating (1" Spade Bit, 1" C-Cutter, Small Bulb Head, Small Drop Head), Pin Key;

All Kits Include: 2775-211: SWITCH PACK™ Powered Base, SWITCH PACK™ Drum w/ Anchor Cable, (1) M18™ REDLITHIUM™ XC5.0 Battery Pack, Multi-Voltage Charger

Related Accessories:

- 47-53-2775 SWITCH PACK™ Drum w/ Anchor Cable
- 47-53-2774 CABLE DRIVE™ Assembly
- 47-53-2773 Mounting Plate
- 47-53-2776 Guide Hose

M18 FUEL
Drain Snake w/ CABLE DRIVE™ Kit for 1/4" - 3/8" Cable

2772A-21 (2772A-20 Tool-Only), 2772B-21XC

Specifications:

Maximum Drain Line Capacity	1-1/4" – 3" up to 50'
Drum Capacity	1/4" x 50', Best for 1-1/4" – 2" drain lines; 5/16" x 50', Best for 1-1/4" – 2-1/2" drain lines; 3/8" x 35', Best for 2" – 3" drain lines
Powered Cable Feed & Retract	Yes, CABLE DRIVE™
Variable Feed Speed	0 – 8" Per Second
Variable Spin Speed	0 – 600 RPM
Feed Lock	Yes, Twist Lock
Cable Lock	Yes, Twist Lock
LED Light	Yes
Length / Weight	19.5" / 8.2 lbs



Includes: 2772A-21 (1) M18™ REDLITHIUM™ CP2.0 Battery Pack, 5/16" x 35' Inner Core Bulb Head Cable w/ RUST GUARD™ Plating; 2772B-21XC (1) M18™ REDLITHIUM™ XC5.0 Battery Pack, 1/4" x 35' Inner Core Bulb Head Cable w/ RUST GUARD™ Plating, 3/8" x 35' Inner Core Coupling Cable w/ RUST GUARD™ Plating, (4) Cable Attachments (1" Spade Bit, 1" C-Cutter, Small Bulb Head, Small Drop Head), Pin Key; 2772A-20 Only Includes 5/16" x 35' Inner Core Bulb Head Cable w/ RUST GUARD™ Plating, Battery and Charger Sold Separately;

All Kits Include: Multi-Voltage Charger, Storage Bucket

Drain Cleaning Accessories

Compatible with MILWAUKEE® and other professional brand drain cleaning machines

RUST GUARD™ Plated Cables

- 48-53-2563 1/4" x 25' Inner Core Bulb Head Handheld Cable
- 48-53-2564 1/4" x 25' Inner Core Drop Head Handheld Cable
- 48-53-2671 1/4" x 35' Inner Core Bulb Head Handheld Cable
- 48-53-2672 1/4" x 50' Inner Core Bulb Head Handheld Cable
- 48-53-2561 5/16" x 25' Inner Core Bulb Head Handheld Cable
- 48-53-2562 5/16" x 25' Inner Core Drop Head Handheld Cable
- 48-53-2673 5/16" x 35' Inner Core Bulb Head Handheld Cable
- 48-53-2674 5/16" x 50' Inner Core Bulb Head Handheld Cable
- 48-53-2772 5/16" x 75' Inner Core Drop Head Cable
- 48-53-2676 3/8" x 25' Inner Core Handheld Cable
- 48-53-2675 3/8" x 35' Inner Core Handheld Cable

RUST GUARD™ Plated Cable Attachments

Compatible with MILWAUKEE® Coupling Cables

- 48-53-2681 Small Bulb Head
- 48-53-2682 Small Drop Head
- 48-53-2683 1" Spade Bit
- 48-53-2684 1" C-Cutter
- 48-53-2685 2" – 3" Head Attachment Kit
- 48-53-2786 Medium Funnel Head
- 48-53-2787 Medium Drop Head
- 48-53-2788 1-1/2" Spade Bit
- 48-53-2789 1-1/2" C-Cutter
- 48-53-2790 2" – 3" Head Attachment Kit





M18™ 120' Pipeline Inspection System Kit

2973-22 (2973-20 Tool-Only)

Specifications:

Line Capacity	2" – 6"
Push Cable	10 mm, 120'
Camera Head	25 mm, Self-Leveling, Sapphire Lens
Camera Resolution	1080P
Internal Storage	500GB
Sonde Frequency	512kHz, 33kHz
Line Trace Frequency	33kHz, 83kHz



Includes: (2) M18™ REDLITHIUM™ XC5.0 Battery Packs, 120' Mid-Stiff Pipeline Inspection Reel, M18™ 500GB Control Hub, Tablet Mount, Medium Camera Head Skid for 25 mm Camera, Small Camera Head Skid for 25 mm Camera, Rapid Charger

Related Accessories:

2971-20 M18™ Wireless Monitor
2970-20 M18™ 500GB Control Hub
48-53-2970 Tablet Mount



M18™ 200' Stiff Pipeline Inspection System Kit

2974-21 (2974-20 Reel-Only)

Specifications:

Line Capacity	3" – 10"
Push Cable	12 mm, 200'
Camera Head	34 mm, Self-Leveling, Sapphire Lens
Camera Resolution	1080P
Internal Storage	500GB
Sonde Frequency	512kHz, 640Hz, 33kHz
Line Trace Frequency	33kHz, 83kHz



Includes: (2) M18™ REDLITHIUM™ XC5.0 Battery Packs, 200' Stiff Pipeline Inspection Reel, M18™ 500GB Control Hub, Tablet Mount, Medium Camera Head Skid for 34 mm Camera, Small Camera Head Skid for 34 mm Camera, Rapid Charger

M18™ Wireless Monitor

2971-20 Tool-Only

Specifications:

Screen	8" Daylight Readable
Resolution	800 x 600
Wireless Range	200'
Weight	4 lbs

Battery and Charger Sold Separately

Includes: USB-C Cable



M18™ Transfer Pump Kit

2771-21 (2771-20 Tool-Only)

Specifications:

Gallons Per Hour	480
Gallons Per Battery (w/ M18™ XC3.0 Battery)	144
Maximum Lift	18'
Maximum Head Height	75'
Self-Priming	Yes
Flexible Impeller	Yes
Fittings	3/4" Brass Inlet and Outlet
Weight	7.5 lbs



Includes: (1) M18™ REDLITHIUM™ XC3.0 Battery Pack, (2) 3/4" Brass Fittings, Multi-Voltage Charger



OUTDOOR POWER EQUIPMENT

M18 FUEL
DRIVEN TO OUTPERFORM.



MORE POWER **FULL THROTTLE UNDER 1 SECOND** **MORE RUN-TIME**

NO GAS HEADACHES



NO PULL START



NO ENGINE MAINTENANCE



LOW NOISE



NO EMISSIONS



NO MIXING GAS AND OIL

ALL M18™ TOOLS FIT M18™ BATTERIES

1 SYSTEM



200+ TOOLS

M18 FUEL
16" Chainsaw Kit

2727-21HD (2727-20 Tool-Only)

Specifications:

Bar Length	16"
Chain Gauge	.043"
Chain Pitch	3/8" Low Profile
RPM	6,600
Length / Weight	33.0" / 13.9 lbs



Includes: (1) M18™ REDLITHIUM™ HIGH OUTPUT™ HD12.0 Battery Pack, 16" Oregon® Bar and Chain, Srench, Scabbard, Rapid Charger



M18 FUEL
14" Chainsaw

2727-20C Tool-Only

Specifications:

Bar Length	14"
Chain Gauge	.043"
Chain Pitch	3/8" Low Profile
RPM	6,600
Length / Weight	31.0" / 10.4 lbs



Battery and Charger Sold Separately

Includes: 14" Oregon® Bar and Chain, Srench, Scabbard

M18 FUEL
Pole Saw Kit w/ QUIK-LOK™

2825-21PS (2825-20PS Tool-Only)

Specifications:

RPM	0 – 4,600
Bar Length	10"
Chain Gauge	.043"
Chain Pitch	3/8" Low Profile
Length / Weight	84.0" / 12.7 lbs



Includes: M18 FUEL™ Power Head w/ QUIK-LOK™, M18 FUEL™ QUIK-LOK™ 10" Pole Saw Attachment, QUIK-LOK™ 3' Attachment Extension, (1) M18™ REDLITHIUM™ HIGH OUTPUT™ XC8.0 Battery Pack, Oregon® Bar and Chain, Srench, Rapid Charger

M18 FUEL
String Trimmer Kit w/ QUIK-LOK™

2825-21ST (2825-20ST Tool-Only)

Specifications:

Cutting Swath	14" – 16"
Line Diameter	.080" / .095"
RPM	0 – 4,900 / 0 – 6,200
Trigger	Variable Speed
Feed System	Bump Feed
Length / Weight	73.6" / 12.3 lbs



Includes: M18 FUEL™ Power Head w/ QUIK-LOK™, M18 FUEL™ QUIK-LOK™ String Trimmer Attachment, (1) M18™ REDLITHIUM™ HIGH OUTPUT™ XC8.0 Battery Pack, Rapid Charger



M18 FUEL
QUIK-LOK™ Attachments

Compatible with M18 FUEL™ Power Head w/ QUIK-LOK™ (2825-20)

- 49-16-2717 M18 FUEL™ String Trimmer Attachment
- 49-16-2718 M18 FUEL™ Edger Attachment
- 49-16-2719 M18 FUEL™ Articulating Hedge Trimmer Attachment
- 49-16-2720 M18 FUEL™ 10" Pole Saw Attachment
- 49-16-2721 M18 FUEL™ 3' Attachment Extension



M18™ Brushless String Trimmer Kit

2828-21 (2828-20 Tool-Only)

Specifications:

Cutting Swath	14" – 16"
Line Diameter	.080" / .095"
RPM	0 – 4,600 / 0 – 6,200
Trigger	Variable Speed
Feed System	Bump Feed
Length / Weight	73.6" / 11.5 lbs



Includes: (1) M18™ REDLITHIUM™ HIGH OUTPUT™ XC6.0 Battery Pack, Multi-Voltage Charger



M18 FUEL
Blower Kit

2724-21HD (2724-20 Tool-Only)

Specifications:

Max Air Volume	450 CFM
Max Air Speed	120 MPH
Noise Rating (db)	62 (ANSI B175)
Lock On Button	Yes
Length / Weight	36.9" / 7.3 lbs



Includes: (1) M18™ REDLITHIUM™ HIGH OUTPUT™ XC8.0 Battery Pack, Rapid Charger

M18 FUEL
24" Hedge Trimmer Kit

2726-21HD (2726-20 Tool-Only)

Specifications:

Blade Length	24"
Cut Capacity	3/4"
SPM	3,400
Gear Case	All Metal
Length / Weight	45.5" / 11.1 lbs



Includes: (1) M18™ REDLITHIUM™ HIGH OUTPUT™ XC8.0 Battery Pack, Scabbard, Rapid Charger

M18™ SWITCH TANK™ 4-Gallon Backpack Sprayer Kit

2820-21PS (2820-20PS Tool-Only)

Specifications:

Tank Capacity	4 Gallon
Pump Type	Dual Diaphragm Pump
PSI Range	20 – 120 PSI (5 Modes)
Spray Distance	Up to 25'
Flow Rate Range	0.10 – 0.51 Gal/Min
Dry Weight	18.3 lbs



Includes: M18™ SWITCH TANK™ Powered Base, SWITCH TANK™ 4 Gallon Sprayer Tank Assembly, (1) M18™ REDLITHIUM™ XC3.0 Battery Pack, Adjustable Nozzle, Fan Nozzle, Multi-Voltage Charger

Related Accessories:

- 49-16-28WS SWITCH TANK™ 4 Gallon Water Supply Tank Assembly
- 49-16-28CS SWITCH TANK™ 4 Gallon Concrete Sprayer Tank Assembly
- 49-16-28PS SWITCH TANK™ 4 Gallon Sprayer Tank Assembly



M18™ ROCKET™ Dual Pack Tower Light w/ ONE-KEY™ Kit
2120-22HD (2120-20 Tool-Only)

Specifications:

Lumens	5,400 / 3,100 / 1,600 (Customizable)
Modes	High, Medium, Low
Water & Dust Rating	IP67
Height	22" Collapsed, 5'5" Fully Extended
Weight	8.2 lbs



Includes: (2) M18™ REDLITHIUM™ HIGH OUTPUT™ XC8.0 Battery Packs, Shoulder Strap, Rapid Charger



M18™ ROCKET™ Tower Light/Charger Kit
2136-21 (2136-20 Tool-Only)

Specifications:

Lumens	6,000 / 3,200 / 1,700
Modes	High, Medium, Low
Battery Charger	Charges M18™ Batteries and USB Devices
Height	40" Collapsed, 7' Fully Extended
Weight	21 lbs



Includes: (1) M18™ REDLITHIUM™ HIGH OUTPUT™ XC8.0 Battery Pack, M18™ ROCKET™ Tower Light Carry Bag




M18™ ROCKET™ Dual Power Tower Light
2131-20 Tool-Only

Specifications:

Lumens	2,500 / 1,100 / 700
Modes	High, Medium, Low
Height	40" Collapsed, 7' Fully Extended
Weight	15.3 lbs



Battery and Charger Sold Separately




M18™ RADIUS™ Site Light/Charger w/ ONE-KEY™
2150-20 Tool-Only

Specifications:

Lumens	9,000 / 4,800 / 2,500 (Customizable)
Modes	High, Medium, Low
Water & Dust Rating	IP54
Height / Weight	29.5" / 27.1 lbs



Battery and Charger Sold Separately




M18™ RADIUS™ Site Light
2151-20 Tool-Only

Specifications:

Lumens	9,000 / 4,800 / 2,500
Modes	High, Medium, Low
Height / Weight	29.5" / 23.2 lbs



Battery and Charger Sold Separately



M18™ RADIUS™ Compact Site Light w/ ONE-KEY™
2146-20 Tool-Only


Specifications:

Lumens	4,400 / 2,100 / 1,000 (Customizable)
Modes	High, Medium, Low
Water & Dust Rating	IP54
Hands-Free	Self-Centering Metal Hook
Daisy Chain Compatible	Yes
Weight	10.6 lbs



Battery and Charger Sold Separately

Includes: Security Cable; 2147-20 Equipped with NEMA L5-20 Twistlock Outlets Also Available



M18™ RADIUS™ Compact Site Light
2145-20 Tool-Only


Specifications:

Lumens	4,400 / 2,100 / 1,000
Modes	High, Medium, Low
Water & Dust Rating	IP54
Hands-Free	Self-Centering Metal Hook
Daisy Chain Compatible	Yes
Weight	10.6 lbs



Battery and Charger Sold Separately

Includes: Security Cable




M18™ RADIUS™ Compact Site Light w/ Flood Mode
2144-20 Tool-Only

Specifications:

Lumens (Area)	2,200 / 1,100 / 550
Lumens (Flood)	1,000 / 500 / 250
Modes	High, Medium, Low
Hands-Free	Self-Centering Metal Hook
Height / Weight	10.4" / 4.4 lbs



Battery and Charger Sold Separately




M18™ PACKOUT™ Light/Charger
2357-20 Tool-Only

Specifications:

Lumens	3,000 / 1,500 / 1,000
Modes	High, Medium, Low
Battery Charger	Charges all M18™ Batteries
USB Charger	2.1A USB Charging Port for External Devices
Device Storage	Weather Sealed



Battery and Charger Sold Separately



M18™ ROVER™ Mounting Flood Light
2365-20 Tool-Only

Specifications:

Lumens	1,500 / 650 / 300
Modes	High, Medium, Low
Water & Dust Rating	IP54
Rotating Head	Horizontal and Vertical
Hands-Free	Integrated Magnet, Spring Loaded Clamp
Length / Weight	6.3" / 3.2 lbs



Battery and Charger Sold Separately

M18™ ROVER™ Flood Light
2361-20 Tool-Only

Specifications:

Lumens	1,500 / 780
Modes	High, Low
Water & Dust Rating	IP54
Hands-Free	(1) EMT Hanger
Length / Weight	8.8" / 3.1 lbs



Battery and Charger Sold Separately

M18™ Stick Light
2352-20 Tool-Only

Specifications:

Lumens	300 / 150
Modes	High, Low
Water & Dust Rating	IP54
Pivoting Head	45°
Hands-Free	2 Stainless Steel Hooks
Length / Weight	11.6" / 1.1 lbs



Battery and Charger Sold Separately

M18™ Trouble Light w/ USB Charging
2363-20 Tool-Only

Specifications:

Lumens	700 / 350 / 70 / 700
Modes	High, Medium, Low, Strobe
Run-Time	Up to 100 Hours
Beam Pattern	Adjustable Task – Area
Water & Dust Rating	IPX4
Hands-Free	2 Stainless Steel Hooks
USB Charger	2.1A USB Charging Port for External Devices
Length / Weight	11.5" / 1.2 lbs



Battery and Charger Sold Separately




M18™ Search Light Kit
2354-21 (2354-20 Tool-Only)

Specifications:

Lumens	1,250 / 1,200 / 600 / 1,200
Modes	Spot/Flood, Flood, Spot, Strobe
Beam Distance	730 yd / 668 m
Water & Dust Rating	IP54
Head Rotation	198°
Length / Weight	11.5" / 3.1 lbs



Includes: (1) M18™ REDLITHIUM™ XC5.0 Battery Pack, Shoulder Strap, Multi-Voltage Charger



M18™ Utility Bucket Light Kit

2122-22HD, 2122-21HD (2122-20 Tool-Only)

Specifications:

Lumens	2,500 / 2,200 / 800
Modes	Flood, Spot/Flood, Spot
Hands-Free	Patented Spring-Loaded Bucket Clamp
Water & Dust Rating	IP56
Length / Weight	13.8" / 8.3 lbs



Includes: 2122-22HD (2) M18™ REDLITHIUM™ HIGH OUTPUT™ XC8.0 Packs;
2122-21HD (1) M18™ REDLITHIUM™ HIGH OUTPUT™ XC8.0 Pack;



All Kits Include: Rapid Charger, Storage Bag

M18™ Utility Remote Control Search Light

2123-21HD (2123-20 Tool-Only)

Specifications:

Lumens	4,250 / 3,500 / 1,250 / 1,500
Modes	Flood, Spot/Flood Low
Water & Dust Rating	IP56 Built For Outdoor Use
Mounting	Portable Magnetic Base or 12V DC Permanent Base



Includes: 2123-21HD (1) M18™ REDLITHIUM™ HIGH OUTPUT™ HD12.0 Battery Pack, Rapid Charger, 12V DC Permanent Base, M18™ Portable Base, Remote Control, Dash Mount, Carry Bag

2123-20 12V DC Permanent Base, M18™ Portable Base, Remote Control, Dash Mount, Lanyard, Carry Bag

Related Accessory:

49-16-2123B M18™ Utility Remote Control Search Light Magnetic Base w/ Carry Bag

M18™ Work Light

2735-20 Tool-Only

Specifications:

Lumens	100
Hands-Free	Integrated Hook
Head Rotation	90°



Battery and Charger Sold Separately

M18™ Compact Blower

0884-20 Tool-Only

Specifications:

Max Air Volume	100 CFM
Max Air Speed	160 MPH
Switch	3-Speed Electronic
Length / Weight	20.5" / 2.6 lbs



Battery and Charger Sold Separately

Includes: Flexible Nozzle, 9" Extension, Universal Inflator/Deflator

M18™ Jobsite Fan

0886-20 Tool-Only

Specifications:

Max Air Flow	284 CFMs (18 MPH)
Max Air Speed	15 MPH
Max Air Volume	600 CFM
Speed Settings	3
RPM (3 Settings)	1,370 / 1,900 / 2,350
Head Rotation	120°
Length / Weight	10.3" / 5.2 lbs
Additional Features	Key Holes, Pass-Through Holes



Battery and Charger Sold Separately

Includes: AC Adapter

POWERED BY



M18 FUEL 3-in-1 Backpack Vacuum Kit

0885-21HD (0885-20 Tool-Only)

Specifications:

Air Volume	55 CFM
Sealed Suction	75" H ₂ O
Run-Time (w/ M18™ HIGH OUTPUT™ XC8.0 Battery)	20 min
Capacity	1 Gallon
Inlet Diameter	1-7/8"
Weight	15.6 lbs



Includes: (1) M18™ REDLITHIUM™ HIGH OUTPUT™ XC8.0 Battery Pack, Telescoping Extension Wand, Flexible Hose, HEPA Filter, Crevice Tool, Dust Extraction Adapter and Floor Tool, Rapid Charger

Related Accessories:

49-90-1963 HEPA Filter
49-90-1964 9' Hose Accessory



M18 FUEL Compact Vacuum

0940-20 Tool-Only

Specifications:

Air Volume	32 CFM
Sealed Suction	80" H ₂ O
Run-Time (w/ M18™ XC5.0 Battery)	Up to 28 Min
Capacity	.25 Gallon
Inlet Diameter	1-1/4"
Weight	4.4 lbs



Battery and Charger Sold Separately

Includes: Powered Floor Tool, Floor Tool, HEPA Filter, Foam Pre-Filter, Extension Wand, 6' Flexible Hose, Accessory Holder, Brush Tool, Utility Tool, Crevice Tool

Related Accessory:

49-90-1951 HEPA Dry Filter Kit (2 pk)
49-90-2012 HEPA Filter
49-90-2017 1-1/4" Round Brush Tool
49-90-2018 Vacuum Power Tool Adapter

M18 FUEL PACKOUT™ 2.5 Gallon Wet/Dry Vacuum

0970-20 Tool-Only

Specifications:

Air Volume	50 CFM
Sealed Suction	47" H ₂ O
Run-Time (w/ M18™ HIGH OUTPUT™ XC8.0 Battery)	Up to 50 Min
Capacity	2.5 Gallons
Inlet Diameter	1-1/4"
Weight	11.3 lbs



Battery and Charger Sold Separately

Includes: HEPA Filter, 6' Flexible Hose, Utility Nozzle, Crevice Tool, Vacuum Power Tool Adapter

Related Accessories:

49-90-1900 HEPA Filter
49-90-2015 Foam Wet Filter
49-90-2016 3 pk Fleece Dust Bags
49-90-2017 1-1/4" Round Brush Tool
49-90-2018 Vacuum Power Tool Adapter

M18™ 2 Gallon Wet/Dry Vacuum

0880-20 Tool-Only

Specifications:

Air Volume	45 CFM
Sealed Suction	32" H ₂ O
Run-Time (w/ M18™ HD9.0 Battery)	30 min
Capacity	2 Gallons
Inlet Diameter	1-1/4"
Weight	11.3 lbs



Battery and Charger Sold Separately

Includes: HEPA Filter, 6' Flexible Hose, Crevice Tool, Utility Nozzle

Related Accessories:

49-90-1900 HEPA Filter
49-90-2015 Foam Wet Filter
49-90-2017 1-1/4" Round Brush Tool
49-90-2018 Vacuum Power Tool Adapter

M18™ Compact Vacuum

0882-20 Tool-Only

Specifications:

Air Volume	40 CFM
Sealed Suction	38" H ₂ O
Run-Time (w/ M18™ XC5.0 Battery)	25 min
Capacity	36 oz
Inlet Diameter	1-1/4"
Weight	4.3 lbs



Battery and Charger Sold Separately

Includes: 4' Flexible Hose, (2) Extension Tools, Crevice Tool, Floor Tool, Removable HEPA Filter

Related Accessories:

49-90-1951 HEPA Filter (2 pk)
49-90-2017 1-1/4" Round Brush Tool
49-90-2018 Vacuum Power Tool Adapter

M18™ PACKOUT™ Radio + Charger

2950-20 Tool-Only

Specifications:

Modes	Bluetooth® 4.2, AM/FM, AUX
Battery Charger	Charges all M18™ Batteries
Bluetooth® Range	100 ft
USB Charging Port	2.1A USB Charging Port for External Devices
Device Storage	Weather Sealed



Battery Sold Separately

Includes: 3.2 mm Auxiliary Input Cord, (2) AAA Batteries (For Memory Backup)

CHARGES



POWERED BY



M18™ Jobsite Radio/Charger

2792-20 Tool-Only

Specifications:

Modes	AM, FM, AUX, Bluetooth®
Battery Charger	Charges all M18™ Batteries
Bluetooth® Range	100 ft
USB Charging Port	2.1A USB Charging Port for External Devices
Device Storage	Weather Sealed Auxiliary Compartment



Battery Sold Separately

Includes: 3.2 mm Auxiliary Input Cord, (2) AAA Batteries (For Memory Backup)

CHARGES



POWERED BY



M18™ Jobsite Radio

2890-20 Tool-Only

Specifications:

Modes	AM, FM, AUX
USB Charging Port	2.1A USB Charging Port for External Devices
Device Storage	Weather Sealed Auxiliary Compartment



Battery and Charger Sold Separately

Includes: 3.2 mm Auxiliary Input Cord, (2) AAA Batteries (For Memory Backup)

CHARGES



POWERED BY



M18™ / M12™ Wireless Jobsite Speaker

2891-20 Tool-Only

Specifications:

Modes	Bluetooth®, AUX (Cable Not Included)
Bluetooth® Range	100 ft
USB Charging Port	2.1A USB Charging Port for External Devices



Battery and Charger Sold Separately

Includes: AC Adapter

CHARGES



POWERED BY



M18™ Power Source

49-24-2371

Specifications:

USB Charging Port	2.1A USB Charging Port for External Devices
Run-Time	Up to 18 Hours
Powered By	All M18™ Batteries



Battery Sold Separately

Powers all MILWAUKEE® M12™ Heated Gear



M18™ TOP-OFF™ 175W Power Supply

2846-20 Tool Only

Specifications:

Continuous Watts	175W
Power Source	Any M18™ Battery
DC Output	(1) USB-A Port, (1) USB-C PD Port
AC Output	(1) AC Outlet



Battery Sold Separately

M18™ REDLITHIUM™ HIGH OUTPUT™ HD12.0 System Starter Kit

48-59-1200

Includes: (1) M18™ REDLITHIUM™ HIGH OUTPUT™ HD12.0 Battery Pack, Rapid Charger



M18™ REDLITHIUM™ HIGH OUTPUT™ XC8.0 System Starter Kit

48-59-1880

Includes: (1) M18™ REDLITHIUM™ HIGH OUTPUT™ XC8.0 Battery Pack, Rapid Charger



M18™ REDLITHIUM™ XC5.0 System Starter Kit

48-59-1850

Includes: (1) M18™ REDLITHIUM™ XC5.0 Battery Pack, Multi-Voltage Charger



M18™ REDLITHIUM™ HIGH OUTPUT™ CP3.0 System Starter Kit

48-59-1835

Includes: (1) M18™ REDLITHIUM™ HIGH OUTPUT™ CP3.0 Battery Pack, Multi-Voltage Charger



M18™ & M12™ Super Charger

48-59-1811

Specifications:

Compatibility	All M18™ and M12™ Batteries
Charge Sequence	Sequential (First In, First Charged)
Charge Speed	Charges up to 4X Faster, Charges All HIGH OUTPUT™ Batteries in One Hour Or Less
On-Board Indicator Light	Yes
Integrated Hang-Holes	Yes
Cell Voltage Monitoring	Yes



Batteries Sold Separately

M18™ Six-Pack Sequential Charger

48-59-1806

Specifications:

Compatibility	All M18™ Batteries
Charge Sequence	Sequential (Counter-Clockwise Rotation)
Skip Button	Manually Designate which Battery Charges First
Integrated Hang-Holes	Yes
Cell Voltage Monitoring	Yes
Pass-Through Plug	Yes



Batteries Sold Separately

Pass-Through Plug

M18™ & M12™ Rapid Charge Station

48-59-1807

Specifications:

Compatibility	All M18™ and M12™ Batteries
Charge Sequence	Charges 3 Batteries Simultaneously
Charge Speed	Charges Individual Batteries up to 40% Faster
Capacity	Holds (3) M18™ and (3) M12™ Batteries
Integrated Hang-Holes	Yes
Cell Voltage Monitoring	Yes
Pass-Through Plug	Yes



Batteries Sold Separately

Pass-Through Plug

M18™ Dual Bay Simultaneous Rapid Charger

48-59-1802

Specifications:

Compatibility	All M18™ Batteries
Charge Sequence	Simultaneous
Charge Speed	Charges Individual Batteries up to 40% Faster
Integrated Hang-Holes	Yes



Batteries Sold Separately

M18™ & M12™ Rapid Charger

48-59-1808

Specifications:

Compatibility	All M18™ and M12™ Batteries
Charge Sequence	Sequential (First In, First Charged)
Charge Speed	Charges Individual Batteries up to 40% Faster
On-Board Indicator Light	Yes
Integrated Hang-Holes	Yes
Cell Voltage Monitoring	Yes



Batteries Sold Separately

M18™ & M12™ Multi-Voltage Charger

48-59-1812

Specifications:

Compatibility	All M18™ and M12™ Batteries
Charge Sequence	Sequential (First In, First Charged)
Integrated Hang-Holes	Yes
On-Board Indicator Light	Yes
Cell Voltage Monitoring	Yes



Batteries Sold Separately

M18™ & M12™ Vehicle Charger

48-59-1810

Specifications:

Compatibility	All M18™ and M12™ Batteries
Charge Sequence	Sequential (First In, First Charged)
On-Board Indicator Light	Yes
Cell Voltage Monitoring	Yes



Batteries Sold Separately

M18 REDLITHIUM™ HIGH OUTPUT™

50% MORE POWER & RUNS COOLER VS REDLITHIUM™

CP XC HD

LIGHT DEMAND FITS M18 TOOLS HEAVY DEMAND

CP Less weight and smaller size

XC More power and run-time, great performance for all demands

HD Best performance for high demand applications

HIGH OUTPUT 48-11-1835 48-11-1837 M18™ REDLITHIUM™ HIGH OUTPUT™ CP3.0 Battery Pack 2-Pack

HIGH OUTPUT 48-11-1820 M18™ REDLITHIUM™ CP2.0 Battery Pack

HIGH OUTPUT 48-11-1815 48-11-1811 M18™ REDLITHIUM™ CP1.5 Battery Pack 2-Pack

HIGH OUTPUT 48-11-1880 M18™ REDLITHIUM™ HIGH OUTPUT™ XC8.0 Battery Pack

HIGH OUTPUT 48-11-1865 48-11-1862 M18™ REDLITHIUM™ HIGH OUTPUT™ XC6.0 Battery Pack 2-Pack

HIGH OUTPUT 48-11-1850 48-11-1852 M18™ REDLITHIUM™ XC5.0 Battery Pack 2-Pack

HIGH OUTPUT 48-11-1851 48-11-1851 10-Pack

HIGH OUTPUT 48-11-1840 M18™ REDLITHIUM™ XC4.0 Battery Pack


HIGH OUTPUT 48-11-1828 48-11-1822 M18™ REDLITHIUM™ XC3.0 Battery Pack 2-Pack

MILWAUKEE® is committed to improving productivity by providing performance-driven and trade-focused solutions so users can perform an entire day's work on one battery system. *Due to the physical size increase of the M18™ REDLITHIUM™ HIGH OUTPUT™ HD12.0, it does not fit the following tools prior to a 6/1/2018 manufacturing date without applicable service part: 2787-20, 2788-20, 2771-20, 2122-20, 2130-20, 2135-20, 2361-20, 2145-20, 2146-20, 2360-20. MILWAUKEE® is committed to protecting end user's investments, offering FREE service upgrades for the listed products to any customer that purchases a HIGH OUTPUT™ HD12.0 battery pack (starting summer 2018 you will be able to visit eService to request your service upgrade).

M18™ COMBO KITS

	2 PIECE KITS										3 - 4 PIECE KITS		LARGE KITS			
	2996-22	2997-22	2893-22CX	2893-22	2697-22CT	2892-22CT	2691-22	2694-22	2992-22	2999-22	2897-22CT	2695-24	2696-24	2998-25	2696-26	2997-27
Kit Tool Total	2	2	2	2	2	2	2	2	2	2	2	4	4	5	6	7
M18 FUEL™ 1/2" Hammer Drill/Driver w/ ONE-KEY™	■															
M18 FUEL™ 1/2" Hammer Drill/Driver		■								■				■		■
M18™ 1/2" Brushless Hammer Drill/Driver			■	■					■							
M18™ 1/2" Compact Hammer Drill/Driver					■			■				■	■		■	
M18™ 1/2" Compact Brushless Drill/Driver						■										
M18™ 1/2" Compact Drill/Driver							■									
M18 FUEL™ Drywall Screw Gun											■					
M18 FUEL™ 1/4" Hex Impact Driver w/ ONE-KEY™	■															
M18 FUEL™ SURGE™ 1/4" Hex Hydraulic Driver									■	■						
M18 FUEL™ 1/4" Hex Impact Driver		■												■		■
M18™ 1/4" Hex Brushless Impact Driver			■			■										
M18™ Brushless 1/4" Hex 3-Speed Impact Driver				■												
M18™ 1/4" Hex Impact Driver*					■		■				■	■			■	
M18 FUEL™ 1/2" Mid-Torque Impact Wrench w/ Friction Ring																■
M18 FUEL™ SAWZALL® Reciprocating Saw								■						■		■
M18™ SAWZALL® Reciprocating Saw												■			■	
M18™ HACKZALL® One-Handed Reciprocating Saw											■					
M18 FUEL™ 6-1/2" Circular Saw														■		■
M18™ 6-1/2" Circular Saw															■	
M18™ Brushless 7-1/4" Circular Saw								■								
M18 FUEL™ 4-1/2" / 5" Grinder Paddle Switch, No-Lock																■
M18™ 4-1/2" Cut-Off / Grinder																■
M18™ Work Light												■	■	■	■	■
Also Includes																
M18™ and M12™ Multi-Voltage Charger	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
M18™ REDLITHIUM™ CP1.5 Battery Pack					2		2									
M18™ REDLITHIUM™ CP2.0 Battery Pack			1		2					2						
M18™ REDLITHIUM™ XC3.0 Battery Pack											2	2		2		
M18™ REDLITHIUM™ XC4.0 Battery Pack			1	2				2								
M18™ REDLITHIUM™ XC5.0 Battery Pack	2	2					2		2					2		2
Carrying Case	■	■								■						
Contractor Bag			■	■	■	■	■	■	■	■	■	■	■	■	■	2

*M18™ 1/4" Hex Impact Driver is the single, variable speed model



M18

**PERFORMANCE DRIVEN
TRADE FOCUSED
SYSTEM WIDE**

Milwaukee
Nothing but **HEAVY DUTY**®

**LEARN
MORE**



or visit <https://qr.mke.tl/2jd5d>



**EQUIPMENT REDEFINED
TRADE FOCUSED
SYSTEM WIDE**

**ALL MX FUEL™ BATTERIES FIT
ALL MX FUEL™ EQUIPMENT**



MX FUEL™
14" Cut-Off Saw
MXF314-2XC



MX FUEL™
Handheld Core Drill
MXF301-2CP



MX FUEL™
Breaker
MXF368-1XC



MX FUEL™
ROCKET™ Tower Light/Charger
MXF041-1XC



MX FUEL™
Sewer Drum Machine w/ POWERTREDZ™
MXF501-1CP



MX FUEL™
Backpack Concrete Vibrator
MXF371-2XC



MX FUEL™
CARRY-ON™ 3600W/1800W Power Supply
MXF002-2XC



MX FUEL™
Vibratory Screenshot
MXF381-2CP





EQUIPMENT REDEFINED.

The MX FUEL™ Equipment System revolutionizes the light equipment market by delivering the performance, run-time and durability demanded by the trades without the hazards associated with emissions, noise, vibration and the frustrations of gas maintenance. This completely compatible system goes beyond the limitations of gasoline and power cord units, utilizing the industry's most advanced batteries, motors and electronics to deliver a best-in-class experience for users. This is Equipment Redefined.


1 REDLITHIUM™ BATTERY PACK

- Industry Leader in LITHIUM-ION Technology
- Patented Designs Protect Against Drops, Water and Harsh Environments
- Robust Electronics Optimize Performance for Every Equipment and Battery Combination




2 REDLINK PLUS™ INTELLIGENCE

- Most Advanced System of Equipment Electronics in the Industry
- Protects Equipment with Best-In-Class Thermal and Overload Monitoring
- Delivers In-Application Communication, Optimizing Equipment Performance



3 POWERSTATE™ BRUSHLESS MOTOR

- Engineered Uniquely for the Demands of Each Piece of Equipment
- Optimized for the Perfect Combination of Performance, Portability and Productivity
- Built with Maximum Copper Content and Top-Grade Rare Earth Magnets



**EQUIPMENT REDEFINED
TRADE FOCUSED
SYSTEM WIDE**

**MX FUEL™
14" Cut-Off Saw Kit**



**NO
GAS
HEADACHES**

**FASTEST
CUTS FROM
START TO FINISH**

**6 FT IN
CONCRETE,
72 CUTS IN
#5 REBAR
PER CHARGE**

MXF314-2XC

Specifications:

Blade Diameter	14"
Cut Depth	5"
Blade Arbor	1" / 20 mm
RPM	5,350
On-Board Water Delivery	Yes
Weight w/ Battery	32.1 lbs
Push Button Start	Yes
ONE-KEY™ Compatible	Track and Manage.
Battery Compatibility	Fits All MX FUEL™ Battery Packs
Warranty	2 Year Equipment, Battery & Charger

Includes: (2) MX FUEL™ REDLITHIUM™ XC406 Battery Packs, MX FUEL™ Charger, Wrench, Hex Key, Quick Connect, Contractor Bag

Available Accessories: (Not Included)

49-94-1475
14" x 1/8" x 1" Cutting Wheel


49-93-7540
14" Diamond
Ultra Segmented Blade



Additional Equipment: (Not Included)

3100
MX FUEL™
14" Cut-Off Saw Cart

2820-21WS
M18™ SWITCH TANK™
4-Gallon Backpack
Water Supply Kit



**MX FUEL™
Breaker Kit**



**MOST
PRODUCTIVE
LOWEST
VIBRATION**

**LIGHTEST
IN CLASS**

**2 TONS
PER
CHARGE**

MXF368-1XC

Specifications:

Chuck Size	1-1/8" Hex
Blows per Minute	1,300
Impact Energy (ft/lbs)	50
Vibration	4.9 m/s ²
Soft Start	Yes
Weight w/ Battery	63.9 lbs
Push Button Start	Yes
ONE-KEY™ Compatible	Track and Manage.
Battery Compatibility	Fits All MX FUEL™ Battery Packs
Warranty	2 Year Equipment, Battery & Charger

Includes: (1) MX FUEL™ REDLITHIUM™ XC406 Battery Pack, MX FUEL™ Charger, Cart, (3) Chisels

Available Accessories: (Not Included)

8960-20
8 Gallon
Dust Extractor

5321-DE
Dust Extraction
Attachment

48-62-4001
1-1/8" Hex 16"
Moil Point

48-62-4006
1-1/8" Hex 16"
Narrow Chisel



**MX FUEL™ Handheld
Core Drill Kit w/ Stand**



**SAFER
HANDHELD
CORING**

**POWER TO CORE
6" HOLES
IN REINFORCED CONCRETE**

**EASIEST
CORING
ANYWHERE**

MXF301-2CXS

Specifications:

Maximum Bit Capacity	6"
RPMs Low / High	790 / 1,550
Spindle Size	1-1/4" - 7
Wet / Dry Coring	Both
On-Board Water Delivery	Yes
Stand Included	Yes
Weight: Machine w/ CP Battery	21.6 lbs
Weight: Stand Only	29.0 lbs
Push Button Start	Yes
ONE-KEY™ Compatible	Track and Manage.
Battery Compatibility	Fits All MX FUEL™ Battery Packs
Warranty	2 Year Equipment, Battery & Charger

Includes: (1) MX FUEL™ REDLITHIUM™ XC406 Battery Pack, (1) MX FUEL™ REDLITHIUM™ CP203 Battery Pack, MX FUEL™ Charger, Compact Core Drill Stand, Trigger Lock, 5/8" - 11 Bit Adapter, Quick Connect, Hard Case with Wheels



**MX FUEL™ Handheld
Core Drill Kit**



MXF301-2CP

Specifications:

Maximum Bit Capacity	6"
RPMs Low / High	790 / 1,550
Spindle Size	1-1/4" - 7
Wet / Dry Coring	Both
On-Board Water Delivery	Yes
Weight w/ Battery	21.6 lbs
Push Button Start	Yes
ONE-KEY™ Compatible	Track and Manage.
Battery Compatibility	Fits All MX FUEL™ Battery Packs
Warranty	2 Year Equipment, Battery & Charger

Includes: (2) MX FUEL™ REDLITHIUM™ CP203 Battery Packs, MX FUEL™ Charger, Trigger Lock, 5/8" - 11 Bit Adapter, Quick Connect, Hard Case with Wheels

Available Accessories for MXF301-2CP & MXF301-2CXS: (Not Included)

2820-21WS
M18™ SWITCH TANK™
4-Gallon Backpack
Water Supply Kit

8960-20
8 Gallon Dust Extractor

5319-DE
Dry Coring
Dust Extractor Attachment



48-17-5030
3" Diamond
Ultra Wet
Core Bit

48-17-0130
3" Diamond
Ultra Dry
Core Bit



MX FUEL™ CARRY-ON™ 3600W/1800W Power Supply Kit



POWER MORE ON DEMAND

PORTABLE POWER ANYWHERE

MORE EFFICIENT POWER

MXF002-2XC Specifications:

Peak Watts	3,600W
Running Watts	1,800W
Outlets	(2) 120V 15A Outlets
Inverter Output	Pure Sine Wave
Integrated Charger	Yes
Push Button Start	Yes
ONE-KEY™ Compatible	Track and Manage.
Ground Fault Isolated	Yes
Intended For	One 15 Amp Tool
Battery Compatibility	Fits All MX FUEL™ Battery Packs
Warranty	2 Year Equipment and Battery



Includes: (2) MX FUEL™ REDLITHIUM™ XC406 Battery Packs, Detachable Charger Cord

GROUND FAULT ISOLATED

MX FUEL™ Sewer Drum Machine w/ POWERTREDZ™ Kit



POWERTREDZ LIFT ASSIST

POWER TO CLEAR ROOTS AT 200'

MESS CONTAINED

MXF501-1CP Specifications:

Drain Line Capacity	3" – 8" up to 200'
Drum Capacity	100'
Cable Capacity	5/8" and 3/4"
Powered Cable Feed & Retract	Yes, CABLE DRIVE™
Cable Spin Speed	200 RPM
Height / Length	47" / 32.5"
Weight w/ Battery	125 lbs
Lift Assist	Yes, POWERTREDZ™
Push Button Start	Yes
ONE-KEY™ Compatible	Track and Manage.
Battery Compatibility	Fits All MX FUEL™ Battery Packs
Warranty	2 Year Equipment, Battery & Charger



Includes: (1) MX FUEL™ REDLITHIUM™ CP203 Battery Pack, MX FUEL™ Charger, 3/4" Anchor Cable

MX FUEL™ ROCKET™ Tower Light/Charger Kit



MOST PORTABLE 10' LIGHT INSIDE / OUTSIDE

27,000 LUMENS OF TASK OR AREA LIGHTING

WITHSTANDS THE STORM

MXF041-1XC Specifications:

Max Lumens	27,000
Modes	High / Medium / Low
Collapsed Height	44"
Extended Height	10'
Width	20.8"
Depth	24.8"
Weight w/ Battery	110 lbs
Ingress Rating	Outdoor Use
Push Button Start	Yes
ONE-KEY™ Compatible	Customize. Track. Manage.
Battery Compatibility	Fits All MX FUEL™ Battery Packs
Warranty	2 Year Equipment and Battery



Includes: (1) MX FUEL™ REDLITHIUM™ XC406 Battery Pack

MX FUEL™ Sewer Drum Machine Accessories

- Compatible with MXF501-1CP, MXF500-1CP
- Machine Accessories**
 47-53-5001 6-1/2" Guide Hose
 47-53-5002 Load Wheel
- 5/8" Inner Core Cables**
 48-53-2325 – 25'
 48-53-2350 – 50'
 48-53-2310 – 100'
- 3/4" Inner Core Cables**
 48-53-2425 – 25'
 48-53-2450 – 50'
 48-53-2410 – 100'
- Leader Cables & Anchor Cable**
 48-53-2802 Leader Cable
 48-53-2902 Leader Cable
 48-53-2905 Anchor Cable
- Cable Head Attachments**
 48-53-2830 Straight Auger
 48-53-2831 Funnel Auger
 48-53-2835 Small Opening Tool
 48-53-2836 Medium Opening Tool
 48-53-2832 3" Root Cutters
 48-53-2833 4" Root Cutters
 48-53-2834 6" Root Cutters
 48-53-2837 3" Grease Cutters
 48-53-2838 4" Grease Cutters
 48-53-2829 Pin Key
 48-53-2839 Case
 48-53-2840 9 pc Cable Head Attachment Kit

Also Available: MX FUEL™ Sewer Drum Machine Kit MXF500-1CP

Specifications:

Drain Line Capacity	3" – 8" up to 200'
Drum Capacity	100'
Cable Capacity	5/8" and 3/4"
Powered Cable Feed & Retract	Yes, CABLE DRIVE™
Cable Spin Speed	200 RPM
Height / Length	47" / 32.5"
Weight w/ Battery	110 lbs
Lift Assist	No
Push Button Start	Yes
ONE-KEY™ Compatible	Track and Manage.
Battery Compatibility	Fits All MX FUEL™ Battery Packs
Warranty	2 Year Equipment, Battery & Charger



Includes: (1) MX FUEL™ REDLITHIUM™ CP203 Battery Pack, MX FUEL™ Charger, 3/4" Anchor Cable

MX FUEL™ Backpack Concrete Vibrator Kit



POWER TO PUSH 2.5" HEAD

NO GAS HEADACHES

70 YDS³ PER CHARGE, 1-1/2" HEAD, 7' WHIP

MXF371-2XC

Specifications:

Maximum Head Size	2-1/2"
Maximum Shaft Length	21 ft
Quick Connect	Yes
Weight w/ Battery	34.5 lbs
Push Button Start	Yes
Removable Harness	Yes
ONE-KEY™ Compatible	Track and Manage.
Battery Compatibility	Fits All MX FUEL™ Batteries
Wireless Remote Included	Yes
Compatible w/ Oztec	Yes
Warranty	2 Year Equipment, Battery & Charger



Includes: (2) MX FUEL™ REDLITHIUM™ XC406 Battery Packs, MX FUEL™ Charger, MX FUEL™ Concrete Vibrator Remote

Available Accessories:
(Not Included)

48-37-5015 1-1/2" Head	48-37-7007 7' Shaft	
48-37-5020 2" Head	48-37-7014 14' Shaft	

MX FUEL™ Vibratory Screed Kit



POWER TO PULL 16' BAR

NO GAS HEADACHES

2 HOURS PER CHARGE, w/ 12' BAR

MXF381-2CP

Specifications:

VPM	4,000 – 9,000
Bar Range	4 – 16 ft
Adjustable Handlebars	Yes
Kickstand	Yes
Weight w/ Battery	37 lbs
Push Button Start	Yes
ONE-KEY™ Compatible	Track and Manage.
Battery Compatibility	Fits All MX FUEL™ Battery Packs
Compatible w/ MBW Bars	Yes
Warranty	2 Year Equipment, Battery & Charger



Includes: (2) MX FUEL™ REDLITHIUM™ CP203 Battery Packs, MX FUEL™ Charger, (1) 9/16 Wrench

Available Accessories:
(Not Included)

48-38-2016	16 ft Screed Bar
48-38-2014	14 ft Screed Bar
48-38-2012	12 ft Screed Bar
48-38-2010	10 ft Screed Bar
48-38-2008	8 ft Screed Bar
48-38-2006	6 ft Screed Bar
48-38-2004	4 ft Screed Bar



MX FUEL™ Batteries and Charger



MX FUEL™ REDLITHIUM™ XC406 Battery
MXFC406

Specifications:

Compatibility	Fits All MX FUEL™ Equipment
Charge Duration	90 min
Capacity	6.0 Ah
Fuel Gauge	Yes
REDLINK™ Intelligence	Yes
ONE-KEY™ Compatible	Yes
Warranty	2 Year

MX FUEL™ REDLITHIUM™ CP203 Battery
MXFCP203

Specifications:

Compatibility	Fits All MX FUEL™ Equipment
Charge Duration	45 min
Capacity	3.0 Ah
Fuel Gauge	Yes
REDLINK™ Intelligence	Yes
ONE-KEY™ Compatible	No
Warranty	2 Year

MX FUEL™ REDLITHIUM™ XC406 Battery/Charger Expansion Kit
MXFC-2XC

Includes: (2) MX FUEL™ REDLITHIUM™ XC406 Battery Packs, MX FUEL™ Charger



MX FUEL™ Charger
MXFC

Specifications:

Compatibility	Charges All MX FUEL™ Batteries
Charge Speed	Charges MX FUEL™ CP203 Battery in 45 min Charges MX FUEL™ XC406 Battery in 90 min
REDLINK™ Intelligence	Yes
On-Board Fan	Yes
Cell Voltage Monitoring	Yes
On-Board Indicator Light	Yes
Warranty	2 Year

LEARN MORE



NEW ONE-KEY™ BLUETOOTH™ TRACKING TAG

AVAILABLE IN
1 PC 48-21-2301 2 PC 48-21-2302 10 PC 48-21-2310



DOWNLOAD THE FREE APP NOW!



Apple, the Apple logo and iBeacon are trademarks of Apple Inc., registered in the U.S. and other countries. App Store is a service mark of Apple Inc. Google Play and the Google Play logo are trademarks of Google Inc.
The Bluetooth® word mark and logos are registered trademarks owned by the Bluetooth SIG, Inc. and any use of such marks by Milwaukee Tool is under license. Other trademarks and trade names are those of their respective owners.

PORTABLE POWER TOOL
(including cordless product – tool, battery pack(s) & battery charger and Work Lights – cordless flashlights)
LIMITED WARRANTY

Every MILWAUKEE® **power tool*** (see exceptions below) is warranted to the **original purchaser only** to be free from defects in material and workmanship. Subject to certain exceptions, MILWAUKEE will repair or replace any part on an electric power tool which, after examination, is determined by MILWAUKEE to be defective in material or workmanship for a period of **five (5) years**** after the date of purchase unless otherwise noted. Return of the power tool to a MILWAUKEE *factory* Service Center location or MILWAUKEE Authorized Service Station, freight prepaid and insured, is required. A copy of the proof of purchase should be included with the return product. This warranty does not apply to damage that MILWAUKEE determines to be from repairs made or attempted by anyone other than MILWAUKEE authorized personnel, misuse, alterations, abuse, normal wear and tear, lack of maintenance, or accidents.

Normal Wear: Many power tools need periodic parts replacement and service to achieve best performance. This warranty does not cover repair when normal use has exhausted the life of a part including, but not limited to, chucks, brushes, cords, saw shoes, blade clamps, o-rings, seals, bumpers, driver blades, pistons, strikers, lifters, and bumper cover washers.

*This **warranty** does not cover Air Nailers & Staplers; Airless Paint Sprayer; Cordless Battery Packs; Gasoline Driven Portable Power Generators; Hand Tools; Hoist – Electric, Lever & Hand Chain; M12™ Heated Gear; Reconditioned Product; and Test & Measurement Products. **There are separate and distinct warranties** available for these products.

The warranty period for **Job Site Radios, M12™ Power Port, M18™ Power Source, Jobsite Fan and Trade Titan™ Industrial Work Carts is **one (1) year** from the date of purchase. The warranty period for the **M18 FUEL™ 1" D-Handle High Torque Impact Wrenches, Drain Cleaning Cables, AIRSNAKE™ Drain Cleaning Air Gun Accessories, REDLITHIUM™ USB Laser Levels, TRAPSSNAKE™ 25' Auger w/ CABLE DRIVE™** and **FORCE LOGIC™ Press Tool Accessories** is **two (2) years** from the date of purchase. The warranty period for the **M18™ Compact Heat Gun, 8 Gallon Dust Extractor, M18™ Framing Nailers, M18 FUEL™ 1/2" Ext. Anvil Controlled Torque Impact Wrench w/ ONE-KEY™, M18 FUEL™ 1" High Torque Impact Wrench w/ ONE-KEY™, M18 FUEL™ 2 Gal. Compact Quiet Compressor, M12™ Laser Levels, 165' Laser Detector, M12™ 23GA Pin Nailer, M18 FUEL™ 1/4" Blind Rivet Tool w/ ONE-KEY™, M12 FUEL™ Low Speed Tire Buffer, M18 FUEL™ Random Orbital Polishers, and the M18™ Utility Fencing Stapler** is **three (3) years** from the date of purchase. The warranty period for the **LED** in the LED Work Light and the **LED Upgrade Bulb** for the Work Light is the lifetime of the product subject to the limitations above. If during normal use the LED or LED Bulb fails, the part will be replaced free of charge.

Warranty Registration is not necessary to obtain the applicable warranty on a MILWAUKEE power tool product. The manufacturing date of the product will be used to determine the warranty period if no proof of purchase is provided at the time warranty service is requested.

ACCEPTANCE OF THE EXCLUSIVE REPAIR AND REPLACEMENT REMEDIES DESCRIBED HEREIN IS A CONDITION OF THE CONTRACT FOR THE PURCHASE OF EVERY MILWAUKEE PRODUCT. IF YOU DO NOT AGREE TO THIS CONDITION, YOU SHOULD NOT PURCHASE THE PRODUCT. IN NO EVENT SHALL MILWAUKEE BE LIABLE FOR ANY INCIDENTAL, SPECIAL, CONSEQUENTIAL OR PUNITIVE DAMAGES, OR FOR ANY COSTS, ATTORNEY FEES, EXPENSES, LOSSES OR DELAYS ALLEGED TO BE AS A CONSEQUENCE OF ANY DAMAGE TO, FAILURE OF, OR DEFECT IN ANY PRODUCT INCLUDING, BUT NOT LIMITED TO, ANY CLAIMS FOR LOSS OF PROFITS. SOME STATES DO NOT ALLOW THE EXCLUSION OR LIMITATION OF INCIDENTAL OR CONSEQUENTIAL DAMAGES, SO THE ABOVE LIMITATION OR EXCLUSION MAY NOT APPLY TO YOU. THIS WARRANTY IS EXCLUSIVE AND IN LIEU OF ALL OTHER EXPRESS WARRANTIES, WRITTEN OR ORAL. TO THE EXTENT PERMITTED BY LAW, MILWAUKEE DISCLAIMS ANY IMPLIED WARRANTIES, INCLUDING WITHOUT LIMITATION ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR USE OR PURPOSE; TO THE EXTENT SUCH DISCLAIMER IS NOT PERMITTED BY LAW, SUCH IMPLIED WARRANTIES ARE LIMITED TO THE DURATION OF THE APPLICABLE EXPRESS WARRANTY AS DESCRIBED ABOVE. SOME STATES DO NOT ALLOW LIMITATIONS ON HOW LONG AN IMPLIED WARRANTY LASTS, SO THE ABOVE LIMITATION MAY NOT APPLY TO YOU, THIS WARRANTY GIVES YOU SPECIFIC LEGAL RIGHTS, AND YOU MAY ALSO HAVE OTHER RIGHTS WHICH VARY FROM STATE TO STATE.

This warranty applies to *product* sold in the U.S.A. and Canada only.

Please consult the **'Service Center Search'** in the **Parts & Service** section of MILWAUKEE's website www.milwaukeetool.com or call 1.800.SAWDUST (1.800.729.3878) to locate your nearest service facility for warranty and non-warranty service on a MILWAUKEE **electric power tool**.

CORDLESS BATTERY PACK
LIMITED WARRANTY

Every MILWAUKEE® **battery pack** (sold with cordless product and/or as a replacement battery pack) is warranted to the **original purchaser only** to be free from defects in material and workmanship. Subject to certain exceptions, MILWAUKEE will repair or replace a battery pack which, after examination, is determined by MILWAUKEE to be defective in material or workmanship for the **stated warranty period** from date of purchase. Return of the battery pack to a MILWAUKEE *factory* Service Center location or MILWAUKEE Authorized Service Station, freight prepaid and insured, is required. For the proper shipping procedure of battery packs, contact 1.800.SAWDUST (1.800.729.3878), or go to www.milwaukeetool.com. A copy of the proof of purchase should be included with the return product. This warranty does not apply to damage that MILWAUKEE determines to be from repairs made or attempted by anyone other than MILWAUKEE authorized personnel, misuse, alterations, abuse, normal wear and tear, lack of maintenance, or accidents.

Battery Pack Cat. No.	Chemistry	Warranty Period (from date of purchase)
48-11-1812 48-11-1828 <i>(Serial number prefix "B41E" and later)</i> 48-11-1840 48-11-1850 48-11-1850R 48-11-1860 48-11-1865 48-11-1880 48-11-1890 48-11-2402 48-11-2440 48-11-2460 48-11-2830 <i>(Serial number prefix "C71")</i>	LITHIUM-ION	Three (3) Years
48-11-0490 48-11-1815 48-11-1820 48-11-1835 48-11-2001 48-11-2401 48-11-2420 48-11-2430	LITHIUM-ION	Two (2) Years
48-11-1828 <i>(Serial number prefix "B41D" and earlier)</i> 48-11-1830 <i>(Serial number prefix "A95")</i> 48-11-2830 <i>(Serial number prefix "A71")</i>	LITHIUM-ION	Two (2) Years – plus, Three (3) Years Pro-Rata (prorated)*
48-11-0100 48-11-1024 48-11-1830 <i>(Serial number prefix "E95")</i> 48-11-1970 48-11-2230	Nickel-Cadmium (Ni-Cd), Nickel-Metal-Hydride (Ni-MH), LITHIUM-ION	One (1) Year

*The warranty period for MILWAUKEE M18™ 48-11-1828 (with the serial number prefix "B41D" and earlier), V18™ 48-11-1830 (with the serial number prefix "A95"), and V28™ 48-11-2830 (with the serial number prefix "A71") is five (5) years / 2000 charges from the date of purchase, whichever first occurs. The first 1000 charges or 2 years of the warranty, whichever first occurs, are covered through free replacement of the defective battery. This means that for the earlier of the first 1000 charges or two (2) years from the date of purchase/first charge, a replacement battery will be provided to the customer for any defective battery free of charge. Thereafter, the remaining charges up to a total of 2000 or the remainder of the five (5) year period from the date of purchase, whichever first occurs, will be covered on a pro rata basis. This means that every customer gets an additional 1000 charges or three (3) years of pro rata warranty on the these battery packs, depending upon the amount of use. MILWAUKEE M18™ 48-11-1828 (with the serial number prefix "B41E" and later), V18™ 48-11-1830 (with the serial number prefix "E95"), and M28™ 48-11-2830 (with the serial number prefix "C71") have different warranty periods, as listed.

Warranty Registration is not necessary to obtain the applicable warranty on a MILWAUKEE battery pack. The manufacturing date of the product will be used to determine the warranty period if no proof of purchase is provided at the time warranty service is requested.

ACCEPTANCE OF THE EXCLUSIVE REPAIR AND REPLACEMENT REMEDIES DESCRIBED HEREIN IS A CONDITION OF THE CONTRACT FOR THE PURCHASE OF EVERY MILWAUKEE PRODUCT. IF YOU DO NOT AGREE TO THIS CONDITION, YOU SHOULD NOT PURCHASE THE PRODUCT. IN NO EVENT SHALL MILWAUKEE BE LIABLE FOR ANY INCIDENTAL, SPECIAL, CONSEQUENTIAL OR PUNITIVE DAMAGES, OR FOR ANY COSTS, ATTORNEY FEES, EXPENSES, LOSSES OR DELAYS ALLEGED TO BE AS A CONSEQUENCE OF ANY DAMAGE TO, FAILURE OF, OR DEFECT IN ANY PRODUCT INCLUDING, BUT NOT LIMITED TO, ANY CLAIMS FOR LOSS OF PROFITS. SOME STATES DO NOT ALLOW THE EXCLUSION OR LIMITATION OF INCIDENTAL OR CONSEQUENTIAL DAMAGES, SO THE ABOVE LIMITATION OR EXCLUSION MAY NOT APPLY TO YOU. THIS WARRANTY IS EXCLUSIVE AND IN LIEU OF ALL OTHER EXPRESS WARRANTIES, WRITTEN OR ORAL. TO THE EXTENT PERMITTED BY LAW, MILWAUKEE DISCLAIMS ANY IMPLIED WARRANTIES, INCLUDING WITHOUT LIMITATION ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR USE OR PURPOSE; TO THE EXTENT SUCH DISCLAIMER IS NOT PERMITTED BY LAW, SUCH IMPLIED WARRANTIES ARE LIMITED TO THE DURATION OF THE APPLICABLE EXPRESS WARRANTY AS DESCRIBED ABOVE. SOME STATES DO NOT ALLOW LIMITATIONS ON HOW LONG AN IMPLIED WARRANTY LASTS, SO THE ABOVE LIMITATION MAY NOT APPLY TO YOU, THIS WARRANTY GIVES YOU SPECIFIC LEGAL RIGHTS, AND YOU MAY ALSO HAVE OTHER RIGHTS WHICH VARY FROM STATE TO STATE.

This warranty applies to *product* sold in the U.S.A. and Canada only.

Please consult the **'Service Center Search'** in the **Parts & Service** section of MILWAUKEE's website www.milwaukeetool.com or call 1.800.SAWDUST (1.800.729.3878) to locate your nearest *service* facility for warranty and non-warranty service on a MILWAUKEE **battery pack**.

HEATED GEAR
LIMITED WARRANTY

Every MILWAUKEE® **Heated Gear product** (including its battery holder/controller) is warranted to the **original purchaser only** to be free from defects in material and workmanship. Subject to certain exceptions, MILWAUKEE will repair or replace any part on a Heated Gear product which, after examination, is determined by MILWAUKEE to be defective in material or workmanship for a period of **one (1) year*** after the date of purchase. Return of a Heated Gear product to a MILWAUKEE *factory* Service Center location, freight prepaid and insured, is required. A copy of the proof of purchase should be included with the return product. This warranty does not apply to damage that MILWAUKEE determines to be from repairs made or attempted by anyone other than MILWAUKEE personnel, misuse, alterations, abuse, normal wear and tear, or accidents.

*This warranty does not cover a M12™ LITHIUM-ION Battery Pack, a M12™ Charger, or a REDLITHIUM™ USB battery; **there are separate and distinct warranties** available for these products.

Warranty Registration is not necessary to obtain the applicable warranty on MILWAUKEE Heated Gear products. The manufacturing date of the product will be used to determine the warranty period if no proof of purchase is provided at the time warranty service is requested.

ACCEPTANCE OF THE EXCLUSIVE REPAIR AND REPLACEMENT REMEDIES DESCRIBED HEREIN IS A CONDITION OF THE CONTRACT FOR THE PURCHASE OF EVERY MILWAUKEE PRODUCT. IF YOU DO NOT AGREE TO THIS CONDITION, YOU SHOULD NOT PURCHASE THE PRODUCT. IN NO EVENT SHALL MILWAUKEE BE LIABLE FOR ANY INCIDENTAL, SPECIAL, CONSEQUENTIAL OR PUNITIVE DAMAGES, OR FOR ANY COSTS, ATTORNEY FEES, EXPENSES, LOSSES OR DELAYS ALLEGED TO BE AS A CONSEQUENCE OF ANY DAMAGE TO, FAILURE OF, OR DEFECT IN ANY PRODUCT INCLUDING, BUT NOT LIMITED TO, ANY CLAIMS FOR LOSS OF PROFITS. SOME STATES DO NOT ALLOW THE EXCLUSION OR LIMITATION OF INCIDENTAL OR CONSEQUENTIAL DAMAGES, SO THE ABOVE LIMITATION OR EXCLUSION MAY NOT APPLY TO YOU. THIS WARRANTY IS EXCLUSIVE AND IN LIEU OF ALL OTHER EXPRESS WARRANTIES, WRITTEN OR ORAL. TO THE EXTENT PERMITTED BY LAW, MILWAUKEE DISCLAIMS ANY IMPLIED WARRANTIES, INCLUDING WITHOUT LIMITATION ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR USE OR PURPOSE; TO THE EXTENT SUCH DISCLAIMER IS NOT PERMITTED BY LAW, SUCH IMPLIED WARRANTIES ARE LIMITED TO THE DURATION OF THE APPLICABLE EXPRESS WARRANTY AS DESCRIBED ABOVE. SOME STATES DO NOT ALLOW LIMITATIONS ON HOW LONG AN IMPLIED WARRANTY LASTS, SO THE ABOVE LIMITATION MAY NOT APPLY TO YOU, THIS WARRANTY GIVES YOU SPECIFIC LEGAL RIGHTS, AND YOU MAY ALSO HAVE OTHER RIGHTS WHICH VARY FROM STATE TO STATE..

This warranty applies to *product* sold in the U.S.A. and Canada only.

Please consult the **'Service Center Search'** in the **Parts & Service** section of MILWAUKEE's website www.milwaukeetool.com or call 1.800.SAWDUST (1.800.729.3878) to locate your nearest MILWAUKEE *factory* Service Center location.

OUTDOOR POWER EQUIPMENT LIMITED WARRANTY

Every MILWAUKEE® **outdoor power equipment product*** (see exceptions below) is warranted to the **original purchaser only** to be free from defects in material and workmanship. Subject to certain exceptions, MILWAUKEE will repair or replace any part on an outdoor power equipment product which, after examination, is determined by MILWAUKEE to be defective in material or workmanship for a period of **three (3) years**** after the date of purchase unless otherwise noted. Return of the outdoor power equipment to a MILWAUKEE *factory* Service Center location or participating MILWAUKEE Authorized Service Station, freight prepaid and insured, is required. A copy of the proof of purchase should be included with the return product. This warranty does not apply to damage that MILWAUKEE determines to be from repairs made or attempted by anyone other than MILWAUKEE authorized personnel, misuse, alterations, abuse, normal wear and tear, lack of maintenance, or accidents.

Normal Wear: Many outdoor power equipment products need periodic parts replacement and service to achieve best performance. This warranty does not cover repair when normal use has exhausted the life of a part including, but not limited to mower blades, trimmer head, trimmer head spool, cutting lines, blades, chains, blower tubes, brushes, o-rings, and seals.

*This **warranty** does not cover Cordless Battery Packs or Reconditioned Product. **There are separate and distinct warranties** available for these products

The warranty period for SWITCH TANK™ tank assemblies, hoses, handles, and wands are **one (1) year from the date of purchase.

MILWAUKEE does **not** cover freight or labor charges associated with the inspection and testing of **outdoor power equipment products** which are found by MILWAUKEE **not** to be a valid warranty claim. A valid warranty claim **must be substantiated** by the discovery of defective material or workmanship by MILWAUKEE.

ACCEPTANCE OF THE EXCLUSIVE REPAIR AND REPLACEMENT REMEDIES DESCRIBED HEREIN IS A CONDITION OF THE CONTRACT FOR THE PURCHASE OF EVERY MILWAUKEE PRODUCT. IF YOU DO NOT AGREE TO THIS CONDITION, YOU SHOULD NOT PURCHASE THE PRODUCT. IN NO EVENT SHALL MILWAUKEE BE LIABLE FOR ANY INCIDENTAL, SPECIAL, CONSEQUENTIAL OR PUNITIVE DAMAGES, OR FOR ANY COSTS, ATTORNEY FEES, EXPENSES, LOSSES OR DELAYS ALLEGED TO BE AS A CONSEQUENCE OF ANY DAMAGE TO, FAILURE OF, OR DEFECT IN ANY PRODUCT INCLUDING, BUT NOT LIMITED TO, ANY CLAIMS FOR LOSS OF PROFITS. SOME STATES DO NOT ALLOW THE EXCLUSION OR LIMITATION OF INCIDENTAL OR CONSEQUENTIAL DAMAGES, SO THE ABOVE LIMITATION OR EXCLUSION MAY NOT APPLY TO YOU. THIS WARRANTY IS EXCLUSIVE AND IN LIEU OF ALL OTHER EXPRESS WARRANTIES, WRITTEN OR ORAL. TO THE EXTENT PERMITTED BY LAW, MILWAUKEE DISCLAIMS ANY IMPLIED WARRANTIES, INCLUDING WITHOUT LIMITATION ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR USE OR PURPOSE; TO THE EXTENT SUCH DISCLAIMER IS NOT PERMITTED BY LAW, SUCH IMPLIED WARRANTIES ARE LIMITED TO THE DURATION OF THE APPLICABLE EXPRESS WARRANTY AS DESCRIBED ABOVE. SOME STATES DO NOT ALLOW LIMITATIONS ON HOW LONG AN IMPLIED WARRANTY LASTS, SO THE ABOVE LIMITATION MAY NOT APPLY TO YOU, THIS WARRANTY GIVES YOU SPECIFIC LEGAL RIGHTS, AND YOU MAY ALSO HAVE OTHER RIGHTS WHICH VARY FROM STATE TO STATE.

This warranty applies to *product* sold in the U.S.A. and Canada only.

Please consult the **‘Service Center Search’** in the **Parts & Service** section of MILWAUKEE’s website www.milwaukeeetool.com or call 1.800.SAWDUST (1.800.729.3878) to locate your nearest *service* facility for warranty and non-warranty service on a MILWAUKEE **electric power tool**.

REDLITHIUM USB LIMITED WARRANTY

Every MILWAUKEE® **REDLITHIUM USB battery and charger*** is warranted to the **original purchaser only** to be free from defects in material and workmanship. Subject to certain exceptions, MILWAUKEE will repair or replace repair a REDLITHIUM USB battery or charger which, after examination, is determined by MILWAUKEE to be defective in material or workmanship for a period of **two (2) years** after the date of purchase unless otherwise noted. Return of the REDLITHIUM USB battery or charger to a MILWAUKEE *factory* Service Center location or MILWAUKEE Authorized Service Station, freight prepaid and insured, is required. For the proper shipping procedure of battery packs, contact 1.800.SAWDUST (1.800.729.3878), or go to www.milwaukeeetool.com. A copy of the proof of purchase should be included with the return product. This warranty does not apply to damage that MILWAUKEE determines to be from repairs made or attempted by anyone other than MILWAUKEE authorized personnel, misuse, alterations, abuse, normal wear and tear, lack of maintenance, or accidents.

Normal Wear: This warranty does not cover repair or replacement when normal use has exhausted the life of a part including, but not limited to charging cables, and wall plugs.

*This **warranty** does not cover any cordless product sold with the REDLITHIUM USB battery and/or charger. **There are separate and distinct warranties** available for these products

Warranty Registration is not necessary to obtain the applicable warranty on MILWAUKEE Heated Gear products. The manufacturing date of the product will be used to determine the warranty period if no proof of purchase is provided at the time warranty service is requested.

ACCEPTANCE OF THE EXCLUSIVE REPAIR AND REPLACEMENT REMEDIES DESCRIBED HEREIN IS A CONDITION OF THE CONTRACT FOR THE PURCHASE OF EVERY MILWAUKEE PRODUCT. IF YOU DO NOT AGREE TO THIS CONDITION, YOU SHOULD NOT PURCHASE THE PRODUCT. IN NO EVENT SHALL MILWAUKEE BE LIABLE FOR ANY INCIDENTAL, SPECIAL, CONSEQUENTIAL OR PUNITIVE DAMAGES, OR FOR ANY COSTS, ATTORNEY FEES, EXPENSES, LOSSES OR DELAYS ALLEGED TO BE AS A CONSEQUENCE OF ANY DAMAGE TO, FAILURE OF, OR DEFECT IN ANY PRODUCT INCLUDING, BUT NOT LIMITED TO, ANY CLAIMS FOR LOSS OF PROFITS. SOME STATES DO NOT ALLOW THE EXCLUSION OR LIMITATION OF INCIDENTAL OR CONSEQUENTIAL DAMAGES, SO THE ABOVE LIMITATION OR EXCLUSION MAY NOT APPLY TO YOU. THIS WARRANTY IS EXCLUSIVE AND IN LIEU OF ALL OTHER EXPRESS WARRANTIES, WRITTEN OR ORAL. TO THE EXTENT PERMITTED BY LAW, MILWAUKEE DISCLAIMS ANY IMPLIED WARRANTIES, INCLUDING WITHOUT LIMITATION ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR USE OR PURPOSE; TO THE EXTENT SUCH DISCLAIMER IS NOT PERMITTED BY LAW, SUCH IMPLIED WARRANTIES ARE LIMITED TO THE DURATION OF THE APPLICABLE EXPRESS WARRANTY AS DESCRIBED ABOVE. SOME STATES DO NOT ALLOW LIMITATIONS ON HOW LONG AN IMPLIED WARRANTY LASTS, SO THE ABOVE LIMITATION MAY NOT APPLY TO YOU, THIS WARRANTY GIVES YOU SPECIFIC LEGAL RIGHTS, AND YOU MAY ALSO HAVE OTHER RIGHTS WHICH VARY FROM STATE TO STATE.

This warranty applies to *product* sold in the U.S.A. and Canada only.

Please consult the **‘Find a Service Center’** search in the **Parts & Service** section of MILWAUKEE’s website www.milwaukeeetool.com or call 1.800.SAWDUST (1.800.729.3878) to locate your nearest MILWAUKEE *factory* Service Center location.

PERSONAL LIGHTING

(A) 2010R Milwaukee® Rechargeable 250L Penlight w/ Laser, 2011R Milwaukee® Rechargeable 500L Everyday Carry Flashlight w/ Magnet, and 2012R Milwaukee® Rechargeable Magnetic Headlamp and Task Light
2 YEAR LIMITED WARRANTY

The **rechargeable personal lighting products** referenced above are warranted to the **original purchaser only** to be free from defects in material and workmanship. Subject to certain exceptions, MILWAUKEE will repair or replace any part on the above Rechargeable Personal Lighting Products which, after examination, is determined by MILWAUKEE to be defective in material or workmanship for a period of **two (2) years** after the date of purchase.

(B) All other MILWAUKEE® Personal Lighting Products
LIMITED LIFETIME WARRANTY

All other MILWAUKEE **personal lighting products*** (see exceptions below) are warranted to the **original purchaser only** to be free from defects in material and workmanship. Subject to certain exceptions, MILWAUKEE will repair or replace any part on a personal lighting product which, after examination, is determined by MILWAUKEE to be defective in material or workmanship for the **lifetime** of such personal lighting products.

Normal Wear: This warranty does not cover repair or replacement when normal use has exhausted the life of a part including, but not limited to clips, straps, charging cables, wall plugs, and rubber gaskets. This warranty does cover the **LED** in the personal lighting products, subject to the limitations herein.

*This warranty does not cover Cordless Battery Packs or Chargers. **There are separate and distinct warranties** available for these products.

Return of all personal lighting products to a MILWAUKEE *factory* Service Center location or MILWAUKEE Authorized Service Station, freight prepaid and insured, is required. A copy of the proof of purchase should be included with the return product. The above warranties do not apply to damage that MILWAUKEE determines to be from repairs made or attempted by anyone other than MILWAUKEE authorized personnel, misuse, alterations, abuse, normal wear and tear, lack of maintenance, accidents, or caused by alkaline batteries.

ACCEPTANCE OF THE EXCLUSIVE REPAIR AND REPLACEMENT REMEDIES DESCRIBED HEREIN IS A CONDITION OF THE CONTRACT FOR THE PURCHASE OF EVERY MILWAUKEE PRODUCT. IF YOU DO NOT AGREE TO THIS CONDITION, YOU SHOULD NOT PURCHASE THE PRODUCT. IN NO EVENT SHALL MILWAUKEE BE LIABLE FOR ANY INCIDENTAL, SPECIAL, CONSEQUENTIAL OR PUNITIVE DAMAGES, OR FOR ANY COSTS, ATTORNEY FEES, EXPENSES, LOSSES OR DELAYS ALLEGED TO BE AS A CONSEQUENCE OF ANY DAMAGE TO, FAILURE OF, OR DEFECT IN ANY PRODUCT INCLUDING, BUT NOT LIMITED TO, ANY CLAIMS FOR LOSS OF PROFITS. SOME STATES DO NOT ALLOW THE EXCLUSION OR LIMITATION OF INCIDENTAL OR CONSEQUENTIAL DAMAGES, SO THE ABOVE LIMITATION OR EXCLUSION MAY NOT APPLY TO YOU. THE ABOVE WARRANTIES ARE EXCLUSIVE AND IN LIEU OF ALL OTHER EXPRESS WARRANTIES, WRITTEN OR ORAL. TO THE EXTENT PERMITTED BY LAW, MILWAUKEE DISCLAIMS ANY IMPLIED WARRANTIES, INCLUDING WITHOUT LIMITATION ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR USE OR PURPOSE; TO THE EXTENT SUCH DISCLAIMER IS NOT PERMITTED BY LAW, SUCH IMPLIED WARRANTIES ARE LIMITED TO THE DURATION OF THE APPLICABLE EXPRESS WARRANTIES AS DESCRIBED ABOVE. SOME STATES DO NOT ALLOW LIMITATIONS ON HOW LONG AN IMPLIED WARRANTY LASTS, SO THE ABOVE LIMITATION MAY NOT APPLY TO YOU, THESE WARRANTIES GIVES YOU SPECIFIC LEGAL RIGHTS, AND YOU MAY ALSO HAVE OTHER RIGHTS WHICH VARY FROM STATE TO STATE.

This warranty applies to *product* sold in the U.S.A. and Canada only.

Please consult the **‘Find a Service Center’** search in the **Parts & Service** section of MILWAUKEE’s website www.milwaukeeetool.com or call 1.800.SAWDUST (1.800.729.3878) to locate your nearest MILWAUKEE *factory* Service Center location.

MX FUEL™ PRODUCT, BATTERY PACKS, AND CHARGERS LIMITED WARRANTY

Every MILWAUKEE® **MX FUEL™ product, battery pack, and charger** is warranted to the **original purchaser only** to be free from defects in material and workmanship. Subject to certain exceptions, MILWAUKEE will repair or replace a MX FUEL™ product, battery pack, or charger which, after examination, is determined by MILWAUKEE to be defective in material or workmanship for a period of **two (2) years** after the date of purchase. Return of the MX FUEL™ product, battery pack, or charger to a MILWAUKEE *factory* Service Center location or MILWAUKEE Authorized Service Station, freight prepaid and insured, is required. For the proper shipping procedure of battery packs, contact 1.800.SAWDUST (1.800.729.3878), or go to www.milwaukeeetool.com. A copy of the proof of purchase should be included with the return product. This warranty does not apply to damage that MILWAUKEE determines to be from repairs made or attempted by anyone other than MILWAUKEE authorized personnel, misuse, alterations, abuse, normal wear and tear, lack of maintenance, or accidents.

Normal Wear: Many MX FUEL™ products need periodic parts replacement and service to achieve best performance. This warranty does not cover repair when normal use has exhausted the life of a part including, but not limited to, assist & drive belts, pulleys, blade flanges, vacuum gaskets, tool free handles, set pins, skis, drive couplers, rubber boots, auto feed, stabilize blocks, wheels, carrier wheels, cords, o-rings, seals, bumpers, driver blades, pistons, strikers, lifters, tool holder, and bumper cover washers.

Warranty Registration is not necessary to obtain the applicable warranty on a MX FUEL product, battery pack, or charger

ACCEPTANCE OF THE EXCLUSIVE REPAIR AND REPLACEMENT REMEDIES DESCRIBED HEREIN IS A CONDITION OF THE CONTRACT FOR THE PURCHASE OF EVERY MILWAUKEE PRODUCT. IF YOU DO NOT AGREE TO THIS CONDITION, YOU SHOULD NOT PURCHASE THE PRODUCT. IN NO EVENT SHALL MILWAUKEE BE LIABLE FOR ANY INCIDENTAL, SPECIAL, CONSEQUENTIAL OR PUNITIVE DAMAGES, OR FOR ANY COSTS, ATTORNEY FEES, EXPENSES, LOSSES OR DELAYS ALLEGED TO BE AS A CONSEQUENCE OF ANY DAMAGE TO, FAILURE OF, OR DEFECT IN ANY PRODUCT INCLUDING, BUT NOT LIMITED TO, ANY CLAIMS FOR LOSS OF PROFITS. SOME STATES DO NOT ALLOW THE EXCLUSION OR LIMITATION OF INCIDENTAL OR CONSEQUENTIAL DAMAGES, SO THE ABOVE LIMITATION OR EXCLUSION MAY NOT APPLY TO YOU. THIS WARRANTY IS EXCLUSIVE AND IN LIEU OF ALL OTHER EXPRESS WARRANTIES, WRITTEN OR ORAL. TO THE EXTENT PERMITTED BY LAW, MILWAUKEE DISCLAIMS ANY IMPLIED WARRANTIES, INCLUDING WITHOUT LIMITATION ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR USE OR PURPOSE; TO THE EXTENT SUCH DISCLAIMER IS NOT PERMITTED BY LAW, SUCH IMPLIED WARRANTIES ARE LIMITED TO THE DURATION OF THE APPLICABLE EXPRESS WARRANTY AS DESCRIBED ABOVE. SOME STATES DO NOT ALLOW LIMITATIONS ON HOW LONG AN IMPLIED WARRANTY LASTS, SO THE ABOVE LIMITATION MAY NOT APPLY TO YOU, THIS WARRANTY GIVES YOU SPECIFIC LEGAL RIGHTS, AND YOU MAY ALSO HAVE OTHER RIGHTS WHICH VARY FROM STATE TO STATE.

This warranty applies to *product* sold in the U.S.A. and Canada only.

Please consult the **‘Service Center Search’** in the **Parts & Service** section of MILWAUKEE’s website www.milwaukeeetool.com or call 1.800.SAWDUST (1.800.729.3878) to locate your nearest *service* facility for warranty and non-warranty service on a MILWAUKEE **MX FUEL™ product, battery pack or charger**.

LIGHTNING MAX REPAIR

MILWAUKEE® understands the unpredictability of the jobsite and the need for fast, reliable repairs and replacements. Through our Lightning Max Repair Program we are committed to providing you the best service so you can minimize downtime and get the job done.

SPEED: Repair of your tool in 7 – 10 days

PAY LESS, NOT MORE: Guaranteed to never pay more than the quoted Lightning Max Repair price

RELIABILITY: All repairs are serviced by experienced, certified factory technicians

QUALITY: Only genuine MILWAUKEE® parts used

WHERE TO GO FOR LIGHTNING MAX REPAIRS

eSERVICE

Solution for quick, convenient repairs, best for smaller tool quantities.

- FedEx shipping to MILWAUKEE® repair facility
- Your tool returned directly to you – no need to pick it up
- Go to www.milwaukeetool.com/eService

FACTORY SERVICE CENTERS

Factory Service Centers also carry the widest variety of MILWAUKEE® Tools and Accessories for all your needs.
1-800-SAWDUST (1-800-729-3878)

Anaheim

1130 N Magnolia
Anaheim, CA 92801

Atlanta

6155 Jimmy Carter Blvd
Suite F2
Norcross, GA 30071

Boston

375 University Avenue
Westwood, MA 02090

Chicago

6310 Gross Point Road
Niles, IL 60714

Cleveland

8200 Sweet Valley Drive
Valley View, OH 44125

Dallas

1625 W Mockingbird Ln
Unit 205
Dallas, TX 75235

Denver

2500 W 8th Avenue, Unit E
Denver, CO 80204

Houston

3566 West T.C. Jester Blvd
Houston, TX 77018

Las Vegas

5580 S Decatur Blvd
Unit 110
Las Vegas, NV 89118

Miami

3311 NW 82nd Avenue
Miami, FL 33122

Minneapolis/St. Paul

9705 Valley View Road
Eden Prairie, MN 55344

Milwaukee

13145 W Lisbon Road
Brookfield, WI 53005

New York City

3068 Whitestone Expressway
Flushing, NY 11354

Philadelphia

711 West Chester Pike
Havertown, PA 19064

San Antonio

14329 San Pedro Avenue, Suite D
San Antonio, TX 78232

San Diego

7849 – 7851 Clairemont Mesa Blvd.
San Diego, CA 92111

San Francisco/Oakland

2341 Lincoln Avenue
Hayward, CA 94545

Seattle

5963 Corson Avenue South
Suite 104
Seattle, WA 98108

Washington D.C.

11900 Baltimore Ave
Suite B
Beltsville, MD 20705

CANADA

1-800-268-4015

Edmonton

14506 – 115th Avenue NW
Edmonton AB T5M 3B9

Halifax

Unit 102 50 Akerley Blvd
Dartmouth NS B3B 1R8

Saskatoon

Unit 630 3530 Millar Ave
Saskatoon SK S7P 0B3

Vancouver

9000 Bill Fox Way, Unit 103A
Burnaby BC V5J 5J3

Vaughan

140 Fernstaff Court, Unit 4
Vaughan ON L4K 3L8

Winnipeg

675 Berry St, Unit H
Winnipeg MB R3H 1A7

