



Recovery Cylinders

Recovery Cylinders

- Powder-coated cylinders for a high gloss, durable finish.
- Proprietary primer provides excellent protection against corrosion.
- Atmospherically controlled heat treatment and precharged cylinders assure a clean dry interior.
- UL certified dual port, Liquid/Vapor valve is standard on all cylinders.
- Brad Harrison 3-pin connector level sensor available.
- Manufactured to AHRI guidelines.
- Other cylinder sizes available.



Recovery Cylinders	30 lb	50 lb	123 lb
Water Capacity (lb/kg)	26.2/11.9	47.6/21.6	123/55.8
Tare Weight (lb/kg)	17.2/7.8	27.6/12.5	54.7/24.8
Height (in/mm)	17.4/443	19.2/487	53.9/1370
Diameter (in/mm)	9.2/233	12.2/310	10.0/254
Collar Height (in/mm)	4.0/101	4.2/106	N/A
Collar Diameter (in/mm)	7.2/183	7.2/183	N/A
Foot Ring Diameter (in/mm)	8.0/203	8.0/203	10.0/254
Service Pressure (psi/bar)	400/27.6	400/27.6	400/27.6
Test Pressure (psi/bar)	800/55.2	800/55.2	800/55.2
Second Port	3/4" - 14NPT	3/4" - 14NPT	N/A
Construction Standards	DOT 4BA400 TC 4BAM28	DOT 4BA400 TC 4BAM28	DOT 4BW400 TC 4BWM28

All dimensions and tare weights are approximate.



1400 Division Road, West Warwick, RI USA 02893
T: 800.426.8765 F: 800.293.1519
www.amtrol.com