

PLASTIC-HANDLE SCREWDRIVERS



Nickel-chrome, precision-forged and polished blades with black tips

Internal flanges provide solid, twist-resistant shaft anchor and chrome-plated shaft helps prevent corrosion

Tough smooth Comfordome handle fits in the palm of the hand comfortably

Plastic-Handle Screwdrivers

Includes core Plastic-Handle Screwdriver features plus:

- Precision-machined Phillips tips provide a more consistent geometric symmetry to ensure accurate fit and torque without slippage
- Small-diameter cabinet-tip shanks for use in recessed holes or tight places and is well-suited for electrical and telecommunications work
- 35% larger than comparable screwdriver handles, the oversized Bull Driver handles deliver up to 50% extra power to perform tough jobs with minimal effort
- Meets or exceeds applicable ASME / ANSI specifications



BD308

Cat. No.	Tip Type	Shank Type	Shank Length	Overall Length
A000	3/32" (2.4 mm) Keystone	Round	1.5" (3.8 cm)	2.875" (7.3 cm)
A216-4	1/8" (3.2 mm) Cabinet	Round	4" (10.2 cm)	7" (17.8 cm)
A216-6	1/8" (3.2 mm) Cabinet	Round	6" (15.2 cm)	9" (22.9 cm)
Bull Driver™ Plastic Handle Screwdrivers				
BD308	5/16" (7.9 mm) Keystone	Square	8" (20.3 cm)	13.188" (33.5 cm)
BD111	#1 Phillips	Round	3" (7.6 cm)	6.625" (16.8 cm)
BD122	#2 Phillips	Round	4" (10.2 cm)	8.5" (21.6 cm)
BD133	#3 Phillips	Round	6" (15.2 cm)	11.188" (28.4 cm)

Pocket-Clip Screwdrivers

Includes core Plastic-Handle Screwdriver features plus:

- Specially designed for delicate instrument work



A116-3

Cat. No.	Tip Type	Shank Type	Shank Length	Overall Length
A130-2	1/8" (3.2 mm) Keystone	Round	2" (5.1 cm)	3.875" (9.8 cm)
A130-3	1/8" (3.2 mm) Keystone	Round	3" (7.6 cm)	4.875" (12.4 cm)
A116-2	3/32" (2.4 mm) Keystone	Round	2" (5.1 cm)	4.438" (11.3 cm)
A116-3	3/32" (2.4 mm) Keystone	Round	3" (7.6 cm)	5.438" (13.8 cm)
A131-2	1/8" (3.2 mm) Keystone	Round	2" (5.1 cm)	4.438" (11.3 cm)
P12	#0 Phillips	Round	2.5" (6.4 cm)	5" (12.7 cm)

Phillips-Tip Screw-Holding Screwdrivers

- Positive gripping action holds and starts Phillips screws in awkward, hard-to-reach places
- Blade separates to hold the fastener
- Not designed for torquing or tightening



K16

Cat. No.	Tip Type	Shank Type	Overall Length
K14	Screw Holding	Round	5" (12.7 cm)
K16	Screw Holding	Round	7" (17.8 cm)
K19	Screw Holding	Round	9" (22.9 cm)



Pliers
Strippers, Cutters, and Crimpers
Drivers and Wrenches
Conduit Tools and Measurement
Tool Kits
Safety, PPE and Comfort
Job Site Accessories
Tool Storage
Voice/Data/Video
Test and Measurement
Power Tools and Accessories
Lifting, Pulling and Structural