




THE OLD WAY




THE WEBSTONE WAY
REPLACES 4 COMPONENTS
ELIMINATES 3 LEAK PATHS
SAVES 27 MINUTES OF LABOR


- Eliminate assemblies needed to isolate & drain any portion of a piped system
- **Press** or SWT × FIP option designed specifically for use with pre-fabricated threaded headers
- Reversible handle for added versatility
- Exclusive adjustable flow path allows for draining from either side of the ball



THE OLD WAY



THE WEBSTONE WAY
REPLACES 6 COMPONENTS
ELIMINATES 5 LEAK PATHS
SAVES 45 MINUTES OF LABOR



- Winterize an entire building with simple quarter-turn actions




- All the features of the ball drain, with integrated union connection
- Easily disconnect and replace any portion of a piped system

T-Flow Ball




Adjustable stem directs flow into the hi-flow hose drain from either side of the ball

DRAINING FROM ABOVE BALL



DRAINING FROM BELOW BALL



BALL DRAIN

Full Port Forged Brass Ball Valve w/ Hi-Flow Hose Drain, Reversible Handle & Adjustable Packing Glands

STANDARD BRASS

LEAD-FREE BRASS

Certified to NSF/ANSI 61 & 372

SIZE	ITEM #	CTN/CASE	CASE WT	ITEM #	CTN/CASE	CASE WT
FIP						
1/2"	H-40612	6/36	32	H-40612W	6/36	32
3/4"	H-40613	6/36	40	H-40613W	6/36	40
1"	H-40614	4/24	39	H-40614W	4/24	38
1 1/4"	H-40615	2/12	27	H-40615W	2/12	27
1 1/2"	H-40616	2/12	37	H-40616W	2/8	26
2"	H-40617	1/6	29	H-40617W	1/6	29
SWT						
1/2"	H-50612	6/36	29	H-50612W	6/36	29
3/4"	H-50613	6/36	39	H-50613W	6/36	39
1"	H-50614	4/24	38	H-50614W	4/24	37
1 1/4"	H-50615	2/12	27	H-50615W	2/12	27
1 1/2"	H-50616	2/12	41	H-50616W	2/8	27
2"	H-50617	1/6	32	H-50617W	1/6	30
SWT × FIP						
1/2"	H-54612	6/36	30	H-54612W	6/36	30
3/4"	H-54613	6/36	40	H-54613W	6/36	39
1"	H-54614	4/24	37	H-54614W	4/24	37
Press						
1/2"	H-80612	4/40	39	H-80612W	4/40	38
3/4"	H-80613	4/32	40	H-80613W	4/32	40
1"	H-80614	2/20	35	H-80614W	2/20	35
1 1/4"	H-80615	2/16	43	H-80615W	2/16	43
1 1/2"	-	-	-	H-80616W	1/8	29
2"	-	-	-	H-80617W	1/6	34
Press × FIP						
3/4"	H-84613	4/32	37	-	-	-
1"	H-84614	2/20	33	-	-	-
Press × ASTM F1807 PEX*						
1/2"	-	-	-	H-81612W	4/40	38
3/4"	-	-	-	H-81613W	4/32	30
1"	-	-	-	H-81614W	2/20	19
Press × ASTM F1960 PEX*						
1/2"	-	-	-	H-83612W	4/40	38
3/4"	-	-	-	H-83613W	4/32	30
1"	-	-	-	H-83614W	2/20	19

*CERTIFIED TO NSF/ANSI 61 & 372, NSF/ANSI 14 & IAPMO ANSI Z1157

UNION BALL DRAIN


Full Port Forged Brass Ball Valve w/ Single Union End, Hi-Flow Hose Drain, Reversible Handle & Adjustable Packing Glands

STANDARD BRASS

LEAD-FREE BRASS

Certified to NSF/ANSI 61 & 372

SIZE	ITEM #	CTN/CASE	CASE WT	ITEM #	CTN/CASE	CASE WT
FIP Union × FIP						
3/4"	H-40433	6/24	41	H-40433W	6/24	40
1"	H-40434	4/16	36	H-40434W	4/16	36
1 1/4"	H-40435	2/12	40	H-40435W	2/12	38
1 1/2"	H-40436	2/12	56	H-40436W	2/8	38
SWT × FIP Union						
3/4"	H-50433	6/24	40	H-50433W	6/24	39
1"	H-50434	4/16	36	H-50434W	4/16	31
1 1/4"	H-50435	2/12	38	H-50435W	2/12	38
1 1/2"	H-50436	2/12	56	H-50436W	2/8	38
Press × FIP Union						
3/4"	-	-	-	H-80433W	4/16	28
1"	-	-	-	H-80434W	2/16	36
1 1/4"	-	-	-	H-80435W	2/8	27
1 1/2"	-	-	-	H-80436W	1/5	25





THE OLD WAY



THE WEBSTONE WAY
REPLACES 2 COMPONENTS
ELIMINATES 1 LEAK PATH
SAVES 9 MINUTES OF LABOR

HANDLE OPERATION



- Install anywhere a drain or purge valve is required
- Hi-flow alternative for filling, draining, or venting closed-loop hydronic systems

T-DRAIN


Full Port Forged Brass Fitting w/ Hi-Flow Hose Drain & Adjustable Packing Gland

LEAD-FREE BRASS

Certified to NSF/ANSI 61-G


SIZE	ITEM #	CTN/CASE	CASE WT
SWT			600 CWP
1/2"	H-50672W	8/80	42
3/4"	H-50673W	6/48	39
1"	H-50674W	4/40	36
1 1/4"	H-50675W	4/40	43
1 1/2"	H-50676W	2/24	34
2"	H-50677W	2/20	34
Press			250 CWP/250 F
1/2"	H-80672W	4/40	25
3/4"	H-80673W	4/16	16
1"	H-80674W	4/16	18
1 1/4"	H-80675W	4/16	20

PURGE & FILL





- Simultaneously drain, flush & refill any hydronic, solar, or closed loop system
- Reversible handle for added versatility

THE OLD WAY



THE WEBSTONE WAY
REPLACES 7 COMPONENTS
ELIMINATES 6 LEAK PATHS
SAVES 54 MINUTES OF LABOR

HANDLE OPERATION



PURGE & FILL

Full Port Forged Brass Ball Valve w/ (2) Hi-Flow Hose Drains, Reversible Handle & Adjustable Packing Glands

STANDARD BRASS			
SIZE	ITEM #	CTN/CASE	CASE WT
FIP			600 CWP
3/4"	H-48613	1/12	20
1"	H-48614	1/12	26
1 1/4"	H-48615	1/12	38
1 1/2"	H-48616	1/12	49
SWT			600 CWP
3/4"	H-58613	1/12	23
1"	H-58614	1/12	26
1 1/4"	H-58615	1/12	38
1 1/2"	H-58616	1/12	51
Press			250 CWP/250 F
3/4"	H-88613	1/12	20
1"	H-88614	1/12	27
1 1/4"	H-88615	1/12	40
1 1/2"	H-88616	1/6	27




- The only way to place a ball valve between closely spaced tees
- Precision crafting achieves hydraulic separation
- Ideal for primary/secondary piping

PURGE-TEE

Full Port Forged Brass Ball Valve w/ Reversible Handle & Adjustable Packing Gland


STANDARD BRASS			
SIZE	ITEM #	CTN/CASE	CASE WT
SWT (1" Primary Loop)			600 CWP
1" x 3/4"	H-58643	1/12	23
1" x 1"	H-58644	1/12	24
SWT (1 1/4" Primary Loop)			600 CWP
1 1/4" x 3/4"	H-58653	1/12	39
1 1/4" x 1"	H-58654	1/12	38
1 1/4" x 1 1/4"	H-58655	1/12	37
Press (1" Primary Loop)			250 CWP/250 F
1" x 3/4"	H-88643	1/12	34
1" x 1"	H-88644	1/12	34
Press (1 1/4" Primary Loop)			250 CWP/250 F
1 1/4" x 1"	H-88654	1/12	51
1 1/4" x 1 1/4"	H-88655	1/12	52

THE OLD WAY



THE WEBSTONE WAY
REPLACES 7 COMPONENTS
ELIMINATES 4 LEAK PATHS
SAVES 54 MINUTES OF LABOR

HANDLE OPERATION



Normal Operation

System Isolation & Tank Draining



- The 3-way ball controls flow between the expansion tank and the system
- Easily install, isolate, drain & replace any expansion tank
- Quickly connect entire system to the cold water feed
- MIP model for direct connection to air separator or tee
- FIP model allows for distance between tank and system



IDEAL FOR USE WITH
Webstone
Air Separator

THE WEBSTONE WAY
REPLACES 5 COMPONENTS*
ELIMINATES 4 LEAK PATHS
SAVES 36 MINUTES OF LABOR



THE OLD WAY
*Correct spacing for hydraulic separation cannot be achieved using off-the-shelf components.
The Purge Tee is the ONLY way to place a valve between closely spaced tees.

HANDLE OPERATION



Normal Operation

Power Purging

EXPANSION TANK PRO SERVICE VALVE

Full Port Forged Brass Ball Valve w/ Hi-Flow Hose Drain

STANDARD BRASS			
SIZE	ITEM #	CTN/CASE	CASE WT
MIP/SWT x FIP x FIP x Hose			600 CWP
1/2"	H-41672	1/30	29
FIP x Hose			600 CWP
1/2"	H-44672	1/30	31