

## CO<sub>2</sub> DRAIN OPENER

- Superior clearing power
- Revolutionary new design
- Reversible dual fit cartridge base
- Fits both 16g and 20g CO<sub>2</sub> cartridges
- Lightweight and compact
- Heavy duty tool design
- Flexible hose assembly

### Description

The Gallo Gun™ is a heavy duty CO<sub>2</sub> powered tool that quickly and easily clears condensate drain lines with 800psi of oil free air! The Gallo Gun has a strong and rugged design, built with ergonomic finger grips, and comes equipped with a flexible hose assembly and tapered fitting to fit up to a 1" drain opening. The Gallo Gun utilizes a revolutionary dual fit cartridge base that can quickly and easily fit either a 16g or larger 20g cartridge for 25% more clearing power.

### Application

Use the Gallo Gun to clear clogged or slow moving drain lines. The 16g CO<sub>2</sub> cartridge will clear one standard condensate drain line, while the 20g CO<sub>2</sub> cartridge will clear two standard or one industrial drain line.

### Packaging

**4179-01** Gallo Gun

**4179-16** Mag™ 16g CO<sub>2</sub> Cartridge

**4179-20** Mag™ 20g CO<sub>2</sub> Cartridge

### Directions for Use:

1. Place the CO<sub>2</sub> cartridge in the dual-sized cup and start threading it on to the drain cleaner making sure the threads are starting in correct alignment.

## Indoor Air Quality Products

### Gallo Gun™



2. While holding the tool with the cartridge in an upright position (the tip of the cartridge facing upward), screw in until the cartridge just contacts the puncture pin, and then quickly and firmly twist it in until it stops. This will prevent loss of CO<sub>2</sub> gas.

3. Make sure the fittings on the hose are screwed in hand tight to seal and the nozzle is placed correctly and held in place firmly in the line to be cleared.

4. Press the trigger button firmly for burst of CO<sub>2</sub> (about a one to two second burst) the drain should clear and you will have a second burst left to make sure the drain is cleared or go from another direction

**Important** make sure to completely discharge any unused gas and remove the cartridge after use. This prevents the seals from setting and extends the life of the tool

**CO<sub>2</sub> Cartridge Warning:** Contents under pressure. Do not heat above 120°F/49°C or puncture. Do not inhale or discharge toward face or body. Keep cartridge and dispenser out of the reach of children.

Do not leave cartridge in a vehicle as overheating may occur causing rupture and serious injury. Discharge causes very cold temperatures and risk of frostbite to skin. co2un1013