

6DP3R35ME-TSK

New Model:

6DPNR35ME-TSK**Copeland**
brand productsHCFC, R-22, 60Hz, 3- Phase, 208/230 V
Air Conditioning

Production Status: Available for sale to all U.S. customers. Please check with your local Emerson Climate Technologies Representative for international availability.

Performance

Evap(°F)/Cond(°F)	45 / 130	35 / 105
RG(°F)/Liq(°F)	65 / 115	55 / 90
Capacity (Btu/hr)	387000	377000
Power (Watts):	35000	27100
Current (Amps):	52.70	43.15
EER (Btu/Wh):	11.10	13.90
Mass Flow (lbs/hr):	5700	5000
Sound Power (dBA):	0 Avg	0 Max
Vibration (mils(peak-)	0.0 Avg	0.0 Max
Record Date:	2007-06-12	

Mechanical

Number of Cylinders:	6	Displ(in^3/Rev):	74.50
Bore Size(in):	2.69	Displ(ft^3/hr):	4526.69
Stroke(in):	2.19		
Overall Length (in):	30.19	Mounting Length (in):	15.00
Overall Width (in):	22.44	Mounting Width (in):	12.00
Overall Height (in):	20.34	Mounting Height (in):	21.53 *
Suction Size (in):	2 1/8 Sweat		
Discharge Size (in):	1 5/8		
Oil Recharge (oz):	130		
Initial Oil Charge (oz):	140		
Net Weight (lbs):	550		
Internal Free Volume (in^3):			
Horse Power:	30		
*Overall compressor height on Copeland Brand Product's specified mounting grommets.			

Electrical

LRA-High*:	565.0	MCC (Amps):	175.2	UL File No:	SA-2337
LRA-Half Winding:	340.0	RPM:		UL File Date:	07-Apr-1971
LRA Low*:		Max Operating Current:			
RLA(=MCC/1.4;use for contactor selection):		125.1			
RLA(=MCC/1.56;use for breaker & wire size)		112.3			
*Low and High refer to the low and high nominal voltage ranges for which the motor is approved.					

Alternate Applications

Refrigerant	Freq (Hz)	Phase	Voltage	Application
R-404A HFC	50	3	380/400	Medium Temp, Low Condensing
R-507 HFC	50	3	380/400	Medium Temp, Low Condensing
R-407A HFC	50	3	200	Air Conditioning
R-407A HFC	50	3	380/400	Air Conditioning
R-407A HFC	50	3	200	Medium Temp, Low Condensing
R-407A HFC	50	3	380/400	Medium Temp, Low Condensing
R-407C HFC	50	3	200	Air Conditioning
R-407C HFC	50	3	380/400	Air Conditioning
R-407C HFC	50	3	200	Medium Temp, Low Condensing
R-407C HFC	50	3	380/400	Medium Temp, Low Condensing
R-407A HFC	60	3	460	Air Conditioning

Alternate Applications

<u>Refrigerant</u>	<u>Freq (Hz)</u>	<u>Phase</u>	<u>Voltage</u>	<u>Application</u>
R-404A HFC	60	3	208/230	Medium Temp, Low Condensing
R-404A HFC	60	3	208/230	Air Conditioning
R-507 HFC	60	3	208/230	Medium Temp, Low Condensing
R-507 HFC	60	3	208/230	Air Conditioning
R-407C HFC	60	3	208/230	Air Conditioning
R-407C HFC	60	3	208/230	Medium Temp, Low Condensing
R-407A HFC	60	3	208/230	Air Conditioning
R-407A HFC	60	3	208/230	Medium Temp, Low Condensing
R-407F HFC	60	3	208/230	
R-407F HFC	60	3	208/230	
R-22 HCFC	50	3	380/400	Air Conditioning
R-22 HCFC	50	3	380/400	Medium Temp, Low Condensing
R-502 CFC	50	3	380/400	Medium Temperature
R-404A HFC	50	3	380/400	Medium Temp, Low Condensing
R-404A HFC	50	3	380/400	Air Conditioning
R-507 HFC	50	3	380/400	Medium Temp, Low Condensing
R-507 HFC	50	3	380/400	Air Conditioning
R-407C HFC	50	3	380/400	Air Conditioning
R-407C HFC	50	3	380/400	Medium Temp, Low Condensing
R-407A HFC	50	3	380/400	Air Conditioning
R-407A HFC	50	3	380/400	Medium Temp, Low Condensing
R-407F HFC	50	3	380/400	
R-407F HFC	50	3	380/400	

Alternate Applications

Refrigerant	Freq (Hz)	Phase	Voltage	Application
R-22 HCFC	50	3	200	Air Conditioning
R-22 HCFC	50	3	200	Medium Temp, Low Condensing
R-502 CFC	50	3	200	Medium Temperature
R-404A HFC	50	3	200	
R-404A HFC	50	3	200	Air Conditioning
R-507 HFC	50	3	200	
R-507 HFC	50	3	200	Air Conditioning
R-407A HFC	60	3	208/230	Air Conditioning
R-407A HFC	60	3	208/230	Medium Temp, Low Condensing
R-407A HFC	60	3	460	Medium Temp, Low Condensing
R-407C HFC	60	3	208/230	Air Conditioning
R-407C HFC	60	3	460	Air Conditioning
R-407C HFC	60	3	460	Medium Temp, Low Condensing
R-407C HFC	60	3	208/230	Medium Temp, Low Condensing
R-407A HFC	50	3	200	
R-407A HFC	50	3	380/400	
R-407A HFC	50	3	380/400	
R-407C HFC	50	3	200	
R-407C HFC	50	3	380/400	
R-407A HFC	50	3	200	
R-407C HFC	50	3	200	
R-407C HFC	50	3	380/400	
R-407C HFC	50	3	200	Air Conditioning
R-407C HFC	50	3	200	Medium Temp, Low Condensing
R-407A HFC	50	3	200	Air Conditioning
R-407A HFC	50	3	200	Medium Temp, Low Condensing
R-407F HFC	50	3	200	
R-407F HFC	50	3	200	
R-22 HCFC	60	3	460	Air Conditioning
R-22 HCFC	60	3	460	Medium Temp, Low Condensing
R-502 CFC	60	3	460	
R-404A HFC	60	3	460	Medium Temp, Low Condensing
R-404A HFC	60	3	460	Air Conditioning
R-507 HFC	60	3	460	Medium Temp, Low Condensing
R-507 HFC	60	3	460	Air Conditioning
R-407C HFC	60	3	460	Air Conditioning
R-407C HFC	60	3	460	Medium Temp, Low Condensing
R-407A HFC	60	3	460	Air Conditioning
R-407A HFC	60	3	460	Medium Temp, Low Condensing
R-407F HFC	60	3	460	
R-407F HFC	60	3	460	
R-22 HCFC	60	3	208/230	Medium Temp, Low Condensing
R-502 CFC	60	3	208/230	