

5-5/8" DIAMETER MOTORS

A.O. Smith

Capacitor Start Resilient Base Motors

FEATURES:

- Class B insulation.
- Open construction.
- 2, 4 and 6 pole.
- 60 Hz.
- Auto protector.
- High start torque.
- Reversible.
- 40°C ambient.
- Volts at 1.0 S.F.



HP	RPM	Volts	F.L. Amps	S.F.	Frame	Bearings	Mfr#	Item#	Reman#
1/2	1725	115/230	8.8/4.4	1.25	56	Sleeve	RS1054A	A24-52	
3/4	1725	115/208-230	11.6/5.8	1.25	56	Ball	RB1074A	RB1074A	
3/4	1725	115/230	10.4/5.20	1.25	56	Sleeve	RS1074A	A24-60	A24-60R

A.O. Smith

Split Phase Belted Fan and Blower Motors

FEATURES:

- NEMA service factor.
- 56 and 48/56 combination frame.
- Thermally protected.
- Resilient mount.
- Sleeve bearing.
- Shaft adapter kits included with 48/56 combination frame.



HP	RPM	Amps (60 Hz)	S.F.	Frame	Shaft Dia. x L	Mfr#	Item#	Reman#
1/4	1725	4.6 @ 115V	1.35	48/56	1/2" x 1.5"	GF2024*	A22-14	A22-14R
1/3	1725	5.9 @ 115V	1.35	48/56	1/2" x 1.5"	GF2034*	A22-28	A22-28R
1/2	1725	7.2 @ 115V	1.25	48/56	1/2" x 1.5"	GF2054*	A22-42	A22-42R
1/2	1725	7.2/3.6 @ 115/230V	1.25	48/56	1/2" x 1.5"	GF2054D*	A22-46	
3/4	1725	10.9 @ 115V	1.25	56	1/2" x 1.5"	GK2074	A22-60	A22-58R
3/4	1725	11.5/5.5 @ 115/230V	1.25	56	5/8" key x 1-7/8"	GK2074D		A22-60R
1	1725	13.6/6.5 @ 115/230V	1.15	56	5/8" key x 1-7/8"	GK2104D	A22-80	A22-80R

*Includes 5/8" adapter. For 56 frame application.