

**8 Ton Heat Pump Outdoor Unit - 208/230 VAC, 3-Phase, 60Hz  
1X (AOUA96RLBV1)**

**Job Name** \_\_\_\_\_  
**Location** \_\_\_\_\_  
**Engineer** \_\_\_\_\_  
**Submitted To** \_\_\_\_\_  
**Submitted By** \_\_\_\_\_  
**Reference** \_\_\_\_\_

**Date** \_\_\_\_\_  
**Approval** \_\_\_\_\_  
**Construction** \_\_\_\_\_  
**Unit No** \_\_\_\_\_  
**Drawing No** \_\_\_\_\_

- Inverter driven compressor
- New style high power DC fan motor.
- Blue fin heat-exchanger (Corrosion resistance)
- 10 Year warranty on parts and compressor. See Warranty Statement for details.
- Optional: Internet, BACnet, LonWorks, or Modbus communication.



CAPACITY	
Nominal Cooling Capacity - BTU/h [kW]	96,000 [28.1]
Nominal Heating Capacity - BTU/h [kW]	108,000 [31.7]
Nominal Tonnage - Ton(s)	8
Maximum Connectable Indoor Units	16
Connectable Capacity	50% to 150%
Cooling Power Input - kW	7.67
Heating Power Input - kW	7.9
Unit Group	1X (AOUA96RLBV1)

OPERATING TEMPERATURES	
Operating Temp. Cooling (DB) - °F [°C]	5 to 115 [-15 to 46]
Operating Temp. Heating (DB) - °F [°C]	-4 to 70 [-20 to 21]

ELECTRICAL	
Electrical Power Requirements	208/230 VAC, 3-Phase, 60Hz
Voltage Range	187 to 253 VAC
Maximum Circuit Breaker - A	50
Minimum Circuit Ampacity (MCA) - A	41
Cooling Power Input - kW	7.67
Heating Power Input - kW	7.9
Maximum Starting Current (MSC) - A	33.2
Compressor - Rated Load Amperage (RLA) - A	25
Fan Motor - Full Load Amperage (FLA) - A	3

EFFICIENCY	
EER Cooling (Ducted/Non Ducted)	11.3 / 11.7
IEER Cooling (Ducted/Non Ducted)	20.20 / 23.60
COP / High Heating 47°F	3.60 / 3.72

COMPRESSOR	
Compressor Type	Rotary Inverter
Refrigerant Type	R410A
Refrigerant Charge - lbs [kg]	25.79 [11.70]
Compressor Crankcase Heater - W	2X 35
Refrigerant Oil / Lubricant	VG74 (Ester oil)
Compressor Capacity Control - Steps/Range	951 / 20 - 115

WIRING	
Communication Cable	LonWorks (Fujitsu Pink Cable. See AE Bulletin 009)

FAN	
Fan Type	Propeller fan
Fan Airflow Rate - CFM [m3/h]	6,533 [11,100]
Fan Power Output - W	740
Fan Motor - Full Load Amperage (FLA) - A	3
External Static Pressure (Max) - in.WG [Pa]	0.32 [80]

PIPING	
Max. Total Refrigerant Line Length - ft [m]	3,280 [1,000]
PipeConnection:Max Height Diff. (ODU & ID)(Upper/Lower) - ft [m]	164/131 [50/40]
Pipe Connection Method: Liquid/Gas	Brazed
Pipe Connection: Liquid - in [mm]	1/2 [12.70]
Pipe Connection: Discharge Gas - in [mm]	3/4[19.05]
Pipe Connection: Suction Gas - in [mm]	7/8 [22.22]

HEAT EXCHANGER	
H. E. Pipe Type (Material)	Grooved H-pin (Copper)
H. E. Fin Tube (Material)	Corrugate (Aluminum)
H. E. Fin Surface Treatment	Corrosion resistance (Blue fin)
H. E. Fin Pitch - FPI [mm]	18 [1.45]
H. E. Rows x Stages	3 x 60
H. E. Face Area - Ft² [m²]	23 [2.2]
H. E. Length - in [mm]	69-5/16 [1760]

SOUND	
Sound Pressure Levels (Cooling/Heating) - dB(A)	59 / 59

WEIGHT	
Net Weight - lbs [kg]	564 [256]
Gross Weight - lbs [kg]	611 [277]

DIMENSIONS	
Dim.Net (HxWxD) - in [mm]	66-9/16 x 36-5/8 x 30-1/8 [1690 x 930 x 765]

Dim.Gross (HxWxD) - in [mm]	71-5/16 x 39-7/16 x 33-3/8 [1811 x 1002 x 847]
-----------------------------	---

CODE	
ETL	3170288
AHRI Certified	Standard 1230

Note: Specifications are based on the following conditions:  
 Cooling: Indoor temperature of 80°F (26.7°C) DB/67°F (19.4°C) WB, and outdoor temperature of 95°F (35°C) DB/75°F (23.9°C) WB.  
 Heating: Indoor temperature of 70°F (21.1°C) DB/60°F (15.6°C) WB, and outdoor temperature of 47°F (8.3°C) DB/43°F (6.1°C) WB.  
 Pipe length: 25ft. (7.5m), Height difference: 0ft. (0m) (Outdoor unit – indoor unit).



Fujitsu General America, Inc.  
 353 Route 46 West  
 Fairfield, NJ 07004  
 Toll Free: (888) 888-3424  
 Fax: (973) 836-0453  
[www.airstagevf.com](http://www.airstagevf.com)

**Submittal AOUA96RLBV1**

**8 Ton Heat Pump Outdoor Unit - 208/230 VAC, 3-Phase, 60Hz  
1X (AOUA96RLBV1)**

**DIMENSIONS**

Unit: In. (mm)

