

## Inverter Driven Heat Pump

30,000 BTU Multi Position AHU

Job Name \_\_\_\_\_  
 Location \_\_\_\_\_  
 Engineer \_\_\_\_\_  
 Submitted To \_\_\_\_\_  
 Submitted By \_\_\_\_\_  
 Reference \_\_\_\_\_

Date \_\_\_\_\_  
 Approval \_\_\_\_\_  
 Construction \_\_\_\_\_  
 Unit No \_\_\_\_\_  
 Drawing No \_\_\_\_\_

### PRODUCT FEATURES

Up to 1.0" WC  
 2-Wire Wired Remote Controls  
 Aluminum Indoor Unit Coil  
 True four position : Up, Down, Right/Left  
 Long Lineset Lengths (up to 246')  
 Low Air Leakage Rate (2% or less)  
 Built in Base Pan Heater  
 Heating operation rated down to -15°F outdoor temperature  
 Integral Electric Heat Kit - Optional  
 Airzone Zoning Kit - Optional



MODEL NUMBERS	
Indoor Unit	AMUG30LMAS
Outdoor Unit	AOUH30LUAH1
System	30LUAH1M

EFFICIENCIES	
SEER	19.1
SEER 2	18.8
EER	12
EER 2	11.7
HSPF	10.5
HSPF 2 (IV) / HSPF 2 (V)	9.7/8.1
COP	kW/kW 3.64
COP	Btu/hW 12.42
COP2	kW/kW 3.46
COP2	Btu/hW 11.81

OUTDOOR TEMPERATURE OPERATION RANGE	
Cooling	-5 to 115 (-21 to 46)
Heating*	*-15 to 75 (-26 to 24)

CAPACITIES	
Cooling	Rated 28600
	Min.-Max. 9,600-35,000
Heating	Rated 32000
	Min.-Max. 9,200-39,000

LINESET REQUIREMENTS	
Connection Method	Flare
Liquid	in (mm) Ø 3/8 (Ø 9.52)
Gas	Ø 5/8 (Ø 15.88)
Pre-charge length	98 (30)
Minimum Length	16 (5)
Max. length	246 (75)
Max. height difference	98 (30)

INDOOR DIMENSIONS & WEIGHT	
Net (H x W x D)	in (mm) 42-1/2 x 21 x 21-11/16
Gross (H x W x D)	42-3/4 x 24 x 25-5/16
Net Weight	lb (kg) 104 (47.0)
Gross Weight	116 (52.5)

OUTDOOR DIMENSIONS & WEIGHT	
Net (H x W x D)	in (mm) 39-5/16 x 38-3/16 x 14-9/16 (998 x 970 x 370)
Gross (H x W x D)	45-3/4 x 41-7/8 x 18-13/16
Net Weight	lb (kg) 187 (85)
Gross Weight	209 (95)

\* System continues to operate below rated outdoor operation temperature range, subject to varying conditions. System has no low temperature cut out. Capacity is not tested outside of the rated temperature range.

### Warranty Information



7 Year Compressor, 5 Year Parts out-of-the-box Warranty



10 Year Compressor, 10 Year Parts Warranty when registered within 60 days of installation in a residence



12 Year Compressor, 12 Year Parts Warranty when registered within 60 days of installation in a residence, and installed by a Fujitsu Elite contractor

### ACCESSORIES

UTY-RNRUZ-Series	Wired Remote Controller
UTY-RSRY	Simple Remote Controller
UTY-RHRY	Simple Remote Controller
UTY-LBTUM	IR Receiver Kit with Wireless Remote Controller
UTY-XSZX	Remote Sensor Unit
UTY-XWZXZG	External Connect Kit
UTY-XCSX	External Input and Output PCB
UTY-XWZXZI	Wire Kit
UTY-VTGX	Network Converter
UTY-TTRXZ1	Thermostat Converter
UTY-VMSX	Modbus Converter

Due to continuous product improvements, specifications are subject to change without notice. Please log in to the Fujitsu Portal for the most up-to-date documentation  
<https://connect.fujitsugeneral.com>

Effective Date: 04/18/2024

Fujitsu General America, Inc. • 342 Changebridge Rd, Pine Brook, NJ 07058 • Toll Free: (888) 888-3424 • [www.fujitsugeneral.com](http://www.fujitsugeneral.com)

Inverter Driven Heat Pump

30,000 BTU Multi Position AHU

FAN DATA

Indoor Unit Airflow rate	Cooling	HIGH	CFM (m3/h)	870 (1,478)
		MED		730 (1,240)
		LOW		590 (1,002)
		QUIET		310 (527)
	Heating	HIGH		870 (1,478)
		MED		730 (1,240)
		LOW		590 (1,002)
		QUIET		310 (527)
Outdoor Unit Airflow rate	Cooling			2,590 (4,400)
	Heating			2,590 (4,400)

SOUND PRESSURE

Indoor Unit	Cooling	HIGH	dB (A)	42
		MED		37
		LOW		33
		QUIET		28
	Heating	HIGH		39
		MED		36
		LOW		32
		QUIET		25
Outdoor Unit	Cooling			52
	Heating			53

REFRIGERANT

REFRIGERANT			
Type	R410A		
Charge	lb oz	7 lb 8 oz	
	g	3400	
Oil Type	POE (RB68)		

ELECTRICAL SPECIFICATIONS

Voltage/Frequency/Phase		208/230 V ~ 60 Hz		
Available Voltage Range		187–253 V		
Current	Cooling	Rated	A	11
	Heating	Rated		12.1
Maximum Operating Current	Cooling			19.8
	Heating			26.8
Starting current				11.4
MCA				31.9
Maximum Circuit Breaker				35
Input Power	Cooling	Rated	kW	2.44
		Min.–Max.		0.44–3.40
	Heating	Rated		2.71
		Min.–Max.		0.60–4.17
Power Factor	Cooling		%	96.4
	Heating			97.4


OTHER

Moisture Removal		pints/h (L/h)	6.8 (3.2)
Energy Star			No
Drain hose	Material		LDPE
	Tip diameter	in (mm)	Ø1/2 (13.0) [I.D.], Ø5/8 to Ø11/16 (16.0 to 16.7) [O.D.]
Operation Range	Cooling	°F (°C)	64 to 90 (18 to 32)
	Heating	%RH	80 or less
Static pressure range		°F (°C)	60 to 86 (16 to 30)
		inWG (Pa)	0.08 to 1 (20 to 250)

DIMENSIONS:

Units: In. (mm)

Indoor Unit:



Model	A (Supply duct)	W (Unit width)	H (Unit height)
AMUG30LMAS	19-1/2 (495)	21 (533)	42-1/2 (1,080)

Return Opening Dimensions	
Width	Depth
19 3/8	19 3/4


## Inverter Driven Heat Pump

### 30,000 BTU Multi Position AHU

## DIMENSIONS

Units: In. (mm)

## Outdoor Unit



The Fujitsu logo is a worldwide trademark of Fujitsu General Limited. The Airstage logo and name is a worldwide trademark of Fujitsu General Limited and is a registered trademark in Japan, the USA and other countries or areas. Copyright 2024 Fujitsu General America, Inc. Fujitsu's products are subject to continuous improvements. Fujitsu reserves the right to modify product design, specifications and information in this brochure without notice and without incurring any obligations.

Note: Specifications are based on the following conditions:  
Cooling: Indoor temperature of 80°F (26.7°C) DB/67°F (19.4°C) WB, and outdoor temperature of 95°F (35°C) DB/75°F (23.9°C) WB. Heating: Indoor temperature of 70°F (21.1°C) DB/60°F (15.6°C) WB, and outdoor temperature of 47°F (8.3°C) DB/43°F (6.1°C) WB. Pipe length: 25ft. (7.5m), Height difference: 0ft. (0m) (Outdoor unit – indoor unit).

## Inverter Driven Heat Pump

30,000 BTU Multi Position AHU

## Electric Heat Kit

For 2.5 Ton System:

HEATER PART #	STAGE	VOLTAGE	PH/HZ	HEATER KW	HEATER AMPS	DESCRIPTION
RXBH-1724A03J-A	SINGLE	208/240	1/60	2.25 / 3.0	10.8 / 12.5	3 KW ELECTRIC HEAT KIT WITH BREAKER 208/230 1PH
RXBH-1724A05J-A	SINGLE	208/240	1/60	3.6 / 4.8	17.3 / 20.0	5 KW ELECTRIC HEAT KIT WITH BREAKER 208/230 1PH
RXBH-1724A07J-A	SINGLE	208/240	1/60	5.4 / 7.2	26.0 / 30.0	7 KW ELECTRIC HEAT KIT WITH BREAKER 208/230 1PH
RXBH-1724A10J-A	SINGLE	208/240	1/60	7.2 / 9.6	34.6 / 40.0	10 KW ELECTRIC HEAT KIT WITH BREAKER 208/230 1PH
RXBH-1724B05J-A	SINGLE	208/240	1/60	3.6 / 4.8	17.3 / 20.0	5 KW ELECTRIC HEAT KIT NO BREAKER 208/230 1PH
RXBH-1724B07J-A	SINGLE	208/240	1/60	5.4 / 7.2	26.0 / 30.0	7 KW ELECTRIC HEAT KIT NO BREAKER 208/230 1PH
RXBH-1724B10J-A	SINGLE	208/240	1/60	7.2 / 9.6	34.6 / 40.0	10 KW ELECTRIC HEAT KIT NO BREAKER 208/230 1PH
RXBH-1724C05J-A	SINGLE	208/240	1/60	3.6 / 4.8	17.3 / 20.0	HTR KIT-5KW 208/230/1/60 (PULL OUT DISCONNECT)
RXBH-1724C07J-A	SINGLE	208/240	1/60	5.4 / 7.2	26.0 / 30.0	HTR KIT-7KW 208/230/1/60 (PULL OUT DISCONNECT)
RXBH-1724C10J-A	SINGLE	208/240	1/60	7.2 / 9.6	34.6 / 40.0	HTR KIT-10KW 208/230/1/60 (PULL OUT DISCONNECT)

Accessories:

Model #	Description
RXHB-21	COMBUSTIBLE FLOOR BASE 21"
RXHF-21	EXTERNAL FILTER BASE FOR FAN COILS - 21"
RXBJ-A21	JUMPER BAR (USED WITH 13kW (or larger) HEATER KIT)