

Medium Static Pressure Duct (72,000 BTU) Indoor Unit  
For Heat-recovery/Heat-pump Airstage VRF System

Job Name		Date	
Location		Approval	
Engineer		Construction	
Submitted To		Unit No	
Submitted By		Drawing No	
Reference			

- FEATURES**
- Quiet 3-speed fan
  - Adjustable Static pressure from 0 to 1.2 in.WG
  - Auxiliary heat operation capability
  - 10 year Extended Warranty on parts and compressor. See Warranty Statement.



STATIC PRESSURE	
Static Pressure Range - in.WG [Pa]	0 to 1.2 [0 to 300]
Standard Static Pressure - in.WG [Pa]	0.60 [150]

CAPACITY	
Capacity - Cooling - Btu/h [kW]	72,000 [21.1]
Capacity - Heating - Btu/h [kW]	81,000 [23.7]

PIPING ACCESSORIES	
UTP-AX090A	Separation Tube - 2-Pipe - 90 MBH or Less
UTP-AX180A	Separation Tube - 2-Pipe - 91 to 180 MBH
UTP-AX567A	Separation Tube - 2-Pipe - 180 MBH or More

ELECTRICAL	
Power Source	208 / 230V, 1-Phase, 60Hz
Available Voltage Range - VAC	187 to 253
Input Power - W	618
Full Load Amps - FLA - A	6.5
Max Circuit Breaker - A	15
Minimum Circuit Ampacity - MCA - A	8.13
Fuse - A (V)	

CONTROLLER	
UTY-RNRUZ4	Individual Touch Panel Controller (Wired Remote)
UTY-RSRY	Simple Remote (WITH Master Control) 2-Wire
UTY-RHRY	Simple Remote (WITHOUT Master Control) 2-Wire
UTY-LNHU	Wireless Remote Controller (requires IR Receiver)
UTY-DCGY	Central Remote Controller (100 units)
UTY-DTGYZ1	Touch Panel Controller with Internet (400 units)

FAN	
Fan Type	2X (Sirocco)
Airflow Rate - High   Medium High - CFM [m³/h]	2,297 [3,900]
Airflow Rate - Medium   Medium Low - CFM [m³/h]	1,944 [3,300]
Airflow Rate - Low   Quiet - CFM [m³/h]	1,767 [3,000]

ACCESSORIES	
UTD-RF204	Flange (Round) for Duct IU

SOUND PRESSURE	
Sound Pressure Level - dB(A)	47/43/40

WIRING	
Communication Cable	LonWorks (Fujitsu Pink Cable. See AE Bulletin 009)

WEIGHT AND DIMENSIONS	
Enclosure - Net Weight - lbs [kg]	203 [92]
Enclosure - Gross Weight - lbs [kg]	238 [108]
Dimensions - Net (H x W x D) - in [mm]	17-11/16 x 62-1/2 x 27-9/16 [450 x 1,587 x 700]
Dimensions - Gross (H x W x D) - in [mm]	20-1/2 x 68-7/8 x 32-1/2 [520 x 1,750 x 825]

PIPING	
Connection Pipe Diameter - Liquid (Brazing) - in [mm]	ø 3/8 [9.52]
Connection Pipe Diameter - Gas (Brazing) - in [mm]	ø 3/4 [19.05]
Connection Pipe Diameter - Drain (ID; OD) - in [mm]	ø 3/4 [19]
Drain-Pump	Optional

ETL	
E.T.L.	91987

TEMPERATURE RANGES	
Operating Temp. Cooling (DB) - °F [°C]	64 to 88 [18 to 31]
Operating Temp. Heating (DB) - °F [°C]	50 to 88 [10 to 31]

Note: Specifications are based on the following conditions:  
Cooling: Indoor temperature of 80°F (26.7°C) DB/67°F (19.4°C) WB, and outdoor temperature of 95°F (35°C) DB/75°F (23.9°C) WB. Heating: Indoor temperature of 70°F (21.1°C) DB/60°F (15.6°C) WB, and outdoor temperature of 47°F (8.3°C) DB/43°F (6.1°C) WB. Pipe length: 25ft. (7.5m), Height difference: 0ft. (0m) (Outdoor unit – indoor unit).



FUJITSU GENERAL AMERICA, INC.  
340 Changebridge Rd.  
Pine brook, NJ 07058  
Toll Free: (888) 888-3424  
Fax: (973) 836-0453  
www.airstagevrf.com

# SUBMITTAL ARUH72TLAV2

Medium Static Pressure Duct (72,000 BTU) Indoor Unit  
For Heat-recovery/Heat-pump Airstage VRF System

DIMENSIONS

Unit: In. (mm)

