

Compact Cassette (12,000 BTU) Indoor Unit For Heat-recovery/Heat-pump Airstage VRF System

Job Name _____
 Location _____
 Engineer _____
 Submitted To _____
 Submitted By _____
 Reference _____

Date _____
 Approval _____
 Construction _____
 Unit No _____
 Drawing No _____

FEATURES

- Compatible with 2-wire remotes only
- Quiet 3 speed fan
- Built-in high-lift drain pump
- Built-in IR Receiver
- Support for fresh-air intake kit
- Grille includes built-in modulating louvers
- Grille must be ordered separately (UTG-CCGVG)
- Auxiliary heat operation capability
- 10 year Extended Warranty on parts and compressor. See Warranty Statement.



PIPING ACCESSORIES

| | |
|------------|--|
| UTP-AX090A | Separation Tube - 2-Pipe - 90 MBH or Less |
| UTP-AX180A | Separation Tube - 2-Pipe - 91 to 180 MBH |
| UTP-AX567A | Separation Tube - 2-Pipe - 180 MBH or More |

CONTROLLER

| | |
|------------|---|
| UTY-RNRUZZ | Individual Touch Panel Controller (Wired Remote) |
| UTY-PSRY | Simple Remote (WITH Master Control) 2-Wire |
| UTY-RHRY | Simple Remote (WITHOUT Master Control) 2-Wire |
| UTY-LNHU | Wireless Remote Controller (requires IR Receiver) |

| | |
|------------|--|
| UTY-DCGY | Central Remote Controller (100 units) |
| UTY-DTGYZ1 | Touch Panel Controller with Internet (400 units) |

ACCESSORIES

| | |
|----------|---|
| UTR-YDZB | Air Outlet Shutter Plate for Compact Cassette |
| UTZ-KXGC | Insulation Kit for High Humidity for Compact Cassette |
| UTY-TEKX | External Switch Controller. Use with 3-Wire remotes only. |
| UTY-XSZX | Remote Sensor for ducted units |

WEIGHT AND DIMENSIONS

| | |
|---|---|
| Enclosure - Net Weight - lbs [kg] | 32 [14.5] |
| Enclosure - Gross Weight - lbs [kg] | 42 [19] |
| Dimensions - Net (H x W x D) - in [mm] | 9-5/8 x 22-7/16 x 22-7/16 [245 x 570 x 570] |
| Dimensions - Gross (H x W x D) - in [mm] | 10-7/16 x 28-3/4 x 24-5/8 [265 x 730 x 625] |
| Grille Weight Net - lbs [kg] | 5 (2.3) |
| Grille Weight Gross - lbs [kg] | 10 [4.5] |
| Grille Dimensions Net (H x W x D) - in [mm] | 1-15/16 x 24 7/16 x 24 7/16 [50 x 620 x 620] |
| Grille Dimensions Gross (H x W x D) - in [mm] | 5 x 30 x 30 [127 x 762 x 762] |

CAPACITY

| | |
|---------------------------------|--------------|
| Capacity - Cooling - Btu/h [kW] | 12,000 [3.5] |
| Capacity - Heating - Btu/h [kW] | 13,500 [4] |

ELECTRICAL

| | |
|------------------------------------|---------------------------|
| Power Source | 208 / 230V, 1-Phase, 60Hz |
| Available Voltage Range - VAC | 187 to 253 |
| Input Power - W | 29 |
| Full Load Amps - FLA - A | 0.41 |
| Max Circuit Breaker - A | 15 |
| Minimum Circuit Ampacity - MCA - A | 0.51 |
| Fuse - A (V) | 3.15 (250) |

FAN

| | |
|---|-----------------------|
| Fan Type | Turbo |
| Airflow Rate - High Medium High - CFM [m³/h] | 353 [600] 330 [560] |
| Airflow Rate - Medium Medium Low - CFM [m³/h] | 306 [520] 283 [480] |
| Airflow Rate - Low Quiet - CFM [m³/h] | 253 [430] 230 [390] |

SOUND PRESSURE

| | |
|------------------------------|-------------------|
| Sound Pressure Level - dB(A) | 37/34/33/31/29/27 |
|------------------------------|-------------------|

WIRING

| | |
|---------------------|--|
| Communication Cable | LonWorks (Fujitsu Pink Cable. See AE Bulletin 009) |
|---------------------|--|

PIPING

| | |
|---|---------------|
| Connection Pipe Diameter - Liquid (Brazing) - in [mm] | ø 1/4 [6.35] |
| Connection Pipe Diameter - Gas (Brazing) - in [mm] | ø 1/2 [12.70] |
| Connection Pipe Diameter - Drain (ID; OD) - in [mm] | ø 3/4 [19] |
| Drain-Pump | Built-in |
| Drain-Pump Lift - in [mm] | 27 9/16 [700] |

ETL

| | |
|--------|---------|
| E.T.L. | 3170288 |
|--------|---------|

TEMPERATURE RANGES

| | |
|--|---------------------|
| Operating Temp. Cooling (DB) - °F [°C] | 64 to 88 [18 to 31] |
| Operating Temp. Heating (DB) - °F [°C] | 50 to 88 [10 to 31] |

Note: Specifications are based on the following conditions:
 Cooling: Indoor temperature of 80°F (26.7°C) DB/67°F (19.4°C) WB, and outdoor temperature of 95°F (35°C) DB/75°F (23.9°C) WB. Heating: Indoor temperature of 70°F (21.1°C) DB/60°F (15.6°C) WB, and outdoor temperature of 47°F (8.3°C) DB/43°F (6.1°C) WB. Pipe length: 25ft. (7.5m), Height difference: 0ft. (0m) (Outdoor unit - indoor unit).

Compact Cassette (12,000 BTU) Indoor Unit
For Heat-recovery/Heat-pump Airstage VRF System

DIMENSIONS

Unit: In. (mm)

