

CHECK VALVES | BRASS & PLASTIC



Stop & Waste Valve
CPVC

Item No.	Size	Connection	Inner	MC
105-323	1/2"	SLIP x SLIP	12	72
105-323HN	1/2"	SLIP x SLIP	-	20
105-324	3/4"	SLIP x SLIP	12	72
105-324HN	3/4"	SLIP x SLIP	-	20

Features:

- Rated for 100 PSI @ 180°F
- Rising stem for positive open and close operation
- For use with hot or cold water
- Not for use with compressed air
- Solvent connection for use with CPVC tubing size pipe
- Plug allows draining of non-pressure side of valve when closed



Swing Check Valve
Brass | Hard Seat
Threaded

Item No.	Size	Connection	Inner	MC
101-001NL	1/4"	FIP x FIP	10	100
101-002NL	3/8"	FIP x FIP	10	100
101-003NL	1/2"	FIP x FIP	-	15
101-004NL	3/4"	FIP x FIP	-	15
101-005NL	1"	FIP x FIP	5	40
101-006NL	1-1/4"	FIP x FIP	5	30
101-007NL	1-1/2"	FIP x FIP	4	24
101-008NL	2"	FIP x FIP	2	16
101-009NL	2-1/2"	FIP x FIP	-	-
101-010NL	3"	FIP x FIP	-	-

Features:

- 200 PSI WOA



Swing Check Valve
Brass | Hard Seat
Solder

Item No.	Size	Connection	Inner	MC
101-503NL	1/2"	C x C	-	15
101-504NL	3/4"	C x C	-	15
101-505NL	1"	C x C	5	40
101-506NL	1-1/4"	C x C	5	30
101-507NL	1-1/2"	C x C	4	24
101-508NL	2"	C x C	2	16
101-509NL	2-1/2"	C x C	-	-
101-510NL	3"	C x C	-	-

Features:

- 200 PSI WOA



Swing Check Valve
Bronze | "Y" Pattern
Threaded

Item No.	Size	Connection	Inner	MC
101-203	1/2"	FIP x FIP	10	120
101-204	3/4"	FIP x FIP	10	80
101-205	1"	FIP x FIP	10	60
101-206	1-1/4"	FIP x FIP	5	30
101-207	1-1/2"	FIP x FIP	4	24
101-208	2"	FIP x FIP	2	16

Features:

- 300 PSI non-shock WOG
- 150 PSI working steam pressure
- Heavy bronze construction
- Screw-on cap
- Swing-type disc with integral seat
- PTFE face on disc for positive seal
- Vertical or horizontal installation