

COMMERCIAL DEFROST CONTROLS

Paragon

Defrost Controls

Time initiated, time terminated, 40 amp.

FEATURES:

- Adjustable frequency defrost from 1 – 6 cycle per day. Min. 4 hours between successive operations.
- Adjustable duration of defrost cycle from 4 – 110 min. in 2 min. increments.
- Defrost duration accurate to ± 2 min.
- Positive switch action slider bar.
- Switch rating per pole: 40 amps, 2 hp per pole, 690 va pilot duty, 120-240 volts AC.
- Heavy-duty, synchronous, industrial type motor.



8041 SERIES - FOR ELECTRIC HEAT DEFROSTING - AUXILIARY CONTACT MODELS

| Switch Contact Arrangement | Volts @ 60 Hz | Replaces | Mfr# | New Item# | Reman# |
|--------------------------------------|---------------|----------|---------|-----------|-----------|
| 2 - 4 close, 1 - 3 open, 3 - N close | 120 | --- | 8041-00 | C255-110 | C255-110R |
| Same as above | 208/240 | --- | 8041-20 | C255-112 | C255-112R |

8045 SERIES - FOR ELECTRIC HEAT, HOT GAS OR COMPRESSOR SHUTDOWN DEFROSTING

| | | | | | |
|-------------------------------------|---------|----------------------|---------|----------|-----------|
| 2 - 4 close, 1 - 3 open, 3 - N none | 120 | 305-MB, 8005, 8015-0 | 8045-00 | C255-118 | C255-118R |
| Same as above | 208/240 | 306-MB, 8006, 8015-3 | 8045-20 | C255-120 | C255-120R |

8047 SERIES - FOR ELECTRIC HEAT DEFROSTING - AUXILIARY CONTACT MODELS

| | | | | | |
|-------------------------------------|---------|--------------|---------|----------|-----------|
| 2 - 4 open, 1 - 3 open, 3 - N close | 120 | 8007, 8017-0 | 8047-00 | C255-122 | C255-122R |
| Same as above | 208/240 | 8008, 8017-3 | 8047-20 | | C255-124R |

Note: Remanufactured products available only on exchange for similar defective units.