

Specialty Clamp Meters

Differential Temperature Clamp Meter

NEW!

Includes:

- Carrying case
- Test leads with CAT III/CAT IV safety caps
- Two Type K thermocouples
- 3 x AAA Batteries



- **CL450** HVAC Clamp Meter is an automatically ranging true root mean square (TRMS) digital clamp meter that measures differential temperature via K-Type thermocouple probes; AC current and Inrush current via the clamp; AC/DC voltage, DC Microamps, resistance, continuity, frequency, capacitance, and test diodes via test leads.



2000A Digital Clamp Meter

NEW!

Includes:

- Carrying Case
- Instruction Manual
- Straight Input Test Leads
- 2 x AAA Batteries



- **CL900** is an auto-ranging, true root mean square (TRMS) 2000A digital clamp meter that measures AC/DC current via the clamp and measures AC/DC voltage, resistance, continuity, frequency, duty cycle, capacitance, and tests diodes via test leads. It features a Low Impedance (LoZ) mode for identifying and eliminating ghost or stray voltages, and has a dedicated mode for capturing Inrush Current.



Features	CL450	CL900
Drop Protection	6.6 ft. (2 m)	6.6 ft. (2 m)
Ingress Protection	—	IP40
Safety	CAT IV 600V CAT III 1000V	CAT IV 600V CAT III 1000V
AC Voltage (Volts)	1000V	1000V
DC Voltage (Volts)	1000V	1000V
AC + DC Voltage	•	—
AC Current (Amps)	600A	•
DC Current (Amps)	—	•
Ohms (Resistance)	60MΩ	60MΩ
DC Millivolts	•	—
DC Microamps	•	•
True RMS	•	•
Non-Contact Voltage Testing	•	•
Low-Pass Filter	•	—
Low Impedance	•	•
Inrush Current	•	•
Audible Continuity	•	•
Backlight	•	•
Differential Temperature	-40° – 1832°F (-40° – 1000°C)	—
Digital Temperature Calibration	•	—
Auto Ranging	•	•
Range Hold	•	•
Data Hold	•	•
Diode Test	•	•
Capacitance Test	•	•
Frequency / Duty Cycle	•	•
Max / Min	•	•
Relative Mode	•	—
Auto-Power Off	•	•
LCD Display Count	6000	6000

Cat. No.	Batteries	Jaw Size	Standard	Included	Overall Length	Overall Height	Overall Width	Weight
CL450 NEW!	3 x AAA	1-5/8" (41.3 mm)	CAT IV 600V: CE Certified	Carry Case, Test Leads, 2 Type K Thermocouples, Batteries	10" (250.0 mm)	1-9/16" (39.7 mm)	3-3/4" (95.3 mm)	13.6 oz (386 g)
CL900 NEW!	2 x AAA	2" (50.4 mm)	CAT IV 600V, CAT III 1000V	Carrying Case, Instruction Manual, Straight Input Test Leads, Batteries	10-25/64" (264.2 mm)	1-45/64" (44.1 mm)	3.9" (99.1 mm)	17.6oz (499 g)