

**HARD START KITS**

**Torque Plus—Hard Start Kits**

Totally solid state, our DST 5 is just right for all permanent split capacitor (PSC) compressors from 1/2 to 10 H.P. It can be used on units that operate on 120 through 288 Volts. The DST 6 offers a larger capacitor for severely hard to start compressors. The DST 6 can be used on all PSC single phase compressors from 1 1/2 to 10 H.P. A unique combination of relay and safety timer. The capacitor is automatically disconnected in 0.5 seconds if the compressor fails to start.



CATALOG NO.	DESCRIPTION	UOM	ORDER MULTIPLE
<b>DST-5</b>	Torque Plus – 300% Torque Multiplier	EA	1
<b>DST-6</b>	Torque Plus – 500% Torque Multiplier	EA	1

**DiversiTech Hard Start Kits**

DiversiTech hard start kits reduce contractor call backs by boosting the starting capacitor for a compressor. This prevents home brownouts and improves homeowner satisfaction with your service. DiversiTech's hard start kits feature a potential relay that disconnects the start capacitor from the circuit at exactly the moment it is no longer needed to boost the compressor. This results in a precision compressor start even under hard starting conditions. Replaces the Kickstart KS-1 and the 5-n-1 kit.



CATALOG NO.	DESCRIPTION	UOM	ORDER MULTIPLE
<b>HSK1</b>	Hard Start Kit for 3.5 to 5HP Compressor	EA	1
<b>HSK5</b>	Hard Start Kit for 1 to 3HP Compressor	EA	1

**CONTACTORS**

**Eaton Contactor Accessories**

These auxiliary contacts are side mounted contact kits for Eaton's definite purpose contactors with contact rating of 15A to 75A.



CATALOG NO.	DESCRIPTION	UOM	ORDER MULTIPLE
<b>DPEAUX10</b>	15-75A, 1NO	EA	1
<b>DPEAUX11</b>	15-75A, 1NO-1NC	EA	1
<b>DPEAUX11QC</b>	15-75A, 1NO-1NC with Quick Connect	EA	1
<b>DPEAUX22</b>	25-75A, 2NO-2NC	EA	1

**FAN CENTERS**

**Fan Centers**

The fan centers offer low voltage for one and two speed fan motors; auxiliary circuits in heating cooling, or heating/ cooling applications. This has a DPDT Relay and is UL rated. There are color coded pre stripped leads on this center. This product has a 24V coil voltage, power, and duty rated contacts. It mounts directly to a 4in. electrical box.



CATALOG NO.	VOLTAGE	UOM	ORDER MULTIPLE
<b>D-90113</b>	120	EA	1
<b>D-90118</b>	208/240	EA	1