



YOUR DIRECT SOURCE

for professional 12V electrical and transportation supplies

Free
Shipping
Over \$99

1-2 Day
Delivery

15,000+ Products
in Stock

Efficient
Global
Fulfillment

General Use Wire



!
View the inside catalog cover for Prop 65 Warning.

Special Note

Please specify a color by applying a 2-digit suffix to the part number (corresponding to your color preference):

01 - red	08 - gray
02 - white	09 - purple
03 - blue	10 - orange
04 - green	11 - pink
05 - black	12 - tan
06 - yellow	13 - lt. blue
07 - brown	14 - lt. green

Example: when ordering a 100-ft spool of 20-Ga wire, 11201, in blue please order 1120103.

specification guide

SAE size	conductor stranding	wall mils*	nominal O.D.
20 ga	7/0.0126	0.023"	0.084"
18 ga	16/0.010	0.023"	0.094"
16 ga	19/0.0112	0.023"	0.103"
14 ga	19/0.0140	0.023"	0.117"
12 ga	19/0.0177	0.026"	0.142"
10 ga	19/0.0223	0.031"	0.168"
8 ga	19/0.0281	0.037"	0.208"

* wall mils = insulation thickness

Primary Wire

This single-conductor copper stranded polyvinyl chloride (PVC) insulated primary wire is standard for original equipment and replacement applications. Rated to 60V DC. Meets or exceeds SAE J1128 and RoHS. Please specify color with a 2-digit suffix; see special note box below.

part no.	ga.	reel size	lbs per spool	spool dia.	01 - red	02 - white	03 - blue	04 - green	05 - black	06 - yellow	07 - brown	08 - gray	09 - purple	10 - orange	11 - pink	12 - tan	13 - lt blue	14 - lt green
11201	20	100'	1	3½"	x	x	x	x	x	x	x	x	x	x	x	x	—	—
11205		500'	4	6½"	x	x	x	x	x	x	x	x	x	x	x	x	—	—
11200		1000'	7	6½"	x	x	x	x	x	x	x	x	x	x	x	x	—	—
11208		6000'	41	15½"	x	x	x	x	x	x	x	x	x	x	x	x	—	—
11181	18	100'	1	3½"	x	x	x	x	x	x	x	x	x	x	x	x	x	x
11185		500'	5	10½"	x	x	x	x	x	x	x	x	x	x	x	x	x	x
11180		1000'	7	10½"	x	x	x	x	x	x	x	x	x	x	x	x	x	x
11187		3000'	27	10½"	x	x	x	x	x	x	x	x	x	x	x	x	x	x
11188	16	6000'	58	15½"	x	x	x	x	x	x	x	x	x	x	x	x	x	x
11161		100'	2	3½"	x	x	x	x	x	x	x	x	x	x	x	x	x	x
11165		500'	6	6½"	x	x	x	x	x	x	x	x	x	x	x	x	x	x
11160		1000'	12	6½"	x	x	x	x	x	x	x	x	x	x	x	x	x	x
11167	14	2500'	30	10½"	x	x	x	x	x	x	x	x	x	x	x	x	x	x
11168		5000'	63	15½"	x	x	x	x	x	x	x	x	x	x	x	x	x	x
11141		100'	2	3½"	x	x	x	x	x	x	x	x	x	x	x	x	x	x
11145		500'	9	6½"	x	x	x	x	x	x	x	x	x	x	x	x	x	x
11140	10	1000'	18	10½"	x	x	x	x	x	x	x	x	x	x	x	x	x	x
11147		2000'	32	10½"	x	x	x	x	x	x	x	x	x	x	x	x	x	x
11148		4000'	70	15½"	x	x	x	x	x	x	x	x	x	x	x	x	x	x
11121		100'	3	5"	x	x	x	x	x	x	x	x	x	x	x	—	—	—
11125	12	500'	13	6½"	x	x	x	x	x	x	x	x	x	x	x	—	—	—
11120		1000'	26	10½"	x	x	x	x	x	x	x	x	x	x	x	—	—	—
11127		1500'	38	10½"	x	x	x	x	x	x	x	x	x	x	x	—	—	—
11128		4000'	106	15½"	x	x	x	x	x	x	x	x	x	x	x	—	—	—
11101	10	100'	5	5"	x	x	x	x	x	x	x	x	x	x	x	—	—	—
11105		500'	21	10½"	x	x	x	x	x	x	x	x	x	x	x	—	—	—
11107		1000'	39	10½"	x	x	x	x	x	x	x	x	x	x	x	—	—	—
11108		3000'	124	15½"	x	x	x	x	x	x	x	x	x	x	x	—	—	—
11081	8	100'	7	6½"	x	x	—	x	x	—	—	—	—	x	—	—	—	—
11087		500'	30	10½"	x	x	—	x	x	—	—	—	x	—	—	—	—	—
11088		1000'	66	15½"	x	x	—	x	x	—	—	—	x	—	—	—	—	—



Thrifty Spools

Thrifty spools are standard packages of primary wire in graduated lengths so that each spool has the same value and sells for the same price. Meets or exceeds SAE specification J1128. Rated to 60V DC.

part no.	ga.	length	color	part no.	ga.	length	color
8181	18	45 ft	red	8141	14	25 ft	red
8182			white	8142			white
8183			blue	8143			blue
8184			green	8144			green
8185			black	8145			black
8186			yellow	8146			yellow
8187			brown	8147			brown
8161	16	35 ft	red	8121DL	12	15 ft	red
8162			white	8125			black
8163			blue	8101	10	10 ft	red
8164			green	8105			black
8165			black				
8166			yellow				
8167			brown				