

# Honeywell Thermostat Wire

As the world's leading thermostat manufacturer, Honeywell knows about home comfort systems. Although it's hidden behind the walls, the thermostat wire is a key component of heating and cooling systems. The quality of the wire can impact performance. As systems continue to get more intelligent, quality wire becomes a more important factor.



## Quality:

Honeywell thermostat wire, like all Honeywell products, is manufactured to the highest quality standards and is recommended for use with all thermostats, ensuring optimal system performance.

## Commitment:

If any Honeywell thermostat wire fails to perform to our specification during the life of any original installation, we will replace the cable, three for one. No one else in the industry makes that guarantee.

## Features:

- Full range of thermostat and electronic low voltage wire
- Polypropylene insulation provides exceptional dielectric and strips easily and cleanly, saving time
- Available for General Purpose (CL2) or Plenum (CL2P) Applications
- Ripcord for quick jacket removal
- Room and zone markings printed right on jacket
- Packaging options: Spools, Speedbags™ and Pull Boxes
- Manufactured in ISO 9001:2000 facility to exacting quality standards
- 100% guaranteed


# Thermostat Cable, Plenum Rated

**Applications:** Wiring of Thermostat Controls, Heating and Air Conditioning Equipment, Doorbells, as well as other Low Voltage Applications. Sunlight Resistant.

**Code Restrictions:** OK for use with all Power-Limited Circuits except those in Risers and Plenums.

**Features:** Available in 250 foot or 500 foot spools. Sequential Footage Markings.

**Construction:** Copper Conductors, Polypropylene Insulation, Polyvinyl-Chloride Jacket. Standard Jacket Color: Brown or White. Conductor Color Code Chart 6 (up to 12 conductors)



## THERMOSTAT CABLE 60° C

AWG	#/COND.	PACKAGING	SOL	NOM. O.D.	NOM. CAP. PF/FT	LISTINGS	AVG. WT. PER MFT	PART#
20	2	4 x 500 S	SOL	.118	22	CL2	11	<b>4701</b>
20	3	4 x 500 S	SOL	.124	22	CL2	14	<b>4702</b>
20	4	4 x 250 S	SOL	.136	22	CL2	17	<b>4703</b>
20	5	4 x 250 S	SOL	.148	22	CL2	20	<b>4704</b>
20	6	4 x 250 S	SOL	.161	22	CL2	23	<b>4705</b>
20	7	4 x 250 S	SOL	.161	22	CL2	26	<b>4706</b>
20	8	4 x 250 S	SOL	.174	22	CL2	30	<b>4707</b>
20	9	4 x 250 S or 1 x 500 S	SOL	.188	22	CL2	33	<b>4708</b> •
20	10	4 x 250 S or 1 x 500 S	SOL	.204	22	CL2	36	<b>4709</b> •
18	2	4 x 500 S	SOL	.136	25	CL2	16	<b>4710</b>
18	3	4 x 500 S	SOL	.144	25	CL2	22	<b>4711</b>
18	4	4 x 250 S	SOL	.157	25	CL2	27	<b>4712</b>
18	5	4 x 250 S	SOL	.172	25	CL2	33	<b>4713</b>
18	6	4 x 250 S or 1 x 500 S or B	SOL	.188	25	CL2	38	<b>4714</b>
18	7	4 x 250 S or 1 x 500 S or B	SOL	.188	25	CL2	44	<b>4715</b>
18	8	4 x 250 S or 1 x 500 S or B	SOL	.204	25	CL2	50	<b>4716</b>
18	9	4 x 250 S or 1 x 500 S or B	SOL	.220	25	CL2	55	<b>4717</b>
18	10	4 x 250 S or 1 x 500 S or B	SOL	.240	25	CL2	60	<b>4718</b>
18	12	1 x 250 S or 1 x 500 S or B	SOL	.248	25	CL2	71	<b>4719</b>

S: Spools

B: Boxes

• Consult factory for availability.


# Thermostat Cable

**Applications:** Wiring of Thermostat Controls, Heating and Air Conditioning Equipment, Doorbells, as well as other Low Voltage Applications.

**Code Restrictions:** OK for use with all Power-Limited Circuits.

**Features:** Available in 250 foot or 500 foot spools. Sequential Footage Markings.

**Construction:** Copper Conductors, Low Smoke PVC, Low Smoke PVC Jacket. Standard Jacket Color: Natural. Conductor Color Code Chart 6 (up to 12 conductors).



ARTICLE 725

## THERMOSTAT CABLE, PLENUM RATED

AWG	#/COND.	PACKAGING	SOL	NOM. O.D.	NOM. CAP. PF/FT	LISTINGS	AVG. WT. PER MFT	PART#
18	2	4 x 500 S	SOL	.136	39	CL2P	17	<b>4760</b>
18	3	4 x 500 S	SOL	.144	39	CL2P	23	<b>4761</b>
18	4	4 x 250 S	SOL	.157	39	CL2P	29	<b>4762</b>
18	5	4 x 250 S	SOL	.172	39	CL2P	35	<b>4763</b>
18	6	4 x 250 S or 1 x 500 S or B	SOL	.188	39	CL2P	42	<b>4764</b>
18	7	4 x 250 S or 1 x 500 S or B	SOL	.188	39	CL2P	47	<b>4765</b> •
18	8	4 x 250 S or 1 x 500 S or B	SOL	.204	39	CL2P	54	<b>4766</b>
18	9	4 x 250 S or 1 x 500 S or B	SOL	.220	39	CL2P	60	<b>4767</b> •
18	10	1 x 250 S or 1 x 500 S or B	SOL	.240	39	CL2P	67	<b>4768</b>
18	12	4 x 250 S or 1 x 500 S or B	SOL	.248	39	CL2P	79	<b>4769</b>

S: Spools

B: Boxes

• Consult factory for availability.

