



**WIRING DEVICES cont'd**

**Vinyl Grommet Assortment Packs**

These grommets exhibit high dielectric strength and are oil, ozone, and UV resistant.



CATALOG NO.	DESCRIPTION	UOM	ORDER MULTIPLE
<b>ED320</b>	General Assortment – contains all grommet sizes	EA	1

**Heat Shrink Tubing Assortments\***

Heat Shrink Tubing is made of flame-retardant polyolefin. Thin walled, all purpose tubing. Rated 600V, 125°C. 2500 volts/mil. dielectric strength. Inert to fungus. Virtually unaffected by corrosives, common fluids, and solvents. Pieces are 6" in length.



CATALOG NO.	COLOR	INNER DIAMETER MAX SUPPLIED	MIN. RECOVERED	UOM	ORDER MULTIPLE
<b>6370</b>	Black & White, pack of 12	1/8", 1/4"	1/16", 1/8"	PK	1
<b>6371</b>	Black & White, pack of 7	1/8", 1/4", 3/8"	1/16", 1/8", 3/16"	PK	1
<b>63070</b>	Black, pack of 3	3/8" – 1/2"	3/16" – 1/4"	PK	1

**Indicator Lights**

Terminals are tin plated brass. Wire leads are 22 AWG, 4.4"–4.8" long, 1/2" stripped. Mounting will snap-fit into .500-.505 diameter hole in .020"-.100" thick panels.



CATALOG NO.	LENS COLOR	LENS MATERIAL	VOLTAGE	BULB TYPE	UOM	ORDER MULTIPLE
<b>ED600</b>	Red, pack of 2	Polycarbonate	28V	Incandescent	PK	1
<b>ED601</b>	Green, pack of 2	Polycarbonate	28V	Incandescent	PK	1
<b>ED602</b>	Amber, pack of 2	Polycarbonate	28V	Incandescent	PK	1
<b>ED603</b>	Blue, pack of 2	Polycarbonate	28V	Incandescent	PK	1
<b>ED610</b>	Red, pack of 2	Nylon	105–125V AC	Neon	PK	1
<b>ED611</b>	Green, pack of 2	Polycarbonate	105–125V AC	Neon**	PK	1
<b>ED612</b>	Amber, pack of 2	Nylon	105–125V AC	Neon	PK	1
<b>ED613</b>	Blue, pack of 2	Polycarbonate	105–125V AC	Neon†	PK	1
<b>ED620</b>	Red, pack of 2	Polycarbonate	208–250V AC	Neon	PK	1
<b>ED621</b>	Green, pack of 2	Polycarbonate	208–250V AC	Neon**	PK	1

**6190 Series Terminal Blocks\***

These terminal blocks are constructed of phenolic 9/16 in. centers. They are rated 30A 600V.



CATALOG NO.	DESCRIPTION	NO. OF POSITIONS	LENGTH (in.)	WIDTH (in.)	SCREW SIZE	MAX. WIRE SIZE	UOM	ORDER MULTIPLE
<b>6193</b>	Terminal Block	6	4.34	1.31	8-32	14-12	EA	1
<b>6194</b>	Terminal Block	8	5.47	1.31	8-32	14-12	EA	1
<b>6195X</b>	Terminal Block	10	6.59	1.31	8-32	14-12	EA	1

**Indicator Lights\***

Terminals are tin plated brass. Wire leads are 22 AWG, 4.4"–4.8" long, 1/2" stripped. .31" minimum diameter mounting.



CATALOG NO.	LENS COLOR	LENS MATERIAL	VOLTAGE	BULB TYPE	UOM	ORDER MULTIPLE
<b>ED710</b>	Red, pack of 2	Polycarbonate	105–125V AC	Neon	PK	1

**Winged Wire Connectors\***

Durable thermoplastic material. Flame retardant, abrasion resistant, non porous, and non corrosive. Expandable spring grips into the wire and adjusts itself to the wire size and shape so pre twisting is unnecessary. Even during temperature changes, they resist vibrations and retain holding power. Parts 8284 and 8286 are for use with copper to copper, aluminum to aluminum, and copper to aluminum (dry locations only).



CATALOG NO.	DESCRIPTION	UOM	ORDER MULTIPLE
<b>8284</b>	Small Yellow Winged Wire Connectors, pack of 18	PK	1
<b>8284CX-B</b>	Small Yellow Winged Wire Connectors, pack of 100	PK	1
<b>8286</b>	Medium Red Winged Wire Connectors, pack of 14	PK	1
<b>8286CX-B</b>	Medium Red Winged Wire Connectors, pack of 100	PK	1
<b>8282LX</b>	X-Large Blue Winged Wire Connectors, pack of 50	PK	1

-B indicates boxed product. All other catalog numbers are poly bagged.

\*Items in this section are Underwriter's Laboratories listed or recognized under the prime manufacturer's name.