



**XTRAFLEX Liquidtight Conduit Tubing & Fittings**  
**T&B Catalog Number:**

**UPC Number:** EFC050  
**Status:** 78621078961  
**Description:** Active

1/2 in. black corrugated PVC flexible tubing.

**Features**

- Maximum flexibility in tight applications.
- Extremely fast installation
- Liquidtight with specified fittings.
- Good tensile strength provides excellent pullout protection and smooth inner diameter allows easy wire pulling.

**Application**

Protection of fiber optic cable, installation of instrumentation and control cable, indoor and outdoor lighting, packaging equipment, marine and ship-board wiring, and flexing-component wiring protection on robots, graphic arts equipments, etc.

**General**

Material	PVC
Color	Black
Working Temperatures	-18 C to +60 C

**Dimension Information**

Size (inches)	1/2
I.D. - Minimum (inches)	0.622
I.D. - Maximum (inches)	0.642
O.D. - Minimum (inches)	0.82
O.D. - Maximum (inches)	0.84

**Packaging**

T&B Order Multiple	100
Package in Units	100
T&B Sold in UOM	Feet
T&B Weight Per UOM	10.3 lbs. per 100

**Application Support**

Guide to Nonmetallic Conduit Applications	Available on Website
XTRAFLEX System Specifications	Available on Website

**Certifications**

RoHS Compliance	Yes
-----------------	-----

**Certifications**



File Nbr:  
 E 96548



**For further technical assistance, please contact us...**

Thomas & Betts - USA  
8155 T&B Blvd.  
Memphis, TN 38125  
[www.tnb.com](http://www.tnb.com)

T&B Technical Support  
MS 3B-50  
8155 T&B Blvd.  
Memphis, TN 38125

Hours: 7AM - 6PM CDT  
Monday-Friday  
Phone: (888) 862-3289  
Fax: (901) 252-1321  
Email: [techsupport@tnb.com](mailto:techsupport@tnb.com)