



44 Electrical Tape

Polyester Web-Reinforced Film with Thermosetting Rubber, Pressure-Sensitive Adhesive

Data Sheet

- Puncture resistant
- Excellent electrical properties
- UL recognized
- Class B (130°C)
- Conformable

3M™ Electrical Tape 44 is a combination polyester film/polyester web coated with a rubber thermosetting pressure-sensitive adhesive. For maximum solvent resistance and holding properties, the tape should be thermoset at one of the following cycles:

- 1 hour @ 150°C (300°F)
- 2 hours @ 135°C (275°F)
- 3 hours @ 120°C (250°F)

The tape is suggested for use in stick-wound coils/transformers and in bobbin-wound coils for banding, anchoring, and insulating, and for protecting start wires, leads, terminal strips, insulation paper, end turns and connections in motors and transformers.

UL Component Recognition

- Temperatures not exceeding 130°C

UL File Number E17385 A and B, Guide OANZ2. Underwriters Laboratories (UL) recognized products have been evaluated for use as components of end-product equipment that is listed or classified by UL. To achieve Underwriters Laboratories recognition, component construction must meet UL specifications and conditions of acceptability for proper and safe use of the component or product.

Properties	Typical Values*
Thickness	5.5 mils (0.139 mm)
Breaking Strength ¹	40 lbs./in (70 N/10 mm)
Elongation ¹	50%
Adhesion to Steel ¹	65 oz/in (7.1 N/10 mm)
Puncture Resistance ³	12 lbs. (5.4 kg)
Dielectric Strength ¹	5500V
Temperature Class	130°C
Insulation Resistance	>1x10 ⁶ megohms
Electrolytic Corrosion Factor ²	1.0
CTI Material Group	I

*Not recommended for specification purposes. Product specifications will be provided upon request.

Test methods: ¹ ASTM D-1000
² 3M Test Method
³ Federal Spec. L-T-001512

Important Notice

Technical information provided by 3M is based on experience and/or tests believed to be reliable, but their accuracy is not guaranteed and the results may not be relevant to every user's application. For this reason 3M does not accept responsibility or liability, direct or consequential, arising from reliance upon any information provided and the user should determine the suitability of the products for their intended use. Nothing in this statement will be deemed to exclude or restrict 3M's liability for death or personal injury arising from its negligence. All questions of liability relating to 3M products are governed by the seller's terms of sale subject where applicable to the prevailing law

If any goods supplied or processed by or on behalf of 3M prove on inspection to be defective in material or workmanship, 3M will (at its option) replace the same or refund to the Buyer the price paid for the goods or services. Except as set out above, all warranties and conditions, whether express or implied, statutory or otherwise are excluded to the fullest extent permissible at law.

3M and Scotchcast are trademarks of the 3M Company. Printed in the UK.

© 3M United Kingdom PLC, 1999

3M United Kingdom PLC
Electrical Products Group
Hudson Road
Bedford MK41 0HR
Tel: 01234 268868
Fax: 01234 229433

3M Ireland
Electrical products Group
3M House, Adelphi Centre
Dun Loaghair, CO. Dublin, Ireland
Tel: (01) 2803555
Fax: (01) 2803509

3M Innovation

Jan. 2000