



EXTROL[®] PRO

Hydronic Expansion: EX-PRO Series

125 PSIG Working Pressure

Construction

Shell	Steel
Diaphragm	Heavy Duty Butyl/EPDM
System Connection	Stainless Steel
Liner	Polypropylene Oxygen Barrier
Finish	Urethane Topcoat
Air Valve	Projection Welded with InSight [®] Indicator Cap (2 to 6.7 gal.)
Factory Precharge	15 PSIG (1.03 bar)

Performance


Maximum Operating Temperature	200°F (93°C)
Maximum Working Pressure	125 PSIG (6.9 bar)
Warranty	7-Years

Application

- For use in closed, non-potable, hydronic heating and chilled water systems.
- Accepts expanded water as system temperature rises to reduce pressure build-up.
- Helps reduce energy consumption and system maintenance.
- Plastic liner & stainless steel connection protect against corrosion.
- Suitable for propylene glycol applications with mixtures up to 50%.
- 2 through 6.7 gallon models feature patent-pending In-Sight[®] Indicator Cap that changes color to indicate tank service is required.

EXTROL PRO In-Line Models

Model Number	Tank Volume		Max. Acceptance Factor	A Tank Diameter		B Tank Height		System Connection (NPTM)	Shipping Weight	
	Gal	Lit		In	mm	In	mm		Lbs	Kg
EX-15PRO	2.0	8	.50	8	203	13	330	½	5	2.3
EX-30PRO	4.4	17	.57	11	279	15	406	½	9	4.1
EX-60PRO	6.7	25	.40	11	279	20	508	½	13	5.9



All dimensions and weights are approximate.

Job Name _____	Notes _____
Engineer _____	_____
Contractor _____	_____
P.O. No. _____	_____
Sales Rep. _____	_____
Model No. _____	_____

