

Bluetooth[®] ABM-100 AIRFLOW METER

The ABM-100 easily plugs into a smart device and instantly converts air speed into air volume and records the data.

Accurately measures airflow in: Linear feet per minute, cubic feet per minute, cubic meters per hour, linear meters per second

- · Portable, fits in your pocket
- Easy to use no math or formulas to remember
- Automatically generates and emails detailed reports
- 2.5" H x 1.75" W x .75" D
- Plastic storage case with color sleeve



Bluetooth[®]

ABM-200 AIRFLOW AND ENVIRONMENTAL METER

Measures and records a variety of data, including: Airflow velocity, airflow volume, dry bulb temperature, wet bulb temperature, relative humidity, feels like temperature, dew point, air density, wind speed/direction/gusts, indoor vs. outdoor conditions and barometric pressure.

- · On-screen guidance ensures accurate readings
- Rugged housing with 1/4" 20 mount fitting for hands-free use
- Attach to the EXP-64 a 64" aluminum extension pole (sold separately) to take readings without using a ladder
- Connects over 20X faster than traditional Bluetooth
- Emails personalized, professional reports
- 3.3" H x 1.8" W x 0.6" D
- Plastic storage case with color sleeve







Take accurate airflow readings without using a ladder. Mount an ABM-200 or TS-100 to the 1/4"-20 universal threaded end to obtain fast, easy readings from vents mounted on ceilings, high walls or other hard to reach places. The EXP-64 has a rubber grip handle and telescopes from 18" to 64". It has a second 1/4"-20" threaded fitting on the handle end to allow the EXP-64 to be mounted on a floor tripod.



Attach the ABM-200, or TS-100 to the end of the EXP-64, to access hard-toreach areas.

Thumbwheel for attaching/ removing threaded universal end

e EXP-64 can be mount-



TRI-MIN MINI-TRIPOD

This mini tripod has a 1/4"-20 top fitting to attach the TS-100 or ABM-200. It adjusts from 6-8" in height and is collapsible for compact storage.

Makes extended environmental condition readings easy.

