

FFAM-A08Z-CFV-072

HFO, R-448A, 60Hz, 1-Phase, 208/230V

Availability: Custom US OEM Or Wholesaler

Mechanical		Electrical	
Unit Height (in):	16.5	Max Fuse Size:	15
Unit Length (in):	24.1	Min Circuit Ampacity:	8.5
Unit Width (in):	18.3	Compressor:	ZB06KAE-PFV-118
Ship Weight (lbs):	103.0	Compressor LRA - Low:	
Condenser Type:	Air	Compressor LRA - High:	35.7
CopeVap Water Storage:	NA	Compressor LRA - Half winding:	
Liquid Connection Size (in)/Type:	0.375 SWEAT	Compressor RLA	6.0
Suction Connection Size (in)/Type:	0.875 SWEAT	UL:	Listed
Discharge Line Size(in):	0.5	UL File #:	SA633
Water Inlet (in):		UL Guide Card:	LZFE
Water Outlet (in):			
Oil Type:	POE	Amps Per Motor:	
Oil Recharge Amount (oz):	25	Fan Motor Quantity:	1

Performance

Release Date:	16-Jun-2022	Return Gas Temp. (°F):	40
Compressor:	ZB06KAE-PFV-118 x 1	Subcooling (°F):	5
Performance No:	38459	Air Flow Rate (CFM):	696

90 °F Ambient Air Temperature

Evap Temp(°F)	Unit Capacity (BTU/hr)	Cond. Temp.(°F)	Temp. Diff.(°F)	EER(BTU/wh)
-5	3,670	104.8	14.8	4.7
0	4,130	105.7	15.7	5.1
5	4,620	106.6	16.6	5.5

10	5,160	107.6	17.6	6.0
15	5,740	108.6	18.6	6.5
20	6,370	109.7	19.7	7.0
25	7,060	111.0	21.0	7.6