

FFAM-A08Z-TFC-072

HFC, R-404A, 60Hz, 3-Phase, 208/230V

Availability: Custom US OEM Or Wholesaler

Mechanical		Electrical	
Unit Height (in):	16.5	Max Fuse Size:	15
Unit Length (in):	24.1	Min Circuit Ampacity:	7.0
Unit Width (in):	18.3	Compressor:	ZB06KAE-TF5-118
Ship Weight (lbs):	140.0	Compressor LRA - Low:	
Condenser Type:	Air	Compressor LRA - High:	37.8
CopeVap Water Storage:	NA	Compressor LRA - Half winding:	
Liquid Connection Size (in)/Type:	0.375 SWEAT	Compressor RLA	4.8
Suction Connection Size (in)/Type:	0.875 SWEAT	UL:	Listed
Discharge Line Size(in):	0.5	UL File #:	SA633
Water Inlet (in):		UL Guide Card:	LZFE
Water Outlet (in):			
Oil Type:	POE	Amps Per Motor:	
Oil Recharge Amount (oz):	25	Fan Motor Quantity:	1

Performance

Release Date:	16-Jun-2022	Return Gas Temp. (°F):	40
Compressor:	ZB06KAE-TF5-118 x 1	Subcooling (°F):	5
Performance No:	38481	Air Flow Rate (CFM):	696

90 °F Ambient Air Temperature

Evap Temp(°F)	Unit Capacity (BTU/hr)	Cond. Temp.(°F)	Temp. Diff.(°F)	EER(BTU/wh)
-5	4,150	99.8	9.8	5.3
0	4,610	100.7	10.7	5.6
5	5,100	101.6	11.6	6.1

10	5,640	102.6	12.6	6.5
15	6,210	103.7	13.7	7.0
20	6,830	104.9	14.9	7.6
25	7,490	106.1	16.1	8.2