

FFAM-A10Z-CFV-072

HFC, R-404A, 60Hz, 1-Phase, 208/230V

Availability: Custom US OEM Or Wholesaler

Mechanical		Electrical	
Unit Height (in):	16.5	Max Fuse Size:	15
Unit Length (in):	24.1	Min Circuit Ampacity:	8.9
Unit Width (in):	18.3	Compressor:	ZB07KAE-PFV-118
Ship Weight (lbs):	106.0	Compressor LRA - Low:	
Condenser Type:	Air	Compressor LRA - High:	48.0
CopeVap Water Storage:	NA	Compressor LRA - Half winding:	
Liquid Connection Size (in)/Type:	0.375 SWEAT	Compressor RLA	6.3
Suction Connection Size (in)/Type:	0.875 SWEAT	UL:	Listed
Discharge Line Size(in):	0.5	UL File #:	SA633
Water Inlet (in):		UL Guide Card:	LZFE
Water Outlet (in):			
Oil Type:	POE	Amps Per Motor:	
Oil Recharge Amount (oz):	25	Fan Motor Quantity:	1

Performance

Release Date:	16-Jun-2022	Return Gas Temp. (°F):	40
Compressor:	ZB07KAE-PFV-118 x 1	Subcooling (°F):	5
Performance No:	38513	Air Flow Rate (CFM):	696

90 °F Ambient Air Temperature

Evap Temp(°F)	Unit Capacity (BTU/hr)	Cond. Temp.(°F)	Temp. Diff.(°F)	EER(BTU/wh)
-5	4,900	101.6	11.6	5.1
0	5,440	102.6	12.6	5.5
5	6,010	103.8	13.8	5.9

10	6,630	105.0	15.0	6.3
15	7,300	106.2	16.2	6.8
20	8,010	107.6	17.6	7.3
25	8,760	109.0	19.0	7.8