

# FFAM-A10Z-CFV-072

HFC , R-407A, 60Hz, 1-Phase, 208/230V

Availability: Custom US OEM Or Wholesaler

Mechanical		Electrical	
Unit Height (in):	16.5	Max Fuse Size:	15
Unit Length (in):	24.1	Min Circuit Ampacity:	8.9
Unit Width (in):	18.3	Compressor:	ZB07KAE-PFV-118
Ship Weight (lbs):	106.0	Compressor LRA - Low:	
Condenser Type:	Air	Compressor LRA - High:	48.0
CopeVap Water Storage:	NA	Compressor LRA - Half winding:	
Liquid Connection Size (in)/Type:	0.375 SWEAT	Compressor RLA	6.3
Suction Connection Size (in)/Type:	0.875 SWEAT	UL:	Listed
Discharge Line Size(in):	0.5	UL File #:	SA633
Water Inlet (in):		UL Guide Card:	LZFE
Water Outlet (in):			
Oil Type:	POE	Amps Per Motor:	
Oil Recharge Amount (oz):	25	Fan Motor Quantity:	1

## Performance

Release Date:	16-Jun-2022	Return Gas Temp. (°F):	40
Compressor:	ZB07KAE-PFV-118 x 1	Subcooling (°F):	5
Performance No:	38515	Air Flow Rate (CFM):	696

## 90 °F Ambient Air Temperature

Evap Temp(°F)	Unit Capacity (BTU/hr)	Cond. Temp.(°F)	Temp. Diff.(°F)	EER(BTU/wh)
-5	4,290	104.4	14.4	4.8
0	4,810	105.4	15.4	5.1
5	5,390	106.4	16.4	5.6

10	6,030	107.6	17.6	6.0
15	6,710	108.8	18.8	6.5
20	7,460	110.1	20.1	7.1
25	8,260	111.6	21.6	7.7