

FFAM-A10Z-TFC-072

HFC, R-134a, 60Hz, 3-Phase, 208/230V

Availability: Custom US OEM Or Wholesaler

Mechanical		Electrical	
Unit Height (in):	16.5	Max Fuse Size:	15
Unit Length (in):	24.1	Min Circuit Ampacity:	7.5
Unit Width (in):	18.3	Compressor:	ZB07KAE-TF5-118
Ship Weight (lbs):	140.0	Compressor LRA - Low:	
Condenser Type:	Air	Compressor LRA - High:	37.8
CopeVap Water Storage:	NA	Compressor LRA - Half winding:	
Liquid Connection Size (in)/Type:	0.375 SWEAT	Compressor RLA	5.2
Suction Connection Size (in)/Type:	0.875 SWEAT	UL:	Listed
Discharge Line Size(in):	0.5	UL File #:	SA633
Water Inlet (in):		UL Guide Card:	LZFE
Water Outlet (in):		Amps Per Motor:	
Oil Type:	POE	Fan Motor Quantity:	1
Oil Recharge Amount (oz):	25		

Performance

Release Date:	16-Jun-2022	Return Gas Temp. (°F):	40
Compressor:	ZB07KAE-TF5-118 x 1	Subcooling (°F):	5
Performance No:	38539	Air Flow Rate (CFM):	696

90 °F Ambient Air Temperature

Evap Temp(°F)	Unit Capacity (BTU/hr)	Cond. Temp.(°F)	Temp. Diff.(°F)	EER(BTU/wh)
-5	2,720	96.3	6.3	4.9
0	3,070	97.1	7.1	5.4
5	3,470	97.9	7.9	5.9

10	3,910	98.9	8.9	6.4
15	4,390	99.9	9.9	7.1
20	4,930	101.0	11.0	7.8
25	5,520	102.2	12.2	8.5