

# FFAM-A10Z-TFC-072

HFC , R-407A, 60Hz, 3-Phase, 208/230V

Availability: Custom US OEM Or Wholesaler

Mechanical		Electrical	
Unit Height (in):	16.5	Max Fuse Size:	15
Unit Length (in):	24.1	Min Circuit Ampacity:	7.5
Unit Width (in):	18.3	Compressor:	ZB07KAE-TF5-118
Ship Weight (lbs):	140.0	Compressor LRA - Low:	
Condenser Type:	Air	Compressor LRA - High:	37.8
CopeVap Water Storage:	NA	Compressor LRA - Half winding:	
Liquid Connection Size (in)/Type:	0.375 SWEAT	Compressor RLA	5.2
Suction Connection Size (in)/Type:	0.875 SWEAT	UL:	Listed
Discharge Line Size(in):	0.5	UL File #:	SA633
Water Inlet (in):		UL Guide Card:	LZFE
Water Outlet (in):			
Oil Type:	POE	Amps Per Motor:	
Oil Recharge Amount (oz):	25	Fan Motor Quantity:	1

## Performance

Release Date:	16-Jun-2022	Return Gas Temp. (°F):	40
Compressor:	ZB07KAE-TF5-118 x 1	Subcooling (°F):	5
Performance No:	38543	Air Flow Rate (CFM):	696

## 90 °F Ambient Air Temperature

Evap Temp(°F)	Unit Capacity (BTU/hr)	Cond. Temp.(°F)	Temp. Diff.(°F)	EER(BTU/wh)
-5	4,290	104.3	14.3	4.8
0	4,820	105.3	15.3	5.2
5	5,400	106.4	16.4	5.7

10	6,030	107.5	17.5	6.1
15	6,720	108.8	18.8	6.7
20	7,460	110.1	20.1	7.2
25	8,270	111.5	21.5	7.8