

**FFAM-A10Z-TFC-072**

HFO, R-448A, 60Hz, 3-Phase, 208/230V

Availability: Custom US OEM Or Wholesaler

Mechanical		Electrical	
Unit Height (in):	16.5	Max Fuse Size:	15
Unit Length (in):	24.1	Min Circuit Ampacity:	7.5
Unit Width (in):	18.3	Compressor:	ZB07KAE-TF5-118
Ship Weight (lbs):	140.0	Compressor LRA - Low:	
Condenser Type:	Air	Compressor LRA - High:	37.8
CopeVap Water Storage:	NA	Compressor LRA - Half winding:	
Liquid Connection Size (in)/Type:	0.375 SWEAT	Compressor RLA	5.2
Suction Connection Size (in)/Type:	0.875 SWEAT	UL:	Listed
Discharge Line Size(in):	0.5	UL File #:	SA633
Water Inlet (in):		UL Guide Card:	LZFE
Water Outlet (in):			
Oil Type:	POE	Amps Per Motor:	
Oil Recharge Amount (oz):	25	Fan Motor Quantity:	1

**Performance**

Release Date:	16-Jun-2022	Return Gas Temp. (°F):	40
Compressor:	ZB07KAE-TF5-118 x 1	Subcooling (°F):	5
Performance No:	38547	Air Flow Rate (CFM):	696

**90 °F Ambient Air Temperature**

Evap Temp(°F)	Unit Capacity (BTU/hr)	Cond. Temp.(°F)	Temp. Diff.(°F)	EER(BTU/wh)
-5	4,360	106.4	16.4	4.7
0	4,900	107.4	17.4	5.1
5	5,480	108.5	18.5	5.5

10	6,110	109.6	19.6	6.0
15	6,790	110.9	20.9	6.5
20	7,530	112.2	22.2	7.0
25	8,320	113.6	23.6	7.5