

FFAM-A12Z-TFC-072

HFC, R-507, 60Hz, 3-Phase, 208/230V

Availability: Custom US OEM Or Wholesaler

Mechanical		Electrical	
Unit Height (in):	16.5	Max Fuse Size:	15
Unit Length (in):	24.1	Min Circuit Ampacity:	8.0
Unit Width (in):	18.3	Compressor:	ZB08KAE-TF5-118
Ship Weight (lbs):	104.0	Compressor LRA - Low:	
Condenser Type:	Air	Compressor LRA - High:	37.8
CopeVap Water Storage:	NA	Compressor LRA - Half winding:	
Liquid Connection Size (in)/Type:	0.375 SWEAT	Compressor RLA	5.3
Suction Connection Size (in)/Type:	0.875 SWEAT	UL:	Listed
Discharge Line Size(in):	0.5	UL File #:	SA633
Water Inlet (in):		UL Guide Card:	LZFE
Water Outlet (in):			
Oil Type:	POE	Amps Per Motor:	1.1
Oil Recharge Amount (oz):	25	Fan Motor Quantity:	1

Performance

Release Date:	16-Jun-2022	Return Gas Temp. (°F):	40
Compressor:	ZB08KAE-TF5-118 x 1	Subcooling (°F):	5
Performance No:	38611	Air Flow Rate (CFM):	1070

90 °F Ambient Air Temperature

Evap Temp(°F)	Unit Capacity (BTU/hr)	Cond. Temp.(°F)	Temp. Diff.(°F)	EER(BTU/wh)
-5	6,050	99.8	9.8	5.1
0	6,710	100.7	10.7	5.5
5	7,410	101.8	11.8	5.9

10	8,170	102.9	12.9	6.4
15	8,990	104.0	14.0	6.8
20	9,860	105.3	15.3	7.3
25	10,800	106.6	16.6	7.9