

**FFAP-060Z-TFC-071**

HCFC, R-22, 60Hz, 3-Phase, 208/230V

Availability: Custom US OEM Or Wholesaler

Mechanical		Electrical	
Unit Height (in):	26.6	Max Fuse Size:	50
Unit Length (in):	44.1	Min Circuit Ampacity:	33.4
Unit Width (in):	28.3	Compressor:	ZS45K4E-TF5-250
Ship Weight (lbs):	320.0	Compressor LRA - Low:	
Condenser Type:	Air	Compressor LRA - High:	156.0
CopeVap Water Storage:	NA	Compressor LRA - Half winding:	
Liquid Connection Size (in)/Type:	0.5 SWEAT	Compressor RLA	20
Suction Connection Size (in)/Type:	1.125 SWEAT	UL:	Listed
Discharge Line Size(in):	0.5	UL File #:	SA633
Water Inlet (in):		UL Guide Card:	LZFE
Water Outlet (in):			
Oil Type:	POE	Amps Per Motor:	
Oil Recharge Amount (oz):	64	Fan Motor Quantity:	2

**Performance**

Release Date:	21-Jun-2022	Return Gas Temp. (°F):	40
Compressor:	ZS45K4E-TF5-250 x 1	Subcooling (°F):	5
Performance No:	41305	Air Flow Rate (CFM):	4240

**90 °F Ambient Air Temperature**

Evap Temp(°F)	Unit Capacity (BTU/hr)	Cond. Temp.(°F)	Temp. Diff.(°F)	EER(BTU/wh)
15	42,100	113.4	23.4	7.3
20	46,300	115.4	25.4	7.7
25	50,500	117.5	27.5	8.0