

**FFAP-060Z-TFC-071**

HFC, R-404A, 60Hz, 3-Phase, 208/230V

Availability: Custom US OEM Or Wholesaler

Mechanical		Electrical	
Unit Height (in):	26.6	Max Fuse Size:	50
Unit Length (in):	44.1	Min Circuit Ampacity:	33.4
Unit Width (in):	28.3	Compressor:	ZS45K4E-TF5-250
Ship Weight (lbs):	320.0	Compressor LRA - Low:	
Condenser Type:	Air	Compressor LRA - High:	156.0
CopeVap Water Storage:	NA	Compressor LRA - Half winding:	
Liquid Connection Size (in)/Type:	0.5 SWEAT	Compressor RLA	23.9
Suction Connection Size (in)/Type:	1.125 SWEAT	UL:	Listed
Discharge Line Size(in):	0.5	UL File #:	SA633
Water Inlet (in):		UL Guide Card:	LZFE
Water Outlet (in):			
Oil Type:	POE	Amps Per Motor:	
Oil Recharge Amount (oz):	64	Fan Motor Quantity:	2

**Performance**

Release Date:	21-Jun-2022	Return Gas Temp. (°F):	40
Compressor:	ZS45K4E-TF5-250 x 1	Subcooling (°F):	5
Performance No:	41308	Air Flow Rate (CFM):	4240

**90 °F Ambient Air Temperature**

Evap Temp(°F)	Unit Capacity (BTU/hr)	Cond. Temp.(°F)	Temp. Diff.(°F)	EER(BTU/wh)
-25	19,600	101.9	11.9	4.1
-20	22,000	103.0	13.0	4.4
-15	24,500	104.1	14.1	4.7

-10	27,200	105.4	15.4	5.0
-5	30,100	106.7	16.7	5.3
0	33,100	108.1	18.1	5.6
5	36,400	109.6	19.6	5.9
10	39,700	111.2	21.2	6.3
15	43,300	112.8	22.8	6.6
20	47,100	114.5	24.5	6.9
25	51,000	116.3	26.3	7.3