

**FFAP-060Z-TFC-071**

HFC , R-407A, 60Hz, 3-Phase, 208/230V

Availability: Custom US OEM Or Wholesaler

Mechanical		Electrical	
Unit Height (in):	26.6	Max Fuse Size:	50
Unit Length (in):	44.1	Min Circuit Ampacity:	33.4
Unit Width (in):	28.3	Compressor:	ZS45K4E-TF5-250
Ship Weight (lbs):	320.0	Compressor LRA - Low:	
Condenser Type:	Air	Compressor LRA - High:	156.0
CopeVap Water Storage:	NA	Compressor LRA - Half winding:	
Liquid Connection Size (in)/Type:	0.5 SWEAT	Compressor RLA	22.8
Suction Connection Size (in)/Type:	1.125 SWEAT	UL:	Listed
Discharge Line Size(in):	0.5	UL File #:	SA633
Water Inlet (in):		UL Guide Card:	LZFE
Water Outlet (in):			
Oil Type:	POE	Amps Per Motor:	
Oil Recharge Amount (oz):	64	Fan Motor Quantity:	2

**Performance**

Release Date:	21-Jun-2022	Return Gas Temp. (°F):	40
Compressor:	ZS45K4E-TF5-250 x 1	Subcooling (°F):	5
Performance No:	41312	Air Flow Rate (CFM):	4240

**90 °F Ambient Air Temperature**

Evap Temp(°F)	Unit Capacity (BTU/hr)	Cond. Temp.(°F)	Temp. Diff.(°F)	EER(BTU/wh)
-25	16,500	104.7	14.7	3.6
-20	18,800	105.6	15.6	4.0
-15	21,300	106.7	16.7	4.3

-10	23,900	107.8	17.8	4.7
-5	26,800	109.0	19.0	5.0
0	30,000	110.3	20.3	5.4
5	33,400	111.7	21.7	5.8
10	37,000	113.3	23.3	6.2
15	40,900	114.9	24.9	6.6
20	45,100	116.6	26.6	7.0
25	49,500	118.5	28.5	7.5