

FFAP-A20Z-TFC-072

HFC, R-134a, 50Hz, 3-Phase, 200/220V

Availability: Custom US OEM Or Wholesaler

Mechanical		Electrical	
Unit Height (in):	18.9	Max Fuse Size:	20
Unit Length (in):	34.1	Min Circuit Ampacity:	13.9
Unit Width (in):	25.0	Compressor:	ZS13KAE-TF5-118
Ship Weight (lbs):	174.0	Compressor LRA - Low:	
Condenser Type:	Air	Compressor LRA - High:	59.0
CopeVap Water Storage:	NA	Compressor LRA - Half winding:	
Liquid Connection Size (in)/Type:	0.375 SWEAT	Compressor RLA	9.7
Suction Connection Size (in)/Type:	0.875 SWEAT	UL:	None
Discharge Line Size(in):	0.5	UL File #:	None
Water Inlet (in):		UL Guide Card:	None
Water Outlet (in):			
Oil Type:	POE	Amps Per Motor:	0.6
Oil Recharge Amount (oz):	25	Fan Motor Quantity:	2

Performance

Release Date:	21-Jun-2022	Return Gas Temp. (°F):	40
Compressor:	ZS13KAE-TF5-118 x 1	Subcooling (°F):	5
Performance No:	41667	Air Flow Rate (CFM):	1680

90 °F Ambient Air Temperature

Evap Temp(°F)	Unit Capacity (BTU/hr)	Cond. Temp.(°F)	Temp. Diff.(°F)	EER(BTU/wh)
-5	4,080	95.9	5.9	4.9
0	4,630	96.7	6.7	5.4
5	5,230	97.6	7.6	6.0

10	5,890	98.6	8.6	6.6
15	6,610	99.6	9.6	7.3
20	7,400	100.7	10.7	8.0
25	8,270	101.9	11.9	8.8