

**FFAP-A20Z-TFC-072**

HFC, R-404A, 60Hz, 3-Phase, 208/230V

Availability: Custom US OEM Or Wholesaler

Mechanical		Electrical	
Unit Height (in):	18.9	Max Fuse Size:	20
Unit Length (in):	34.1	Min Circuit Ampacity:	13.9
Unit Width (in):	25.0	Compressor:	ZS13KAE-TF5-118
Ship Weight (lbs):	174.0	Compressor LRA - Low:	
Condenser Type:	Air	Compressor LRA - High:	58.0
CopeVap Water Storage:	NA	Compressor LRA - Half winding:	
Liquid Connection Size (in)/Type:	0.375 SWEAT	Compressor RLA	9.7
Suction Connection Size (in)/Type:	0.875 SWEAT	UL:	Listed
Discharge Line Size(in):	0.5	UL File #:	SA633
Water Inlet (in):		UL Guide Card:	LZFE
Water Outlet (in):			
Oil Type:	POE	Amps Per Motor:	0.6
Oil Recharge Amount (oz):	25	Fan Motor Quantity:	2

**Performance**

Release Date:	21-Jun-2022	Return Gas Temp. (°F):	40
Compressor:	ZS13KAE-TF5-118 x 1	Subcooling (°F):	5
Performance No:	41676	Air Flow Rate (CFM):	1927

**90 °F Ambient Air Temperature**

Evap Temp(°F)	Unit Capacity (BTU/hr)	Cond. Temp.(°F)	Temp. Diff.(°F)	EER(BTU/wh)
-25	5,360	97.8	7.8	4.1
-20	6,130	98.7	8.7	4.4
-15	6,940	99.8	9.8	4.7

-10	7,800	100.8	10.8	5.1
-5	8,700	102.0	12.0	5.4
0	9,670	103.2	13.2	5.8
5	10,700	104.4	14.4	6.1
10	11,800	105.8	15.8	6.6
15	12,900	107.2	17.2	7.0
20	14,200	108.6	18.6	7.5
25	15,500	110.2	20.2	7.9